



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 1 Reference</p> <p>Definition</p>	<p style="text-align: center;"><b>INTERNATIONAL STANDARDS AND RECOMMENDED PRACTICES</b></p> <p style="text-align: center;"><b>CHAPTER 1. DEFINITIONS</b></p> <p><b>N1.</b> <i>All references to "Radio Regulations" are to the Radio Regulations published by the International Telecommunication Union (ITU). Radio Regulations are amended from time to time by the decisions embodied in the Final Acts of World Radiocommunication Conferences held normally every two to three years. Further information on the ITU processes as they relate to aeronautical radio system frequency use is contained in the Handbook on Radio Frequency Spectrum Requirements for Civil Aviation including statement of approved ICAO policies (Doc 9718).</i></p> <p><b>N2.</b> <i>The Mode S extended squitter system is subject to patent rights from the Massachusetts Institute of Technology (MIT) Lincoln Laboratory. On 22 August 1996, MIT Lincoln Laboratory issued a notice in the Commerce Business Daily (CBD), a United States Government publication, of its intent not to assert its rights as patent owner against any and all persons in the commercial or non-commercial practice of the patent, in order to promote the widest possible use of the Mode S extended squitter technology. Further, by letter to ICAO dated 27 August 1998, MIT Lincoln Laboratory confirmed that the CBD notice has been provided to satisfy ICAO requirements for a statement of patent rights for techniques that are included in SARPs, and that the patent holders offer this technique free of charge for any use.</i></p> <p><b>Airborne collision avoidance system (ACAS).</b> An aircraft system based on secondary surveillance radar (SSR) transponder signals which operates independently of ground-based equipment to provide advice to the pilot on potential conflicting aircraft that are equipped with SSR transponders.</p>	<p>Civil Aviation Rule (CAR) 171.53(a)(1).</p>	<p>No Difference</p>		<p>Note: any definition not otherwise referenced is deemed to be incorporated by reference (IBR) in CAR 171.53(a)(1).</p>



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<i>Note.— SSR transponders referred to above are those operating in Mode C or Mode S.</i>				
Chapter 1 Reference  Definition	<b>Aircraft address.</b> A unique combination of twenty-four bits available for assignment to an aircraft for the purpose of air-ground communications, navigation and surveillance. <i>Note.— SSR Mode S transponders transmit extended squitters to support the broadcast of aircraft-derived position for surveillance purposes. The broadcast of this type of information is a form of automatic dependent surveillance (ADS) known as ADS-broadcast (ADS-B).</i>	CAR 171.53(a)(1).	No Difference		IBR.
Chapter 1 Reference  Definition	<b>Automatic dependent surveillance-broadcast (ADS-B) IN.</b> A function that receives surveillance data from ADS-B OUT data sources.	CAR 171.53(a)(1).	No Difference		CAR 171.53(a)(1).
Chapter 1 Reference  Definition	<b>Automatic dependent surveillance-broadcast (ADS-B) OUT.</b> A function on an aircraft or vehicle that periodically broadcasts its state vector (position and velocity) and other information derived from on-board systems in a format suitable for ADS-B IN capable receivers.	CAR 171.53(a)(1).	No Difference		IBR.
Chapter 1 Reference  Definition	<b>Collision avoidance logic.</b> The sub-system or part of ACAS that analyses data relating to an intruder and own aircraft, decides whether or not advisories are appropriate and, if so, generates the advisories. It includes the following functions: range and altitude tracking, threat detection and RA generation. It excludes surveillance.	CAR 171.53(a)(1).	No Difference		IBR.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Human Factors principles.</b> Principles which apply to design, certification, training, operations and maintenance and which seek safe interface between the human and other system components by proper consideration to human performance.	CAR 171.53(a)(1).	No Difference		IBR.
Chapter 1 Reference  Definition	<b>Secondary surveillance radar (SSR).</b> A surveillance radar system which uses transmitters/receivers (interrogators) and transponders. <i>Note.— The requirements for interrogators and transponders are specified in Chapter 3.</i>	Airways Corporation of New Zealand (ACNZ) Manual of Air Traffic Services (MATS) RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Surveillance radar.</b> Radar equipment used to determine the position of an aircraft in range and azimuth.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Traffic information service – broadcast (TIS-B) IN.</b> A surveillance function that receives and processes surveillance data from TIS-B OUT data sources.	CAR 171.53(a)(1).	No Difference		IBR.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<p><b>Traffic information service – broadcast (TIS-B) OUT.</b> A function on the ground that periodically broadcasts the surveillance information made available by ground sensors in a format suitable for TIS-B IN capable receivers.</p> <p><i>Note.— This technique can be achieved through different data links. The requirements for Mode S extended squitters are specified in Annex 10, Volume IV, Chapter 5. The requirements for Mode extended squitters are specified in Annex 10, Volume IV, Chapter 5. The requirements for VHF digital link (VDL) Mode 4 and universal access transceiver (UAT) are specified in Annex 10, Volume III, Part I.</i></p>	CAR 171.53(a)(1).	No Difference		IBR.
Chapter 2 Reference 2.1.1  Standard	<p style="text-align: center;"><b>CHAPTER 2. GENERAL</b></p> <p style="text-align: center;"><b>2.1 SECONDARY SURVEILLANCE RADAR (SSR)</b></p> <p>When SSR is installed and maintained in operation as an aid to air traffic services, it shall conform with the provisions of 3.1 unless otherwise specified in this 2.1.</p> <p><i>Note.— As referred to in this Annex, Mode A/C transponders are those which conform to the characteristics prescribed in 3.1.1. Mode S transponders are those which conform to the characteristics prescribed in 3.1.2. The functional capabilities of Mode A/C transponders are an integral part of those of Mode S transponders.</i></p>	CAR 171.53(a)(1).	No Difference		The rule incorporates the relevant SARPs by reference.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.2.1  Standard	<p><b>2.1.2 Interrogation modes (ground-to-air)</b></p> <p>Interrogation for air traffic services shall be performed on the modes described in 3.1.1.4.3 or 3.1.2. The uses of each mode shall be as follows:</p> <ol style="list-style-type: none"> <li>1) <i>Mode A</i> — to elicit transponder replies for identity and surveillance.</li> <li>2) <i>Mode C</i> — to elicit transponder replies for automatic pressure-altitude transmission and surveillance.</li> <li>3) <i>Intermode</i> —             <ol style="list-style-type: none"> <li>a) <i>Mode A/C/S all-call</i>: to elicit replies for surveillance of Mode A/C transponders and for the acquisition of Mode S transponders.</li> <li>b) <i>Mode A/C-only all-call</i>: to elicit replies for surveillance of Mode A/C transponders. Mode S transponders do not reply.</li> </ol> </li> <li>4) <i>Mode S</i> —             <ol style="list-style-type: none"> <li>c) <i>Mode S-only all-call</i>: to elicit replies for acquisition of Mode S transponders.</li> <li>d) <i>Broadcast</i>: to transmit information to all Mode S transponders. No replies are elicited.</li> <li>e) <i>Selective</i>: for surveillance of, and communication with, individual Mode S transponders. For each interrogation, a reply is elicited only from the transponder uniquely addressed by the interrogation.</li> </ol> </li> </ol> <p>N1. <i>Mode A/C transponders are suppressed by Mode S interrogations and do not reply.</i></p> <p>N2. <i>There are 25 possible interrogation (uplink) formats and 25 possible Mode S reply (downlink) formats. For format assignment see 3.1.2.3.2, Figures 3-7 and 3-8.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.2.1.1  Recommendation	<b>Recommendation.</b> — <i>Administrations should coordinate with appropriate national and international authorities those implementation aspects of the SSR system which will permit its optimum use.</i>  <i>Note.</i> — <i>In order to permit the efficient operation of ground equipment designed to eliminate interference from unwanted aircraft transponder replies to adjacent interrogators (defruiting equipment), States may need to develop coordinated plans for the assignment of pulse recurrence frequencies (PRF) to SSR interrogators.</i>	Doc 9673 Vol II, Part V Appendix; MATS RAC 6.	No Difference		
Chapter 2 Reference 2.1.2.1.2  Standard	The assignment of interrogator identifier (II) codes, where necessary in areas of overlapping coverage, across international boundaries of flight information regions, shall be the subject of regional air navigation agreements.	Doc 9673 Vol II, Part V Appendix; MATS RAC 6.	No Difference		
Chapter 2 Reference 2.1.2.1.3  Standard	The assignment of surveillance identifier (SI) codes, where necessary in areas of overlapping coverage, shall be the subject of regional air navigation agreements.  <i>Note.</i> — <i>The SI lockout facility cannot be used unless all Mode S transponders within coverage range are equipped for this purpose.</i>	Doc 9673 Vol II, Part V Appendix; MATS RAC 6.	No Difference		
Chapter 2 Reference 2.1.2.2  Standard	Mode A and Mode C interrogations shall be provided.  <i>Note.</i> — <i>This requirement may be satisfied by intermode interrogations which elicit Mode A and Mode C replies from Mode A/C transponders.</i>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.2.3  Recommendation	<b>Recommendation.</b> — <i>In areas where improved aircraft identification is necessary to enhance the effectiveness of the ATC system, SSR ground facilities having Mode S features should include aircraft identification capability.</i> <i>Note.</i> — <i>Aircraft identification reporting through the Mode S data link provides unambiguous identification of aircraft suitably equipped.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 2 Reference 2.1.2.4.1  Standard	<b>2.1.2.4 SIDE-LOBE SUPPRESSION CONTROL INTERROGATION</b>  Side-lobe suppression shall be provided in accordance with the provisions of 3.1.1.4 and 3.1.1.5 on all Mode A, Mode C and intermode interrogations.	CAR 171.53(a)(1).	No Difference		
Chapter 2 Reference 2.1.2.4.2  Standard	Side-lobe suppression shall be provided in accordance with the provisions of 3.1.2.1.5.2.1 on all Mode S-only all-call interrogations.	CAR 171.53(a)(1).	No Difference		
Chapter 2 Reference 2.1.3.1  Standard	<b>2.1.3 Transponder reply modes (air-to-ground)</b>  Transponders shall respond to Mode A interrogations in accordance with the provisions of 3.1.1.7.12.1 and to Mode C interrogations in accordance with the provisions of 3.1.1.7.12.2. <i>Note.</i> — <i>If pressure-altitude information is not available, transponders reply to Mode C interrogations with framing pulses only.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.3.1.1  Standard	The pressure altitude reports contained in Mode S replies shall be derived as specified in 3.1.1.7.12.2. <i>Note.— 3.1.1.7.12.2 is intended to relate to Mode C replies and specifies, inter alia, that Mode C pressure-altitude reports be referenced to a standard pressure setting of 1 013 .25 hectopascals. The intention of 2.1.3.1.1 is to ensure that all transponders, not just Mode C transponders, report uncorrected pressure-altitude.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.3.2  Standard	Where the need for Mode C automatic pressure-altitude transmission capability within a specified airspace has been determined, transponders, when used within the airspace concerned, shall respond to Mode C interrogations with pressure-altitude encoding in the information pulses.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.3.2.1  Standard	From 1 January 1999, all transponders, regardless of the airspace in which they will be used, shall respond to Mode C interrogations with pressure-altitude information. <i>Note.— Operation of the airborne collision avoidance system (ACAS) depends upon intruder aircraft reporting pressure-altitude in Mode C replies.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.3.2.2  Standard	For aircraft equipped with 7.62 m (25 ft) or better pressure-altitude sources, the pressure-altitude information provided by Mode S transponders in response to selective interrogations (i.e. in the AC field, 3.1.2.6.5.4) shall be reported in 7.62 m (25 ft) increments. <i>Note.— Performance of the ACAS is significantly enhanced when an intruder aircraft is reporting pressure-altitude in 7.62 m (25 ft) increments.</i>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.3.2.3  Standard	All Mode A/C transponders shall report pressure-altitude encoded in the information pulses in Mode C replies.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.3.2.4  Standard	All Mode S transponders shall report pressure-altitude encoded in the information pulses in Mode C replies and in the AC field of Mode S replies.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.3.2.5  Standard	When a Mode S transponder is not receiving more pressure-altitude information from a source with a quantization of 7.62 m (25 ft) or better increments, the reported value of the altitude shall be the value obtained by expressing the measured value of the uncorrected pressure-altitude of the aircraft in 30.48 m (100 ft) increments and the Q bit (see 3.1.2.6.5.4 b)) shall be set to 0. <i>Note.— This requirement relates to the installation and use of the Mode S transponder. The purpose is to ensure that altitude data obtained from a 30.48 m (100 ft) increment source are not reported using the formats intended for 7.62 m (25 ft) data.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.3.3  Standard	Transponders used within airspace where the need for Mode S airborne capability has been determined shall also respond to intermode and Mode S interrogations in accordance with the applicable provisions of 3.1.2.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.3.3.1  Standard	Requirements for mandatory carriage of SSR Mode S transponders shall be on the basis of regional air navigation agreements which shall specify the airspace and the airborne implementation timescales.	Doc 9673 Vol II, Part V Appendix.	No Difference		Note: Mode S is catered for, but is not mandatory in New Zealand airspace.
Chapter 2 Reference 2.1.3.3.2  Recommendation	<b>Recommendation.</b> — <i>The agreements indicated in 2.1.3.3.1 should provide at least five years' notice.</i>	Doc 9673 Vol II, Part V Appendix.	No Difference		
Chapter 2 Reference 2.1.4.1  Standard	<b>2.1.4 Mode A reply codes (information pulses)</b>  All transponders shall be capable of generating 4 096 reply codes conforming to the characteristics given in 3.1.1.6.2.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.4.1.1  Recommendation	<b>Recommendation.</b> — <i>ATS authorities should establish the procedures for the allotment of SSR codes in conformity with Regional Air Navigation agreements, taking into account other users of the system.</i>  <i>Note.</i> — <i>Principles for the allocation of SSR codes are given in Doc 4444, Chapter 8.</i>	CAR 91.247.	No Difference		
Chapter 2 Reference 2.1.4.2  Standard	The following Mode A codes shall be reserved for special purposes:	CAR 91.247.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.4.2.1  Standard	Code 7700 to provide recognition of an aircraft in an emergency.	CAR 91.247.	No Difference		
Chapter 2 Reference 2.1.4.2.2  Standard	Code 7600 to provide recognition of an aircraft with radiocommunication failure.	CAR 91.247.	No Difference		
Chapter 2 Reference 2.1.4.2.3  Standard	Code 7500 to provide recognition of an aircraft which is being subjected to unlawful interference.	CAR 91.247.	No Difference		
Chapter 2 Reference 2.1.4.3  Standard	Appropriate provisions shall be made in ground decoding equipment to ensure immediate recognition of Mode A codes 7500, 7600 and 7700.	CAR 171.53(a)(1).	No Difference		
Chapter 2 Reference 2.1.4.4  Recommendation	<b>Recommendation.</b> — <i>Mode A code 0000 should be reserved for allocation subject to regional agreement, as a general purpose code.</i>		Not Applicable		Not used in New Zealand.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.4.5  Standard	Mode A code 2000 shall be reserved to provide recognition of an aircraft which has not received any instructions from air traffic control units to operate the transponder.	CAR 91.247.	No Difference		
Chapter 2 Reference 2.1.5.1  Standard	<p align="center"><b>2.1.5 Mode S airborne equipment capability</b></p> <p>All Mode S transponders shall conform to one of the following five levels:  <i>Note.— The transponder used for a Mode S site monitor may differ from the requirements defined for a normal Mode S transponder. For example, it may be necessary to reply to all-call interrogations when on the ground. For more details see the Aeronautical Surveillance Manual (Doc 9924) Appendix D.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.5.1.1  Standard	<p>Level 1 — Level 1 transponders shall have the capabilities prescribed for:</p> <ul style="list-style-type: none"> <li>a) Mode A identity and Mode C pressure-altitude reporting (3.1.1);</li> <li>b) intermode and Mode S all-call transactions (3.1.2.5);</li> <li>c) addressed surveillance altitude and identity transaction (3.1.2.6.1, 3.1.2.6.3, 3.1.2.6.5 and 3.1.2.6.7);</li> <li>d) lockout protocols (3.1.2.6.9);</li> <li>e) basic data protocols except data link capability reporting (3.1.2.6.10); and</li> <li>f) air-air service and squitter transactions (3.1.2.8).</li> </ul> <p><i>Note.— Level 1 permits SSR surveillance based on pressure-altitude reporting and the Mode A identity code. In an SSR Mode S environment, technical performance relative to a Mode A/C transponder is improved due to Mode S selective aircraft interrogation.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.5.1.2  Standard	<p>Level 2 — Level 2 transponders shall have the capabilities of 2.1.5.1.1 and also those prescribed for:</p> <ul style="list-style-type: none"> <li>a) standard length communications (Comm-A and Comm-B) (3.1.2.6.2, 3.1.2.6.4, 3.1.2.6.6, 3.1.2.6.8 and 3.1.2.6.11);</li> <li>b) data link capability reporting (3.1.2.6.10.2.2);</li> <li>c) aircraft identification reporting (3.1.2.9); and</li> <li>d) data parity with overlay control (3.1.2.6.11.2.5) for equipment certified on or after 1 January 2020.</li> </ul> <p><i>Note.— Level 2 permits aircraft identification reporting and other standard length data link communications from ground to air and air to ground. The aircraft identification reporting capability requires an interface and appropriate input device.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		Note: compliance with (d) yet to be considered.
Chapter 2 Reference 2.1.5.1.3  Standard	<p>Level 3 — Level 3 transponders shall have the capabilities of 2.1.5.1.2 and also those prescribed for ground-to-air extended length message (ELM) communications (3.1.2.7.1 to 3.1.2.7.5).</p> <p><i>Note.— Level 3 permits extended length data link communications from ground to air and thus may provide retrieval from ground-based data banks and receipt of other air traffic services which are not available with Level 2 transponders.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.5.1.4  Standard	<p>Level 4 — Level 4 transponders shall have the capabilities of 2.1.5.1.3 and also those prescribed for air-to-ground extended length message (ELM) communications (3.1.2.7.7 and 3.1.2.7.8).</p> <p><i>Note.— Level 4 permits extended length data link communications from air to ground and thus may provide access from the ground to airborne data sources and the transmission of other data required by air traffic services which are not available with Level 2 transponders.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.5.1.5  Standard	Level 5 — Level 5 transponders shall have the capabilities of 2.1.5.1.4 and also those prescribed for enhanced Comm-B and extended length message (ELM) communications (3.1.2.6.11.3.4, 3.1.2.7.6 and 3.1.2.7.9). <i>Note.— Level 5 permits Comm-B and extended length data link communications with multiple interrogators without requiring the use of multisite reservations. this level of transponder has a higher minimum data link capacity than the other transponder levels.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.5.1.6  Standard	<i>Extended squitter</i> — Extended squitter transponders shall have the capabilities of 2.1.5.1.2, 2.1.5.1.3, 2.1.5.1.4 or 2.1.5.1.5, the capabilities prescribed for extended squitter operation (3.1.2.8.6) and the capabilities prescribed for ACAS cross-link operation (3.1.2.8.3 and 3.1.2.8.4). Transponders with these capabilities shall be designated with a suffix “e”. <i>Note.— For example, a level 4 transponder with extended squitter capability would be designated “level 4e”.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.5.1.7  Standard	<i>SI capability</i> — Transponders with the ability to process SI codes shall have the capabilities of 2.1.5.1.1, 2.1.5.1.2, 2.1.5.1.3, 2.1.5.1.4 or 2.1.5.1.5 and also those prescribed for SI code operation (3.1.2.3.2.1.4, 3.1.2.5.2.1, 3.1.2.6.1.3, 3.1.2.6.1.4.1, 3.1.2.6.9.1.1 and 3.1.2.6.9.2). Transponders with this capability shall be designated with a suffix “s”. <i>Note.— For example, a level 4 transponder with extended squitter capability and SI capability would be designated “level 4es”.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.5.1.7.1  Standard	SI code capability shall be provided in accordance with the provisions of 2.1.5.1.7 for all Mode S transponders installed on or after 1 January 2003 and by all Mode S transponders by 1 January 2005. <i>Note.— Mandates from certain States may require applicability in advance of these dates.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.5.1.8  Standard	<i>Extended squitter non-transponder devices.</i> Devices that are capable of broadcasting extended squitters that are not part of a Mode S transponder shall conform to all of the 1 090 MHz RF signals in space requirements specified for a Mode S transponder, except for transmit power levels for the identified equipment class as specified in 5.1.1.	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 2 Reference 2.1.5.2  Standard	All Mode S transponders used by international civil air traffic shall conform, at least, to the requirements of Level 2 prescribed in 2.1.5.1.2. <i>N1.Level 1 may be admitted for use within an individual State or within the terms of a regional air navigation agreement. The Mode S Level 1 transponder comprises the minimum set of features for compatible operation of Mode S transponders with SSR Mode S interrogators. It is defined to prevent a proliferation of transponder types below Level 2 which would be incompatible with SSR Mode S interrogators.</i> <i>N2.The intent of the requirement for a Level 2 capability is to ensure the widespread use of an ICAO standard transponder capability to allow worldwide planning of Mode S ground facilities and services. The requirement also discourages an initial installation with Level 1 transponders that would be rendered obsolete by later requirements in certain airspace for mandatory carriage of transponders having Level 2 capabilities.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.5.3  Standard	<p>Mode S transponders installed on aircraft with gross mass in excess of 5 700 kg or a maximum cruising true airspeed capability in excess of 463 km/h (250 kt) shall operate with antenna diversity as prescribed in 3.1.2.10.4 if:</p> <ul style="list-style-type: none"> <li>a) the aircraft individual certificate of airworthiness is first issued on or after 1 January 1990; or</li> <li>b) Mode S transponder carriage is required on the basis of regional air navigation agreement in accordance with 2.1.3.3.1 and 2.1.3.3.2.</li> </ul> <p><i>Note.— Aircraft with maximum cruising true airspeed exceeding 324 km/h (175 kt) are required to operate with a peak power of not less than 21.0 dBW as specified in 3.1.2.10.2 c).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.5.4.1  Standard	<p>2.1.5.4 CAPABILITY REPORTING IN MODE S SQUITTERS</p> <p>Capability reporting in Mode S acquisition squitters (unsolicited downlink transmissions) shall be provided in accordance with the provisions of 3.1.2.8.5.1 for all Mode S transponders installed on or after 1 January 1995.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.5.4.2  Recommendation	<p><b>Recommendation.—</b> <i>Transponders equipped for extended squitter operation should have a means to disable acquisition squitters when extended squitters are being emitted.</i></p> <p><i>Note.— This will facilitate the suppression of acquisition squitters if all ACAS units have been converted to receive the extended squitter.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.1.5.5  Standard	<p><b>EXTENDED LENGTH MESSAGE (ELM) TRANSMIT POWER</b> In order to facilitate the conversion of existing Mode S transponders to include full Mode S capability, transponders originally manufactured before 1 January 1999 shall be permitted to transmit a burst of 16 ELM segments at a minimum power level of 20 dBW. <i>Note.— This represents a 1 dB relaxation from the power requirement specified in 3.1.2.10.2.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.1.6  Standard	<p><b>SSR Mode S address (aircraft address)</b> The SSR Mode S address shall be one of 16 777 214 twenty-four-bit aircraft addresses allocated by ICAO to the State of Registry or common mark registering authority and assigned as prescribed in 3.1.2.4.1.2.3.1.1 and the Appendix to Chapter 9, Part I, Volume III, Annex 10.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 2 Reference 2.2  Recommendation	<p><b>HUMAN FACTORS CONSIDERATIONS</b> <b>Recommendation.—</b> <i>Human Factors principles should be observed in the design and certification of surveillance radar, transponder and collision avoidance systems.</i> <i>Note.— Guidance material on Human Factors principles can be found in Doc 9683, Human Factors Training Manual and Circular 249 (Human Factors Digest No. 11 — Human Factors in CNS/ATM Systems).</i></p>		Not Applicable		New Zealand does not design or certify these systems.
Chapter 2 Reference 2.2.1.1  Standard	<p><b>2.2.1 Operation of controls</b> Transponder controls which are not intended to be operated in flight shall not be directly accessible to the flight crew.</p>		Not Applicable		New Zealand does not design or certify these systems.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.2.1.2  <b>Recommendation</b>	<p><b>Recommendation.</b>— <i>The operation of transponder controls, intended for use during flight, should be evaluated to ensure they are logical and tolerant to human error. In particular, where transponder functions are integrated with other system controls, the manufacturer should ensure that unintentional transponder mode switching (i.e. an operational state to 'STANDBY' or 'OFF') is minimized.</i></p> <p><i>Note.</i>— <i>This may take the form of a confirmation of mode switching, required by the flight crew. Typically 'Line Select' Keys, 'Touch Screen' or 'Cursor Controlled/Tracker-ball' methods used to change transponder modes should be carefully designed to minimize flight crew error.</i></p>		Not Applicable		New Zealand does not design or certify these systems.
Chapter 2 Reference 2.2.1.3  <b>Recommendation</b>	<p><b>Recommendation.</b>— <i>The flight crew should have access at all times to the information of the operational state of the transponder.</i></p> <p><i>Note.</i>— <i>Information on the monitoring of the operational state of the transponder is provided in RTCA DO-181 E, Minimum Operational Performance Standards for Air Traffic Control Radar Beacon System/Mode Select (ATCRBS/Mode S) Airborne Equipment, and in EUROCAE ED-73E, Minimum Operational Performance Specification for Secondary Surveillance Radar Mode S Transponders.</i></p>		Not Applicable		New Zealand does not design or certify these systems.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.1.1  Standard	<p style="text-align: center;"><b>CHAPTER 3. SURVEILLANCE SYSTEMS</b></p> <p style="text-align: center;"><b>3.1 SECONDARY SURVEILLANCE RADAR (SSR) SYSTEM CHARACTERISTICS</b></p> <p><i>N1. Section 3.1.1 prescribes the technical characteristics of SSR systems having only Mode A and Mode C capabilities. Section 3.1.2 prescribes the characteristics of systems with Mode S capabilities. Chapter 5 prescribes additional requirements on Mode S extended squitters.</i></p> <p><i>N2. Systems using Mode S capabilities are generally used for air traffic control surveillance systems. In addition, certain ATC applications may use Mode S emitters, e.g. for vehicle surface surveillance or for fixed target detection on surveillance systems. Under such specific conditions, the term "aircraft" can be understood as "aircraft or vehicle (A/V)". While those applications may use a limited set of data, any deviation from standard physical characteristics must be considered very carefully by the appropriate authorities. They must take into account not only their own surveillance (SSR) environment but also possible effects on other systems like ACAS.</i></p> <p><i>N3. Non-Standard-International alternative units are used as permitted by Annex 5, Chapter 3, 3.2.2.</i></p> <p><b>3.1.1 Systems having only Mode A and Mode C capabilities</b></p> <p><i>N4. In this section, SSR modes are designated by letters A and C. Suffixes letters, e.g. A<sub>2</sub>, C<sub>4</sub>, are used to designate the individual pulses used in the air-to-ground pulse trains. This common use of letters is not to be construed as implying any particular association of modes and codes.</i></p> <p><i>N5. Provisions for the recording and retention of radar data are contained in Annex 11, Chapter 6.</i></p> <p style="text-align: center;">3.1.1.1 INTERROGATION AND CONTROL</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	(INTERROGATION SIDE-LOBE SUPPRESSION) RADIO FREQUENCIES (GROUND-TO-AIR)  The carrier frequency of the interrogation and control transmissions shall be 1 030 MHz.				
Chapter 3 Reference 3.1.1.1.2  Standard	The frequency tolerance shall be plus or minus 0.2 MHz.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.1.3  Standard	The carrier frequencies of the control transmission and of each of the interrogation pulse transmissions shall not differ from each other by more than 0.2 MHz.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.2.1  Standard	3.1.1.2 REPLY CARRIER FREQUENCY (AIR-TO-GROUND)  The carrier frequency of the reply transmission shall be 1 090 MHz.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.2.2  Standard	The frequency tolerance shall be plus or minus 3 MHz.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.3  Standard	POLARIZATION Polarization of the interrogation, control and reply transmissions shall be predominantly vertical.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.4.1  Standard	3.1.1.4 INTERROGATION MODES (SIGNALS-IN-SPACE)  The interrogation shall consist of two transmitted pulses designated $P_1$ and $P_3$ . A control pulse $P_2$ shall be transmitted following the first interrogation pulse $P_1$ .	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.4.2  Standard	Interrogation Modes A and C shall be as defined in 3.1.1.4.3.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.4.3  Standard	The interval between $P_1$ and $P_3$ shall determine the mode of interrogation and shall be as follows: Mode A $8 \pm 0.2$ microseconds Mode C $21 \pm 0.2$ microseconds	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.4.4  Standard	The interval between $P_1$ and $P_2$ shall be 2.0 plus or minus 0.15 microseconds.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.4.5  Standard	The duration of pulses $P_1$ , $P_2$ and $P_3$ shall be 0.8 plus or minus 0.1 microsecond.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.4.6  Standard	The rise time of pulses $P_1$ , $P_2$ and $P_3$ shall be between 0.05 and 0.1 microsecond. <i>N1.The definitions are contained in Figure 3-1 "Definitions of secondary surveillance radar waveform shapes, intervals and the reference point for sensitivity and power".</i> <i>N2.The intent of the lower limit of rise time (0.05 microsecond) is to reduce sideband radiation. Equipment will meet this requirement if the sideband radiation is no greater than that which, theoretically, would be produced by a trapezoidal wave having the stated rise time.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.4.7  Standard	The decay time of pulses $P_1$ , $P_2$ and $P_3$ shall be between 0.05 and 0.2 microsecond. <i>Note.— The intent of the lower limit of decay time (0.05 microsecond) is to reduce sideband radiation. Equipment will meet this requirement if the sideband radiation is no greater than that which, theoretically, would be produced by a trapezoidal wave having the stated decay time.</i>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.5.1  Standard	3.1.1.5 INTERROGATOR AND CONTROL TRANSMISSION CHARACTERISTICS (INTERROGATION SIDE-LOBE SUPPRESSION — SIGNALS-IN-SPACE)  The radiated amplitude of $P_2$ at the antenna of the transponder shall be: a) equal to or greater than the radiated amplitude of $P_1$ from the side-lobe transmissions of the antenna radiating $P_1$ ; and b) at a level lower than 9 dB below the radiated amplitude of $P_1$ , within the desired arc of interrogation.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.5.2  Standard	Within the desired beam width of the directional interrogation (main lobe), the radiated amplitude of $P_3$ shall be within 1 dB of the radiated amplitude of $P_1$ .	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.6.1  Standard	3.1.1.6 REPLY TRANSMISSION CHARACTERISTICS (SIGNALS-IN-SPACE)  Framing pulses. The reply function shall employ a signal comprising two framing pulses spaced 20.3 microseconds as the most elementary code.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																														
Chapter 3 Reference 3.1.1.6.2  Standard	<p>Information pulses. Information pulses shall be spaced in increments of 1.45 microseconds from the first framing pulse. The designation and position of these information pulses shall be as follows:</p> <table border="0" data-bbox="567 454 924 1153"> <thead> <tr> <th style="text-align: center;"><i>Pulses (microseconds)</i></th> <th style="text-align: center;"><i>Position</i></th> </tr> </thead> <tbody> <tr><td style="text-align: center;">C<sub>1</sub></td><td style="text-align: center;">1.45</td></tr> <tr><td style="text-align: center;">A<sub>1</sub></td><td style="text-align: center;">2.90</td></tr> <tr><td style="text-align: center;">C<sub>2</sub></td><td style="text-align: center;">4.35</td></tr> <tr><td style="text-align: center;">A<sub>2</sub></td><td style="text-align: center;">5.80</td></tr> <tr><td style="text-align: center;">C<sub>4</sub></td><td style="text-align: center;">7.25</td></tr> <tr><td style="text-align: center;">A<sub>4</sub></td><td style="text-align: center;">8.70</td></tr> <tr><td style="text-align: center;">X</td><td style="text-align: center;">10.15</td></tr> <tr><td colspan="2"> </td></tr> <tr><td style="text-align: center;">B<sub>1</sub></td><td style="text-align: center;">11.60</td></tr> <tr><td style="text-align: center;">D<sub>1</sub></td><td style="text-align: center;">13.05</td></tr> <tr><td style="text-align: center;">B<sub>2</sub></td><td style="text-align: center;">14.50</td></tr> <tr><td style="text-align: center;">D<sub>2</sub></td><td style="text-align: center;">15.95</td></tr> <tr><td style="text-align: center;">B<sub>4</sub></td><td style="text-align: center;">17.40</td></tr> <tr><td style="text-align: center;">D<sub>4</sub></td><td style="text-align: center;">18.85</td></tr> </tbody> </table> <p><i>Note.— The Standard relating to the use of these pulses is given in 2.1.4.1. However, the position of the “X” pulse is not used in replies to Mode A or Mode C interrogations and is specified only as a technical standard to safeguard possible future expansion of the system. It has nevertheless been decided that such expansion should be achieved using Mode S. The presence of a pulse in the X pulse position is used in some States to invalidate replies.</i></p>	<i>Pulses (microseconds)</i>	<i>Position</i>	C <sub>1</sub>	1.45	A <sub>1</sub>	2.90	C <sub>2</sub>	4.35	A <sub>2</sub>	5.80	C <sub>4</sub>	7.25	A <sub>4</sub>	8.70	X	10.15			B <sub>1</sub>	11.60	D <sub>1</sub>	13.05	B <sub>2</sub>	14.50	D <sub>2</sub>	15.95	B <sub>4</sub>	17.40	D <sub>4</sub>	18.85	CAR 171.53(a)(1).	No Difference		
<i>Pulses (microseconds)</i>	<i>Position</i>																																		
C <sub>1</sub>	1.45																																		
A <sub>1</sub>	2.90																																		
C <sub>2</sub>	4.35																																		
A <sub>2</sub>	5.80																																		
C <sub>4</sub>	7.25																																		
A <sub>4</sub>	8.70																																		
X	10.15																																		
B <sub>1</sub>	11.60																																		
D <sub>1</sub>	13.05																																		
B <sub>2</sub>	14.50																																		
D <sub>2</sub>	15.95																																		
B <sub>4</sub>	17.40																																		
D <sub>4</sub>	18.85																																		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.6.3  Standard	<i>Special position identification pulse (SPI).</i> In addition to the information pulses provided, a special position identification pulse shall be transmitted but only as a result of manual (pilot) selection. When transmitted, it shall be spaced at an interval of 4.35 microseconds following the last framing pulse of Mode A replies only.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.6.4  Standard	<i>Reply pulse shape.</i> All reply pulses shall have a pulse duration of 0.45 plus or minus 0.1 microsecond, a pulse rise time between 0.05 and 0.1 microsecond and a pulse decay time between 0.05 and 0.2 microsecond. The pulse amplitude variation of one pulse with respect to any other pulse in a reply train shall not exceed 1 dB.  <i>Note.— The intent of the lower limit of rise and decay times (0.05 microsecond) is to reduce sideband radiation. Equipment will meet this requirement if the sideband radiation is not greater than that which, theoretically, would be produced by a trapezoidal wave having the stated rise and decay times.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.6.5  Standard	<i>Reply pulse position tolerances.</i> The pulse spacing tolerance for each pulse (including the last framing pulse) with respect to the first framing pulse of the reply group shall be plus or minus 0.10 microsecond. The pulse interval tolerance of the special position identification pulse with respect to the last framing pulse of the reply group shall be plus or minus 0.10 microsecond. The pulse spacing tolerance of any pulse in the reply group with respect to any other pulse (except the first framing pulse) shall not exceed plus or minus 0.15 microsecond.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference												
Chapter 3 Reference 3.1.1.6.6  Standard	<p><i>Code nomenclature.</i> The code designation shall consist of digits between 0 and 7 inclusive, and shall consist of the sum of the subscripts of the pulse numbers given in 3.1.1.6.2 above, employed as follows:</p> <table border="0" style="margin-left: 100px;"> <tr> <td style="padding-right: 20px;"><i>Digit</i></td> <td><i>Puls</i></td> </tr> <tr> <td><i>e Group</i></td> <td></td> </tr> <tr> <td>First (most significant)</td> <td>A</td> </tr> <tr> <td>Second</td> <td>B</td> </tr> <tr> <td>Third</td> <td>C</td> </tr> <tr> <td>Fourth</td> <td>D</td> </tr> </table>	<i>Digit</i>	<i>Puls</i>	<i>e Group</i>		First (most significant)	A	Second	B	Third	C	Fourth	D	CAR 171.53(a)(1).	No Difference		
<i>Digit</i>	<i>Puls</i>																
<i>e Group</i>																	
First (most significant)	A																
Second	B																
Third	C																
Fourth	D																



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.1  Standard	<p>3.1.1.7 TECHNICAL CHARACTERISTICS OF TRANSPONDERS WITH MODE A AND MODE C CAPABILITIES ONLY</p> <p><i>Reply.</i> The transponder shall reply (not less than 90 per cent triggering) when all of the following conditions have been met:</p> <ul style="list-style-type: none"> <li>a) the received amplitude of <math>P_3</math> is in excess of a level 1 dB below the received amplitude of <math>P_1</math> but no greater than 3 dB above the received amplitude of <math>P_1</math>;</li> <li>b) either no pulse is received in the interval 1.3 microseconds to 2.7 microseconds after <math>P_1</math>, or <math>P_1</math> exceeds by more than 9 dB any pulse received in this interval;</li> <li>c) the received amplitude of a proper interrogation is more than 10 dB above the received amplitude of random pulses where the latter are not recognized by the transponder as <math>P_1</math>, <math>P_2</math> or <math>P_3</math>.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.2  Standard	<p>The transponder shall not reply under the following conditions:</p> <ul style="list-style-type: none"> <li>a) to interrogations when the interval between pulses <math>P_1</math> and <math>P_3</math> differs from those specified in 3.1.1.4.3 by more than plus or minus 1.0 microsecond;</li> <li>b) upon receipt of any single pulse which has no amplitude variations approximating a normal interrogation condition.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.3  Standard	<p><i>Dead time.</i> After recognition of a proper interrogation, the transponder shall not reply to any other interrogation, at least for the duration of the reply pulse train. This dead time shall end no later than 125 microseconds after the transmission of the last reply pulse of the group.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.4.1  Standard	<p><i>3.1.1.7.4 SUPPRESSION</i></p> <p><i>Note.— This characteristic is used to prevent replies to interrogations received via the side lobes of the interrogator antenna, and to prevent Mode A/C transponders from replying to Mode S interrogations.</i></p> <p>The transponder shall be suppressed when the received amplitude of <math>P_2</math> is equal to, or in excess of, the received amplitude of <math>P_1</math> and spaced 2.0 plus or minus 0.15 microseconds. The detection of <math>P_3</math> is not required as a prerequisite for initiation of suppression action.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.4.2  Standard	The transponder suppression shall be for a period of 35 plus or minus 10 microseconds.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.4.2.1  Standard	The suppression shall be capable of being reinitiated for the full duration within 2 microseconds after the end of any suppression period.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.1.7.4.3  Standard</p>	<p>Suppression in presence of <math>S_1</math> pulse <i>Note. — The <math>S_1</math> pulse is used in a technique employed by ACAS known as “whisper-shout” to facilitate ACAS surveillance of Mode A/C aircraft in higher traffic densities. The whisper-shout technique is explained in the Airborne Collision Avoidance System (ACAS) Manual (Doc 9863).</i> When an <math>S_1</math> pulse is detected 2.0 plus or minus 0.15 microseconds before the <math>P_1</math> of a Mode a or Mode C interrogation:  <ul style="list-style-type: none"> <li>a) with <math>S_1</math> and <math>P_1</math> above MTL, the transponder shall be suppressed as specified in 3.1.1.7.4.1;</li> <li>b) with <math>P_1</math> at MTL and <math>S_1</math> at MTL, the transponder shall be suppressed and shall reply to no more than 10 percent of Mode A/C interrogations;</li> <li>c) with <math>P_1</math> at MTL and <math>S_1</math> at MTL -3 dB, the transponder shall reply to Mode A/C interrogations at least 70 per cent of the time; and</li> <li>d) with <math>P_1</math> at MTL and <math>S_1</math> at MTL -6 dB, the transponder shall reply to Mode A/C interrogations at least 90 per cent of the time.</li> </ul> <p>N1.<i>The suppression action is because of the detection of <math>S_1</math> and <math>P_1</math> and does not require detection of a <math>P_2</math> or <math>P_3</math> pulse.</i>  N2.<i><math>S_1</math> has a lower amplitude than <math>P_1</math>. Certain ACAS use this mechanism to improve target detection (4.3.7.1).</i>  N3.<i>These requirements also apply to a Mode A/C only capable transponder when an <math>S_1</math> precedes an intermode interrogation (2.1.2.1).</i></p> </p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.5.1  Standard	<p><i>3.1.1.7.5 RECEIVER SENSITIVITY AND DYNAMIC RANGE</i></p> <p>The minimum triggering level of the transponder shall be such that replies are generated to at least 90 per cent of the interrogation signals when:</p> <ul style="list-style-type: none"> <li>a) the two pulses <math>P_1</math> and <math>P_3</math> constituting an interrogation are of equal amplitude and <math>P_2</math> is not detected; and</li> <li>b) the amplitude of these signals is nominally 71 dB below 1 mW, with limits between 69 dB and 77 dB below 1 mW.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.5.2  Standard	The reply and suppression characteristics shall apply over a received amplitude of $P_1$ between minimum triggering level and 50 dB above that level.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.5.3  Standard	The variation of the minimum triggering level between modes shall not exceed 1 dB for nominal pulse spacings and pulse widths.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.6  Standard	<i>Pulse duration discrimination.</i> Signals of received amplitude between minimum triggering level and 6 dB above this level, and of a duration less than 0.3 microsecond, shall not cause the transponder to initiate reply or suppression action. With the exception of single pulses with amplitude variations approximating an interrogation, any single pulse of a duration more than 1.5 microseconds shall not cause the transponder to initiate reply or suppression action over the signal amplitude range of minimum triggering level (MTL) to 50 dB above that level.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.7  Standard	<i>Echo suppression and recovery.</i> The transponder shall contain an echo suppression facility designed to permit normal operation in the presence of echoes of signals-in-space. The provision of this facility shall be compatible with the requirements for suppression of side lobes given in 3.1.1.7.4.1.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.7.1  Standard	<i>Desensitization.</i> Upon receipt of any pulse more than 0.7 microsecond in duration, the receiver shall be desensitized by an amount that is within at least 9 dB of the amplitude of the desensitizing pulse but shall at no time exceed the amplitude of the desensitizing pulse, with the exception of possible overshoot during the first microsecond following the desensitizing pulse.  <i>Note.— Single pulses of duration less than 0.7 microsecond are not required to cause the specified desensitization nor to cause desensitization of duration greater than permitted by 3.1.1.7.7.1 and 3.1.1.7.7.2.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.7.2  Standard	<i>Recovery.</i> Following desensitization, the receiver shall recover sensitivity (within 3 dB of minimum triggering level) within 15 microseconds after reception of a desensitizing pulse having a signal strength up to 50 dB above minimum triggering level. Recovery shall be at an average rate not exceeding 4.0 dB per microsecond.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.8  Standard	<i>Random triggering rate.</i> In the absence of valid interrogation signals, Mode A/C transponders shall not generate more than 30 unwanted Mode A or Mode C replies per second as integrated over an interval equivalent to at least 300 random triggers, or 30 seconds, whichever is less. This random triggering rate shall not be exceeded when all possible interfering equipments installed in the same aircraft are operating at maximum interference levels.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.8.1  Standard	<i>Random triggering rate in the presence of low-level in-band continuous wave (CW) interference.</i> The total random trigger rate on all Mode A and/or Mode C replies shall not be greater than 10 reply pulse groups or suppressions per second, averaged over a period of 30 seconds, when operated in the presence of non-coherent CW interference at a frequency of 1 030 ±0.2 MHz and a signal level of -60 dBm or less.	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.9.1  Standard	<p><i>3.1.1.7.9 REPLY RATE</i></p> <p>All transponders shall be capable of continuously generating at least 500 replies per second for a 15-pulse coded reply. Transponder installations used solely below 4 500m (15 000 ft), or below a lesser altitude established by the appropriate authority or by regional air navigation agreement, and in aircraft with a maximum cruising true airspeed not exceeding 175 kt (324 km/h) shall be capable of generating at least 1 000 15-pulse coded replies per second for a duration of 100 milliseconds. Transponder installations operated above 4 500 m (15 000 ft) or in aircraft with a maximum cruising true airspeed in excess of 175 kt (324 km/h), shall be capable of generating at least 1 200 15-pulse coded replies per second for a duration of 100 milliseconds.</p> <p><i>N1.A 15-pulse reply includes 2 framing pulses, 12 information pulses, and the SPI pulse.</i></p> <p><i>N2.The reply rate requirement of 500 replies per second establishes the minimum continuous reply rate capability of the transponder. As per the altitude and speed criteria above, the 100 or 120 replies in a 100 millisecond interval defines the peak capability of the transponder. The transponder must be capable of replying to this short term burst rate, even though the transponder may not be capable of sustaining this rate. If the transponder is subjected to interrogation rates beyond its reply rate capability, the reply rate limit control of 3.1.1.7.9.2 acts to gracefully desensitize the transponder in a manner that favours closer interrogators. Desensitization eliminates weaker interrogation signals.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.9.2  Standard	<i>Reply rate limit control.</i> To protect the system from the effects of transponder over-interrogation by preventing response to weaker signals when a predetermined reply rate has been reached, a sensitivity reduction type reply limit control shall be incorporated in the equipment. The range of this control shall permit adjustment, as a minimum, to any value between 500 and 2 000 replies per second, or to the maximum reply rate capability if less than 2 000 replies per second, without regard to the number of pulses in each reply. Sensitivity reduction in excess of 3 dB shall not take effect until 90 per cent of the selected value is exceeded. Sensitivity reduction shall be at least 30 dB for rates in excess of 150 per cent of the selected value.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.10  Standard	<i>Reply delay and jitter.</i> The time delay between the arrival, at the transponder receiver, of the leading edge of $P_3$ and the transmission of the leading edge of the first pulse of the reply shall be 3 plus or minus 0.5 microseconds. The total jitter of the reply pulse code group, with respect to $P_3$ , shall not exceed 0.1 microsecond for receiver input levels between 3 dB and 50 dB above minimum triggering level. Delay variations between modes on which the transponder is capable of replying shall not exceed 0.2 microsecond.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.11.1  Standard	<p><b>3.1.1.7.11 TRANSPONDER POWER OUTPUT AND DUTY CYCLE</b></p> <p>The peak pulse power available at the antenna end of the transmission line of the transponder shall be at least 21 dB and not more than 27 dB above 1 W, except that for transponder installations used solely below 4 500 m (15 000 ft), or below a lesser altitude established by the appropriate authority or by regional air navigation agreement, a peak pulse power available at the antenna end of the transmission line of the transponder of at least 18.5 dB and not more than 27 dB above 1 W shall be permitted.</p> <p><i>Note.— An extended squitter non-transponder device on an aerodrome surface vehicle may operate with a lower minimum power output as specified in 5.1.1.2.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.11.2  Recommendation	<p><b>Recommendation.—</b> <i>The peak pulse power specified in 3.1.1.7.11.1 should be maintained over a range of replies from code 0000 at a rate of 400 replies per second to a maximum pulse content at a rate of 1 200 replies per second or a maximum value below 1 200 replies per second of which the transponder is capable.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.12.1  Standard	<p><b>3.1.1.7.12 REPLY CODES</b></p> <p><i>Identification.</i> The reply to a Mode A interrogation shall consist of the two framing pulses specified in 3.1.1.6.1 together with the information pulses (Mode A code) specified in 3.1.1.6.2.</p> <p><i>Note.— The Mode A code designation is a sequence of four digits in accordance with 3.1.1.6.6.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.12.1.1  Standard	The Mode A code shall be manually selected from the 4 096 codes available.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.12.2  Standard	<i>Pressure-altitude transmission.</i> The reply to Mode C interrogation shall consist of the two framing pulses specified in 3.1.1.6.1 above. When digitized pressure-altitude information is available, the information pulses specified in 3.1.1.6.2 shall also be transmitted.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.12.2.1  Standard	Transponders shall be provided with means to remove the information pulses but to retain the framing pulses when the provision of 3.1.1.7.12.2.4 below is not complied with in reply to Mode C interrogation.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.12.2.2  Standard	The information pulses shall be automatically selected by an analog-to-digital converter connected to a pressure-altitude data source in the aircraft referenced to the standard pressure setting of 1 013.25 hectopascals. <i>Note.— The pressure setting of 1 013.25 hectopascals is equal to 29.92 inches of mercury.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.12.2.3  Standard	Pressure-altitude shall be reported in 100-ft increments by selection of pulses as shown in the Appendix to this chapter.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.7.12.2.4  Standard	The digitizer code selected shall correspond to within plus or minus 38.1 m (125 ft), on a 95 per cent probability basis, with the pressure-altitude information (referenced to the standard pressure setting of 1 013.25 hectopascals), used on board the aircraft to adhere to the assigned flight profile.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.13  Standard	<i>Transmission of the special position identification (SPI) pulse.</i> When required, this pulse shall be transmitted with Mode A replies, as specified in 3.1.1.6.3, for a period of between 15 and 30 seconds.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.14.1  Standard	<i>3.1.1.7.14 ANTENNA</i>  The transponder antenna system, when installed on an aircraft, shall have a radiation pattern which is essentially omnidirectional in the horizontal plane.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.1.7.14.2  Recommendation	<b>Recommendation.</b> — <i>The vertical radiation pattern should be nominally equivalent to that of a quarter-wave monopole on a ground plane.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.8.1  Standard	<p><b>3.1.1.8 TECHNICAL CHARACTERISTICS OF GROUND INTERROGATORS WITH MODE A AND MODE C CAPABILITIES ONLY</b></p> <p><i>Interrogation repetition frequency.</i> The maximum interrogation repetition frequency shall be 450 interrogations per second.</p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.8.1.1  Recommendation	<p><b>Recommendation.</b>— <i>To minimize unnecessary transponder triggering and the resulting high density of mutual interference, all interrogators should use the lowest practicable interrogator repetition frequency that is consistent with the display characteristics, interrogator antenna beam width and antenna rotation speed employed.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.8.2  Recommendation	<p><b>RADIATED POWER</b></p> <p><b>Recommendation.</b>— <i>In order to minimize system interference the effective radiated power of interrogators should be reduced to the lowest value consistent with the operationally required range of each individual interrogator site.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.8.3  Recommendation	<p><b>Recommendation.</b>— <i>When Mode C information is to be used from aircraft flying below transition levels, the altimeter pressure reference datum should be taken into account.</i></p> <p><i>Note.</i>— <i>Use of Mode C below transition levels is in accordance with the philosophy that Mode C can usefully be employed in all environments.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.9  Recommendation	<p style="text-align: center;">INTERROGATOR RADIATED FIELD PATTERN</p> <p><b>Recommendation.</b>— <i>The beam width of the directional interrogator antenna radiating P<sub>3</sub> should not be wider than is operationally required. The side- and back-lobe radiation of the directional antenna should be at least 24 dB below the peak of the main-lobe radiation.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.10.1  Standard	<p>The range and azimuth accuracy of the ground interrogator shall be monitored at sufficiently frequent intervals to ensure system integrity.</p> <p><i>Note.</i>— <i>Interrogators that are associated with and operated in conjunction with primary radar may use the primary radar as the monitoring device; alternatively, an electronic range and azimuth accuracy monitor would be required.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.10.2  Recommendation	<p><b>Recommendation.</b>— <i>In addition to range and azimuth monitoring, provision should be made to monitor continuously the other critical parameters of the ground interrogator for any degradation of performance exceeding the allowable system tolerances and to provide an indication of any such occurrence.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.1.11.1  Recommendation	<p style="text-align: center;"><b>3.1.1.11 SPURIOUS EMISSIONS AND SPURIOUS RESPONSES</b></p> <p><i>SPURIOUS RADIATION</i></p> <p><b>Recommendation.</b>— <i>CW radiation should not exceed 76 dB below 1 W for the interrogator and 70 dB below 1 W for the transponder.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.1.11.2  Recommendation	<i>SPURIOUS RESPONSES</i> <b>Recommendation.</b> — <i>The response of both airborne and ground equipment to signals not within the receiver pass band should be at least 60 dB below normal sensitivity.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1  Standard	<b>3.1.2 Systems having Mode S capabilities</b>  <i>Interrogation signals-in-space characteristics.</i> The paragraphs herein describe the signals-in-space as they can be expected to appear at the antenna of the transponder. <i>Note.</i> — <i>Because signals can be corrupted in propagation, certain interrogation pulse duration, pulse spacing and pulse amplitude tolerances are more stringent for interrogators as described in 3.1.2.11.4.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.1  Standard	<i>Interrogation carrier frequency.</i> The carrier frequency of all interrogations (uplink transmissions) from ground facilities with Mode S capabilities shall be 1 030 plus or minus 0.01 MHz, except during the phase reversal, while maintaining the spectrum requirements of 3.1.2.1.2. <i>Note.</i> — <i>During the phase reversal the frequency of the signal may shift by several MHz before returning to the specified value.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.2  Standard	<i>Interrogation spectrum.</i> The spectrum of a Mode S interrogation about the carrier frequency shall not exceed the limits specified in Figure 3-2. <i>Note.</i> — <i>The Mode S interrogation spectrum is data dependent. The broadest spectrum is generated by an interrogation that contains all binary ONES.</i>	CAR 171.53(a)(1).	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.1.3  Standard	<i>Polarization.</i> Polarization of the interrogation and control transmissions shall be nominally vertical.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.4  Standard	<i>Modulation.</i> For Mode S interrogations, the carrier frequency shall be pulse modulated. In addition, the data pulse, $P_6$ , shall have internal phase modulation.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.4.1  Standard	<i>Pulse modulation.</i> Intermode and Mode S interrogations shall consist of a sequence of pulses as specified in 3.1.2.1.5 and Tables 3-1, 3-2, 3-3, and 3-4.  <i>Note.— The 0.8 microsecond pulses used in intermode and Mode S interrogations are identical in shape to those used in Modes A and C as defined in 3.1.1.4.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.4.2  Standard	<i>Phase modulation.</i> The short (16.25-microsecond) and long (30.25-microsecond) $P_6$ pulses of 3.1.2.1.4.1 shall have internal binary differential phase modulation consisting of 180-degree phase reversals of the carrier at a 4 megabit per second rate.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.1.4.2.1  Standard	<p><i>Phase reversal duration.</i> The duration of the phase reversal shall be less than 0.08 microsecond and the phase shall advance (or retard) monotonically throughout the transition region. There shall be no amplitude modulation applied during the phase transition.</p> <p><i>N1.</i> The minimum duration of the phase reversal is not specified. Nonetheless, the spectrum requirements of 3.1.2.1.2 must be met.</p> <p><i>N2.</i> The phase reversal can be generated using different methods. This includes hard keying with strong amplitude drop and rapid phase reversal or other techniques with little or no amplitude drop, but with frequency shift during the phase reversal and slow phase reversal (80ns). A demodulator cannot make any assumption on the type of modulation technology used and therefore cannot rely on the specificities of the signal during the phase reversal to detect a phase reversal.</p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.4.2.2  Standard	<p><i>Phase relationship.</i> The tolerance on the 0 and 180-degree phase relationship between successive chips and on the sync phase reversal (3.1.2.1.5.2.2) within the <math>P_6</math> pulse shall be plus or minus 5 degrees.</p> <p><i>Note.— In Mode S a “chip” is the 0.25 microsecond carrier interval between possible data phase reversals.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.5  Standard	<p><i>Pulse and phase reversal sequences.</i> Specific sequences of the pulses or phase reversals described in 3.1.2.1.4 shall constitute interrogations.</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3  Reference 3.1.2.1.5.1.1  Standard	<p>3.1.2.1.5.1 <i>Intermode interrogation</i></p> <p><i>Mode A/C/S all-call interrogation.</i> This interrogation shall consist of three pulses: <math>P_1</math>, <math>P_3</math>, and the long <math>P_4</math> as shown in Figure 3-3. One or two control pulses (<math>P_2</math> alone, or <math>P_1</math> and <math>P_2</math>) shall be transmitted using a separate antenna pattern to suppress responses from aircraft in the side lobes of the interrogator antenna.</p> <p><i>Note.— The Mode A/C/S all-call interrogation elicits a Mode A or Mode C reply (depending on the <math>P_1</math>-<math>P_3</math> pulse spacing) from a Mode A/C transponder because it does not recognize the <math>P_4</math> pulse. A Mode S transponder recognizes the long <math>P_4</math> pulse and responds with a Mode S reply. This interrogation was originally planned for use by isolated or clustered interrogators. Lockout for this interrogation was based on the use of <math>II</math> equals 0. The development of the Mode S subnetwork now dictates the use of a non-zero <math>II</math> code for communication purposes. For this reason, <math>II</math> equals 0 has been reserved for use in support of a form of Mode S acquisition that uses stochastic/lockout override (3.1.2.5.2.1.4 and 3.1.2.5.2.1.5). The Mode A/C/S all-call cannot be used with full Mode S operation since <math>II</math> equals 0 can only be locked out for short time periods (3.1.2.5.2.1.5.2.1). This interrogation cannot be used with stochastic/lockout override, since probability of reply cannot be specified.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.1.5.1.1.1  Standard	Mode A/C/S all-call interrogations shall not be used on or after 1 January 2020. <i>N1.The use of Mode A/C/S all-call interrogations does not allow the use of stochastic lockout override and therefore might not ensure a good probability of acquisition in areas of high density of flights or when other interrogators lockout transponder on II=0 for supplementary acquisition.</i> <i>N2.The replies to Mode A/C/S all-call interrogations will no longer be supported by equipment certified on or after 1 January 2020 in order to reduce the RF pollution generated by the replies triggered by the false detection of Mode A/C/S all-call interrogations within other types of interrogation.</i>	CAR 171.53(a)(1).	Less protective or partially implemented or not implemented	Yet to be addressed.	
Chapter 3 Reference 3.1.2.1.5.1.2  Standard	<i>Mode A/C-only all-call interrogation.</i> This interrogation shall be identical to that of the Mode A/C/S all-call interrogation except that the short P <sub>4</sub> pulse shall be used. <i>Note.— The Mode A/C-only all-call interrogation elicits a Mode A or Mode C reply from a Mode A/C transponder. A Mode S transponder recognizes the short P<sub>4</sub> pulse and does not reply to this interrogation.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.5.1.3  Standard	<i>Pulse intervals.</i> The pulse intervals between P <sub>1</sub> , P <sub>2</sub> and P <sub>3</sub> shall be as defined in 3.1.1.4.3 and 3.1.1.4.4. The pulse interval between P <sub>3</sub> and P <sub>4</sub> shall be 2 plus or minus 0.05 microsecond.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.1.5.1.4  Standard	<i>Pulse amplitudes.</i> Relative amplitudes between pulses $P_1$ , $P_2$ and $P_3$ shall be in accordance with 3.1.1.5. The amplitude of $P_4$ shall be within 1 dB of the amplitude of $P_3$ .	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.5.2  Standard	<i>Mode S interrogation.</i> The Mode S interrogation shall consist of three pulses: $P_1$ , $P_2$ and $P_6$ as shown in Figure 3-4. <i>Note.— <math>P_6</math> is preceded by a <math>P_1 - P_2</math> pair which suppresses replies from Mode A/C transponders to avoid synchronous garble due to random triggering by the Mode S interrogation. The sync phase reversal within <math>P_6</math> is the timing mark for demodulation of a series of time intervals (chips) of 0.25 microsecond duration. This series of chips starts 0.5 microsecond after the sync phase reversal and ends 0.5 microsecond before the trailing edge of <math>P_6</math>. A phase reversal may or may not precede each chip to encode its binary information value.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.5.2.1  Standard	<i>Mode S side-lobe suppression.</i> The $P_5$ pulse shall be used with the Mode S-only all-call interrogation (UF = 11, see 3.1.2.5.2) to prevent replies from aircraft in the side and back lobes of the antenna (3.1.2.1.5.2.5). When used, $P_5$ shall be transmitted using a separate antenna pattern. <i>N1.The action of <math>P_5</math> is automatic. Its presence, if of sufficient amplitude at the receiving location, masks the sync phase reversal of <math>P_6</math>.</i> <i>N2.The <math>P_5</math> pulse may be used with other Mode S interrogations.</i>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.1.5.2.2  Standard	<i>Sync phase reversal.</i> The first phase reversal in the $P_6$ pulse shall be the sync phase reversal. It shall be the timing reference for subsequent transponder operations related to the interrogation.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.5.2.3  Standard	<i>Data phase reversals.</i> Each data phase reversal shall occur only at a time interval (N times 0.25) plus or minus 0.02 microsecond (N equal to, or greater than 2) after the sync phase reversal. The 16.25-microsecond $P_6$ pulse shall contain at most 56 data phase reversals. The 30.25-microsecond $P_6$ pulse shall contain at most 112 data phase reversals. The last chip, that is the 0.25-microsecond time interval following the last data phase reversal position, shall be followed by a 0.5-microsecond guard interval.  <i>Note.— The 0.5 microsecond guard interval following the last chip prevents the trailing edge of <math>P_6</math>, from interfering with the demodulation process.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.1.5.2.4  Standard	<i>Intervals.</i> The pulse interval between $P_1$ and $P_2$ shall be 2 plus or minus 0.05 microsecond. The interval between the leading edge of $P_2$ and the sync phase reversal of $P_6$ shall be 2.75 plus or minus 0.05 microsecond. The leading edge of $P_6$ shall occur 1.25 plus or minus 0.05 microsecond before the sync phase reversal. $P_5$ , if transmitted, shall be centred over the sync phase reversal; the leading edge of $P_5$ shall occur 0.4 plus or minus 0.05 microsecond before the sync phase reversal.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.1.5.2.5  Standard	<i>Pulse amplitudes.</i> The amplitude of $P_2$ and the amplitude of the first microsecond of $P_6$ shall be greater than the amplitude of $P_1$ minus 0.25 dB. Exclusive of the amplitude transients associated with phase reversals, the amplitude variation of $P_6$ shall be less than 1 dB and the amplitude variation between successive chips in $P_6$ shall be less than 0.25 dB. The radiated amplitude of $P_5$ at the antenna of the transponder shall be: a) equal to or greater than the radiated amplitude of $P_6$ from the side-lobe transmissions of the antenna radiating $P_6$ ; and b) at a level lower than 9 dB below the radiated amplitude of $P_6$ within the desired arc of interrogation.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.2.1  Standard	3.1.2.2 REPLY SIGNALS-IN-SPACE CHARACTERISTICS  <i>Reply carrier frequency.</i> The carrier frequency of all replies (downlink transmissions) from transponders with Mode S capabilities shall be 1 090 plus or minus 1 MHz.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.2.2  Standard	<i>Reply spectrum.</i> The spectrum of a Mode S reply about the carrier frequency shall not exceed the limits specified in Figure 3-5.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.2.3  Standard	<i>Polarization.</i> Polarization of the reply transmissions shall be nominally vertical.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.2.4  Standard	<i>Modulation.</i> The Mode S reply shall consist of a preamble and a data block. The preamble shall be a 4-pulse sequence and the data block shall be binary pulse-position modulated at a 1 megabit per second data rate.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.2.4.1  Standard	<i>Pulse shapes.</i> Pulse shapes shall be as defined in Table 3-2. All values are in microseconds.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.2.5  Standard	<i>Mode S reply.</i> The Mode S reply shall be as shown in Figure 3-6. The data block in Mode S replies shall consist of either 56 or 112 information bits.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.2.5.1  Standard	<i>Pulse intervals.</i> All reply pulses shall start at a defined multiple of 0.5 microsecond from the first transmitted pulse. The tolerance in all cases shall be plus or minus 0.05 microsecond.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.2.5.1.1  Standard	<i>Reply preamble.</i> The preamble shall consist of four pulses, each with a duration of 0.5 microsecond. The pulse intervals from the first transmitted pulse to the second, third and fourth transmitted pulses shall be 1, 3.5 and 4.5 microseconds, respectively.	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.2.5.1.2  Standard	<i>Reply data pulses.</i> The reply data block shall begin 8 microseconds after the leading edge of the first transmitted pulse. Either 56 or 112 one-microsecond bit intervals shall be assigned to each transmission. A 0.5-microsecond pulse shall be transmitted either in the first or in the second half of each interval. When a pulse transmitted in the second half of one interval is followed by another pulse transmitted in the first half of the next interval, the two pulses merge and a one-microsecond pulse shall be transmitted.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.2.5.2  Standard	<i>Pulse amplitudes.</i> The pulse amplitude variation between one pulse and any other pulse in a Mode S reply shall not exceed 2 dB.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.3.1.1  Standard	3.1.2.3 MODE S DATA STRUCTURE  3.1.2.3.1 DATA ENCODING  <i>Interrogation data.</i> The interrogation data block shall consist of the sequence of 56 or 112 data chips positioned after the data phase reversals within $P_6$ (3.1.2.1.5.2.3). A 180-degree carrier phase reversal preceding a chip shall characterize that chip as a binary ONE. The absence of a preceding phase reversal shall denote a binary ZERO.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.3.1.2  Standard	<i>Reply data.</i> The reply data block shall consist of 56 or 112 data bits formed by binary pulse position modulation encoding of the reply data as described in 3.1.2.2.5.1.2. A pulse transmitted in the first half of the interval shall represent a binary ONE whereas a pulse transmitted in the second half shall represent a binary ZERO.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.3.1.3  Standard	<p><i>Bit numbering.</i> The bits shall be numbered in the order of their transmission, beginning with bit 1. Unless otherwise stated, numerical values encoded by groups (fields) of bits shall be encoded using positive binary notation and the first bit transmitted shall be the most significant bit (MSB). Information shall be coded in fields which consist of at least one bit.</p> <p><i>Note.— In the description of Mode S formats the decimal equivalent of the binary code formed by the bit sequence within a field is used as the designator of the field function or command.</i></p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.3.2.1</p> <p>Standard</p>	<p><i>3.1.2.3.2 FORMATS OF MODE S INTERROGATIONS AND REPLIES</i></p> <p><i>Note.— A summary of all Mode S interrogation and reply formats is presented in Figures 3-7 and 3-8. A summary of all fields appearing in uplink and downlink formats is given in Table 3-3 and a summary of all subfields is given in Table 3-4.</i></p> <p><i>Essential fields.</i> Every Mode S transmission shall contain two essential fields. One is a descriptor which shall uniquely define the format of the transmission. This shall appear at the beginning of the transmission for all formats. The descriptors are designated by the UF (uplink format) or DF (downlink format) fields. The second essential field shall be a 24-bit field appearing at the end of each transmission and shall contain parity information. In all uplink and in currently defined downlink formats parity information shall be overlaid either on the aircraft address (3.1.2.4.1.2.3.1) or on the interrogator identifier according to 3.1.2.3.3.2. The designators are AP (address/parity) or PI (parity/interrogator identifier).</p> <p><i>Note.— The remaining coding space is used to transmit the mission fields. For specific functions, a specific set of mission fields is prescribed. Mode S mission fields have two-letter designators. Subfields may appear within mission fields. Mode S subfields are labelled with three-letter designators.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.3.2.1.1</p> <p>Standard</p>	<p><i>UF: Uplink format.</i> This uplink format field (5 bits long except in format 24 where it is 2 bits long) shall serve as the uplink format descriptor in all Mode S interrogations and shall be coded according to Figure 3-7.</p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.3.2.1.2  Standard	<i>DF: Downlink format.</i> This downlink format field (5 bits long except in format 24 where it is 2 bits long) shall serve as the downlink format descriptor in all Mode S replies and shall be coded according to Figure 3-8.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.3.2.1.3  Standard	<i>AP: Address/parity.</i> This 24-bit (33-56 or 89-112) field shall appear in all uplink and currently defined downlink formats except the Mode S-only all-call reply, DF = 11. The field shall contain parity overlaid on the aircraft address according to 3.1.2.3.3.2.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.3.2.1.4  Standard	<i>PI: Parity/interrogator identifier.</i> This 24-bit (33-56) or (89-112) downlink field shall have parity overlaid on the interrogator's identity code according to 3.1.2.3.3.2 and shall appear in the Mode S all-call reply, DF = 11 and in the extended squitter, DF = 17 or DF = 18. If the reply is made in response to a Mode A/C/S all-call, a Mode S-only all-call with CL field (3.1.2.5.2.1.3) and IC field (3.1.2.5.2.1.2) equal to 0, or is an acquisition or an extended squitter (3.1.2.8.5, 3.1.2.8.6 or 3.1.2.8.7), the II and the SI codes shall be 0.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																												
Chapter 3 Reference 3.1.2.3.2.1.5  Standard	<p><i>DP: Data parity.</i> This 24-bit (89-112) downlink field shall contain the parity overlaid on a “Modified AA” field which is established by performing a modulo-2 summation (e.g. Exclusive-Or function ) of the discrete address most significant 8 bits and BDS1, BDS2 where BDS1 (3.1.2.6.11.2.2) and BDS2 (3.1.2.6.11.2.3) are provided by the “RR” (3.1.2.6.1.2) and “RRS” (3.1.2.6.1.4.1) as specified in 3.1.2.6.11.2.2 and 3.1.2.6.11.2.3.</p> <p>Example:</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 20%;">Discrete Address</td> <td style="width: 10%;">=</td> <td style="width: 40%;">AA AA AA Hex</td> <td style="width: 10%;">=</td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td></td> <td>1010 1010</td> <td></td> <td>1010</td> </tr> <tr> <td></td> <td></td> <td>1010 1010</td> <td></td> <td>1010</td> </tr> <tr> <td>BDS1,BDS2</td> <td>=</td> <td>5F 00 00 Hex</td> <td>=</td> <td></td> </tr> <tr> <td></td> <td></td> <td>0101 1111</td> <td></td> <td>0000</td> </tr> <tr> <td></td> <td></td> <td>0000 0000</td> <td></td> <td>0000</td> </tr> <tr> <td>Discrete address</td> <td>⊕</td> <td>BDS1, BDS2 Hex</td> <td>=</td> <td></td> </tr> <tr> <td></td> <td></td> <td>1111 0101</td> <td></td> <td>1010</td> </tr> <tr> <td></td> <td></td> <td>1010 1010</td> <td></td> <td>1010</td> </tr> <tr> <td>“Modified AA”</td> <td>=</td> <td>F5 AA AA Hex</td> <td>=</td> <td></td> </tr> <tr> <td></td> <td></td> <td>1111 0101</td> <td></td> <td>1010</td> </tr> <tr> <td></td> <td></td> <td>1010 1010</td> <td></td> <td>1010</td> </tr> </table> <p>where “⊕” prescribes modulo-2 addition The resulting “Modified AA” field then represents the 24 bit sequence (a1, a2...a24) that shall be used to generate the DP field in accordance with paragraph 3.1.2.3.3.2. The DP field shall be used in DF=20 and DF=21 replies if the transponder is capable of supporting the DP field and if the overlay control (OVC - 3.1.2.6.1.4.1.i) bit is set to one (1) in the interrogation requesting downlink of GICB registers.</p>	Discrete Address	=	AA AA AA Hex	=				1010 1010		1010			1010 1010		1010	BDS1,BDS2	=	5F 00 00 Hex	=				0101 1111		0000			0000 0000		0000	Discrete address	⊕	BDS1, BDS2 Hex	=				1111 0101		1010			1010 1010		1010	“Modified AA”	=	F5 AA AA Hex	=				1111 0101		1010			1010 1010		1010	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Discrete Address	=	AA AA AA Hex	=																																																														
		1010 1010		1010																																																													
		1010 1010		1010																																																													
BDS1,BDS2	=	5F 00 00 Hex	=																																																														
		0101 1111		0000																																																													
		0000 0000		0000																																																													
Discrete address	⊕	BDS1, BDS2 Hex	=																																																														
		1111 0101		1010																																																													
		1010 1010		1010																																																													
“Modified AA”	=	F5 AA AA Hex	=																																																														
		1111 0101		1010																																																													
		1010 1010		1010																																																													



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.3.2.2  Standard	<i>Unassigned coding space.</i> Unassigned coding space shall contain all ZEROs as transmitted by interrogators and transponders. <i>Note.— Certain coding space indicated as unassigned in this section is reserved for other applications such as ACAS, data link, etc.</i>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.3.2.3  Standard	<i>Zero and unassigned codes.</i> A zero code assignment in all defined fields shall indicate that no action is required by the field. In addition, codes not assigned within the fields shall indicate that no action is required. <i>Note.— The provisions of 3.1.2.3.2.2 and 3.1.2.3.2.3 ensure that future assignments of previously unassigned coding space will not result in ambiguity. That is, Mode S equipment in which the new coding has not been implemented will clearly indicate that no information is being transmitted in newly assigned coding space.</i>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.3.2.4  Standard	<i>Formats reserved for military use.</i> States shall ensure that uplink formats are only used for selectively addressed interrogations and that transmissions of uplink or downlink formats do not exceed the RF power, interrogation rate, reply rate and squitter rate requirements of Annex 10.	CAR 171.53(a)(1).	No Difference		Note: the service provider for both military and civil operations is the same.
Chapter 3 Reference 3.1.2.3.2.4.1  Recommendation	<b>Recommendation.—</b> <i>Through investigation and validation, States should ensure that military applications do not unduly affect the existing 1 030/1 090 MHz civil aviation operations environment.</i>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.3.3.1  Standard	<b>3.1.2.3.3 ERROR PROTECTION</b>  <i>Technique.</i> Parity check coding shall be used within Mode S interrogations and replies to provide protection against the occurrence of errors.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.3.3.1.1  Standard	<i>Parity check sequence.</i> A sequence of 24 parity check bits shall be generated by the rule described in 3.1.2.3.3.1.2 and shall be incorporated into the field formed by the last 24 bits of all Mode S transmissions. The 24 parity check bits shall be combined with either the address coding or the interrogator identifier coding as described in 3.1.2.3.3.2. The resulting combination then forms either the AP (address/parity, 3.1.2.3.2.1.3) field or the PI (parity/interrogator identifier, 3.1.2.3.2.1.4) field.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.3.3.1.2</p> <p>Standard</p>	<p><i>Parity check sequence generation.</i> The sequence of 24 parity bits (<math>p_1, p_2, \dots, p_{24}</math>) shall be generated from the sequence of information bits (<math>m_1, m_2, \dots, m_k</math>) where <math>k</math> is 32 or 88 for short or long transmissions respectively. This shall be done by means of a code generated by the polynomial:</p> $G(x) = 1 + x^3 + x^{10} + x^{12} + x^{13} + x^{14} + x^{15} + x^{16} + x^{17} + x^{18} + x^{19} + x^{20} + x^{21} + x^{22} + x^{23} + x^{24}$ <p>When by the application of binary polynomial algebra, <math>x^{24} [M(x)]</math> is divided by <math>G(x)</math> where the information sequence <math>M(x)</math> is:</p> $m_k + m_{k-1}x + m_{k-2}x^2 + \dots + m_1x^{k-1}$ <p>the result is a quotient and a remainder <math>R(x)</math> of degree less than 24. The bit sequence formed by this remainder represents the parity check sequence. Parity bit <math>p_i</math>, for any <math>i</math> from 1 to 24, is the coefficient of <math>x^{24-i}</math> in <math>R(x)</math>.</p> <p><i>Note.— The effect of multiplying <math>M(x)</math> by <math>x^{24}</math> is to append 24 ZERO bits to the end of the sequence.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.3.3.2  Standard	<p><i>AP and PI field generation.</i> Different address parity sequences shall be used for the uplink and downlink.</p> <p><i>Note.— The uplink sequence is appropriate for a transponder decoder implementation. The downlink sequence facilitates the use of error correction in downlink decoding.</i></p> <p>The code used in uplink AP field generation shall be formed as specified below from either the aircraft address (3.1.2.4.1.2.3.1.1), the all-call address (3.1.2.4.1.2.3.1.2) or the broadcast address (3.1.2.4.1.2.3.1.3).</p> <p>The code used in downlink AP field generation shall be formed directly from the sequence of 24 Mode S address bits (<math>a_1, a_2, \dots, a_{24}</math>), where <math>a_i</math> is the <math>i</math>-th bit transmitted in the aircraft address (AA) field of an all-call reply (3.1.2.5.2.2.2).</p> <p>The code used in downlink PI field generation shall be formed by a sequence of 24 bits (<math>a_1, a_2, \dots, a_{24}</math>), where the first 17 bits are ZEROS, the next three bits are a replica of the code label (CL) field (3.1.2.5.2.1.3) and the last four bits are a replica of the interrogator code (IC) field (3.1.2.5.2.1.2).</p> <p><i>Note.— The PI code is not used in uplink transmissions.</i></p> <p>A modified sequence (<math>b_1, b_2, \dots, b_{24}</math>) shall be used for uplink AP field generation. Bit <math>b_i</math> is the coefficient of <math>x^{48-i}</math> in the polynomial <math>G(x)A(x)</math>, where:</p> $A(x) = a_1x^{23} + a_2x^{22} + \dots + a_{24}$ <p>and <math>G(x)</math> is as defined in 3.1.2.3.3.1.2.</p> <p>In the aircraft address <math>a_i</math> shall be the <math>i</math>-th bit transmitted in the AA field of an all-call reply. In the all-call and broadcast addresses <math>a_i</math> shall equal 1 for all values of <math>i</math>.</p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.3.3.2.1  Standard	<p><i>Uplink transmission order.</i> The sequence of bits transmitted in the uplink AP field is:</p> $t_{k+1}, t_{k+2} \dots t_{k+24}$ <p>where the bits are numbered in order of transmission, starting with <math>k + 1</math>.</p> <p>In uplink transmissions:</p> $t_{k+i} = b_i \oplus p_i$ <p>where “<math>\oplus</math>” prescribes modulo-2 addition; <math>i</math> equals 1 is the first bit transmitted in the AP field.</p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.3.3.2.2  Standard	<p><i>Downlink transmission order.</i> The sequence of bits transmitted in the downlink AP and PI field is:</p> $t_{k+1}, t_{k+2} \dots t_{k+24}$ <p>where the bits are numbered in order of transmission, starting with <math>k + 1</math>. In downlink transmissions:</p> $t_{k+i} = a_i \oplus p_i$ <p>where “<math>\oplus</math>” prescribes modulo-2 addition; <math>i</math> equals 1 is the first bit transmitted in the AP or PI field.</p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.1  Standard	<p>3.1.2.4 GENERAL INTERROGATION-REPLY PROTOCOL</p> <p><i>Transponder transaction cycle.</i> A transponder transaction cycle shall begin when the SSR Mode S transponder has recognized an interrogation. The transponder shall then evaluate the interrogation and determine whether it shall be accepted. If accepted, it shall then process the received interrogation and generate a reply, if appropriate. The transaction cycle shall end when:</p> <ul style="list-style-type: none"> <li>a) any one of the necessary conditions for acceptance has not been met, or</li> <li>b) an interrogation has been accepted and the transponder has either: <ul style="list-style-type: none"> <li>1) completed the processing of the accepted interrogation if no reply is required, or</li> <li>2) completed the transmission of a reply.</li> </ul> </li> </ul> <p>A new transponder transaction cycle shall not begin until the previous cycle has ended.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.1  Standard	<p><i>Interrogation recognition.</i> SSR Mode S transponders shall be capable of recognizing the following distinct types of interrogations:</p> <ul style="list-style-type: none"> <li>a) Modes A and C;</li> <li>b) intermode; and</li> <li>c) Mode S.</li> </ul> <p><i>Note.— The recognition process is dependent upon the signal input level and the specified dynamic range (3.1.2.10.1).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.4.1.1.1</p> <p>Standard</p>	<p><i>Mode A and Mode C interrogation recognition.</i> A Mode A or Mode C interrogation shall be recognized when a <math>P_1 - P_3</math> pulse pair meeting the requirements of 3.1.1.4 has been received, and the leading edge of a <math>P_4</math> pulse with an amplitude that is greater than a level 6 dB below the amplitude of <math>P_3</math> is not received within the interval from 1.7 to 2.3 microseconds following the leading edge of <math>P_3</math>.</p> <p>If a <math>P_1 - P_2</math> suppression pair and a Mode A or Mode C interrogation are recognized simultaneously, the transponder shall be suppressed. An interrogation shall not be recognized as Mode A or Mode C if the transponder is in suppression (3.1.2.4.2). If a Mode A and a Mode C interrogation are recognized simultaneously the transponder shall complete the transaction cycle as if only a Mode C interrogation had been recognized.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.4.1.1.2</p> <p>Standard</p>	<p><i>Intermode interrogation recognition.</i> An intermode interrogation shall be recognized when a <math>P_1 - P_3 - P_4</math> pulse triplet meeting the requirements of 3.1.2.1.5.1 is received. An interrogation shall not be recognized as an intermode interrogation if:</p> <ul style="list-style-type: none"> <li>a) the received amplitude of the pulse in the <math>P_4</math> position is smaller than 6 dB below the amplitude of <math>P_3</math>; or</li> <li>b) the pulse interval between <math>P_3</math> and <math>P_4</math> is larger than 2.3 microseconds or shorter than 1.7 microseconds; or</li> <li>c) the received amplitude of <math>P_1</math> and <math>P_3</math> is between MTL and -45 dBm and the pulse duration of <math>P_1</math> or <math>P_3</math> is less than 0.3 microsecond; or</li> <li>d) the transponder is in suppression (3.1.2.4.2).</li> </ul> <p>If a <math>P_1 - P_2</math> suppression pair and a Mode A or Mode C intermode interrogation are recognized simultaneously the transponder shall be suppressed.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.1.1.3  Standard	<i>Mode S interrogation recognition.</i> A Mode S interrogation shall be recognized when a $P_6$ pulse is received with a sync phase reversal within the interval from 1.20 to 1.30 microseconds following the leading edge of $P_6$ . A Mode S interrogation shall not be recognized if a sync phase reversal is not received within the interval from 1.05 to 1.45 microseconds following the leading edge of $P_6$ .	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.2  Standard	<i>Interrogation acceptance.</i> Recognition according to 3.1.2.4.1 shall be a prerequisite for acceptance of any interrogation.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.2.1  Standard	<i>Mode A and Mode C interrogation acceptance.</i> Mode A and Mode C interrogations shall be accepted when recognized (3.1.2.4.1.1.1).	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.2.2.1  Standard	<i>3.1.2.4.1.2.2 Intermode interrogation acceptance</i>  <i>Mode A/C/S all-call interrogation acceptance.</i> A Mode A/C/S all-call interrogation shall be accepted if the trailing edge of $P_4$ is received within 3.45 to 3.75 microseconds following the leading edge of $P_3$ and no lockout condition (3.1.2.6.9) prevents acceptance. A Mode A/C/S all-call shall not be accepted if the trailing edge of $P_4$ is received earlier than 3.3 or later than 4.2 microseconds following the leading edge of $P_3$ , or if a lockout condition (3.1.2.6.9) prevents acceptance.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.1.2.2.2  Standard	<p><i>Mode A/C-only all-call interrogation acceptance.</i> A Mode A/C-only all-call interrogation shall not be accepted by a Mode S transponder.</p> <p><i>Note.— The technical condition for non-acceptance of a Mode A/C-only all-call is given in the preceding paragraph by the requirement for rejecting an intermode interrogation with a P<sub>4</sub> pulse having a trailing edge following the leading edge of P<sub>3</sub> by less than 3.3 microseconds.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.2.3  Standard	<p><i>Mode S interrogation acceptance.</i> A Mode S interrogation shall only be accepted if:</p> <ul style="list-style-type: none"> <li>a) the transponder is capable of processing the uplink format (UF) of the interrogation (3.1.2.3.2.1.1);</li> <li>b) the address of the interrogation matches one of the addresses as defined in 3.1.2.4.1.2.3.1 implying that parity is established, as defined in 3.1.2.3.3;</li> <li>c) in the case of an all-call interrogation, no all-call lockout condition applies, as defined in 3.1.2.6.9; and</li> <li>d) the transponder is capable of processing the uplinked data of a long air-air surveillance (ACAS) interrogation (UF-16) and presenting it at an output interface as prescribed in 3.1.2.10.5.2.2.1.</li> </ul> <p><i>Note.— A Mode S interrogation may be accepted if the conditions specified in 3.1.2.4.1.2.3 a) and b) are met and the transponder is not capable of both processing the uplinked data of a Comm-A interrogation (UF=20 and 21) and presenting it at an output interface as prescribed in 3.1.2.10.5.2.2.1.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.2.3.1  Standard	<p><i>Addresses.</i> Mode S interrogations shall contain either:</p> <ul style="list-style-type: none"> <li>a) aircraft address; or</li> <li>b) the all-call address; or</li> <li>c) the broadcast address.</li> </ul>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.1.2.3.1.1  Standard	<i>Aircraft address.</i> If the aircraft's address is identical to the address extracted from a received interrogation according to the procedure of 3.1.2.3.3.2 and 3.1.2.3.3.2.1, the extracted address shall be considered correct for purposes of Mode S interrogation acceptance.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.2.3.1.2  Standard	<i>All-call address.</i> A Mode S-only all-call interrogation (uplink format UF = 11) shall contain an address, designated the all-call address, consisting of twenty-four consecutive ONEs. If the all-call address is extracted from a received interrogation with format UF = 11 according to the procedure of 3.1.2.3.3.2 and 3.1.2.3.3.2.1, the address shall be considered correct for Mode S-only all-call interrogation acceptance.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.2.3.1.3  Standard	<i>Broadcast address.</i> To broadcast a message to all Mode S transponders within the interrogator beam, a Mode S interrogation uplink format 20 or 21 shall be used and an address of twenty-four consecutive ONEs shall be substituted for the aircraft address. If the UF code is 20 or 21 and this broadcast address is extracted from a received interrogation according to the procedure of 3.1.2.3.3.2 and 3.1.2.3.3.2.1, the address shall be considered correct for Mode S broadcast interrogation acceptance.  <i>Note.— Transponders associated with airborne collision avoidance systems also accept a broadcast with UF = 16.</i>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.3  Standard	<i>Transponder replies.</i> Mode S transponders shall transmit the following reply types: a) Mode A and Mode C replies; and b) Mode S replies.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.1.3.1  Standard	<i>Mode A and Mode C replies.</i> A Mode A (Mode C) reply shall be transmitted as specified in 3.1.1.6 when a Mode A (Mode C) interrogation has been accepted.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.3.2  Standard	<i>Mode S replies.</i> Replies to other than Mode A and Mode C interrogations shall be Mode S replies.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.3.2.1  Standard	<i>Replies to intermode interrogations.</i> A Mode S reply with downlink format 11 shall be transmitted in accordance with the provisions of 3.1.2.5.2.2 when a Mode A/C/S all-call interrogation has been accepted. Equipment certified on or after 1 January 2020 shall not reply to Intermode Mode A/C/S all-call interrogations. <i>Note.— Since Mode S transponders do not accept Mode A/C-only all-call interrogations, no reply is generated.</i>	CAR Part 91 Appendix A, A.22.	No Difference		The 2020 provision has yet to be addressed.





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.1.3.2.2  Standard	<p><i>Replies to Mode S interrogations.</i> The information content of a Mode S reply shall reflect the conditions existing in the transponder after completion of all processing of the interrogation eliciting that reply. The correspondence between uplink and downlink formats shall be as summarized in Table 3-5.</p> <p><i>Note.— Four categories of Mode S replies may be transmitted in response to Mode S interrogations:</i></p> <ul style="list-style-type: none"> <li>a) <i>Mode S all-call replies (DF = 11);</i></li> <li>b) <i>surveillance and standard-length communications replied (DF = 4, 5, 20 and 21);</i></li> <li>c) <i>extended length communications replies (DF = 24); and</i></li> <li>d) <i>air-air surveillance replies (DF=0 and 16).</i></li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.3.2.2.1  Standard	<p><i>Replies to SSR Mode S-only all-call interrogations.</i> The downlink format of the reply to a Mode S-only all-call interrogation (if required) shall be DF = 11. The reply content and rules for determining the requirement to reply shall be as defined in 3.1.2.5.</p> <p><i>Note.— A Mode S reply may or may not be transmitted when a Mode S interrogation with UF = 11 has been accepted.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.3.2.2.2  Standard	<p><i>Replies to surveillance and standard length communications interrogations.</i> A Mode S reply shall be transmitted when a Mode S interrogation with UF = 4, 5, 20 or 21 and an aircraft address has been accepted. The contents of these interrogations and replies shall be as defined in 3.1.2.6.</p> <p><i>Note.— If a Mode S interrogation with UF = 20 or 21 and a broadcast address is accepted, no reply is transmitted (3.1.2.4.1.2.3.1.3).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.1.3.2.2.3  Standard	<i>Replies to extended length communications interrogations.</i> A series of Mode S replies ranging in number from 0 to 16 shall be transmitted when a Mode S interrogation with UF = 24 has been accepted. The downlink format of the reply (if any) shall be DF = 24. Protocols defining the number and content of the replies shall be as defined in 3.1.2.7.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.1.3.2.2.4  Standard	<i>Replies to air-air surveillance interrogations.</i> A Mode S reply shall be transmitted when a Mode S interrogation with UF = 0 and an aircraft address has been accepted. The contents of these interrogations and replies shall be as defined in 3.1.2.8.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.2.1  Standard	3.1.2.4.2 SUPPRESSION  <i>Effects of suppression.</i> A transponder in suppression (3.1.1.7.4) shall not recognize Mode A, Mode C or intermode interrogations if either the $P_1$ pulse alone or both the $P_1$ and $P_3$ pulses of the interrogation are received during the suppression interval. Suppression shall not affect the recognition of, acceptance of, or replies to Mode S interrogations.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.4.2.2  Standard	<i>Suppression pairs.</i> The two-pulse Mode A/C suppression pair defined in 3.1.1.7.4.1 shall initiate suppression in a Mode S transponder regardless of the position of the pulse pair in a group of pulses, provided the transponder is not already suppressed or in a transaction cycle.  <i>Note.— The <math>P_3 - P_4</math> pair of the Mode A/C-only all-call interrogation both prevents a reply and initiates suppression. Likewise, the <math>P_1 - P_2</math> preamble of a Mode S interrogation initiates suppression independently of the waveform that follows it.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.4.2.3  Standard	Suppression in presence of <i>S<sub>i</sub></i> pulse shall be as defined in 3.1.1.7.4.3.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.5.1  Note	<p>3.1.2.5 INTERMODE AND MODE S ALL-CALL TRANSACTIONS</p> <p><i>INTERMODE TRANSACTIONS</i></p> <p><i>Note.— Intermode transactions permit the surveillance of Mode A/C-only aircraft and the acquisition of Mode S aircraft. The Mode A/C/S all-call interrogation allows Mode A/C-only and Mode S transponders to be interrogated by the same transmissions. The Mode A/C-only all-call interrogation makes it possible to elicit replies only from Mode A/C transponders. In multisite scenarios, the interrogator must transmit its identifier code in the Mode S only all-call interrogation. Thus, a pair of Mode S-only and Mode A/C-only all-call interrogations are used. The intermode interrogations are defined in 3.1.2.1.5.1 and the corresponding interrogation-reply protocols are defined in 3.1.2.4.</i></p>		Not Applicable		Compliance data not required fro Notes.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																	
Chapter 3 Reference 3.1.2.5.2.1  Standard	<p>3.1.2.5.2 <i>MODE S-ONLY ALL-CALL TRANSACTIONS</i>  <i>Note.— These transactions allow the ground to acquire Mode S aircraft by use of an interrogation addressed to all Mode S-equipped aircraft. The reply is via downlink format 11 which returns the aircraft address. The interrogation-reply protocols are defined in 3.1.2.4.</i></p> <p><i>Mode S-only all-call transactions, uplink format 11</i></p> <table style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;">1</td> <td style="padding-right: 20px;">6</td> <td style="padding-right: 20px;">10</td> <td style="padding-right: 20px;">14</td> <td>17</td> </tr> <tr> <td></td> <td>33</td> <td></td> <td></td> <td></td> </tr> <tr> <td>UF</td> <td>PR</td> <td>IC</td> <td>CL</td> <td>AP</td> </tr> <tr> <td>5</td> <td>9</td> <td>13</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td>56</td> <td></td> <td></td> <td></td> </tr> </table> <p>The format of this interrogation shall consist of these fields:</p> <table style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;"><i>Field</i></td> <td style="padding-right: 20px;"><i>Ref</i></td> </tr> <tr> <td><i>erence</i></td> <td></td> </tr> <tr> <td>UF uplink format</td> <td>3.1.</td> </tr> <tr> <td>2.3.2.1.1</td> <td></td> </tr> <tr> <td>PR probability of reply</td> <td>3.1.</td> </tr> <tr> <td>2.5.2.1.1</td> <td></td> </tr> <tr> <td>IC interrogator code</td> <td>3.1.</td> </tr> <tr> <td>2.5.2.1.2</td> <td></td> </tr> <tr> <td>CL code label</td> <td>3.1.</td> </tr> <tr> <td>2.5.2.1.3</td> <td></td> </tr> <tr> <td>spare — 16 bits</td> <td></td> </tr> <tr> <td>AP address/parity</td> <td></td> </tr> </table>	1	6	10	14	17		33				UF	PR	IC	CL	AP	5	9	13	16	32		56				<i>Field</i>	<i>Ref</i>	<i>erence</i>		UF uplink format	3.1.	2.3.2.1.1		PR probability of reply	3.1.	2.5.2.1.1		IC interrogator code	3.1.	2.5.2.1.2		CL code label	3.1.	2.5.2.1.3		spare — 16 bits		AP address/parity		CAR 171.53(a)(1).	No Difference		
1	6	10	14	17																																																		
	33																																																					
UF	PR	IC	CL	AP																																																		
5	9	13	16	32																																																		
	56																																																					
<i>Field</i>	<i>Ref</i>																																																					
<i>erence</i>																																																						
UF uplink format	3.1.																																																					
2.3.2.1.1																																																						
PR probability of reply	3.1.																																																					
2.5.2.1.1																																																						
IC interrogator code	3.1.																																																					
2.5.2.1.2																																																						
CL code label	3.1.																																																					
2.5.2.1.3																																																						
spare — 16 bits																																																						
AP address/parity																																																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	3.1.  2.3.2.1.3				
Chapter 3 Reference 3.1.2.5.2.1.1  Standard	<p><i>PR: Probability of reply.</i> This 4-bit (6-9) uplink field shall contain commands to the transponder specifying the probability of reply to that interrogation (3.1.2.5.4). Codes are as follows:</p> <p>0                    signifies reply with probability of 1</p> <p>1                    signifies reply with probability of 1/2</p> <p>2                    signifies reply with probability of 1/4</p> <p>3                    signifies reply with probability of 1/8</p> <p>4                    signifies reply with probability of 1/16</p> <p>5, 6, 7            not assigned</p> <p>8                    signifies disregard lockout, reply with probability of 1</p> <p>9                    signifies disregard lockout, reply with probability of 1/2</p> <p>10                  signifies disregard lockout, reply with probability of 1/4</p> <p>11                  signifies disregard lockout, reply with probability of 1/8</p> <p>12                  signifies disregard lockout, reply with probability of 1/16</p> <p>13, 14, 15        not assigned.</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.5.2.1.2  Standard	<i>IC: Interrogator code.</i> This 4-bit (10-13) uplink field shall contain either the 4-bit interrogator identifier code (3.1.2.5.2.1.2.3) or the lower 4 bits of the 6-bit surveillance identifier code (3.1.2.5.2.1.2.4) depending on the value of the CL field (3.1.2.5.2.1.3).	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.2.1.2.1  Recommendation	<b>Recommendation.</b> — <i>It is recommended that whenever possible an interrogator should operate using a single interrogator code.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.2.1.2.2  Standard	<i>The use of multiple interrogator codes by one interrogator.</i> An interrogator shall not interleave Mode S-only all-call interrogations using different interrogator codes.  <i>Note.</i> — <i>An explanation of RF interference issues, sector size and impact on data link transactions is presented in the Aeronautical Surveillance Manual (Doc 9924).</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.2.1.2.3  Standard	<i>II: Interrogator identifier.</i> This 4-bit value shall define an interrogator identifier (II) code. These II codes shall be assigned to interrogators in the range from 0 to 15. The II code value of 0 shall only be used for supplementary acquisition in conjunction with acquisition based on lockout override (3.1.2.5.2.1.4 and 3.1.2.5.2.1.5). When two II codes are assigned to one interrogator only, one II code shall be used for full data link purposes.  <i>Note.</i> — <i>Limited data link activity including single segment Comm-A, uplink and downlink broadcast protocols and GICB extraction may be performed by both II codes.</i>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.5.2.1.2.4  Standard	<i>SI: Surveillance identifier.</i> This 6-bit value shall define a surveillance identifier (SI) code. These SI codes shall be assigned to interrogators in the range from 1 to 63. The SI code value of 0 shall not be used. The SI codes shall be used with the multisite lockout protocols (3.1.2.6.9.1). The SI codes shall not be used with the multisite communications protocols (3.1.2.6.11.3.2, 3.1.2.7.4 or 3.1.2.7.7).	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.2.1.3  Standard	<i>CL: Code label.</i> This 3-bit (14-16) uplink field shall define the contents of the IC field. <i>Coding (in binary)</i> 000            signifies that the IC field contains the II code 001            signifies that the IC field contains SI codes 1 to 15 010            signifies that the IC field contains SI codes 16 to 31 011            signifies that the IC field contains SI codes 32 to 47 100            signifies that the IC field contains SI codes 48 to 63  The other values of the CL field shall not be used.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.2.1.3.1  Standard	<i>Surveillance identifier (SI) code capability report.</i> Transponders which process the SI codes (3.1.2.5.2.1.2.4) shall report this capability by setting bit 35 to 1 in the surveillance identifier capability (SIC) subfield of the MB field of the data link capability report (3.1.2.6.10.2.2).	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.5.2.1.4.1  Standard	<p>3.1.2.5.2.1.4 Operation based on lockout override</p> <p>N1.The Mode S-only all-call lockout override provides the basis for acquisition of Mode S aircraft for interrogators that have not been assigned a unique IC (II or SI code) for full Mode S operation (protected acquisition by ensuring that no other interrogator on the same IC can lock out the target in the same coverage area).</p> <p>N2.Lockout override is possible using any interrogator code.</p> <p>Maximum Mode S-only all-call interrogation rate. The maximum rate of Mode S-only all-call interrogations made by an interrogator using acquisition based on lockout override shall depend on the reply probability as follows:</p> <ul style="list-style-type: none"> <li>a) for a reply probability equal to 1.0: the smaller of 3 interrogations per 3 dB beam dwell or 30 interrogations per second;</li> <li>b) for a reply probability equal to 0.5: the smaller of 5 interrogations per 3 dB beam dwell or 60 interrogations per second; and</li> <li>c) for a reply probability equal to 0.25 or less: the smaller of 10 interrogations per 3 dB beam dwell or 125 interrogations per second.</li> </ul> <p>Note.— These limits have been defined in order to minimize the RF pollution generated by such a method while keeping a minimum of replies to allow acquisition of aircraft within a beam dwell.</p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.2.1.4.2  Recommendation	<p><b>Recommendation.</b>— Passive acquisition without using all-call interrogations should be used in the place of lockout override.</p> <p>Note.— The Aeronautical Surveillance Manual (Doc 9924) provides guidance on different passive acquisition methods.</p>	CAR 171.53(a)(1).	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3  Reference 3.1.2.5.2.1.4.3  Standard	<p><i>Field content for a selectively addressed interrogation used by an interrogator without an assigned interrogator code.</i> An interrogator that has not been assigned with a unique discrete interrogator code and is authorized to transmit shall use the II code 0 to perform the selective interrogations. In this case, selectively addressed interrogations used in connection with acquisition using lockout override shall have interrogation field contents restricted as follows:</p> <p style="margin-left: 40px;">UF = 4, 5, 20 or 21 PC = 0 RR ≠ 16 if RRS = 0 DI = 7 IIS = 0 LOS = 0 except as specified in 3.1.2.5.2.1.5 TMS = 0</p> <p><i>Note.— These restrictions permit surveillance and GICB transactions, but prevent the interrogation from making any changes to transponder multisite lockout or communications protocol states.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.5.2.1.5.1.1  Recommendation</p>	<p>3.1.2.5.2.1.5 Supplementary acquisition using II equals 0 N1.The acquisition technique defined in 3.1.2.5.2.1.4 provides rapid acquisition for most aircraft. Due to the probabilistic nature of the process, it may take many interrogations to acquire the last aircraft of a large set of aircraft in the same beam dwell and near the same range (termed a local garble zone). Acquisition performance is greatly improved for the acquisition of these aircraft through the use of limited selective lockout using II equals 0. N2.Supplementary acquisition consists of locking out acquired aircraft to II=0 followed by acquisition by means of the Mode S-only all-call interrogation with II=0. Only the aircraft not yet acquired and not yet locked-out will reply resulting in an easier acquisition.  3.1.2.5.2.1.5.1 Lockout within a beam dwell  <b>Recommendation.</b>— When II equals 0 lockout is used to supplement acquisition, all aircraft within the beam dwell of the aircraft being acquired should be commanded to lock out to II equals 0, not just those in the garble zone. Note.— Lockout of all aircraft in the beam dwell will reduce the amount of all-call fruit replies generated to the II equals 0 all-call interrogations.</p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.5.2.1.5.2.1  Recommendation	<p>3.1.2.5.2.1.5.2 <i>Duration of lockout</i></p> <p>Interrogators performing supplementary acquisition using II equals 0 shall perform acquisition by transmitting a lockout command for no more than two consecutive scans to each of the aircraft already acquired in the beam dwell containing the garble zone and shall not repeat it before 48 seconds have elapsed.</p> <p><i>Note.— Minimizing the lockout time reduces the probability of conflict with the acquisition activities of a neighbouring interrogator that is also using II equals 0 for supplementary acquisition.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.2.1.5.2.2  Recommendation	<p><b>Recommendation.—</b> <i>Mode S only all-call interrogations with II = 0 for the purpose of supplementary acquisition should take place within a garble zone over no more than two consecutive scans or a maximum of 18 seconds.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																								
Chapter 3 Reference 3.1.2.5.2.2  Standard	<p><i>All-call reply, downlink format 11</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%; text-align: center;">1</td> <td style="width: 25%; text-align: center;">6</td> <td style="width: 25%; text-align: center;">9</td> <td style="width: 25%; text-align: center;">33</td> </tr> <tr> <td colspan="4" style="text-align: center;">DF CA AA PI</td> </tr> <tr> <td style="text-align: center;">5</td> <td style="text-align: center;">8</td> <td style="text-align: center;">32</td> <td style="text-align: center;">56</td> </tr> </table> <p>The reply to the Mode S-only all-call or the Mode A/C/S all-call interrogation shall be the Mode S all-call reply, downlink format 11. The format of this reply shall consist of these fields:</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><i>Field</i></th> <th style="text-align: left;"><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.</td> </tr> <tr> <td>2 CA capability</td> <td>3.1.2.5.2.2.</td> </tr> <tr> <td>1 AA address announced</td> <td>3.1.2.5.2.2.</td> </tr> <tr> <td>2 PI parity/interrogator identifier</td> <td>3.1.2.3.2.1.</td> </tr> <tr> <td>4</td> <td></td> </tr> </tbody> </table>	1	6	9	33	DF CA AA PI				5	8	32	56	<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.	2 CA capability	3.1.2.5.2.2.	1 AA address announced	3.1.2.5.2.2.	2 PI parity/interrogator identifier	3.1.2.3.2.1.	4		CAR Part 91 Appendix A, A.22.	No Difference		
1	6	9	33																										
DF CA AA PI																													
5	8	32	56																										
<i>Field</i>	<i>Reference</i>																												
DF downlink format	3.1.2.3.2.1.																												
2 CA capability	3.1.2.5.2.2.																												
1 AA address announced	3.1.2.5.2.2.																												
2 PI parity/interrogator identifier	3.1.2.3.2.1.																												
4																													



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.5.2.2.1</p> <p>Standard</p>	<p><i>CA: Capability.</i> This 3-bit (6-8) downlink field shall convey information on the transponder level, the additional information below, and shall be used in formats DF = 11 and DF = 17.</p> <p><i>Coding</i></p> <p>0 signifies Level 1 transponder (surveillance only), and no ability to set CA code 7 and either airborne or on the ground</p> <p>1 reserved</p> <p>2 reserved</p> <p>3 reserved</p> <p>4 signifies Level 2 or above transponder and ability to set CA code 7 and on the ground</p> <p>5 signifies Level 2 or above transponder and ability to set CA code 7 and airborne</p> <p>6 signifies Level 2 or above transponder and ability to set CA code 7 and either airborne or on the ground</p> <p>7 signifies the DR field is not equal to 0 or the FS field equals 2, 3, 4 or 5, and either airborne or on the ground</p> <p>When the conditions for CA code 7 are not satisfied, aircraft with Level 2 or above transponders:</p> <p>a) that do not have automatic means to set the on-the-ground condition shall use CA code 6;</p> <p>b) with automatic on-the-ground determination shall use CA code 4 when on the ground and 5 when airborne; and</p> <p>Data link capability reports (3.1.2.6.10.2.2) shall be available from aircraft installations that set CA code 4, 5, 6 or 7.</p> <p><i>Note.— CA codes 1 to 3 are reserved to maintain backward compatibility.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.5.2.2.2  Standard	<i>AA: Address announced.</i> This 24-bit (9-32) downlink field shall contain the aircraft address which provides unambiguous identification of the aircraft.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.5.3  Standard	<i>Lockout protocol.</i> The all-call lockout protocol defined in 3.1.2.6.9 shall be used by the interrogator with respect to an aircraft once the address of that specific aircraft has been acquired by an interrogator provided that: the interrogator is using an IC code different from zero; and the aircraft is located in an area where the interrogator is authorized to use lockout. <i>N1.Following acquisition, a transponder is interrogated by discretely addressed interrogations as prescribed in 3.1.2.6, 3.1.2.7 and 3.1.2.8 and the all-call lockout protocol is used to inhibit replies to further all-call interrogations.</i> <i>N2.Regional IC allocation bodies may define rules limiting the use of selective interrogation and lockout protocol (e.g. no lockout in defined limited area, use of intermittent lockout in defined areas, and no lockout of aircraft not yet equipped with SI code capability).</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.5.4  Standard	<i>Stochastic all-call protocol.</i> The transponder shall execute a random process upon acceptance of a Mode S-only all-call with a PR code equal to 1 to 4 or 9 to 12. A decision to reply shall be made in accordance with the probability specified in the interrogation. A transponder shall not reply if a PR code equal to 5, 6, 7, 13, 14 or 15 is received (3.1.2.5.2.1.1). <i>Note.— The random occurrence of replies makes it possible for the interrogator to acquire closely spaced aircraft, replies from which would otherwise synchronously garble each other.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																					
Chapter 3  Reference 3.1.2.6.1  Standard	<p>3.1.2.6 ADDRESSED SURVEILLANCE AND STANDARD LENGTH COMMUNICATION TRANSACTIONS</p> <p>N1. <i>The interrogations described in this section are addressed to specific aircraft. There are two basic interrogation and reply types, short and long. The short interrogations and replies are UF 4 and 5 and DF 4 and 5, while the long interrogations and replies are UF 20 and 21 and DF 20 and 21.</i></p> <p>N2. <i>The communications protocols are given in 3.1.2.6.11. These protocols describe the control of the data exchange.</i></p> <p><i>SURVEILLANCE, ALTITUDE REQUEST, UPLINK FORMAT</i></p> <p>4</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;">1</td> <td style="padding-right: 20px;">6</td> <td style="padding-right: 20px;">9</td> <td style="padding-right: 20px;">14</td> <td>17</td> </tr> <tr> <td></td> <td>33</td> <td></td> <td></td> <td></td> </tr> <tr> <td>UF</td> <td>PC</td> <td>RR</td> <td>DI</td> <td>SD AP</td> </tr> <tr> <td>5</td> <td>8</td> <td>13</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td>56</td> <td></td> <td></td> <td></td> </tr> </table> <p>The format of this interrogation shall consist of these fields:</p> <table border="0" style="margin-left: 40px;"> <thead> <tr> <th style="text-align: left;"><i>Field</i></th> <th style="text-align: left;"><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>UF uplink format</td> <td>3.1.2.3.2.1.1</td> </tr> <tr> <td>PC protocol</td> <td>3.1.2.6.1.1</td> </tr> <tr> <td>RR reply request</td> <td>3.1.2.6.1.2</td> </tr> <tr> <td>DI designator identification</td> <td>3.1.2.6.1.3</td> </tr> <tr> <td>SD special designator</td> <td>3.1.2.6.1.4</td> </tr> </tbody> </table>	1	6	9	14	17		33				UF	PC	RR	DI	SD AP	5	8	13	16	32		56				<i>Field</i>	<i>Reference</i>	UF uplink format	3.1.2.3.2.1.1	PC protocol	3.1.2.6.1.1	RR reply request	3.1.2.6.1.2	DI designator identification	3.1.2.6.1.3	SD special designator	3.1.2.6.1.4	CAR 171.53(a)(1).	No Difference		
1	6	9	14	17																																						
	33																																									
UF	PC	RR	DI	SD AP																																						
5	8	13	16	32																																						
	56																																									
<i>Field</i>	<i>Reference</i>																																									
UF uplink format	3.1.2.3.2.1.1																																									
PC protocol	3.1.2.6.1.1																																									
RR reply request	3.1.2.6.1.2																																									
DI designator identification	3.1.2.6.1.3																																									
SD special designator	3.1.2.6.1.4																																									



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	AP address/parity 3.1.2.3.2.1.3				
Chapter 3 Reference 3.1.2.6.1.1  Standard	<p><i>PC: Protocol.</i> This 3-bit, (6-8) uplink field shall contain operating commands to the transponder. The PC field values 2 through 7 shall be ignored and the values 0 and 1 shall be processed for surveillance or Comm-A interrogations containing DI = 3 (3.1.2.6.1.4.1).</p> <p><i>Coding</i></p> <ul style="list-style-type: none"> <li>0 signifies no action</li> <li>1 signifies non-selective all-call lockout (3.1.2.6.9.2)</li> <li>2 not assigned</li> <li>3 not assigned</li> <li>4 signifies close out Comm-B (3.1.2.6.11.3.2.3)</li> <li>5 signifies close out uplink ELM (3.1.2.7.4.2.8)</li> <li>6 signifies close out downlink ELM (3.1.2.7.7.3)</li> <li>7 not assigned.</li> </ul>	CAR 171.53(a)(1).	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.1.2  Standard</p>	<p><i>RR: Reply request.</i> This 5-bit, (9-13) uplink field shall command the length and content of a requested reply. The last four bits of the 5-bit RR code, transformed into their decimal equivalent, shall designate the BDS1 code (3.1.2.6.11.2 or 3.1.2.6.11.3) of the requested Comm-B message if the most significant bit (MSB) of the RR code is 1 (RR is equal to or greater than 16).</p> <p><i>Coding</i></p> <p>RR = 0-15 shall be used to request a reply with surveillance format (DF = 4 or 5);  RR = 16-31 shall be used to request a reply with Comm-B- format (DF = 20 or 21);  RR = 16 shall be used to request transmission of an air-initiated Comm-B according to 3.1.2.6.11.3;  RR = 17 shall be used to request a data link capability report according to 3.1.2.6.10.2.2;  RR = 18 shall be used to request aircraft identification according to 3.1.2.9;  19-31 are not assigned in section 3.1.</p> <p><i>Note.— Codes 19-31 are reserved for applications such as data link communications, airborne collision avoidance systems (ACAS), etc.</i></p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.1.3  Standard	<p><i>DI: Designator identification.</i> This 3-bit (14-16) uplink field shall identify the structure of the SD field (3.1.2.6.1.4).</p> <p><i>Coding</i></p> <p>0 signifies SD not assigned except for ILS, bits 21-27 and 29-32 are not assigned, and bit 28 contains the "OVC" (overlay control - 3.1.2.6.1.4.1.i).</p> <p>1 signifies SD contains multisite and communications control information</p> <p>2 signifies SD contains control data for extended squitter</p> <p>3 signifies SD contains SI multisite lockout, broadcast and GICB control information, and bit 28 contains the "OVC" (overlay control - 3.1.2.6.1.4.1.i).</p> <p>4-6 signifies SD not assigned</p> <p>7 signifies SD contains extended data readout request, multisite and communications control information, and bit 28 contains the "OVC" (overlay control - 3.1.2.6.1.4.1.i).</p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.6.1.4  Standard	<p><i>SD: Special designator.</i> This 16-bit (17-32) uplink field shall contain control codes which depend on the coding in the DI field.</p> <p><i>Note.— The special designator (SD) field is provided to accomplish the transfer of multisite, lockout and communications control information from the ground station to the transponder.</i> <i>(see Annex)</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.1.4.1  Standard</p>	<p><i>Subfields in SD.</i> The SD field shall contain information as follows:</p> <ul style="list-style-type: none"> <li>a) If DI = 0, 1 or 7: IIS, the 4-bit (17-20) interrogator identifier subfield shall contain an assigned identifier code of the interrogator (3.1.2.5.2.1.2.3).</li> <li>b) If DI = 0: bits 21-32 are not assigned.</li> <li>c) If DI = 1: MBS, the 2-bit (21, 22) multisite Comm-B subfield shall have the following codes: 0 signifies no Comm-B action 1 signifies air-initiated Comm-B reservation request (3.1.2.6.11.3.1) 2 signifies Comm-B closeout (3.1.2.6.11.3.2.3) 3 not assigned.</li> </ul> <p>MES, the 3-bit (23-25) multisite ELM subfield shall contain reservation and closeout commands for ELM as follows:</p> <ul style="list-style-type: none"> <li>0 signifies no ELM action</li> <li>1 signifies uplink ELM reservation request (3.1.2.7.4.1)</li> <li>2 signifies uplink ELM closeout (3.1.2.7.4.2.8)</li> <li>3 signifies downlink ELM reservation request (3.1.2.7.7.1.1)</li> <li>4 signifies downlink ELM closeout (3.1.2.7.7.3)</li> <li>5 signifies uplink ELM reservation request and downlink ELM closeout</li> <li>6 signifies uplink ELM closeout and downlink ELM reservation request</li> <li>7 signifies uplink ELM and downlink ELM closeouts.</li> </ul> <p>RSS, the 2-bit (27, 28) reservation status subfield shall request the transponder to report its</p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	<p>AERONAUTICAL TELECOMMUNICATIONS</p> <p>Standard or Recommended Practice</p>	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>reservation status in the UM field. The following codes have been assigned:</p> <p>0 signifies no request</p> <p>1 signifies report Comm-B reservation status in UM</p> <p>2 signifies report uplink ELM reservation status in UM</p> <p>3 signifies report downlink ELM reservation status in UM.</p> <p>d) If DI = 1 or 7: LOS, the 1-bit (26) lockout subfield, if set to 1, shall signify a multisite lockout command from the interrogator indicated in IIS. LOS set to 0, shall be used to signify that no change in lockout state is commanded. TMS, the 4-bit (29-32) tactical message subfield shall contain communications control information used by the data link avionics.</p> <p>e) If DI = 7: RRS, the 4-bit (21-24) reply request subfield in SD shall give the BDS2 code of a requested Comm-B reply. Bits 25, 27 and 28 are not assigned.</p> <p>f) If DI = 2: TCS, the 3-bit (21-23) type control subfield in SD shall control the extended squitter airborne and surface format types reported by the transponder and its response to Mode A/C, Mode A/C/S all-call and Mode S-only all-call interrogations. The following codes have been assigned:</p> <p>0 signifies no surface format type or reply inhibit command</p> <p>1 signifies surface format types for the next 15 seconds (see 3.1.2.6.1.4.2)</p> <p>2 signifies surface format types for the next 60</p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>seconds (see 3.1.2.6.1.4.3) 3 signifies cancel surface format types and reply inhibit commands 4-7 reserved.</p> <p>The transponder shall be able to accept a new command even though a prior command has not as yet timed out. RCS, the 3-bit (24-26) rate control subfield in SD shall control the squitter rate of the transponder when it is reporting the extended squitter surface type formats. This subfield shall have no effect on the transponder squitter rate when it is reporting the extended squitter airborne type formats. The following codes have been assigned: 0 signifies no surface extended squitter rate command 1 signifies report high surface extended squitter rate for 60 seconds 2 signifies report low surface extended squitter rate for 60 seconds 3-7 reserved.</p> <p><i>N1. The definition of high and low extended squitter rates is given in 3.1.2.8.6.4 and applies to the surface position, aircraft identification and category, and the operational status messages.</i> <i>N2. As stated in 3.1.2.8.5.2 d), acquisition squitters are transmitted when surface type format extended squitters are not being transmitted.</i></p> <p>SAS, the 2-bit (27-28) surface antenna subfield in SD shall control the selection of the transponder diversity antenna that is used for (1) the extended squitter when the transponder is reporting the surface type formats, and (2) the acquisition squitter when the transponder is reporting the on-the-ground</p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>status. This subfield shall have no effect on the transponder diversity antenna selection when it is reporting the airborne status. The following codes have been assigned:</p> <ul style="list-style-type: none"> <li>0 signifies no antenna command</li> <li>1 signifies alternate top and bottom antennas for 120 seconds</li> <li>2 signifies use bottom antenna for 120 seconds</li> <li>3 signifies return to the default.</li> </ul> <p><i>Note.— The top antenna is the default condition (3.1.2.8.6.5).</i></p> <p>g) If DI = 3: SIS, the 6-bit (17-22) surveillance identifier subfield in SD shall contain an assigned surveillance identifier code of the interrogator (3.1.2.5.2.1.2.4). LSS, the 1-bit (23) lockout surveillance subfield, if set to 1, shall signify a multisite lockout command from the interrogator indicated in SIS. If set to 0, LSS shall signify that no change in lockout state is commanded. RRS, the 4-bit (24-27) reply request subfield in SD shall contain the BDS2 code of a requested GICB register. Bits 28 to 32 are not assigned.</p> <p>h) If DI=4, 5 or 6 then the SD field has no meaning and shall not impact other transaction cycle protocols. These DI codes remain reserved until future assignment of the SD field.</p> <p>i) If DI = 0, 3, or 7; In addition to the requirements provided above, the “SD” shall contain the following; “OVC”: The 1-bit (bit 28) “overlay control” subfield in “SD” is used by the interrogator to command that the data parity (“DP” 3.1.2.3.2.1.5) be overlaid upon the resulting reply to the interrogation in accordance with paragraph 3.1.2.6.11.2.5.</p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3  Reference 3.1.2.6.1.4.2  Standard	<p><i>TCS subfield equal to one (1) in the SD field for extended squitters.</i> When the TCS subfield in the SD field is set equal to one (1), it shall signify the following:</p> <ul style="list-style-type: none"> <li>a) broadcast of the extended surface formats, including the surface position message (3.1.2.8.6.4.3), the identification and category message (3.1.2.8.6.4.4), the aircraft operational status message (3.1.2.8.6.4.6) and the aircraft status message (3.1.2.8.6.4.6) for the next 15 seconds at the appropriate rates on the top antenna for aircraft systems having the antenna diversity capability, except if otherwise specified by SAS (3.1.2.6.1.4.1.f));</li> <li>b) inhibit replies to Mode A/C, Mode A/C/S all-call and Mode S-only all-call interrogations for the next 15 seconds;</li> <li>c) broadcast of acquisition squitters as per 3.1.2.8.5 using antenna as specified in 3.1.2.8.5.3.a);</li> <li>d) does not impact the air/ground state reported via the CA, FS and VS fields;</li> <li>e) discontinue broadcast of the extended squitter airborne message formats; and</li> <li>f) broadcast of the extended squitter surface formats at the rates according to the TRS subfield unless commanded to transmit at the rates set by the RCS subfield.</li> </ul>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.1.4.3</p> <p>Standard</p>	<p><i>TCS subfield equal to two (2) in the SD field for extended squitters.</i> When the TCS subfield in the SD field is set equal to two (2), it shall signify the following:</p> <ul style="list-style-type: none"> <li>a) broadcast of the extended squitter surface formats, including the surface position message (3.1.2.8.6.4.3), the identification and category message (3.1.2.8.6.4.4), the aircraft operational status message (3.1.2.8.6.4.6) and the aircraft status message (3.1.2.8.6.4.6) for the next 60 seconds at the appropriate rates on the top antenna for aircraft systems having the antenna diversity capability, except if otherwise specified by SAS (3.1.2.6.1.4.1.f);</li> <li>b) inhibit replies to Mode A/C, Mode A/C/S all-call and Mode S-only all-call interrogations for the next 60 seconds;</li> <li>c) broadcast of acquisition squitters as per 3.1.2.8.5 using antenna as specified in 3.1.2.8.5.3.a);</li> <li>d) does not impact the air/ground state reported via CA, FS and VS fields;</li> <li>e) discontinue broadcast of the extended squitter airborne message formats; and</li> <li>f) broadcast of the extended squitter surface formats at the rates according to the TRS subfield unless commanded to transmit at the rates set by the RCS subfield.</li> </ul>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.6.1.5</p> <p>Standard</p>	<p><i>PC and SD field processing.</i> When DI = 1, PC field processing shall be completed before processing the SD field.</p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																															
Chapter 3 Reference 3.1.2.6.2  Standard	<p><i>COMM-A ALTITUDE REQUEST, UPLINK FORMAT 20</i></p> <table border="0" style="width: 100%; text-align: center;"> <tr> <td>1</td><td>6</td><td>9</td><td>14</td><td>17</td> </tr> <tr> <td></td><td>33</td><td>89</td><td></td><td></td> </tr> <tr> <td>UF</td><td>PC</td><td>RR</td><td>DI</td><td>SD</td><td>MA</td><td>AP</td> </tr> <tr> <td>5</td><td>8</td><td>13</td><td>16</td><td>32</td><td></td><td></td> </tr> <tr> <td></td><td>88</td><td>112</td><td></td><td></td><td></td><td></td> </tr> </table> <p>The format of this interrogation shall consist of these fields:</p> <table border="0" style="width: 100%;"> <tr> <td style="text-align: left;"><i>Field</i></td> <td style="text-align: right;"><i>Reference</i></td> </tr> <tr> <td>UF uplink format</td> <td style="text-align: right;">3.1.2.3.2.1.1</td> </tr> <tr> <td>PC protocol</td> <td style="text-align: right;">3.1.2.6.1.1</td> </tr> <tr> <td>RR reply request</td> <td style="text-align: right;">3.1.2.6.1.2</td> </tr> <tr> <td>DI designator identification</td> <td style="text-align: right;">3.1.2.6.1.3</td> </tr> <tr> <td>SD special designator</td> <td style="text-align: right;">3.1.2.6.1.4</td> </tr> <tr> <td>MA message, Comm-A</td> <td style="text-align: right;">3.1.2.6.2.1</td> </tr> <tr> <td>AP address/parity</td> <td style="text-align: right;">3.1.2.3.2.1.3</td> </tr> </table>	1	6	9	14	17		33	89			UF	PC	RR	DI	SD	MA	AP	5	8	13	16	32				88	112					<i>Field</i>	<i>Reference</i>	UF uplink format	3.1.2.3.2.1.1	PC protocol	3.1.2.6.1.1	RR reply request	3.1.2.6.1.2	DI designator identification	3.1.2.6.1.3	SD special designator	3.1.2.6.1.4	MA message, Comm-A	3.1.2.6.2.1	AP address/parity	3.1.2.3.2.1.3	CAR 171.53(a)(1).	No Difference		
1	6	9	14	17																																																
	33	89																																																		
UF	PC	RR	DI	SD	MA	AP																																														
5	8	13	16	32																																																
	88	112																																																		
<i>Field</i>	<i>Reference</i>																																																			
UF uplink format	3.1.2.3.2.1.1																																																			
PC protocol	3.1.2.6.1.1																																																			
RR reply request	3.1.2.6.1.2																																																			
DI designator identification	3.1.2.6.1.3																																																			
SD special designator	3.1.2.6.1.4																																																			
MA message, Comm-A	3.1.2.6.2.1																																																			
AP address/parity	3.1.2.3.2.1.3																																																			
Chapter 3 Reference 3.1.2.6.2.1  Standard	<p><i>MA: Message, Comm-A.</i> This 56-bit (33-88) field shall contain a data link message to the aircraft.</p>	CAR 171.53(a)(1).	No Difference																																																	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																										
Chapter 3 Reference 3.1.2.6.3  Standard	<p><i>SURVEILLANCE IDENTITY REQUEST, UPLINK FORMAT 5</i></p> <table border="0"> <tr> <td>1</td> <td>6</td> <td>9</td> <td>14</td> <td>17</td> </tr> <tr> <td></td> <td>33</td> <td></td> <td></td> <td></td> </tr> <tr> <td>UF</td> <td>PC</td> <td>RR</td> <td>DI</td> <td>SD</td> <td>AP</td> </tr> <tr> <td>5</td> <td>8</td> <td></td> <td>13</td> <td>16</td> <td>32</td> </tr> <tr> <td></td> <td>56</td> <td></td> <td></td> <td></td> <td></td> </tr> </table> <p>The format of this interrogation shall consist of these fields:</p> <table border="0"> <tr> <td><i>Field</i></td> <td><i>Reference</i></td> </tr> <tr> <td>UF uplink format</td> <td>3.1.2.3.2.1.1</td> </tr> <tr> <td>PC protocol</td> <td>3.1.2.6.1.1</td> </tr> <tr> <td>RR reply request</td> <td>3.1.2.6.1.2</td> </tr> <tr> <td>DI designator identification</td> <td>3.1.2.6.1.3</td> </tr> <tr> <td>SD special designator</td> <td>3.1.2.6.1.4</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </table>	1	6	9	14	17		33				UF	PC	RR	DI	SD	AP	5	8		13	16	32		56					<i>Field</i>	<i>Reference</i>	UF uplink format	3.1.2.3.2.1.1	PC protocol	3.1.2.6.1.1	RR reply request	3.1.2.6.1.2	DI designator identification	3.1.2.6.1.3	SD special designator	3.1.2.6.1.4	AP address/parity	3.1.2.3.2.1.3	CAR 171.53(a)(1).	No Difference		
1	6	9	14	17																																											
	33																																														
UF	PC	RR	DI	SD	AP																																										
5	8		13	16	32																																										
	56																																														
<i>Field</i>	<i>Reference</i>																																														
UF uplink format	3.1.2.3.2.1.1																																														
PC protocol	3.1.2.6.1.1																																														
RR reply request	3.1.2.6.1.2																																														
DI designator identification	3.1.2.6.1.3																																														
SD special designator	3.1.2.6.1.4																																														
AP address/parity	3.1.2.3.2.1.3																																														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																															
Chapter 3 Reference 3.1.2.6.4  Standard	<p><i>COMM-A IDENTITY REQUEST, UPLINK FORMAT 21</i></p> <table border="0"> <tr> <td>1</td> <td>6</td> <td>9</td> <td>14</td> <td>17</td> </tr> <tr> <td></td> <td>33</td> <td>89</td> <td></td> <td></td> </tr> <tr> <td>UF</td> <td>PC</td> <td>RR</td> <td>DI</td> <td>SD</td> <td>MA</td> <td>AP</td> </tr> <tr> <td>5</td> <td>8</td> <td>13</td> <td>16</td> <td>32</td> <td></td> <td></td> </tr> <tr> <td></td> <td>88</td> <td>112</td> <td></td> <td></td> <td></td> <td></td> </tr> </table> <p>The format of this interrogation shall consist of these fields:</p> <table border="0"> <tr> <td><i>Field</i></td> <td><i>Reference</i></td> </tr> <tr> <td>UF uplink format</td> <td>3.1.2.3.2.1.1</td> </tr> <tr> <td>PC protocol</td> <td>3.1.2.6.1.1</td> </tr> <tr> <td>RR reply request</td> <td>3.1.2.6.1.2</td> </tr> <tr> <td>DI designator identification</td> <td>3.1.2.6.1.3</td> </tr> <tr> <td>SD special designator</td> <td>3.1.2.6.1.4</td> </tr> <tr> <td>MA message, Comm-A</td> <td>3.1.2.6.2.1</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </table>	1	6	9	14	17		33	89			UF	PC	RR	DI	SD	MA	AP	5	8	13	16	32				88	112					<i>Field</i>	<i>Reference</i>	UF uplink format	3.1.2.3.2.1.1	PC protocol	3.1.2.6.1.1	RR reply request	3.1.2.6.1.2	DI designator identification	3.1.2.6.1.3	SD special designator	3.1.2.6.1.4	MA message, Comm-A	3.1.2.6.2.1	AP address/parity	3.1.2.3.2.1.3	CAR 171.53(a)(1).	No Difference		
1	6	9	14	17																																																
	33	89																																																		
UF	PC	RR	DI	SD	MA	AP																																														
5	8	13	16	32																																																
	88	112																																																		
<i>Field</i>	<i>Reference</i>																																																			
UF uplink format	3.1.2.3.2.1.1																																																			
PC protocol	3.1.2.6.1.1																																																			
RR reply request	3.1.2.6.1.2																																																			
DI designator identification	3.1.2.6.1.3																																																			
SD special designator	3.1.2.6.1.4																																																			
MA message, Comm-A	3.1.2.6.2.1																																																			
AP address/parity	3.1.2.3.2.1.3																																																			



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																				
Chapter 3 Reference 3.1.2.6.5  Standard	<p><i>SURVEILLANCE ALTITUDE REPLY, DOWNLINK FORMAT 4</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%; text-align: center;">1</td> <td style="width: 25%; text-align: center;">6</td> <td style="width: 25%; text-align: center;">9</td> <td style="width: 25%; text-align: center;">14</td> </tr> <tr> <td></td> <td style="text-align: center;">20</td> <td style="text-align: center;">33</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">DF FS DR UM AC AP</td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">5</td> <td style="text-align: center;">8</td> <td style="text-align: center;">13</td> <td style="text-align: center;">19</td> </tr> <tr> <td></td> <td style="text-align: center;">32</td> <td style="text-align: center;">56</td> <td></td> </tr> </table> <p>This reply shall be generated in response to an interrogation UF 4 or 20 with an RR field value less than 16. The format of this reply shall consist of these fields:</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%;"><i>Field</i></td> <td style="width: 40%;"><i>Reference</i></td> </tr> <tr> <td><i>DF downlink format</i></td> <td style="text-align: right;">3.1.2.3</td> </tr> <tr> <td><i>.2.1.2 FS flight status</i></td> <td style="text-align: right;">3.1.2.6</td> </tr> <tr> <td><i>.5.1 DR downlink request</i></td> <td style="text-align: right;">3.1.2.6</td> </tr> <tr> <td><i>.5.2 UM utility message</i></td> <td style="text-align: right;">3.1.2.6</td> </tr> <tr> <td><i>.5.3 AC altitude code</i></td> <td style="text-align: right;">3.1.2.6</td> </tr> <tr> <td><i>.5.4 AP address/parity</i></td> <td style="text-align: right;">3.1.2.3</td> </tr> <tr> <td><i>.2.1.3</i></td> <td></td> </tr> </table>	1	6	9	14		20	33			DF FS DR UM AC AP			5	8	13	19		32	56		<i>Field</i>	<i>Reference</i>	<i>DF downlink format</i>	3.1.2.3	<i>.2.1.2 FS flight status</i>	3.1.2.6	<i>.5.1 DR downlink request</i>	3.1.2.6	<i>.5.2 UM utility message</i>	3.1.2.6	<i>.5.3 AC altitude code</i>	3.1.2.6	<i>.5.4 AP address/parity</i>	3.1.2.3	<i>.2.1.3</i>		CAR Part 91 Appendix A, A.22.	No Difference		
1	6	9	14																																						
	20	33																																							
	DF FS DR UM AC AP																																								
5	8	13	19																																						
	32	56																																							
<i>Field</i>	<i>Reference</i>																																								
<i>DF downlink format</i>	3.1.2.3																																								
<i>.2.1.2 FS flight status</i>	3.1.2.6																																								
<i>.5.1 DR downlink request</i>	3.1.2.6																																								
<i>.5.2 UM utility message</i>	3.1.2.6																																								
<i>.5.3 AC altitude code</i>	3.1.2.6																																								
<i>.5.4 AP address/parity</i>	3.1.2.3																																								
<i>.2.1.3</i>																																									



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.5.1  Standard	<p><i>FS: Flight status.</i> This 3-bit (6-8) downlink field shall contain the following information:</p> <p><i>Coding</i></p> <p>0            signifies no alert and no SPI, aircraft is airborne</p> <p>1            signifies no alert and no SPI, aircraft is on the ground</p> <p>2            signifies alert, no SPI, aircraft is airborne</p> <p>3            signifies alert, no SPI, aircraft is on the ground</p> <p>4            signifies alert and SPI, aircraft is airborne or on the ground</p> <p>5            signifies no alert and SPI, aircraft is airborne or on the ground</p> <p>6            reserved</p> <p>7            not assigned</p> <p><i>Note.— The conditions which cause an alert are given in 3.1.2.6.10.1.1.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																				
<p>Chapter 3 Reference 3.1.2.6.5.2</p> <p>Standard</p>	<p><i>DR: Downlink request.</i> This 5-bit (9-13) downlink field shall contain requests to downlink information.</p> <p><i>Coding</i></p> <table border="0"> <tr> <td>0</td> <td>signifies no downlink request</td> </tr> <tr> <td>1</td> <td>signifies request to send Comm-B message</td> </tr> <tr> <td>2</td> <td>reserved for ACAS</td> </tr> <tr> <td>3</td> <td>reserved for ACAS</td> </tr> <tr> <td>4</td> <td>signifies Comm-B broadcast message 1 available</td> </tr> <tr> <td>5</td> <td>signifies Comm-B broadcast message 2 available</td> </tr> <tr> <td>6</td> <td>reserved for ACAS</td> </tr> <tr> <td>7</td> <td>reserved for ACAS</td> </tr> <tr> <td>8-15</td> <td>not assigned</td> </tr> <tr> <td>16-31</td> <td>see downlink ELM protocol (3.1.2.7.7.1)</td> </tr> </table> <p>Codes 1-15 shall take precedence over codes 16-31.</p> <p><i>Note.— Giving precedence to codes 1-15 permits the announcement of a Comm-B message to interrupt the announcement of a downlink ELM. This gives priority to the announcement of the shorter message.</i></p>	0	signifies no downlink request	1	signifies request to send Comm-B message	2	reserved for ACAS	3	reserved for ACAS	4	signifies Comm-B broadcast message 1 available	5	signifies Comm-B broadcast message 2 available	6	reserved for ACAS	7	reserved for ACAS	8-15	not assigned	16-31	see downlink ELM protocol (3.1.2.7.7.1)	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
0	signifies no downlink request																								
1	signifies request to send Comm-B message																								
2	reserved for ACAS																								
3	reserved for ACAS																								
4	signifies Comm-B broadcast message 1 available																								
5	signifies Comm-B broadcast message 2 available																								
6	reserved for ACAS																								
7	reserved for ACAS																								
8-15	not assigned																								
16-31	see downlink ELM protocol (3.1.2.7.7.1)																								
<p>Chapter 3 Reference 3.1.2.6.5.3</p> <p>Standard</p>	<p><i>UM: Utility message.</i> This 6-bit (14-19) downlink field shall contain transponder communications status information as specified in 3.1.2.6.1.4.1 and 3.1.2.6.5.3.1.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.5.3.1</p> <p><b>Standard</b></p>	<p>Subfields in UM for multisite protocols <i>UM FIELD STRUCTURE</i></p> <p style="text-align: right;">14 18</p> <p style="text-align: right;">IIS IDS 17 19</p> <p>The following subfields shall be inserted by the transponder into the UM field of the reply if a surveillance or Comm-A interrogation (UF equals 4, 5, 20, 21) contains DI = 1 and RSS other than 0:</p> <p>IIS: The 4-bit (14-17) interrogator identifier subfield reports the identifier of the interrogator that is reserved for multisite communications.</p> <p>IDS: The 2-bit (18, 19) identifier designator subfield reports the type of reservation made by the interrogator identified in IIS.</p> <p>Assigned coding is:</p> <ul style="list-style-type: none"> <li>0 signifies no information</li> <li>1 signifies IIS contains Comm-B II code</li> <li>2 signifies IIS contains Comm-C II code</li> <li>3 signifies IIS contains Comm-D II code.</li> </ul>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.5.3.2  Standard	<p><i>Multisite reservation status.</i> The interrogator identifier of the ground station currently reserved for multisite Comm-B delivery (3.1.2.6.11.3.1) shall be transmitted in the IIS subfield together with code 1 in the IDS subfield if the UM content is not specified by the interrogation (when DI = 0 or 7, or when DI = 1 and RSS = 0).</p> <p>The interrogator identifier of the ground station currently reserved for downlink ELM delivery (3.1.2.7.6.1), if any, shall be transmitted in the IIS subfield together with code 3 in the IDS subfield if the UM content is not specified by the interrogation and there is no current Comm-B reservation.</p>	CAR 171.53(a)(1).	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.5.4  Standard	<p><i>AC: Altitude code.</i> This 13-bit (20-32) field shall contain altitude coded as follows:</p> <ul style="list-style-type: none"> <li>a) Bit 26 is designated as the M bit, and shall be 0 if the altitude is reported in feet. M equals 1 shall be reserved to indicate that the altitude reporting is in metric units.</li> <li>b) If M equals 0, then bit 28 is designated as the Q bit. Q equals 0 shall be used to indicate that the altitude is reported in 100-foot increments. Q equals 1 shall be used to indicate that the altitude is reported in 25-foot increments.</li> <li>c) If the M bit (bit 26) and the Q bit (bit 28) equal 0, the altitude shall be coded according to the pattern for Mode C replies of 3.1.1.7.12.2.3. Starting with bit 20 the sequence shall be C1, A1, C2, A2, C4, A4, ZERO, B1, ZERO, B2, D2, B4, D4.</li> <li>d) If the M bit equals 0 and the Q bit equals 1, the 11-bit field represented by bits 20 to 25, 27 and 29 to 32 shall represent a binary coded field with a least significant bit (LSB) of 25 ft. The binary value of the positive decimal integer "N" shall be encoded to report pressure-altitude in the range [(25 N – 1 000) plus or minus 12.5 ft]. The coding of 3.1.2.6.5.4 c) shall be used to report pressure-altitude above 50 187.5 ft.</li> </ul> <p><i>N1. This coding method is only able to provide values between minus 1 000 ft and plus 50 175 ft.</i></p> <p><i>N2. The most significant bit (MSB) of this field is bit 20 as required by 3.1.2.3.1.3.</i></p> <ul style="list-style-type: none"> <li>e) If the M bit equals 1, the 12-bit field represented by bits 20 to 25 and 27 to 31 shall be reserved for encoding altitude in metric units.</li> <li>f) 0 shall be transmitted in each of the 13 bits of the AC field if altitude information is not available or if the altitude has been determined invalid.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																															
Chapter 3 Reference 3.1.2.6.6  Standard	<p><i>COMM-B ALTITUDE REPLY, DOWNLINK FORMAT 20</i></p> <table border="0"> <tr> <td>1</td><td>6</td><td>9</td><td>14</td><td>20</td><td>33</td> </tr> <tr> <td></td><td>89</td><td></td><td></td><td></td><td></td> </tr> <tr> <td>DF</td><td>FS</td><td>DR</td><td>UM</td><td>AC</td><td>MB</td><td>AP</td> </tr> <tr> <td>5</td><td>8</td><td>13</td><td>19</td><td>32</td><td>88</td> </tr> <tr> <td></td><td>112</td><td></td><td></td><td></td><td></td> </tr> </table> <p>This reply shall be generated in response to an interrogation UF 4 or 20 with an RR field value greater than 15. The format of this reply shall consist of these fields:</p> <table border="0"> <thead> <tr> <th><i>Field</i></th> <th><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>FS flight status</td> <td>3.1.2.6.5.1</td> </tr> <tr> <td>DR downlink request</td> <td>3.1.2.6.5.2</td> </tr> <tr> <td>UM utility message</td> <td>3.1.2.6.5.3</td> </tr> <tr> <td>AC altitude code</td> <td>3.1.2.6.5.4</td> </tr> <tr> <td>MB message, Comm-B</td> <td>3.1.2.6.6.1</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </tbody> </table>	1	6	9	14	20	33		89					DF	FS	DR	UM	AC	MB	AP	5	8	13	19	32	88		112					<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	FS flight status	3.1.2.6.5.1	DR downlink request	3.1.2.6.5.2	UM utility message	3.1.2.6.5.3	AC altitude code	3.1.2.6.5.4	MB message, Comm-B	3.1.2.6.6.1	AP address/parity	3.1.2.3.2.1.3	CAR Part 91 Appendix A, A.22.	No Difference		
1	6	9	14	20	33																																															
	89																																																			
DF	FS	DR	UM	AC	MB	AP																																														
5	8	13	19	32	88																																															
	112																																																			
<i>Field</i>	<i>Reference</i>																																																			
DF downlink format	3.1.2.3.2.1.2																																																			
FS flight status	3.1.2.6.5.1																																																			
DR downlink request	3.1.2.6.5.2																																																			
UM utility message	3.1.2.6.5.3																																																			
AC altitude code	3.1.2.6.5.4																																																			
MB message, Comm-B	3.1.2.6.6.1																																																			
AP address/parity	3.1.2.3.2.1.3																																																			
Chapter 3 Reference 3.1.2.6.6.1  Standard	<p><i>MB: Message, Comm-B.</i> This 56-bit (33-88) downlink field shall be used to transmit data link messages to the ground.</p>	CAR Part 91 Appendix A, A.22.	No Difference																																																	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																								
Chapter 3 Reference 3.1.2.6.7  Standard	<p><i>SURVEILLANCE IDENTITY REPLY, DOWNLINK FORMAT 5</i></p> <table border="0" style="width: 100%; text-align: center;"> <tr> <td>1</td><td>6</td><td>9</td><td>14</td><td>20</td></tr> <tr> <td colspan="5">33</td> </tr> <tr> <td>DF</td><td>FS</td><td>DR</td><td>UM</td><td>ID</td><td>AP</td> </tr> <tr> <td>5</td><td>8</td><td>13</td><td>19</td><td>32</td></tr> <tr> <td colspan="5">56</td> </tr> </table> <p>This reply shall be generated in response to an interrogation UF 5 or 21 with an RR field value less than 16. The format of this reply shall consist of these fields:</p> <table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;"><i>Field</i></th> <th style="text-align: left;"><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>FS flight status</td> <td>3.1.2.6.5.1</td> </tr> <tr> <td>DR downlink request</td> <td>3.1.2.6.5.2</td> </tr> <tr> <td>UM utility message</td> <td>3.1.2.6.5.3</td> </tr> <tr> <td>ID identity</td> <td>3.1.2.6.7.1</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </tbody> </table>	1	6	9	14	20	33					DF	FS	DR	UM	ID	AP	5	8	13	19	32	56					<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	FS flight status	3.1.2.6.5.1	DR downlink request	3.1.2.6.5.2	UM utility message	3.1.2.6.5.3	ID identity	3.1.2.6.7.1	AP address/parity	3.1.2.3.2.1.3	CAR Part 91 Appendix A, A.22.	No Difference		
1	6	9	14	20																																									
33																																													
DF	FS	DR	UM	ID	AP																																								
5	8	13	19	32																																									
56																																													
<i>Field</i>	<i>Reference</i>																																												
DF downlink format	3.1.2.3.2.1.2																																												
FS flight status	3.1.2.6.5.1																																												
DR downlink request	3.1.2.6.5.2																																												
UM utility message	3.1.2.6.5.3																																												
ID identity	3.1.2.6.7.1																																												
AP address/parity	3.1.2.3.2.1.3																																												
Chapter 3 Reference 3.1.2.6.7.1  Standard	<p><i>ID: Identity (Mode A code).</i> This 13-bit (20-32) field shall contain aircraft identity code, in accordance with the pattern for Mode A replies in 3.1.1.6. Starting with bit 20, the sequence shall be C1, A1, C2, A2, C4, A4, ZERO, B1, D1, B2, D2, B4, D4.</p>	CAR Part 91 Appendix A, A.22.	No Difference																																										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																				
Chapter 3 Reference 3.1.2.6.8  Standard	<p><i>COMM-B IDENTITY REPLY, DOWNLINK FORMAT 21</i></p> <table border="0"> <tr> <td>1</td> <td>6</td> <td>9</td> <td>14</td> </tr> <tr> <td></td> <td>20</td> <td>33</td> <td>89</td> </tr> <tr> <td>DF FS DR UM ID MB AP</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>8</td> <td>13</td> <td>19</td> </tr> <tr> <td></td> <td>32</td> <td>88</td> <td>112</td> </tr> </table> <p>This reply shall be generated in response to an interrogation UF 5 or 21 with an RR field value greater than 15. The format of this reply shall consist of these fields:</p> <table border="0"> <thead> <tr> <th><i>Field</i></th> <th><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>FS flight status</td> <td>3.1.2.6.5.1</td> </tr> <tr> <td>DR downlink request</td> <td>3.1.2.6.5.2</td> </tr> <tr> <td>UM utility message</td> <td>3.1.2.6.5.3</td> </tr> <tr> <td>ID identity</td> <td>3.1.2.6.7.1</td> </tr> <tr> <td>MB message, Comm-B</td> <td>3.1.2.6.6.1</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </tbody> </table>	1	6	9	14		20	33	89	DF FS DR UM ID MB AP				5	8	13	19		32	88	112	<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	FS flight status	3.1.2.6.5.1	DR downlink request	3.1.2.6.5.2	UM utility message	3.1.2.6.5.3	ID identity	3.1.2.6.7.1	MB message, Comm-B	3.1.2.6.6.1	AP address/parity	3.1.2.3.2.1.3	CAR Part 91 Appendix A, A.22.	No Difference		
1	6	9	14																																						
	20	33	89																																						
DF FS DR UM ID MB AP																																									
5	8	13	19																																						
	32	88	112																																						
<i>Field</i>	<i>Reference</i>																																								
DF downlink format	3.1.2.3.2.1.2																																								
FS flight status	3.1.2.6.5.1																																								
DR downlink request	3.1.2.6.5.2																																								
UM utility message	3.1.2.6.5.3																																								
ID identity	3.1.2.6.7.1																																								
MB message, Comm-B	3.1.2.6.6.1																																								
AP address/parity	3.1.2.3.2.1.3																																								



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.9.1.1  Standard	<p><b>3.1.2.6.9 LOCKOUT PROTOCOLS</b></p> <p><i>Note.— Non-selective all-call lockout and multisite lockout are not mutually exclusive. Interrogators using multisite lockout protocols for interrogator networking coordination may use non-selective lockout commands in the same interrogation. For example, the non-selective lockout may be used to prevent Mode S transponder replies with DF=11 to wrongly detected Mode A/C/S all-call interrogations from Mode A/C-only all-call interrogations. This is because of the misinterpretation of the narrow P<sub>4</sub> pulse as a wide P<sub>4</sub> pulse.</i></p> <p><b>3.1.2.6.9.1 Multisite all-call lockout</b></p> <p><i>Note.— The multisite lockout protocol prevents transponder acquisition from being denied one ground station by lockout commands from an adjacent ground station that has overlapping coverage.</i></p> <p>The multisite lockout command shall be transmitted in the SD field (3.1.2.6.1.4.1). A lockout command for an II code shall be transmitted in an SD with DI = 1 or DI = 7. An II lockout command shall be indicated by LOS code equals 1 and the presence of a non-zero interrogator identifier in the IIS subfield of SD. A lockout command for an SI code shall be transmitted in an SD with DI = 3. SI lockout shall be indicated by LSS equals 1 and the presence of a non-zero interrogator identifier in the SIS subfield of SD. After a transponder has accepted an interrogation containing a multisite lockout command, that transponder shall commence to lock out (i.e. not accept) any Mode S-only all-call interrogation which includes the identifier of the interrogator that commanded the lockout. The lockout shall persist for an interval T<sub>L</sub> (3.1.2.10.3.9) after the last acceptance of an interrogation containing the multisite lockout command. Multisite lockout shall not prevent acceptance of a Mode S-only all-call interrogation containing PR codes 8 to 12. If a lockout</p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>command (LOS = 1) is received together with IIS = 0, it shall be interpreted as a non-selective all-call lockout (3.1.2.6.9.2).</p> <p><i>N1.Fifteen interrogators can send independent multisite II lockout commands. In addition, 63 interrogators can send independent SI lockout commands. Each of these lockout commands must be timed separately.</i></p> <p><i>N2.Multisite lockout (which only uses non-zero II codes) does not affect the response of the transponder to Mode S-only all-call interrogations containing II equals 0 or to Mode A/C/S all-call interrogations.</i></p>				
<p>Chapter 3 Reference 3.1.2.6.9.2  Standard</p>	<p><i>Non-selective all-call lockout</i></p> <p><i>N1.In cases where the multisite lockout protocol for II codes is not required (e.g. there is no overlapping coverage or there is ground station coordination via ground-to-ground communications) the non-selective lockout protocol may be used.</i></p> <p>On acceptance of an interrogation containing code 1 in the PC field, a transponder shall commence to lock out (i.e. not accept) two types of all-call interrogations:</p> <ul style="list-style-type: none"> <li>a) the Mode S-only all-call (UF = 11), with II equals 0; and</li> <li>b) the Mode A/C/S all-call of 3.1.2.1.5.1.1.</li> </ul> <p>This lockout condition shall persist for an interval T<sub>D</sub> (3.1.2.10.3.9) after the last receipt of the command. Non-selective lockout shall not prevent acceptance of a Mode S-only all-call interrogation containing PR codes 8 to 12.</p> <p><i>N2.Non-selective lockout does not affect the response of the transponder to Mode S-only all-call interrogations containing II not equal to 0.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.10.1  Standard	3.1.2.6.10 BASIC DATA PROTOCOLS  <i>Flight status protocol.</i> Flight status shall be reported in the FS field (3.1.2.6.5.1).	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.1.1  Standard	<i>Alert.</i> An alert condition shall be reported in the FS field if the Mode A identity code transmitted in Mode A replies and in downlink formats DF equals 5 and DF equals 21 are changed by the pilot.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.1.1.1  Standard	<i>Permanent alert condition.</i> The alert condition shall be maintained if the Mode A identity code is changed to 7500, 7600 or 7700.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.1.1.2  Standard	<i>Temporary alert condition.</i> The alert condition shall be temporary and shall cancel itself after <i>T<sub>c</sub></i> seconds if the Mode A identity code is changed to a value other than those listed in 3.1.2.6.10.1.1.1. The <i>T<sub>c</sub></i> shall be retriggered and continued for <i>T<sub>c</sub></i> seconds after any change has been accepted by the transponder function.  N1. <i>This retriggering is performed to ensure that the ground interrogator obtains the desired Mode A identity code before the alert condition is cleared.</i>  N2. <i>The value of TC is given in 3.1.2.10.3.9.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.10.1.1.3  Standard	<i>Termination of the permanent alert condition.</i> The permanent alert condition shall be terminated and replaced by a temporary alert condition when the Mode A identity code is set to a value other than 7500, 7600 or 7700.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.1.2  Standard	<i>Ground report.</i> The on-the-ground status of the aircraft shall be reported in the CA field (3.1.2.5.2.2.1), the FS field (3.1.2.6.5.1), and the VS field (3.1.2.8.2.1). If an automatic indication of the on-the-ground condition (e.g. from a weight on wheels or strut switch) is available at the transponder data interface, it shall be used as the basis for the reporting of on-the-ground status except as specified in 3.1.2.6.10.3.1. If such indication is not available at the transponder data interface (3.1.2.10.5.1.3), the FS and VS codes shall indicate that the aircraft is airborne and the CA field shall indicate that the aircraft is either airborne or on the ground (CA = 6).	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.1.3  Standard	<i>Special position identification (SPI).</i> An equivalent of the SPI pulse shall be transmitted by Mode S transponders in the FS field and the surveillance status subfield (SSS) when manually activated. This pulse shall be transmitted for $T_1$ seconds after initiation (3.1.1.6.3, 3.1.1.7.13 and 3.1.2.8.6.3.1.1). <i>Note.— The value of <math>T_1</math> is given in 3.1.2.10.3.9.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2  Standard	<i>Capability reporting protocol.</i> The data structure and content of the data link capability report registers shall be implemented in such a way that interoperability is ensured. <i>N1. Aircraft capability is reported in special fields as defined in the following paragraphs.</i> <i>N2. The data format of the registers for reporting capability is specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.10.2.1  Standard	<i>Capability report.</i> The 3-bit CA field, contained in the all-call reply, DF equals 11, shall report the basic capability of the Mode S transponder as described in 3.1.2.5.2.2.1.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.2  Standard	<i>Data link capability report.</i> The data link capability report shall provide the interrogator with a description of the data link capability of the Mode S installation.  <i>Note.— The data link capability report is contained in register 1016 with a possible extension in registers 1116 to 1616 when any continuation will be required.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.2.1.1  Standard	<i>3.1.2.6.10.2.2.1 Extraction and subfields in MB for data link capability report</i>  <i>Extraction of the data link capability report contained in register 1016.</i> The report shall be obtained by a ground-initiated Comm-B reply in response to an interrogation containing RR equals 17 and DI is not equal to 7 or DI equals 7 and RRS equals 0 (3.1.2.6.11.2).	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.2.1.2  Standard	<i>Sources of data link capability.</i> Data link capability reports shall contain the capabilities provided by the transponder, the ADLP and the ACAS unit. If external inputs are lost, the transponder shall zero the corresponding bits in the data link report.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.10.2.2.1.3  Standard	The data link capability report shall contain information on the following capabilities as specified in Table 3-6.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.2.1.4  Standard	The Mode S subnetwork version number shall contain information to ensure interoperability with older airborne equipment.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.2.1.4.1  Standard	The Mode S subnetwork version number shall indicate that all implemented subnetwork functions are in compliance with the requirements of the indicated version number. The Mode S subnetwork version number shall be set to a non-zero value if at least one DTE or Mode S specific service is installed. <i>Note.— The version number does not indicate that all possible functions of that version are implemented.</i>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.10.2.2.2  Standard	<p><i>Updating of the data link capability report.</i> The transponder shall, at intervals not exceeding four seconds, compare the current data link capability status (bits 41-88 in the data link capability report) with that last reported and shall, if a difference is noted, initiate a revised data link capability report by Comm-B broadcast (3.1.2.6.11.4) for BDS1 = 1 (33-36) and BDS2 = 0 (37-40). The transponder shall initiate, generate and announce the revised capability report even if the aircraft data link capability is degraded or lost. The transponder shall ensure that the BDS code is set for the data link capability report in all cases, including a loss of the interface.</p> <p><i>Note.— The setting of the BDS code by the transponder ensures that a broadcast change of capability report will contain the BDS code for all cases of data link failure (e.g. the loss of the transponder data link interface).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.2.3  Standard	<p><i>Zeroing of bits in the data link capability report</i> If capability information to the transponder fails to provide an update at a rate of at least once every 4 seconds, the transponder shall insert ZERO in bits 41 to 56 of the data link capability report (transponder register 10<sub>16</sub>).</p> <p><i>Note.— Bits 1 to 8 contain the BDS1 and BDS2 codes. Bits 16 and 37 to 40 contain ACAS capability information. Bit 33 indicates the availability of aircraft identification data and is set by the transponder when the data comes from a separate interface and not from the ADLP. Bit 35 is the SI code indication. All of these bits are inserted by the transponder.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.3  Standard	<p><i>Common usage GICB capability report.</i> Common usage GICB services which are being actively updated shall be indicated in transponder register 17<sub>16</sub>.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.10.2.4  Standard	<i>Mode S specific services GICB capability reports.</i> GICB services that are installed shall be reported in registers 18 <sub>16</sub> to 1C <sub>16</sub> .	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.10.2.5  Standard	<i>Mode S specific services MSP capability reports.</i> MSP services that are installed shall be reported in registers 1D <sub>16</sub> to 1F <sub>16</sub> .	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.10.3.1</p> <p>Standard</p>	<p>3.1.2.6.10.3 Validation of on-the-ground status declared by an automatic means</p> <p><i>Note.— For aircraft with an automatic means of determining vertical status, the CA field reports whether the aircraft is airborne or on the ground. ACAS II acquires aircraft using the short or extended squitter, both of which contain the CA field. If an aircraft reports on-the-ground status, that aircraft will not be interrogated by ACAS II in order to reduce unnecessary interrogation activity. If the aircraft is equipped to report extended squitter messages, the function that formats these messages may have information available to validate that an aircraft reporting “on-the-ground” is actually airborne.</i></p> <p>Aircraft with an automatic means for determining the on-the-ground state on which transponders have access to at least one of the parameters, ground speed, radio altitude or airspeed, shall perform the following validation check:</p> <p>If the automatically determined air/ground status is not available or is “airborne”, no validation shall be performed. If the automatically determined air/ground status is available and “on-the-ground” condition is being reported, the air/ground status shall be overridden and changed to “airborne” if:</p> <p>Ground Speed &gt; 100 knots OR Airspeed &gt; 100 knots OR Radio Altitude &gt; 50 feet</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.1  Standard	<p><i>3.1.2.6.11 STANDARD LENGTH COMMUNICATIONS PROTOCOLS</i></p> <p><i>N1.The two types of standard length communications protocols are Comm-A and Comm-B; messages using these protocols are transferred under the control of the interrogator. Comm-A messages are sent directly to the transponder and are completed within one transaction. A Comm-B message is used to transfer information from air to ground and can be initiated either by the interrogator or the transponder. In the case of ground-initiated Comm-B transfers, the interrogator requests data to be read out from the transponder, which delivers the message in the same transaction. In the case of air-initiated Comm-B transfers, the transponder announces the intention to transmit a message; in a subsequent transaction an interrogator will extract the message.</i></p> <p><i>N2.In a non-selective air-initiated Comm-B protocol all transactions necessary can be controlled by any interrogator.</i></p> <p><i>N3.In some areas of overlapping interrogator coverage there may be no means for coordinating interrogator activities via ground communications. Air-initiated Comm-B communications protocols require more than one transaction for completion. Provision is made to ensure that a Comm-B message is closed out only by the interrogator that actually transferred the message. This can be accomplished through the use of the multisite Comm-B communications protocols or through the use of the enhanced Comm-B communications protocols.</i></p> <p><i>N4.The multisite and the non-selective communications protocols cannot be used simultaneously in a region of overlapping interrogator coverage unless the interrogators coordinate their communications activities via ground communications.</i></p> <p><i>N5.The multisite communications protocol is independent of the multisite lockout protocol. That is, the multisite communications protocol may be used with the</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p><i>non-selective lockout protocol and vice versa. The choice of lockout and communications protocols to be used depends upon the network management technique being used.</i></p> <p><i>N6.The broadcast Comm-B protocol can be used to make a message available to all active interrogators.</i></p> <p><i>Comm-A. The interrogator shall deliver a Comm-A message in the MA field of an interrogation UF = 20 or 21.</i></p>				
<p>Chapter 3 Reference 3.1.2.6.11.1.1</p> <p>Standard</p>	<p><i>Comm-A technical acknowledgement. Acceptance of a Comm-A interrogation shall be automatically technically acknowledged by the transponder, by the transmission of the requested reply (3.1.2.10.5.2.2.1).</i></p> <p><i>Note.— The receipt of a reply from the transponder according to the rules of 3.1.2.4.1.2.3 d) and 3.1.2.4.1.3.2.2.2 is the acknowledgement to the interrogator that the interrogation has been accepted by the transponder. If either uplink or downlink fail, this reply will be missing and the interrogator will normally send the message again. In the case of downlink failure, the transponder may receive the message more than once.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.6.11.1.2</p> <p>Standard</p>	<p><i>Comm-A broadcast. If a Comm-A broadcast interrogation is accepted (3.1.2.4.1.2.3.1.3) information transfer shall be handled according to 3.1.2.10.5.2.1.1 but other transponder functions shall not be affected and a reply shall not be transmitted.</i></p> <p><i>N1.There is no technical acknowledgement to a Comm-A broadcast message.</i></p> <p><i>N2.Since the transponder does not process the control fields of a Comm-A broadcast interrogation, the 27 bits following the UF field are also available for user data.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.2.1  Standard	3.1.2.6.11.2 <i>Ground-initiated Comm-B</i>  <i>Comm-B data selector, BDS.</i> The 8-bit BDS code shall determine the register whose contents shall be transferred in the MB field of the Comm-B reply. It shall be expressed in two groups of 4 bits each, BDS1 (most significant 4 bits) and BDS2 (least significant 4 bits).  <i>Note.— The transponder register allocation is specified in Annex 10, Volume III, Part I, Chapter 5, Table 5-24.</i>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.2.2  Standard	<i>BDS1 code.</i> The BDS1 code shall be as defined in the RR field of a surveillance or Comm-A interrogation.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.2.3  Standard	<i>BDS2 code.</i> The BDS2 code shall be as defined in the RRS subfield of the SD field (3.1.2.6.1.4.1) when DI = 7 or DI=3. If no BDS2 code is specified (i.e. DI is not equal to either 7 or 3) it shall signify that BDS2 = 0.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.2.4  Standard	<i>Protocol.</i> On receipt of such a request, the MB field of the reply shall contain the contents of the requested ground-initiated Comm-B register.	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.2.4.1  Standard	If the requested register is not serviced by the aircraft installation, the transponder shall reply and the MB field of the reply shall contain all ZEROS.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.6.11.2.5  Standard	<i>Overlay control.</i> If the “DI” code of the Comm-B requesting interrogation is 0, 3, or 7, the “SD” contains the overlay control (OVC) field in accordance with paragraph 3.1.2.6.1.4.1.i). a) If the “OVC” is equal to “1”, then the reply to the interrogation shall contain the “DP” (data parity) field in accordance with paragraph 3.1.2.3.2.1.5; and b) If the “OVC” is equal to “0”, then the reply to the interrogation shall contain the “AP” field in accordance with paragraph 3.1.2.3.2.1.3.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.1  Standard	<p>3.1.2.6.11.3 <i>Air-initiated Comm-B</i></p> <p><i>General protocol.</i> The transponder shall announce the presence of an air-initiated Comm-B message with the insertion of code 1 in the DR field. To extract an air-initiated Comm-B message, the interrogator shall transmit a request for a Comm-B message reply in a subsequent interrogation with RR equal to 16 and, if DI equals 7, RRS must be equal to 0 (3.1.2.6.11.3.2.1 and 3.1.2.6.11.3.3.1). Receipt of this request code shall cause the transponder to transmit the air-initiated Comm-B message. If a command to transmit an air-initiated Comm-B message is received while no message is waiting to be transmitted, the reply shall contain all ZEROs in the MB field.</p> <p>The reply that delivers the message shall continue to contain code 1 in the DR field. After a Comm-B closeout has been accomplished, the message shall be cancelled and the DR code belonging to this message immediately removed. If another air-initiated Comm-B message is waiting to be transmitted, the transponder shall set the DR code to 1, so that the reply contains the announcement of this next message.</p> <p><i>Note.— The announcement and cancellation protocol ensures that an air-initiated message will not be lost due to uplink or downlink failures that occur during the delivery process.</i></p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.2  Recommendation	<p><i>Additional protocol for multisite air-initiated Comm-B</i></p> <p><i>Note.— The announcement of an air-initiated Comm-B message waiting to be delivered may be accompanied by a multisite reservation status report in the UM field (3.1.2.6.5.3.2).</i></p> <p><b>Recommendation.—</b> <i>An interrogator should not attempt to extract a message if it has determined that it is not the reserved site.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.11.3.2.1</p> <p><b>Standard</b></p>	<p><i>Message transfer.</i> An interrogator shall request a Comm-B reservation and extract an air-initiated Comm-B message by transmitting a surveillance or Comm-A interrogation UF equals 4, 5, 20 or 21 containing: RR = 16 DI = 1 IIS = assigned interrogator identifier MBS = 1 (Comm-B reservation request)</p> <p><i>Note.— A Comm-B multisite reservation request is normally accompanied by a Comm-B reservation status request (RSS = 1). This causes the interrogator identifier of the reserved site to be inserted in the UM field of the reply.</i></p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.11.3.2.1.1</p> <p>Standard</p>	<p>Protocol procedure in response to this interrogation shall depend upon the state of the B-timer which indicates if a Comm-B reservation is active. This timer shall run for <math>T_R</math> seconds.</p> <p>N1. <i>The value of <math>T_R</math> is given in 3.1.2.10.3.9.</i></p> <p>a) If the B-timer is not running, the transponder shall grant a reservation to the requesting interrogator by:</p> <ol style="list-style-type: none"> <li>1) storing the IIS of the interrogation as the Comm-B II; and</li> <li>2) starting the B-timer.</li> </ol> <p>A multisite Comm-B reservation shall not be granted by the transponder unless an air-initiated Comm-B message is waiting to be transmitted and the requesting interrogation contains RR equals 16, DI equals 1, MBS equals 1 and IIS is not 0.</p> <p>b) If the B-timer is running and the IIS of the interrogation equals the Comm-B II, the transponder shall restart the B-timer.</p> <p>c) If the B-timer is running and the IIS of the interrogation does not equal the Comm-B II, then there shall be no change to the Comm-B II or the B-timer.</p> <p>N2. <i>In case c) the reservation request has been denied.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.6.11.3.2.1.2</p> <p>Standard</p>	<p>In each case the transponder shall reply with the Comm-B message in the MB field.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.2.1.3  Standard	An interrogator shall determine if it is the reserved site for this message through coding in the UM field. If it is the reserved site it shall attempt to close out the message in a subsequent interrogation. If it is not the reserved site it shall not attempt to close out the message.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.2.2  Standard	<p><i>Multisite-directed Comm-B transmissions.</i> To direct an air-initiated Comm-B message to a specific interrogator, the multisite Comm-B protocol shall be used. When the B-timer is not running, the interrogator identifier of the desired destination shall be stored as the Comm-B II. Simultaneously the B-timer shall be started and the DR code shall be set to 1. For a multisite-directed Comm-B message, the B-timer shall not automatically time out but shall continue to run until:</p> <ul style="list-style-type: none"> <li>a) the message is read and closed out by the reserved site; or</li> <li>b) the message is cancelled (3.1.2.10.5.4) by the data link avionics.</li> </ul> <p><i>Note.— The protocols of 3.1.2.6.5.3 and 3.1.2.6.11.3.2.1 will then result in delivery of the message to the reserved site. The data link avionics may cancel the message if delivery to the reserved site cannot be accomplished.</i></p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.2.3  Standard	<p><i>Multisite Comm-B closeout.</i> The interrogator shall close out a multisite air-initiated Comm-B by transmitting either a surveillance or a Comm-A interrogation containing:</p> <p><i>either</i> DI = 1 IIS = assigned interrogator identifier MBS = 2 (Comm-B closeout)</p> <p><i>or</i> DI = 0, 1 or 7 IIS = assigned interrogator identifier PC = 4 (Comm-B closeout)</p> <p>The transponder shall compare the IIS of the interrogation to the Comm-B II and if the interrogator identifiers do not match, the message shall not be cleared and the status of the Comm-B II, B-timer, and DR code shall not be changed. If the interrogator identifiers match, the transponder shall set the Comm-B II to 0, reset the B-timer, clear the DR code for this message and clear the message itself. The transponder shall not close out a multisite air-initiated Comm-B message unless it has been read out at least once by the reserved site.</p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.2.4  Standard	<p><i>Automatic expiration of Comm-B reservation.</i> If the B-timer period expires before a multisite closeout has been accomplished, the Comm-B II shall be set to 0 and the B-timer reset. The Comm-B message and the DR field shall not be cleared by the transponder.</p> <p><i>Note.— This makes it possible for another site to read and clear this message.</i></p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.3.1  Standard	<p>3.1.2.6.11.3.3.3 Additional protocol for non-selective air-initiated Comm-B</p> <p>Note.— In cases where the multisite protocols are not required (i.e. no overlapping coverage or sensor coordination via ground-to-ground communication), the non-selective air-initiated Comm-B protocol may be used.</p> <p>Message transfer. The interrogator shall extract the message by transmitting either RR equals 16 and DI is not equal to 7, or RR equals 16, DI equals 7 and RRS equals 0 in a surveillance or Comm-A interrogation.</p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.3.2  Standard	<p>Comm-B closeout. The interrogator shall close out a non-selective air-initiated Comm-B message by transmitting PC equals 4 (Comm-B closeout). On receipt of this command, the transponder shall perform closeout, unless the B-timer is running. If the B-timer is running, indicating that a multisite reservation is in effect, closeout shall be accomplished as per 3.1.2.6.11.3.2.3. The transponder shall not close out a non-selective air-initiated Comm-B message unless it has been read out at least once by an interrogation using non-selective protocols.</p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.4.1  Standard	<p><i>3.1.2.6.11.3.4 Enhanced air-initiated Comm-B protocol</i>  <i>Note.— The enhanced air-initiated Comm-B protocol provides a higher data link capacity by permitting parallel delivery of air-initiated Comm-B messages by up to sixteen interrogators, one for each II code. Operation without the need for multisite Comm-B reservations is possible in regions of overlapping coverage for interrogators equipped for the enhanced air-initiated Comm-B protocol. The protocol is fully conformant to the standard multisite protocol and thus is compatible with interrogators that are not equipped for the enhanced period.</i></p> <p>The transponder shall be capable of storing each of the sixteen II codes: (1) an air-initiated or multisite-directed Comm-B message and (2) the contents of GICB registers 2 through 4.  <i>Note.— GICB registers 2 through 4 are used for the Comm-B linking protocol defined in the Mode S subnetwork SARPs (Annex 10, Volume III, Part I, Chapter 5).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.4.2.1  Standard	<p><i>3.1.2.6.11.3.4.2 Enhanced multisite air-initiated Comm-B protocol</i></p> <p><i>Initiation.</i> An air-initiated Comm-B message input into the transponder shall be stored in the registers assigned to II = 0.</p>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.4.2.2  Standard	<i>Announcement and extraction.</i> A waiting air-initiated Comm-B message shall be announced in the DR field of the replies to all interrogators for which a multisite directed Comm-B message is not waiting. The UM field of the announcement reply shall indicate that the message is not reserved for any II code, i.e., the IIS subfield shall be set to 0. When a command to read this message is received from a given interrogator, the reply containing the message shall contain an IIS subfield content indicating that the message is reserved for the II code contained in the interrogation from that interrogator. After readout and until closeout, the message shall continue to be assigned to that II code. Once a message is assigned to a specific II code, announcement of this message shall be no longer made in the replies to interrogators with other II codes. If the message is not closed out by the assigned interrogator for the period of the B-timer, the message shall revert back to multisite air-initiated status and the process shall repeat. Only one multisite air-initiated Comm-B message shall be in process at a time.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.4.2.3  Standard	<i>Closeout.</i> A closeout for a multisite air-initiated message shall only be accepted from the interrogator that is currently assigned to transfer the message.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.4.2.4  Standard	<i>Announcement of the next message waiting.</i> The DR field shall indicate a message waiting in the reply to an interrogation containing a Comm-B closeout if an unassigned air-initiated message is waiting and has not been assigned to a II code, or if a multisite-directed message is waiting for that II code (3.1.2.6.11.3.4.3).	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.4.3.1  Standard	<p>3.1.2.6.11.3.4.3 Enhanced multisite directed Comm-B protocol</p> <p><i>Initiation.</i> When a multisite directed message is input into the transponder, it shall be placed in the Comm-B registers assigned to the II code specified for the message. If the registers for this II code are already occupied, (i.e. a multisite directed message is already in process to this II code) the new message shall be queued until the current transaction with that II code is closed out.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.6.11.3.4.3.2</p> <p>Standard</p>	<p><i>Announcement.</i> Announcement of a Comm-B message waiting transfer shall be made using the DR field as specified in 3.1.2.6.5.2 with the destination interrogator II code contained in the IIS subfield as specified in 3.1.2.6.5.3.2. The DR field and IIS subfield contents shall be set specifically for the interrogator that is to receive the reply. A waiting multisite directed message shall only be announced in the replies to the intended interrogator. It shall not be announced in the replies to other interrogators.</p> <p><i>N1.If a multisite-directed message is waiting for II = 2, the surveillance replies to that interrogator will contain DR = 1 and IIS = 2. If this is the only message in process, replies to all other interrogators will indicate that no message is waiting.</i></p> <p><i>N2.In addition to permitting parallel operation, this form of announcement enables a greater degree of announcement of downlink ELMs. The announcements for the downlink ELM and the Comm-B share the DR field. Only one announcement can take place at a time due to coding limitations. In case both a Comm-B and a downlink ELM are waiting, announcement preference is given to the Comm-B. In the example above, if an air-directed Comm-B was waiting for II = 2 and a multisite-directed downlink ELM was waiting for II = 6, both interrogators would see their respective announcements on the first scan since there would be no Comm-B announcement to II = 6 to block the announcement of the waiting downlink ELM.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.6.11.3.4.3.3</p> <p>Standard</p>	<p><i>Closeout.</i> Closeout shall be accomplished as specified in 3.1.2.6.11.3.2.3.</p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.3.4.3.4  Standard	<i>Announcement of the next message waiting.</i> The DR field shall indicate a message waiting in the reply to an interrogation containing a Comm-B closeout if another multisite directed message is waiting for that II code, or if an air-initiated message is waiting and has not been assigned to a II code. (See 3.1.2.6.11.3.4.2.4.)	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.3.4.4  Standard	<i>Enhanced non-selective Comm-B protocol.</i> The availability of a non-selective Comm-B message shall be announced to all interrogators. Otherwise, the protocol shall be as specified in 3.1.2.6.11.3.3.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.4.1  Standard	<p><i>3.1.2.6.11.4 Comm-B broadcast</i></p> <p><i>N1.A Comm-B message may be broadcast to all active interrogators within range. Messages are alternately numbered 1 and 2 and are self-cancelling after 18 seconds. Interrogators have no means to cancel Comm-B broadcast messages.</i></p> <p><i>N2.Use of the Comm-B broadcast is restricted to transmission of information which does not require a subsequent ground-initiated uplink response.</i></p> <p><i>N3.The timer used for the Comm-B broadcast cycle is the same as that used for the Comm-B multisite protocol.</i></p> <p><i>N4.Data formats for Comm-B broadcasts are specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i></p> <p><i>Initiation.</i> A Comm-B broadcast cycle shall not be initiated when an air-initiated Comm-B is waiting to be transmitted. A Comm-B broadcast cycle shall begin with:</p> <ul style="list-style-type: none"> <li>a) the insertion of DR code 4 or 5, (3.1.2.6.5.2) into replies with DF 4, 5, 20 or 21; and</li> <li>b) the starting of the B-timer.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.4.2  Standard	<i>Extraction.</i> To extract the broadcast message, an interrogator shall transmit RR equals 16 and DI not equal to 7 or RR equals 16 and DI equals 7 with RRS equals 0 in a subsequent interrogation.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.6.11.4.3  Standard	<i>Expiration.</i> When the B-timer period expires, the transponder shall clear the DR code for this message, discard the present broadcast message and change the broadcast message number (from 1 to 2 or 2 to 1) in preparation for a subsequent Comm-B broadcast.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.6.11.4.4  Standard	<i>Interruption.</i> In order to prevent a Comm-B broadcast cycle from delaying the delivery of an air-initiated Comm-B message, provision shall be made for an air-initiated Comm-B to interrupt a Comm-B broadcast cycle. If a broadcast cycle is interrupted, the B-timer shall be reset, the interrupted broadcast message shall be retained and the message number shall not be changed. Delivery of the interrupted broadcast message shall recommence when no air-initiated Comm-B transaction is in effect. The message shall then be broadcast for the full duration of the B-timer.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.6.11.4.5  Standard	<p><i>Enhanced broadcast Comm-B protocol.</i> A broadcast Comm-B message shall be announced to all interrogators using II codes. The message shall remain active for the period of the B-timer for each II code. The provision for interruption of a broadcast by non-broadcast Comm-B as specified in 3.1.2.6.11.4.4 shall apply separately to each II code. When the B-timer period has been achieved for all II codes, the broadcast message shall be automatically cleared as specified in 3.1.2.6.11.4.3. A new broadcast message shall not be initiated until the current broadcast has been cleared.</p> <p><i>Note.— Due to the fact that broadcast message interruption occurs independently for each II code, it is possible that the broadcast message timeout will occur at different times for different II codes.</i></p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.1  Standard	<p>3.1.2.7 EXTENDED LENGTH COMMUNICATION TRANSACTIONS</p> <p>N1. Long messages, either on the uplink or the downlink, can be transferred by the extended length message (ELM) protocols through the use of Comm-C (UF = 24) and Comm-D (DF = 24) formats respectively. The ELM uplink protocol provides for the transmission on the uplink of up to sixteen 80-bit message segments before requiring a reply from the transponder. They also allow a corresponding procedure on the downlink.</p> <p>N2. In some areas of overlapping interrogator coverage there may be no means for coordinating interrogator activities via ground communications. However, the ELM communication protocols require more than one transaction for completion; coordination is thus necessary to ensure that segments from different messages are not interleaved and that transactions are not inadvertently closed out by the wrong interrogator. This can be accomplished through the use of the multisite communications protocols or through the use of the enhanced ELM protocols.</p> <p>N3. Downlink extended length messages are transmitted only after authorization by the interrogator. The segments to be transmitted are contained in Comm-D replies. As with air-initiated Comm-B messages, downlink ELMs are either announced to all interrogators or directed to a specific interrogator. In the former case an individual interrogator can use the multisite protocol to reserve for itself the ability to close out the downlink ELM transaction. A transponder can be instructed to identify the interrogator that has reserved the transponder for an ELM transaction. Only that interrogator can close out the ELM transaction and reservation.</p> <p>N4. The multisite protocol and the non-selective protocol cannot be used simultaneously in a region of overlapping interrogator coverage unless the interrogators coordinate their communications activities via ground communications.</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																						
	<p><i>COMM-C, UPLINK FORMAT 24</i></p> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%; text-align: center;">1</td> <td style="width: 25%; text-align: center;">3</td> <td style="width: 25%; text-align: center;">5</td> <td style="width: 25%; text-align: center;">9</td> </tr> <tr> <td></td> <td style="text-align: center;">89</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">UF RC NC MC AP</td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">4</td> <td style="text-align: center;">8</td> <td style="text-align: center;">88</td> </tr> <tr> <td></td> <td style="text-align: center;">112</td> <td></td> <td></td> </tr> </table> <p>The format of this interrogation shall consist of these fields:</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><i>Field</i></th> <th style="text-align: left;"><i>Referenc</i></th> </tr> </thead> <tbody> <tr> <td><i>e</i></td> <td></td> </tr> <tr> <td>UF uplink format</td> <td>3.1.2.3.2.1</td> </tr> <tr> <td>.1</td> <td></td> </tr> <tr> <td>RC reply control</td> <td>3.1.2.7.1.1</td> </tr> <tr> <td>NC number of C-segment</td> <td>3.1.2.7.1.2</td> </tr> <tr> <td>MC message, Comm-C</td> <td>3.1.2.7.1.3</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1</td> </tr> <tr> <td>.3</td> <td></td> </tr> </tbody> </table>	1	3	5	9		89				UF RC NC MC AP			2	4	8	88		112			<i>Field</i>	<i>Referenc</i>	<i>e</i>		UF uplink format	3.1.2.3.2.1	.1		RC reply control	3.1.2.7.1.1	NC number of C-segment	3.1.2.7.1.2	MC message, Comm-C	3.1.2.7.1.3	AP address/parity	3.1.2.3.2.1	.3					
1	3	5	9																																								
	89																																										
	UF RC NC MC AP																																										
2	4	8	88																																								
	112																																										
<i>Field</i>	<i>Referenc</i>																																										
<i>e</i>																																											
UF uplink format	3.1.2.3.2.1																																										
.1																																											
RC reply control	3.1.2.7.1.1																																										
NC number of C-segment	3.1.2.7.1.2																																										
MC message, Comm-C	3.1.2.7.1.3																																										
AP address/parity	3.1.2.3.2.1																																										
.3																																											





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.1.1  Standard	<p><i>RC: Reply control.</i> This 2-bit (3-4) uplink field shall designate segment significance and reply decision.</p> <p><i>Coding</i></p> <p>RC = 0 signifies uplink ELM initial segment in MC</p> <p>MC = 1 signifies uplink ELM intermediate segment in MC</p> <p>MC = 2 signifies uplink ELM final segment in MC</p> <p>MC = 3 signifies a request for downlink ELM delivery (3.1.2.7.7.2)</p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.1.2  Standard	<p><i>NC: Number of C-segment.</i> This 4-bit (5-8) uplink field shall designate the number of the message segment contained in MC (3.1.2.7.4.2.1). NC shall be coded as a binary number.</p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.1.3  Standard	<p><i>MC: Message, Comm-C.</i> This 80-bit (9-88) uplink field shall contain:</p> <p>a) one of the segments of a sequence used to transmit an uplink ELM to the transponder containing the 4-bit (9-12) IIS subfield; or</p> <p>b) control codes for a downlink ELM, the 16-bit (9-24) SRS subfield (3.1.2.7.7.2.1) and the 4-bit (25-28) IIS subfield.</p> <p><i>Note.— Message content and codes are not included in this chapter except for 3.1.2.7.7.2.1.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																
Chapter 3 Reference 3.1.2.7.2  Note	<p><i>INTERROGATION-REPLY PROTOCOL FOR UF24</i></p> <p><i>Note.— Interrogation-reply coordination for the above format follows the protocol outlined in Table 3-5 (3.1.2.4.1.3.2.2).</i></p>		Not Applicable		Compliance data not required for Notes.																																
Chapter 3 Reference 3.1.2.7.3  Standard	<p><i>COMM-D, DOWNLINK FORMAT 24</i></p> <table style="margin-left: 40px;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">4</td> <td style="text-align: center;">5</td> <td style="text-align: center;">9</td> </tr> <tr> <td colspan="4" style="text-align: center;">89</td> </tr> <tr> <td style="text-align: center;">DF</td> <td style="text-align: center;">KE</td> <td style="text-align: center;">ND</td> <td style="text-align: center;">MD AP</td> </tr> <tr> <td style="text-align: center;">2</td> <td></td> <td style="text-align: center;">8</td> <td style="text-align: center;">88</td> </tr> <tr> <td colspan="4" style="text-align: center;">112</td> </tr> </table> <p>The format of this reply shall consist of these fields:</p> <table style="margin-left: 40px;"> <tr> <td style="text-align: center;"><i>Field</i></td> <td style="text-align: center;"><i>Reference</i></td> </tr> <tr> <td>DF downlink format spare — 1 bit</td> <td style="text-align: center;">3.1.2.3.2.1.2</td> </tr> <tr> <td>KE control, ELM</td> <td style="text-align: center;">3.1.2.7.3.1</td> </tr> <tr> <td>ND number of D-segment</td> <td style="text-align: center;">3.1.2.7.3.2</td> </tr> <tr> <td>MD message, Comm-D</td> <td style="text-align: center;">3.1.2.7.3.3</td> </tr> <tr> <td>AP address/parity</td> <td style="text-align: center;">3.1.2.3.2.1.3</td> </tr> </table>	1	4	5	9	89				DF	KE	ND	MD AP	2		8	88	112				<i>Field</i>	<i>Reference</i>	DF downlink format spare — 1 bit	3.1.2.3.2.1.2	KE control, ELM	3.1.2.7.3.1	ND number of D-segment	3.1.2.7.3.2	MD message, Comm-D	3.1.2.7.3.3	AP address/parity	3.1.2.3.2.1.3	CAR Part 91 Appendix A, A.22.	No Difference		
1	4	5	9																																		
89																																					
DF	KE	ND	MD AP																																		
2		8	88																																		
112																																					
<i>Field</i>	<i>Reference</i>																																				
DF downlink format spare — 1 bit	3.1.2.3.2.1.2																																				
KE control, ELM	3.1.2.7.3.1																																				
ND number of D-segment	3.1.2.7.3.2																																				
MD message, Comm-D	3.1.2.7.3.3																																				
AP address/parity	3.1.2.3.2.1.3																																				
Chapter 3 Reference 3.1.2.7.3.1  Standard	<p><i>KE: Control, ELM.</i> This 1-bit (4) downlink field shall define the content of the ND and MD fields.</p> <p><i>Coding</i></p> <table style="margin-left: 40px;"> <tr> <td>KE</td> <td>=</td> <td>0</td> <td>signifies downlink ELM transmission</td> </tr> <tr> <td></td> <td></td> <td>1</td> <td>signifies uplink ELM acknowledgement</td> </tr> </table>	KE	=	0	signifies downlink ELM transmission			1	signifies uplink ELM acknowledgement	CAR Part 91 Appendix A, A.22.	No Difference																										
KE	=	0	signifies downlink ELM transmission																																		
		1	signifies uplink ELM acknowledgement																																		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.3.2  Standard	<i>ND: Number of D-segment.</i> This 4-bit (5-8) downlink field shall designate the number of the message segment contained in MD (3.1.2.7.7.2). ND shall be coded as a binary number.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.3.3  Standard	<i>MD: Message, Comm-D.</i> This 80-bit (9-88) downlink field shall contain: a) one of the segments of a sequence used to transmit a downlink ELM to the interrogator; or b) control codes for an uplink ELM.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.4.1  Standard	<i>3.1.2.7.4 MULTISITE UPLINK ELM PROTOCOL</i>  <i>Multisite uplink ELM reservation.</i> An interrogator shall request a reservation for an uplink ELM by transmitting a surveillance or Comm-A interrogation containing: DI = 1 IIS = assigned interrogator identifier MES = 1 or 5 (uplink ELM reservation request)  <i>Note.— A multisite uplink ELM reservation request is normally accompanied by an uplink ELM reservation status request (RSS = 2). This causes the interrogator identifier of the reserved site to be inserted in the UM field of the reply.</i>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.4.1.1  Standard	<p>Protocol procedure in response to this interrogation shall depend upon the state of the C-timer which indicates if an uplink ELM reservation is active. This timer shall run for <math>T_R</math> seconds.</p> <p>N1. <i>The value of <math>T_R</math> is given in 3.1.2.10.3.9.</i></p> <p>a) If the C-timer is not running the transponder shall grant a reservation to the requesting interrogator by:</p> <ol style="list-style-type: none"> <li>1) storing the IIS of the interrogation as the Comm-C II and,</li> <li>2) starting the C-timer.</li> </ol> <p>b) If the C-timer is running and the IIS of the interrogation equals the Comm-C II, the transponder shall restart the C-timer.</p> <p>c) If the C-timer is running and the IIS of the interrogation does not equal the Comm-C II, there shall be no change to the Comm-C II or the C-timer.</p> <p>N2. <i>In case c) the reservation request has been denied.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.4.1.2  Standard	<p>An interrogator shall not start ELM activity unless, during the same scan, having requested an uplink ELM status report, it has received its own interrogator identifier as the reserved interrogator for uplink ELM in the UM field.</p> <p><i>Note.— If ELM activity is not started during the same scan as the reservation, a new reservation request may be made during the next scan.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.4.1.3  Standard	<p>If uplink ELM delivery is not completed on the current scan, the interrogator shall ensure that it still has a reservation before delivering additional segments on a subsequent scan.</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.4.2  Standard	<i>Multisite uplink ELM delivery.</i> The minimum length of an uplink ELM shall be 2 segments, the maximum length shall be 16 segments.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.4.2.1  Standard	<i>Initial segment transfer.</i> The interrogator shall begin the ELM uplink delivery for an n-segment message (NC values from 0 to n-1) by a Comm-C transmission containing RC equals 0. The message segment transmitted in the MC field shall be the last segment of the message and shall carry NC equals n-1. On receipt of an initializing segment (RC = 0) the transponder shall establish a “setup” defined as: <ul style="list-style-type: none"> <li>a) clearing the number and content of previous segment storage registers and the associated TAS field;</li> <li>b) assigning storage space for the number of segments announced in NC of this interrogation; and</li> <li>c) storing the MC field of the segment received.</li> </ul> The transponder shall not reply to this interrogation. Receipt of another initializing segment shall result in a new setup within the transponder.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.4.2.2  Standard	<i>Transmission acknowledgement.</i> The transponder shall use the TAS subfield to report the segments received so far in an uplink ELM sequence. The information contained in the TAS subfield shall be continually updated by the transponder as segments are received.  <i>Note.— Segments lost in uplink transmission are noted by their absence in the TAS report and are retransmitted by the interrogator which will then send further final segments to assess the extent of message completion.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.4.2.2.1  Standard	<i>TAS, transmission acknowledgement subfield in MD.</i> This 16-bit (17-32) downlink subfield in MD reports the segment numbers received so far in an uplink ELM sequence. Starting with bit 17, which denotes segment number 0, each of the following bits shall be set to ONE if the corresponding segment of the sequence has been received. TAS shall appear in MD if KE equals 1 in the same reply.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.4.2.3  Standard	<i>Intermediate segment transfer.</i> The interrogator shall transfer intermediate segments by transmitting Comm-C interrogations with RC equals 1. The transponder shall store the segments and update TAS only if the setup of 3.1.2.7.4.2.1 is in effect and if the received NC is smaller than the value stored at receipt of the initial segment. No reply shall be generated on receipt of an intermediate segment.  <i>Note.— Intermediate segments may be transmitted in any order.</i>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.4.2.4  Standard	<i>Final segment transfer.</i> The interrogator shall transfer a final segment by transmitting a Comm-C interrogation with RC equals 2. The transponder shall store the content of the MC field and update TAS if the setup of 3.1.2.7.4.2.1 is in effect and if the received NC is smaller than the value of the initial segment NC. The transponder shall reply under all circumstances as per 3.1.2.7.4.2.5.  <i>N1.This final segment transfer interrogation can contain any message segment.</i>  <i>N2.RC equals 2 is transmitted any time that the interrogator wants to receive the TAS subfield in the reply. Therefore, more than one "final" segment may be transferred during the delivery of an uplink ELM.</i>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.4.2.5  Standard	<i>Acknowledgement reply.</i> On receipt of a final segment, the transponder shall transmit a Comm-D reply (DF = 24), with KE equals 1 and with the TAS subfield in the MD field. This reply shall be transmitted at 128 microseconds plus or minus 0.25 microsecond following the sync phase reversal of the interrogation delivering the final segment.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.4.2.6  Standard	<i>Completed message.</i> The transponder shall deem the message complete if all segments announced by NC in the initializing segment have been received. If the message is complete, the message content shall be delivered to the outside via the ELM interface of 3.1.2.10.5.2.1.3 and cleared. No later-arriving segments shall be stored. The TAS content shall remain unchanged until either a new setup is called for (3.1.2.7.4.2.1) or until closeout (3.1.2.7.4.2.8).	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.4.2.7  Standard	<i>C-timer restart.</i> The C-timer shall be restarted each time that a received segment is stored and the Comm-C II is not 0. <i>Note.— The requirement for the Comm-C II to be non-zero prevents the C-timer from being restarted during a non-selective uplink ELM transaction.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.4.2.8  Standard	<p><i>Multisite uplink ELM closeout.</i> The interrogator shall close out a multisite uplink ELM by transmitting either a surveillance or a Comm-A interrogation containing:</p> <p><i>either</i> DI = 1 IIS = assigned interrogator identifier MES = 2,6 or 7 (uplink ELM closeout)</p> <p><i>or</i> DI = 0, 1 or 7 IIS = assigned interrogator identifier PC = 5 (uplink ELM closeout)</p> <p>The transponder shall compare the IIS of the interrogation to the Comm-C II and if the interrogator identifiers do not match, the state of the ELM uplink process shall not be changed. If the interrogator identifiers match, the transponder shall set the Comm-C II to 0, reset the C-timer, clear the stored TAS and discard any stored segments of an incomplete message.</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.4.2.9  Standard	<p><i>Automatic multisite uplink ELM closeout.</i> If the C-timer period expires before a multisite closeout has been accomplished the closeout actions described in 3.1.2.7.4.2.8 shall be initiated automatically by the transponder.</p>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.5  Standard	<p><i>NON-SELECTIVE UPLINK ELM</i></p> <p><i>Note.— In cases where the multisite protocols are not required (for example, no overlapping coverage or sensor coordination via ground-to-ground communication), the non-selective uplink ELM protocol may be used.</i></p> <p>Non-selective uplink ELM delivery shall take place as for multisite uplink ELMs described in 3.1.2.7.4.2. The interrogator shall close out an uplink ELM by transmitting PC equals 5 (uplink ELM closeout) in a surveillance or Comm-A interrogation. On receipt of this command, the transponder shall perform closeout, unless the C-timer is running. If the C-timer is running, indicating that a multisite reservation is in effect, the closeout shall be accomplished as per 3.1.2.7.4.2.8. An uncompleted message, present when the closeout is accepted, shall be cancelled.</p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.7.6.1.1</p> <p>Standard</p>	<p>3.1.2.7.6 ENHANCED UPLINK ELM PROTOCOL</p> <p><i>Note.— The enhanced uplink ELM protocol provides a higher data link capacity by permitting parallel delivery of uplink ELM messages by up to sixteen interrogators, one for each II code. Operation without the need for multisite uplink ELM reservations is possible in regions of overlapping coverage for interrogators equipped for the enhanced uplink ELM protocol. The protocol is fully conformant to the standard multisite protocol and thus is compatible with interrogators that are not equipped for the enhanced protocol.</i></p> <p>3.1.2.7.6.1 General</p> <p>The interrogator shall determine from the data link capability report whether the transponder supports the enhanced protocols. If the enhanced protocols are not supported by both the interrogator and the transponder, the multisite reservation protocols specified in 3.1.2.7.4.1 shall be used.</p> <p><i>Note.— If the enhanced protocols are supported, uplink ELMs delivered using the multisite protocol may be delivered without a prior reservation.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.7.6.1.2</p> <p>Recommendation</p>	<p><b>Recommendation.—</b> <i>If the transponder and the interrogator are equipped for the enhanced protocol, the interrogator should use the enhanced uplink protocol.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.6.1.3  Standard	The transponder shall be capable of storing a sixteen segment message for each of the sixteen II codes.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.6.2  Standard	<i>Reservation processing.</i> The transponder shall support reservation processing for each II code as specified in 3.1.2.7.4.1 <i>N1.Reservation processing is required for interrogators that do not support the enhanced protocol.</i> <i>N2.Since the transponder can process simultaneous uplink ELMs for all sixteen II codes, a reservation will always be granted.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.6.3  Standard	<i>Enhanced uplink ELM delivery and closeout.</i> The transponder shall process received segments separately by II code. For each value of II code, uplink ELM delivery and closeout shall be performed as specified in 3.1.2.7.4.2 except that the MD field used to transmit the technical acknowledgment shall also contain the 4-bit (33-36) IIS subfield. <i>Note.— The interrogator may use the II code contained in the technical acknowledgement in order to verify that it has received the correct technical acknowledgement.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.7.1  Standard	<p>3.1.2.7.7 <i>MULTISITE DOWNLINK ELM PROTOCOL</i></p> <p><i>Initialization.</i> The transponder shall announce the presence of a downlink ELM of <i>n</i> segments by making the binary code corresponding to the decimal value 15 + <i>n</i> available for insertion in the DR field of a surveillance or Comm-B reply, DF equals 4, 5, 20, 21. This announcement shall remain active until the ELM is closed out (3.1.2.7.7.3, 3.1.2.7.8.1).</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.7.1.1  Standard	<p><i>Multisite downlink ELM reservation.</i> An interrogator shall request a reservation for extraction of a downlink ELM by transmitting a surveillance or Comm-A interrogation containing:</p> <p style="padding-left: 40px;">DI = 1 IIS = assigned interrogator identifier MES = 3 or 6 (downlink ELM reservation request)</p> <p><i>Note.— A multisite downlink ELM reservation request is normally accompanied by a downlink ELM reservation status request (RSS = 3). This causes the interrogator identifier of the reserved interrogator to be inserted in the UM field of the reply.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.7.7.1.1.1</p> <p>Standard</p>	<p>Protocol procedure in response to this interrogation shall depend upon the state of the D-timer which indicates if a downlink ELM reservation is active. This timer shall run for <math>T_R</math> seconds.</p> <p>N1. <i>The value of <math>T_R</math> is given in 3.1.2.10.3.9.</i></p> <p>a) if the D-timer is not running, the transponder shall grant a reservation to the requesting interrogator by:</p> <ol style="list-style-type: none"> <li>1) storing the IIS of the interrogation as the Comm-D II; and</li> <li>2) starting the D-timer.</li> </ol> <p>A multisite downlink ELM reservation shall not be granted by the transponder unless a downlink ELM is waiting to be transmitted.</p> <p>b) if the D-timer is running and the IIS of the interrogation equals the Comm-D II, the transponder shall restart the D-timer; and</p> <p>c) if the D-timer is running and the IIS of the interrogation does not equal the Comm-D II, there shall be no change to the Comm-D II or D-timer.</p> <p>N2. <i>In case c) the reservation request has been denied.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.7.7.1.1.2</p> <p>Standard</p>	<p>An interrogator shall determine if it is the reserved site through coding in the UM field and, if so, it is authorized to request delivery of the downlink ELM. Otherwise, ELM activity shall not be started during this scan.</p> <p><i>Note.— If the interrogator is not the reserved site, a new reservation request may be made during the next scan.</i></p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.7.7.1.1.3</p> <p>Standard</p>	<p>If downlink ELM activity is not completed on the current scan, the interrogator shall ensure that it still has a reservation before requesting additional segments on a subsequent scan.</p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.7.1.2  Standard	<p><i>Multisite-directed downlink ELM transmissions.</i> To direct a downlink ELM message to a specific interrogator, the multisite downlink ELM protocol shall be used. When the D-timer is not running, the interrogator identifier of the desired destination shall be stored as the Comm-D II. Simultaneously, the D-timer shall be started and the DR code (3.1.2.7.7.1) shall be set. For a multisite-directed downlink ELM, the D-timer shall not automatically time out but shall continue to run until:</p> <ul style="list-style-type: none"> <li>a) the message is read and closed out by the reserved site; or</li> <li>b) the message is cancelled (3.1.2.10.5.4) by the data link avionics.</li> </ul> <p><i>Note.— The protocols of 3.1.2.7.7.1 will then result in the delivery of the message to the reserved site. The data link avionics may cancel the message if delivery to the reserved site cannot be accomplished.</i></p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.7.2  Standard	<p><i>Delivery of downlink ELMs.</i> The interrogator shall extract a downlink ELM by transmitting a Comm-C interrogation with RC equals 3. This interrogation shall carry the SRS subfield which specifies the segments to be transmitted. On receipt of this request, the transponder shall transfer the requested segments by means of Comm-D replies with KE equals 0 and ND corresponding to the number of the segment in MD. The first segment shall be transmitted 128 microseconds plus or minus 0.25 microsecond following the sync phase reversal of the interrogation requesting delivery and subsequent segments shall be transmitted at a rate of one every 136 microseconds plus or minus 1 microsecond. If a request is received to transmit downlink ELM segments and no message is waiting, each reply segment shall contain all ZEROS in the MD field.</p> <p><i>N1.The requested segments may be transmitted in any order.</i></p> <p><i>N2.Segments lost in downlink transmissions will be requested again by the interrogator on a subsequent interrogation carrying the SRS subfield. This process is repeated until all segments have been transferred.</i></p>	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.7.2.1  Standard	<p><i>SRS, segment request subfield in MC.</i> This 16-bit (9-24) uplink subfield in MC shall request the transponder to transfer downlink ELM segments. Starting with bit 9, which denotes segment number 0, each of the following bits shall be set to ONE if the transmission of the corresponding segment is requested. SRS shall appear in MC if RC equals 3 in the same interrogation.</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.7.2.2  Standard	<p><i>D-timer restart.</i> The D-timer shall be restarted each time that a request for Comm-D segments is received if the Comm-D II is non-zero.</p> <p><i>Note.— The requirement for the Comm-D II to be non-zero prevents the D-timer from being restarted during a non-selective downlink ELM transaction.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.7.3  Standard	<p><i>Multisite downlink ELM closeout.</i> The interrogator shall close out a multisite downlink ELM by transmitting either a surveillance or a Comm-A interrogation containing:</p> <p style="padding-left: 40px;"><i>either</i> DI = 1 IIS = assigned interrogator identifier MES = 4, 5 or 7 (downlink ELM closeout)</p> <p style="padding-left: 40px;"><i>or</i> DI = 0, 1 or 7 IIS = assigned interrogator identifier PC = 6 (downlink ELM closeout)</p> <p>The transponder shall compare the IIS of the interrogation to the Comm-D II and if the interrogator identifiers do not match, the state of the downlink process shall not be changed.</p> <p>If the interrogator identifiers match, and if a request for transmission has been complied with at least once, the transponder shall set the Comm-D II to 0, reset the D-timer, clear the DR code for this message and clear the message itself.</p> <p>If another downlink ELM is waiting to be transmitted, the transponder shall set the DR code (if no Comm-B message is waiting to be delivered) so that the reply contains the announcement of the next message.</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.7.4  Standard	<i>Automatic expiration of downlink ELM reservation.</i> If the D-timer period expires before a multisite closeout has been accomplished, the Comm-D II shall be set to 0, and the D-timer reset. The message and DR code shall not be cleared. <i>Note.— This makes it possible for another site to read and clear this message.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.8  Standard	<i>NON-SELECTIVE DOWNLINK ELM</i> <i>Note.— In cases where the multisite protocols are not required (i.e. no overlapping coverage or sensor coordination via ground-to-ground communication), the non-selective downlink ELM protocol may be used.</i> Non-selective downlink ELM delivery shall take place as described in 3.1.2.7.7.2.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.8.1  Standard	<i>Non-selective downlink ELM closeout.</i> The interrogator shall close out a non-selective downlink ELM by transmitting PC equals 6 (downlink ELM closeout) in a surveillance or Comm-A interrogation. On receipt of this command, and if a request for transmission has been complied with at least once, the transponder shall perform closeout unless the D-timer is running. If the D-timer is running, indicating that a multisite reservation is in effect, the closeout shall be accomplished as per 3.1.2.7.7.3.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.7.9.1.1</p> <p>Standard</p>	<p>3.1.2.7.9 ENHANCED DOWNLINK ELM PROTOCOL</p> <p><i>Note.— The enhanced downlink ELM protocol provides a higher data link capacity by permitting parallel delivery of downlink ELM messages by up to sixteen interrogators, one for each II code. Operation without the need for multisite downlink ELM reservations is possible in regions of overlapping coverage for interrogators equipped for the enhanced downlink ELM protocol. The protocol is fully conformant to the standard multisite protocol and thus is compatible with interrogators that are not equipped for the enhanced protocol.</i></p> <p>3.1.2.7.9.1 General</p> <p>The interrogator shall determine from the data link capability report whether the transponder supports the enhanced protocols. If the enhanced protocols are not supported by both the interrogator and the transponder, the multisite reservation protocols specified in 3.1.2.6.11 shall be used for multisite and multisite-directed downlink ELMs.</p> <p><i>Note.— If the enhanced protocols are supported, downlink ELMs delivered using the multisite-directed protocol can be delivered without a prior reservation.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.7.9.1.2</p> <p>Recommendation</p>	<p><b>Recommendation.—</b> <i>If the transponder and the interrogator are equipped for the enhanced protocol, the interrogator should use the enhanced downlink protocol.</i></p>	<p>CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.9.2.1  Standard	<p><i>3.1.2.7.9.2 Enhanced multisite downlink ELM protocol</i></p> <p>The transponder shall be capable of storing a sixteen segment message for each of the sixteen II codes.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.9.2.2  Standard	<p><i>Initialization.</i> A multisite message input into the transponder shall be stored in the registers assigned to II = 0.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.9.2.3  Standard	<p><i>Announcement and extraction.</i> A waiting multisite downlink ELM message shall be announced in the DR field of the replies to all interrogators for which a multisite directed downlink ELM message is not waiting. The UM field of the announcement reply shall indicate that the message is not reserved for any II code, i.e. the IIS subfield shall be set to 0. When a command to reserve this message is received from a given interrogator, the message shall be reserved for the II code contained in the interrogation from that interrogator. After readout and until closeout, the message shall continue to be assigned to that II code. Once a message is assigned to a specific II code, announcement of this message shall no longer be made in the replies to interrogators with other II codes. If the message is not closed out by the associated interrogator for the period of the D-timer, the message shall revert back to multisite status and the process shall repeat. Only one multisite downlink ELM message shall be in process at a time.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.9.2.4  Standard	<i>Closeout.</i> A closeout for a multisite message shall only be accepted from the interrogator that was assigned most recently to transfer the message.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.9.2.5  Standard	<i>Announcement of the next message waiting.</i> The DR field shall indicate a message waiting in the reply to an interrogation containing a downlink ELM closeout if an unassigned multisite downlink ELM is waiting, or if a multisite directed message is waiting for that II code (3.1.2.7.9.2).	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.9.3.1  Standard	<i>3.1.2.7.9.3 Enhanced multisite directed downlink ELM protocol</i>  <i>Initialization.</i> When a multisite directed message is input into the transponder, it shall be placed in the downlink ELM registers assigned to the II code specified for the message. If the registers for this II code are already in use (i.e. a multisite directed downlink ELM message is already in process for this II code), the new message shall be queued until the current transaction with that II code is closed out.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.9.3.2  Standard	<i>Announcement.</i> Announcement of a downlink ELM message waiting transfer shall be made using the DR field as specified in 3.1.2.7.7.1 with the destination interrogator II code contained in the IIS subfield as specified in 3.1.2.6.5.3.2. The DR field and IIS subfield contents shall be set specifically for the interrogator that is to receive the reply. A waiting multisite directed message shall only be announced in the replies to the intended interrogator. It shall not be announced in replies to other interrogators.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.7.9.3.3  Standard	<i>Delivery.</i> An interrogator shall determine if it is the reserved site through coding in the UM field. The delivery shall only be requested if it is the reserved site and shall be as specified in 3.1.2.7.7.2. The transponder shall transmit the message contained in the buffer associated with the II code specified in the IIS subfield of the segment request interrogation.	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.9.3.4  Standard	<i>Closeout.</i> Closeout shall be accomplished as specified in 3.1.2.7.7.3 except that a message closeout shall only be accepted from the interrogator with a II code equal to the one that transferred the message.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.7.9.3.5  Standard	<i>Announcement of the next message waiting.</i> The DR field shall indicate a message waiting in the reply to an interrogation containing a downlink ELM closeout if another multisite directed message is waiting for that II code, or if a downlink message is waiting that has not been assigned a II code (3.1.2.7.9.2).	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.7.9.4  Standard	<i>Enhanced non-selective downlink ELM protocol.</i> The availability of a non-selective downlink ELM message shall be announced to all interrogators. Otherwise, the protocol shall be as specified in 3.1.2.7.7.	CAR 171.53(a)(1); CAR Part 91 Appendix A, A.22.	No Difference		Flag for check



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																										
Chapter 3 Reference 3.1.2.8.1  Standard	<p>3.1.2.8 AIR-AIR SERVICE AND SQUITTER TRANSACTIONS</p> <p><i>Note.— Airborne collision avoidance system (ACAS) equipment uses the formats UF or DF equals 0 or 16 for air-air surveillance.</i></p> <p>SHORT AIR-AIR SURVEILLANCE, UPLINK FORMAT 0</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%; text-align: center;">1</td> <td style="width: 10%;"></td> <td style="width: 10%; text-align: center;">9</td> <td style="width: 10%;"></td> <td style="width: 10%; text-align: center;">14</td> <td style="width: 10%; text-align: center;">15</td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">33</td> <td></td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">UF</td> <td style="text-align: center;">RL</td> <td style="text-align: center;">AQ</td> <td style="text-align: center;">DS</td> <td style="text-align: center;">AP</td> <td></td> </tr> <tr> <td style="text-align: center;">5</td> <td></td> <td></td> <td></td> <td></td> <td style="text-align: center;">22</td> </tr> <tr> <td></td> <td style="text-align: center;">56</td> <td></td> <td></td> <td></td> <td></td> </tr> </table> <p>The format of this interrogation shall consist of these fields:</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><i>Field</i></th> <th style="text-align: left;"><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>UF uplink format spare — 3 bits</td> <td>3.1.2.3.2.1.1</td> </tr> <tr> <td>RL reply length spare — 4 bits</td> <td>3.1.2.8.1.2</td> </tr> <tr> <td>AQ acquisition</td> <td>3.1.2.8.1.1</td> </tr> <tr> <td>DS data selector spare — 10 bits</td> <td>3.1.2.8.1.3</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </tbody> </table>	1		9		14	15			33				UF	RL	AQ	DS	AP		5					22		56					<i>Field</i>	<i>Reference</i>	UF uplink format spare — 3 bits	3.1.2.3.2.1.1	RL reply length spare — 4 bits	3.1.2.8.1.2	AQ acquisition	3.1.2.8.1.1	DS data selector spare — 10 bits	3.1.2.8.1.3	AP address/parity	3.1.2.3.2.1.3	CAR Part 91 Appendix A, A.22.	No Difference		
1		9		14	15																																										
		33																																													
UF	RL	AQ	DS	AP																																											
5					22																																										
	56																																														
<i>Field</i>	<i>Reference</i>																																														
UF uplink format spare — 3 bits	3.1.2.3.2.1.1																																														
RL reply length spare — 4 bits	3.1.2.8.1.2																																														
AQ acquisition	3.1.2.8.1.1																																														
DS data selector spare — 10 bits	3.1.2.8.1.3																																														
AP address/parity	3.1.2.3.2.1.3																																														
Chapter 3 Reference 3.1.2.8.1.1  Standard	<p><i>AQ: Acquisition.</i> This 1-bit (14) uplink field shall contain a code which controls the content of the RI field.</p>	CAR Part 91 Appendix A, A.22.	No Difference																																												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.1.2  Standard	<p><i>RL: Reply length.</i> This 1-bit (9) uplink field shall command the format to be used for the reply.</p> <p><i>Coding</i></p> <p>0            signifies a reply with DF = 0</p> <p>1            signifies a reply with DF = 16</p> <p><i>Note.— A transponder that does not support DF = 16 (i.e. transponder which does not support the ACAS cross-link capability and is not associated with airborne collision avoidance equipment) would not reply to a UF=0 interrogation with RL=1.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.1.3  Standard	<p><i>DS: Data selector.</i> This 8-bit (15-22) uplink field shall contain the BDS code (3.1.2.6.11.2.1) of the GICB register whose contents shall be returned to the corresponding reply with DF = 16.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																				
Chapter 3 Reference 3.1.2.8.2  Standard	<p><i>SHORT AIR-AIR SURVEILLANCE, DOWNLINK FORMAT 0</i></p> <table border="0"> <tr> <td>1</td> <td>6</td> <td>7</td> <td>9</td> <td>14</td> </tr> <tr> <td></td> <td>20</td> <td>33</td> <td></td> <td></td> </tr> <tr> <td>DF</td> <td>VS</td> <td>CC</td> <td>SL</td> <td>RI</td> </tr> <tr> <td></td> <td></td> <td></td> <td>AC</td> <td>AP</td> </tr> <tr> <td>5</td> <td></td> <td></td> <td>11</td> <td>17</td> </tr> <tr> <td></td> <td>32</td> <td>56</td> <td></td> <td></td> </tr> </table> <p>This reply shall be sent in response to an interrogation with UF equals 0 and RL equals 0. The format of this reply shall consist of these fields:</p> <table border="0"> <thead> <tr> <th style="text-align: left;"><i>Field</i></th> <th style="text-align: left;"><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>VS vertical status</td> <td>3.1.2.8.2.1</td> </tr> <tr> <td>CC cross-link capability</td> <td>3.1.2.8.2.3</td> </tr> <tr> <td>spare — 1 bit</td> <td></td> </tr> <tr> <td>SL sensitivity level, ACAS</td> <td>4.3.8.4.2.5</td> </tr> <tr> <td>spare — 2 bits</td> <td></td> </tr> <tr> <td>RI reply information</td> <td>3.1.2.8.2.2</td> </tr> <tr> <td>spare — 2 bits</td> <td></td> </tr> <tr> <td>AC altitude code</td> <td>3.1.2.6.5.4</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </tbody> </table>	1	6	7	9	14		20	33			DF	VS	CC	SL	RI				AC	AP	5			11	17		32	56			<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	VS vertical status	3.1.2.8.2.1	CC cross-link capability	3.1.2.8.2.3	spare — 1 bit		SL sensitivity level, ACAS	4.3.8.4.2.5	spare — 2 bits		RI reply information	3.1.2.8.2.2	spare — 2 bits		AC altitude code	3.1.2.6.5.4	AP address/parity	3.1.2.3.2.1.3	CAR Part 91 Appendix A, A.22.	No Difference		
1	6	7	9	14																																																					
	20	33																																																							
DF	VS	CC	SL	RI																																																					
			AC	AP																																																					
5			11	17																																																					
	32	56																																																							
<i>Field</i>	<i>Reference</i>																																																								
DF downlink format	3.1.2.3.2.1.2																																																								
VS vertical status	3.1.2.8.2.1																																																								
CC cross-link capability	3.1.2.8.2.3																																																								
spare — 1 bit																																																									
SL sensitivity level, ACAS	4.3.8.4.2.5																																																								
spare — 2 bits																																																									
RI reply information	3.1.2.8.2.2																																																								
spare — 2 bits																																																									
AC altitude code	3.1.2.6.5.4																																																								
AP address/parity	3.1.2.3.2.1.3																																																								
Chapter 3 Reference 3.1.2.8.2.1  Standard	<p><i>VS: Vertical status:</i> This 1-bit (6) downlink field shall indicate the status of the aircraft (3.1.2.6.10.1.2).</p> <p><i>Coding</i></p> <table border="0"> <tr> <td>0</td> <td>signifies that the aircraft is airborne</td> </tr> <tr> <td>1</td> <td>signifies that the aircraft is on the ground</td> </tr> </table>	0	signifies that the aircraft is airborne	1	signifies that the aircraft is on the ground	CAR Part 91 Appendix A, A.22.	No Difference																																																		
0	signifies that the aircraft is airborne																																																								
1	signifies that the aircraft is on the ground																																																								





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.2.2</p> <p><b>Standard</b></p>	<p><i>RI: Reply information, air-air.</i> This 4-bit (14-17) downlink field shall report the aircraft's maximum cruising true airspeed capability and type of reply to interrogating aircraft. The coding shall be as follows:</p> <p>0            signifies a reply to an air-air interrogation UF = 0 with AQ = 0, no operating ACAS</p> <p>1-7          reserved for ACAS</p> <p>8-15        signifies a reply to an air-air interrogation UF = 0 with AQ = 1 and that the maximum airspeed is as follows:</p> <p>8            no maximum airspeed data available</p> <p>9            maximum airspeed is .LE. 140 km/h (75 kt)</p> <p>10          maximum airspeed is .GT. 140 and .LE. 280 km/h (75 and 150 kt)</p> <p>11          maximum airspeed is .GT. 280 and .LE. 560 km/h (150 and 300 kt)</p> <p>12          maximum airspeed is .GT. 560 and .LE. 1 110 km/h (300 and 600 kt)</p> <p>13          maximum airspeed is .GT. 1 110 and .LE. 2 220 km/h (600 and 1 200 kt)</p> <p>14          maximum airspeed is more than 2 220 km/h (1 200 kt)</p> <p>15          not assigned..</p> <p><i>Note.— “.LE.” means “less than or equal to” and “.GT.” means “greater than”.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.2.3  Standard	<p><i>CC: Cross-link capability.</i> This 1-bit (7) downlink field shall indicate the ability of the transponder to support the cross-link capability, i.e. decode the contents of the DS field in an interrogation with UF equals 0 and respond with the contents of the specified GICB register in the corresponding reply with DF equals 16.</p> <p><i>Coding</i></p> <p>0 signifies that the transponder cannot support the cross-link capability</p> <p>1 signifies that the transponder supports the cross-link capability.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																						
Chapter 3 Reference 3.1.2.8.3  Standard	<p><i>LONG AIR-AIR SURVEILLANCE, DOWNLINK FORMAT 16</i></p> <p>1            6            9            14            20    33</p> <p>                 89</p> <p>DF VS SL RI            AC MV AP</p> <p>5                            11            17            32    88</p> <p>                 112</p> <p>This reply shall be sent in response to an interrogation with UF equals 0 and RL equals 1. The format of this reply shall consist of these fields:</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="text-align: center;"><i>Field</i></td> <td style="text-align: center;"><i>Reference</i></td> </tr> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>VS vertical status</td> <td>3.1.2.8.2.1</td> </tr> <tr> <td>spare — 2 bits</td> <td></td> </tr> <tr> <td>SL sensitivity level, ACAS</td> <td>4.3.8.4.2.5</td> </tr> <tr> <td>spare — 2 bits</td> <td></td> </tr> <tr> <td>RI reply information</td> <td>3.1.2.8.2.2</td> </tr> <tr> <td>spare — 2 bits</td> <td></td> </tr> <tr> <td>AC altitude code</td> <td>3.1.2.6.5.4</td> </tr> <tr> <td>MV message, ACAS</td> <td>3.1.2.8.3.1</td> </tr> <tr> <td>AP address/parity</td> <td>3.1.2.3.2.1.3</td> </tr> </table>	<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	VS vertical status	3.1.2.8.2.1	spare — 2 bits		SL sensitivity level, ACAS	4.3.8.4.2.5	spare — 2 bits		RI reply information	3.1.2.8.2.2	spare — 2 bits		AC altitude code	3.1.2.6.5.4	MV message, ACAS	3.1.2.8.3.1	AP address/parity	3.1.2.3.2.1.3	CAR Part 91 Appendix A, A.22.	No Difference		
<i>Field</i>	<i>Reference</i>																										
DF downlink format	3.1.2.3.2.1.2																										
VS vertical status	3.1.2.8.2.1																										
spare — 2 bits																											
SL sensitivity level, ACAS	4.3.8.4.2.5																										
spare — 2 bits																											
RI reply information	3.1.2.8.2.2																										
spare — 2 bits																											
AC altitude code	3.1.2.6.5.4																										
MV message, ACAS	3.1.2.8.3.1																										
AP address/parity	3.1.2.3.2.1.3																										
Chapter 3 Reference 3.1.2.8.3.1  Standard	<p><i>MV: Message, ACAS.</i> This 56-bit (33-88) downlink field shall contain GICB information as requested in the DS field of the UF 0 interrogation that elicited the reply.</p> <p><i>Note.— The MV field is also used by ACAS for air-air coordination (4.3.8.4.2.4).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference																								



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.4</p> <p><b>Standard</b></p>	<p><i>AIR-AIR TRANSACTION PROTOCOL</i></p> <p><i>Note.— Interrogation-reply coordination for the air-air formats follows the protocol outlined in Table 3-5 (3.1.2.4.1.3.2.2).</i></p> <p>The most significant bit (bit 14) of the RI field of an air-air reply shall replicate the value of the AQ field (bit 14) received in an interrogation with UF equals 0.</p> <p>If AQ equals 0 in the interrogation, the RI field of the reply shall contain the value 0.</p> <p>If AQ equals 1 in the interrogation, the RI field of the reply shall contain the maximum cruising true airspeed capability of the aircraft as defined in 3.1.2.8.2.2.</p> <p>In response to a UF = 0 with RL = 1 and DS ≠ 0, the transponder shall reply with a DF = 16 reply in which the MV field shall contain the contents of the GICB register designated by the DS value. If the requested register is not serviced by the aircraft installation, the transponder shall reply and the MV field of the reply shall contain all ZEROS.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.8.5.1</p> <p><b>Standard</b></p>	<p><i>3.1.2.8.5 ACQUISITION SQUITTER</i></p> <p><i>Note.— SSR Mode S transponders transmit acquisition squitters (unsolicited downlink transmissions) to permit passive acquisition by interrogators with broad antenna beams, where active acquisition may be hindered by all-call synchronous garble. Examples of such interrogators are an airborne collision avoidance system and an airport surface surveillance system.</i></p> <p><i>Acquisition squitter format.</i> The format used for acquisition squitter transmissions shall be the all-call reply, (DF = 11) with II = 0.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.5.2  Standard</p>	<p><i>Acquisition squitter rate.</i> Acquisition squitter transmissions shall be emitted at random intervals that are uniformly distributed over the range from 0.8 to 1.2 seconds using a time quantization of no greater than 15 milliseconds relative to the previous acquisition squitter, with the following exceptions:</p> <ul style="list-style-type: none"> <li>a) the scheduled acquisition squitter shall be delayed if the transponder is in a transaction cycle (3.1.2.4.1);</li> <li>b) the acquisition squitter shall be delayed if an extended squitter is in process;</li> <li>c) the scheduled acquisition squitter shall be delayed if a mutual suppression interface is active (see Note 1 below); or</li> <li>d) acquisition squitters shall only be transmitted on the surface if the transponder is not reporting the surface position type of Mode S extended squitter.</li> </ul> <p>An acquisition squitter shall not be interrupted by link transactions or mutual suppression activity after the squitter transmission has begun.</p> <p><i>N1.A mutual suppression system may be used to connect onboard equipment operating in the same frequency band in order to prevent mutual interference. Acquisition squitter action resumes as soon as practical after a mutual suppression interval.</i></p> <p><i>N2.The surface report type may be selected automatically by the aircraft or by commands from a squitter ground station (3.1.2.8.6.7).</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.5.3</p> <p>Standard</p>	<p><i>Acquisition squitter antenna selection.</i> Transponders operating with antenna diversity (3.1.2.10.4) shall transmit acquisition squitters as follows:</p> <ul style="list-style-type: none"> <li>a) when airborne (3.1.2.8.6.7), the transponder shall transmit acquisition squitters alternately from the two antennas; and</li> <li>b) when on the surface (3.1.2.8.6.7), the transponder shall transmit acquisition squitters under control of SAS (3.1.2.6.1.4.1 f). In the absence of any SAS commands, use of the top antenna only shall be the default.</li> </ul> <p><i>Note.— Acquisition squitters are not emitted on the surface if the transponder is reporting the surface type of extended squitter (3.1.2.8.6.4.3).</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																
Chapter 3 Reference 3.1.2.8.6.1  Standard	<p>3.1.2.8.6 EXTENDED SQUITTER, DOWNLINK FORMAT 17</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;">1</td> <td style="padding-right: 20px;">6</td> <td style="padding-right: 20px;">9</td> <td>33</td> </tr> <tr> <td></td> <td>89</td> <td></td> <td></td> </tr> <tr> <td>DF CA AA ME PI</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>8</td> <td>32</td> <td>88</td> </tr> <tr> <td></td> <td>112</td> <td></td> <td></td> </tr> </table> <p><i>Note.— SSR Mode S transponders transmit extended squitters to support the broadcast of aircraft-derived position for surveillance purposes. The broadcast of this type of information is a form of automatic dependent surveillance (ADS) known as ADS-broadcast (ADS-B).</i></p> <p><i>Extended squitter format.</i> The format used for the extended squitter shall be a 112-bit downlink format (DF = 17) containing the following fields:</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 100px;"><i>Field</i></td> <td><i>Reference</i></td> </tr> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>CA capability</td> <td>3.1.2.5.2.2.1</td> </tr> <tr> <td>AA address, announced</td> <td>3.1.2.5.2.2.2</td> </tr> <tr> <td>ME message, extended squitter</td> <td>3.1.2.8.6.2</td> </tr> <tr> <td>PI parity/interrogator identifier</td> <td>3.1.2.3.2.1.4</td> </tr> </table> <p>The PI field shall be encoded with II equal to 0.</p>	1	6	9	33		89			DF CA AA ME PI				5	8	32	88		112			<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	CA capability	3.1.2.5.2.2.1	AA address, announced	3.1.2.5.2.2.2	ME message, extended squitter	3.1.2.8.6.2	PI parity/interrogator identifier	3.1.2.3.2.1.4	CAR Part 91 Appendix A, A.22.	No Difference		
1	6	9	33																																		
	89																																				
DF CA AA ME PI																																					
5	8	32	88																																		
	112																																				
<i>Field</i>	<i>Reference</i>																																				
DF downlink format	3.1.2.3.2.1.2																																				
CA capability	3.1.2.5.2.2.1																																				
AA address, announced	3.1.2.5.2.2.2																																				
ME message, extended squitter	3.1.2.8.6.2																																				
PI parity/interrogator identifier	3.1.2.3.2.1.4																																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.6.2  Standard</p>	<p><i>ME: Message, extended squitter.</i> This 56-bit (33-88) downlink field in DF = 17 shall be used to transmit broadcast messages. Extended squitter shall be supported by registers 05, 06, 07, 08, 09, 0A {HEX} and 61-6F {HEX} and shall conform to either version 0, version 1 or version 2 message formats as described below:</p> <ul style="list-style-type: none"> <li>a) Version 0 ES message formats and related requirements report surveillance quality by navigation uncertainty category (NUC), which can be an indication of either the accuracy or integrity of the navigation data used by ADS-B. However, there is no indication as to which of these, integrity or accuracy, the NUC value is providing an indication of.</li> <li>b) Version 1 ES message formats and related requirements report surveillance accuracy and integrity separately as navigation accuracy category (NAC), navigation integrity category (NIC) and surveillance integrity level (SIL). Version 1 ES formats also include provisions for enhanced reporting of status information; and</li> <li>c) Version 2 ES message formats and related requirements contain the provisions of version 1 but further enhance integrity and parameter reporting. Version 2 ES formats separately report position source integrity from the integrity of the ADS-B transmitting equipment. Version 2 ES formats also separate vertical accuracy reporting from horizontal position accuracy, remove vertical integrity from position integrity, and provide for the reporting of the SSR Mode A code. GNSS antenna offset and additional horizontal position integrity values. Version 2 ES formats also modify the target state report to include selected altitude, selected heading, and barometric pressure setting.</li> </ul> <p>N1. <i>The formats and update rates of each register are specified in the</i> Technical Provisions for Mode S Services and</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>Extended Squitter (Doc 9871). The formats and update rates for individual squitters are defined by the version number of the extended squitter.</p> <p>N2.The formats for the three different versions are interoperable. An extended squitter receiver can recognize and decode signals of its own version, as well as lower versions' message formats. The receiver, however, can decode higher version signals according to its own capability.</p> <p>N3.Guidance material on transponder register formats and data sources is included in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</p>				
<p>Chapter 3 Reference 3.1.2.8.6.3.1  Standard</p>	<p>3.1.2.8.6.3 Extended squitter types</p> <p><i>Airborne position squitter.</i> The airborne position extended squitter type shall use format DF = 17 with the contents of GICB register 05 {HEX} inserted in the ME field.</p> <p><i>Note.— A GICB request (3.1.2.6.11.2) containing RR equals 16 and DI equals 3 or 7 and RRS equals 5 will cause the resulting reply to contain the airborne position message in its MB field.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.6.3.1.1</p> <p>Standard</p>	<p><i>SSS, surveillance status subfield in ME.</i> The transponder shall report the surveillance status of the transponder in this 2-bit (38, 39) subfield of ME when ME contains an airborne position message.</p> <p><i>Coding</i></p> <p>0            signifies no status information 1            signifies transponder reporting permanent alert condition (3.1.2.6.10.1.1.1). 2            signifies transponder reporting a temporary alert condition (3.1.2.6.10.1.1.2) 3            signifies transponder reporting SPI condition (3.1.2.6.10.1.3)</p> <p>Codes 1 and 2 shall take precedence over code 3.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.8.6.3.1.2</p> <p>Standard</p>	<p><i>ACS, altitude code subfield in ME.</i> Under control of ATS (3.1.2.8.6.3.1.3), the transponder shall report either navigation-derived altitude, or the barometric altitude code in this 12-bit (41-52) subfield of ME when ME contains an airborne position message. When barometric altitude is reported, the contents of the ACS shall be as specified for the 13-bit AC field (3.1.2.6.5.4) except that the M-bit (bit 26) shall be omitted.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.8.6.3.1.3</p> <p>Standard</p>	<p><i>Control of ACS reporting.</i> Transponder reporting of altitude data in ACS shall depend on the altitude type subfield (ATS) as specified in 3.1.2.8.6.8.2. Transponder insertion of barometric altitude data in the ACS subfield shall take place when the ATS subfield has the value of ZERO. Transponder insertion of barometric altitude data in ACS shall be inhibited when ATS has the value 1.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.3.2  Standard	<i>Surface position squitter.</i> The surface position extended squitter type shall use format DF = 17 with the contents of GICB register 06 {HEX} inserted in the ME field. <i>Note.— A GICB request (3.1.2.6.11.2) containing RR equals 16 and DI equals 3 or 7 and RRS equals 6 will cause the resulting reply to contain the surface position message in its MB field.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.3.3  Standard	<i>Aircraft identification squitter.</i> The aircraft identification extended squitter type shall use format DF = 17 with the contents of GICB register 08 {HEX} inserted in the ME field. <i>Note.— A GICB request (3.1.2.6.11.2) containing RR equals 16 and DI equals 3 or 7 and RRS equals 8 will cause the resulting reply to contain the aircraft identification message in its MB field.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.3.4  Standard	<i>Airborne velocity squitter.</i> The airborne velocity extended squitter type shall use format DF = 17 with the contents of GICB register 09 {HEX} inserted in the ME field. <i>Note.— A GICB request (3.1.2.6.11.2) containing RR equals 16 and DI equals 3 or 7 and RRS equals 9 will cause the resulting reply to contain the airborne velocity message in its MB field.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.3.5.1  Standard	<p>3.1.2.8.6.3.5 <i>Periodic status and event-driven squitters</i></p> <p><i>Periodic status squitter.</i> The periodic status extended squitter types shall use format DF = 17 to convey aircraft status and other surveillance data. The aircraft operational status extended squitter type shall use the contents of GICB register 65 {HEX} inserted in the ME field. The target state and status extended squitter type shall use the contents of GICB register 62 {HEX} inserted in the ME field.</p> <p><i>N1.A GICB request (3.1.2.6.11.2) containing RR equals 22 and DI equals 3 or 7 and RRS equals 5 will cause the resulting reply to contain the aircraft operational status message in its MB field.</i></p> <p><i>N2.A GICB request (3.1.2.6.11.2) containing RR equals 22 and DI equals 3 or 7 and RRS equals 2 will cause the resulting reply to contain the target state and status information in its MB field.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.3.5.2  Standard	<p><i>Event-driven squitter.</i> The event-driven extended squitter type shall use format DF = 17 with the contents of GICB register 0A {HEX} inserted in the ME field.</p> <p><i>Note.— A GICB request (3.1.2.6.11.2) containing RR equals 16 and DI equals 3 or 7 and RRS equals 10 will cause the resulting reply to contain the event-driven message in its MB field.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.4.1  Standard	<p>3.1.2.8.6.4 <i>Extended squitter rate</i></p> <p><i>Initialization.</i> At power up initialization, the transponder shall commence operation in a mode in which it broadcasts only acquisition squitters (3.1.2.8.5). The transponder shall initiate the broadcast of extended squitters for airborne position, surface position, airborne velocity and aircraft identification when data are inserted into transponder registers 05, 06, 09 and 08 {HEX}, respectively. This determination shall be made individually for each squitter type. When extended squitters are broadcast, transmission rates shall be as indicated in the following paragraphs. Acquisition squitters shall be reported in addition to extended squitters unless the acquisition squitter is inhibited (2.1.5.4). Acquisition squitters shall always be reported if both position and velocity extended squitters are not reported.</p> <p><i>N1.</i> This suppresses the transmission of extended squitters from aircraft that are unable to report position, velocity or identity. If input to the register for the position squitter type stops for 60 seconds, broadcast will be discontinued until data insertion is resumed. Broadcast of airborne position squitters is not discontinued if barometric altitude data is available. Terminating broadcast of other squitter types is described in Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</p> <p><i>N2.</i> After timeout (3.1.2.8.6.6), the position squitter type may contain an ME field of all zeroes.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.4.2  Standard	<p><i>Airborne position squitter rate.</i> Airborne position squitter transmissions shall be emitted when the aircraft is airborne (3.1.2.8.6.7) at random intervals that are uniformly distributed over the range from 0.4 to 0.6 seconds using a time quantization of no greater than 15 milliseconds relative to the previous airborne position squitter, with the exceptions as specified in 3.1.2.8.6.4.7.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.4.3  Standard	<i>Surface position squitter rate.</i> Surface position squitter transmissions shall be emitted when the aircraft is on the surface (3.1.2.8.6.7) using one of two rates depending upon whether the high or low squitter rate has been selected (3.1.2.8.6.9). When the high squitter rate has been selected, surface position squitters shall be emitted at random intervals that are uniformly distributed over the range from 0.4 to 0.6 seconds using a time quantization of no greater than 15 milliseconds relative to the previous surface position squitter (termed the high rate). When the low squitter rate has been selected, surface position squitters shall be emitted at random intervals that are uniformly distributed over the range of 4.8 to 5.2 seconds using a time quantization of no greater than 15 milliseconds relative to the previous surface position squitter (termed the low rate). Exceptions to these transmission rates are specified in 3.1.2.8.6.4.7.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.4.4  Standard	<i>Aircraft identification squitter rate.</i> Aircraft identification squitter transmissions shall be emitted at random intervals that are uniformly distributed over the range of 4.8 to 5.2 seconds using a time quantization of no greater than 15 milliseconds relative to the previous identification squitter when the aircraft is reporting the airborne position squitter type, or when the aircraft is reporting the surface position squitter type and the high surface squitter rate has been selected. When the surface position squitter type is being reported at the low surface rate, the aircraft identification squitter shall be emitted at random intervals that are uniformly distributed over the range of 9.8 to 10.2 seconds using a time quantization of no greater than 15 milliseconds relative to the previous identification squitter. Exceptions to these transmission rates are specified in 3.1.2.8.6.4.7.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.4.5  Standard	<i>Airborne velocity squitter rate.</i> Airborne velocity squitter transmissions shall be emitted when the aircraft is airborne (3.1.2.8.6.7) at random intervals that are uniformly distributed over the range from 0.4 to 0.6 seconds using a time quantization of no greater than 15 milliseconds relative to the previous airborne velocity squitter, with the exceptions as specified in 3.1.2.8.6.4.7.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.4.6.1  Standard	<i>3.1.2.8.6.4.6 Periodic status and event-driven squitter rates</i>  <i>Periodic status squitter rates.</i> The periodic status squitter types supported by a Mode S extended squitter transmitting system class, as specified in 5.1.1.2, shall be periodically emitted at defined intervals depending on the on-the-ground status and whether their content has changed.  <i>Note.— The aircraft operational status extended squitter type and the target state and status extended squitter type rates are specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.4.6.2  Standard	<i>Event-driven squitter rate.</i> The event-driven squitter shall be transmitted once, each time that GICB register 0A {HEX} is loaded, while observing the delay conditions specified in 3.1.2.8.6.4.7. The maximum transmission rate for the event-driven squitter shall be limited by the transponder to twice per second. If a message is inserted in the event-driven register and cannot be transmitted due to rate limiting, it shall be held and transmitted when the rate limiting condition has cleared. If a new message is received before transmission is permitted, it shall overwrite the earlier message.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.4.7  Standard	<i>Delayed transmission.</i> Extended squitter transmission shall be delayed in the following circumstances: a) if the transponder is in a transaction cycle (3.1.2.4.1); b) if an acquisition or another type of extended squitter is in process; or c) if a mutual suppression interface is active. The delayed squitter shall be transmitted as soon as the transponder becomes available.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.5  Standard	<i>Extended squitter antenna selection.</i> Transponders operating with antenna diversity (3.1.2.10.4) shall transmit extended squitters as follows: a) when airborne (3.1.2.8.6.7), the transponder shall transmit each type of extended squitter alternately from the two antennas; and b) when on the surface (3.1.2.8.6.7), the transponder shall transmit extended squitters under control of SAS (3.1.2.6.1.4.1 f)). In the absence of any SAS commands, use of the top antenna only shall be the default condition.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.6  Standard	<i>Register time-out and termination.</i> The transponder shall clear and terminate broadcast of information in extended squitter registers as required to prevent the reporting of outdated information. <i>Note.— Timeout and termination of extended squitter broadcast is specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.6.7  Standard</p>	<p><i>Airborne/surface state determination.</i> Aircraft with an automatic means of determining on-the-ground conditions shall use this input to select whether to report the airborne or surface message types. Aircraft without such means shall report the airborne type messages, except as specified in Table 3-7. Use of this table shall only be applicable to aircraft that are equipped to provide data for radio altitude AND, as a minimum, airspeed OR ground speed. Otherwise, aircraft in the specified categories that are only equipped to provide data for airspeed and ground speed shall broadcast the surface format if:</p> <p style="padding-left: 40px;">airspeed&lt;50 knots AND ground speed &lt;50 knots.</p> <p>Aircraft with or without such automatic on-the-ground determination shall use position message types as commanded by control codes in TCS (3.1.2.6.1.4.1 f)). After time-out of the TCS commands, control of airborne/surface determination shall revert to the means described above.</p> <p>N1.<i>Use of this technique may result in the surface position format being transmitted when the air-ground status in the CA fields indicates "airborne or on the ground".</i></p> <p>N2.<i>Extended squitter ground stations determine aircraft airborne or on-the-ground status by monitoring aircraft position, altitude and ground speed. Aircraft determined to be on the ground that are not reporting the surface position message types will be commanded to report the surface formats via TCS (3.1.2.6.1.4.1 f)). The normal return to the airborne position message types is via a ground command to report airborne message types. To guard against loss of communications after take-off, commands to report the surface position message types automatically time-out.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.8  Standard	<i>Squitter status reporting.</i> A GICB request (3.1.2.6.11.2) containing RR equals 16 and DI equals 3 or 7 and RRS equals 7 shall cause the resulting reply to contain the squitter status report in its MB field.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.8.1  Standard	<i>TRS, transmission rate subfield in MB.</i> The transponder shall report the capability of the aircraft to automatically determine its surface squitter rate and its current squitter rate in this 2-bit (33, 34) subfield of MB.  <i>Coding</i> 0 signifies no capability to automatically determine surface squitter rate 1 signifies that the high surface squitter rate has been selected 2 signifies that the low surface squitter rate has been selected 3 unassigned  <i>N1.High and low squitter rate is determined on board the aircraft.</i> <i>N2.The low rate is used when the aircraft is stationary and the high rate is used when the aircraft is moving. For details of how "moving" is determined, see the data format of register 0716 in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.8.2  Standard	<p><i>ATS, altitude type subfield in MB.</i> The transponder shall report the type of altitude being provided in the airborne position extended squitter in this 1-bit (35) subfield of MB when the reply contains the contents of transponder register 07 {HEX}.</p> <p><i>Coding</i></p> <p>0 signifies that barometric altitude shall be reported in the ACS (3.1.2.8.6.3.1.2) of transponder register 05 {HEX}.</p> <p>1 signifies that navigation-derived altitude shall be reported in the ACS (3.1.2.8.6.3.1.2.) of transponder register 05 {HEX}.</p> <p><i>Note.— Details of the contents of transponder registers 05 {HEX} and 07 {HEX} are shown in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.9  Standard	<p><i>Surface squitter rate control.</i> Surface squitter rate shall be determined as follows:</p> <ul style="list-style-type: none"> <li>a) once per second the contents of the TRS shall be read. If the value of TRS is 0 or 1, the transponder shall transmit surface squitters at the high rate. If the value of TRS is 2, the transponder shall transmit surface squitters at the low rate;</li> <li>b) the squitter rate determined via TRS shall be subject to being overridden by commands received via RCS (3.1.2.6.1.4.1 f)). RCS code 1 shall cause the transponder to squitter at the high rate for 60 seconds. RCS code 2 shall cause the transponder to squitter at the low rate for 60 seconds. These commands shall be able to be refreshed for a new 60 second period before time-out of the prior period; and</li> <li>c) after time-out and in the absence of RCS codes 1 and 2, control shall return to TRS.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.6.10  Standard	<p><i>Latitude/longitude coding using compact position reporting (CPR).</i> Mode S extended squitter shall use compact position reporting (CPR) to encode latitude and longitude efficiently into messages.</p> <p><i>Note.— The method used to encode/decode CPR is specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.6.11  Standard	<p><i>Data insertion.</i> When the transponder determines that it is time to emit an airborne position squitter, it shall insert the current value of the barometric altitude (unless inhibited by the ATS subfield, 3.1.2.8.6.8.2) and surveillance status into the appropriate fields of register 05 {HEX}. The contents of this register shall then be inserted into the ME field of DF = 17 and transmitted.</p> <p><i>Note.— Insertion in this manner ensures that (1) the squitter contains the latest altitude and surveillance status, and (2) ground read-out of register 05 {HEX} will yield exactly the same information as the AC field of a Mode S surveillance reply.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference								
Chapter 3 Reference 3.1.2.8.7.1  Standard	<p>3.1.2.8.7 EXTENDED SQUITTER/SUPPLEMENTARY, DOWNLINK FORMAT 18</p> <p>10010 CF:3 PI:24</p> <p><b>N1.</b> <i>This format supports the broadcast of extended squitter ADS-B messages by non-transponder devices, i.e. they are not incorporated into a Mode S transponder. A separate format is used to clearly identify this non-transponder case to prevent ACAS II or extended squitter ground stations from attempting to interrogate these devices.</i></p> <p><b>N2.</b> <i>This format is also used for ground broadcast of ADS-B related services such as traffic information broadcast (TIS-B).</i></p> <p><b>N3.</b> <i>The format of the DF = 18 transmission is defined by the value of the CF field.</i></p> <p><i>ES supplementary format.</i> The format used for ES supplementary shall be a 112-bit downlink format (DF = 18) containing the following fields:</p> <table data-bbox="373 1015 934 1274"> <thead> <tr> <th><i>Field</i></th> <th><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>CF control field</td> <td>3.1.2.8.7.2</td> </tr> <tr> <td>PI parity/interrogator identifier</td> <td>3.1.2.3.2.1.4</td> </tr> </tbody> </table> <p>The PI field shall be encoded with II equal to zero.</p>	<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	CF control field	3.1.2.8.7.2	PI parity/interrogator identifier	3.1.2.3.2.1.4	CAR Part 91 Appendix A, A.22.	No Difference		
<i>Field</i>	<i>Reference</i>												
DF downlink format	3.1.2.3.2.1.2												
CF control field	3.1.2.8.7.2												
PI parity/interrogator identifier	3.1.2.3.2.1.4												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.8.7.2</p> <p><b>Standard</b></p>	<p><i>Control field.</i> This 3-bit (6-8) downlink field in DF = 18 shall be used to define the format of the 112-bit transmission as follows:</p> <p>Code 0 = ADS-B ES/NT devices that report the ICAO 24-bit address in the AA field (3.1.2.8.7)</p> <p>Code 1 = Reserved for ADS-B for ES/NT devices that use other addressing techniques in the AA field (3.1.2.8.7.3)</p> <p>Code 2 = Fine format TIS-B message</p> <p>Code 3 = Coarse format TIS-B message</p> <p>Code 4 = Reserved for TIS-B management messages</p> <p>Code 5 = TIS-B messages that relay ADS-B messages that use other addressing techniques in the AA field</p> <p>Code 6 = ADS-B rebroadcast using the same type codes and message formats as defined for DF = 17 ADS-B messages</p> <p>Code 7 = Reserved</p> <p><i>N1. Administrations may wish to make address assignments for ES/NT devices in addition to the 24-bit addresses allocated by ICAO (Annex 10, Volume III, Part I, Chapter 9) in order to increase the available number of 24-bit addresses.</i></p> <p><i>N2. These non-ICAO 24-bit addresses are not intended for international use.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																
<p>Chapter 3 Reference 3.1.2.8.7.3.1</p> <p>Standard</p>	<p>3.1.2.8.7.3 ADS-B for extended squitter/non-transponder (ES/NT) devices</p> <p>10010 CF=0 AA:24 ME:56 PI:24</p> <p>ES/NT format. The format used for ES/NT shall be a 112-bit downlink format (DF = 18) containing the following fields:</p> <table data-bbox="367 544 934 1177"> <tr> <td><i>Field</i></td> <td><i>Referen</i></td> </tr> <tr> <td><i>ce</i></td> <td></td> </tr> <tr> <td>DF downlink format</td> <td>3.1.2.3.2</td> </tr> <tr> <td>.1.2 CF control field = 0</td> <td>3.1.2.8.7</td> </tr> <tr> <td>.2 AA address, announced</td> <td>3.1.2.5.2</td> </tr> <tr> <td>.2.2 ME message, extended squitter</td> <td>3.1.2.8.6</td> </tr> <tr> <td>.2 PI parity/interrogator identifier</td> <td>3.1.2.3.2</td> </tr> <tr> <td>.1.4</td> <td></td> </tr> </table> <p>The PI field shall be encoded with II equal to zero.</p>	<i>Field</i>	<i>Referen</i>	<i>ce</i>		DF downlink format	3.1.2.3.2	.1.2 CF control field = 0	3.1.2.8.7	.2 AA address, announced	3.1.2.5.2	.2.2 ME message, extended squitter	3.1.2.8.6	.2 PI parity/interrogator identifier	3.1.2.3.2	.1.4		<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<i>Field</i>	<i>Referen</i>																				
<i>ce</i>																					
DF downlink format	3.1.2.3.2																				
.1.2 CF control field = 0	3.1.2.8.7																				
.2 AA address, announced	3.1.2.5.2																				
.2.2 ME message, extended squitter	3.1.2.8.6																				
.2 PI parity/interrogator identifier	3.1.2.3.2																				
.1.4																					
<p>Chapter 3 Reference 3.1.2.8.7.3.2.1</p> <p>Standard</p>	<p>3.1.2.8.7.3.2 ES/NT squitter types</p> <p><i>Airborne position squitter.</i> The airborne position type ES/NT shall use format DF = 18 with the format for register 05 {HEX} as defined in 3.1.2.8.6.2 inserted in the ME field.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>																		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.7.3.2.2  Standard	<i>Surface position squitter.</i> The surface position type ES/NT shall use format DF = 18 with the format for register 06 {HEX} as defined in 3.1.2.8.6.2 inserted in the ME field.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.2.3  Standard	<i>Aircraft identification squitter.</i> The aircraft identification type ES/NT shall use format DF = 18 with the format for register 08 {HEX} as defined in 3.1.2.8.6.2 inserted in the ME field.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.2.4  Standard	<i>Airborne velocity squitter.</i> The airborne velocity type ES/NT shall use format DF = 18 with the format for register 09 {HEX} as defined in 3.1.2.8.6.2 inserted in the ME field.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.2.5.1  Standard	3.1.2.8.7.3.2.5 <i>Periodic status and event-driven squitters</i>  <i>Periodic status squitters.</i> The periodic status extended squitter types shall use format DF = 18 to convey aircraft status and other surveillance data. The aircraft operational status extended squitter type shall use the format of GICB register 65 {HEX} as defined in 3.1.2.8.6.4.6.1 inserted in the ME field. The target state and status extended squitter type shall use the format of GICB register 62 {HEX} as defined in 3.1.2.8.6.4.6.1 inserted in the ME field.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.7.3.2.5.2  Standard	<i>Event-driven squitter.</i> The event-driven type ES/NT shall use format DF=18 with the format for register 0A {HEX} as defined in 3.1.2.8.6.2 inserted in the ME field.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.3.1  Standard	<p>3.1.2.8.7.3.3 <i>ES/NT squitter rate</i></p> <p><i>Initialization.</i> At power up initialization, the non-transponder device shall commence operation in a mode in which it does not broadcast any squitters. The non-transponder device shall initiate the broadcast of ES/NT squitters for airborne position, surface position, airborne velocity and aircraft identification when data are available for inclusion in the ME field of these squitter types. This determination shall be made individually for each squitter type. When ES/NT squitters are broadcast, transmission rates shall be as indicated in 3.1.2.8.6.4.2 to 3.1.2.8.6.4.6.</p> <p>N1.<i>This suppresses the transmission of extended squitters from aircraft that are unable to report position, velocity or identity. If input to the register for the position squitter type stops for 60 seconds, broadcast will cease until data insertion resumes, except for an ES/NT device operating on the surface (as specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871)). Broadcast of airborne position squitters is not discontinued if barometric altitude data is available. Terminating broadcast of other squitter types is described in Doc 9871.</i></p> <p>N2.<i>After timeout (3.1.2.8.7.6) this squitter type may contain an ME field of all zeros.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.7.3.3.2  Standard	<i>Delayed transmission.</i> ES/NT squitter transmission shall be delayed if the non-transponder device is busy broadcasting one of the other squitter types.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.3.2.1  Standard	The delayed squitter shall be transmitted as soon as the non-transponder device becomes available.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.3.3  Standard	<i>ES/NT antenna selection.</i> Non-transponder devices operating with antenna diversity (3.1.2.10.4) shall transmit ES/NT squitters as follows: a) when airborne (3.1.2.8.6.7), the non-transponder device shall transmit each type of ES/NT squitter alternately from the two antennas; and b) when on the surface (3.1.2.8.6.7), the non-transponder device shall transmit ES/NT squitters using the top antenna.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.3.4  Standard	<i>Register timeout and termination.</i> The non-transponder device shall clear message fields and terminate broadcast of extended squitter messages as required to prevent the reporting of outdated information. <i>Note.— The timeout and termination of an extended squitter broadcast is specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.7.3.3.5  Standard	<i>Airborne/surface state determination.</i> Aircraft with an automatic means of determining the on-the-ground state shall use this input to select whether to report the airborne or surface message types except as specified in 3.1.2.6.10.3.1. Aircraft without such means shall report the airborne type message.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.3.3.6  Standard	<i>Surface squitter rate control.</i> Aircraft motion shall be determined once per second. The surface squitter rate shall be set according to the results of this determination.  <i>Note.— The algorithm to determine aircraft motion is specified in the definition of register 0716 in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.7.4.1  Recommendation	3.1.2.8.7.4 <i>Use of ES by other surveillance systems</i>  <i>Surface system control</i> <b>Recommendation.—</b> <i>When a surface surveillance system uses DF=18 as part of a surveillance function, it should not use the formats that have been allocated for the purpose of surveillance of aircraft, vehicles and/or obstacles.</i>  <i>N1.The formats allocated for the purpose of surveillance of aircraft, vehicles and/or obstacles are specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>  <i>N2.The transmission of any message format used for conveying position, velocity, identification, state information, etc., may result in the initiation and maintenance of false tracks in other 1090ES receivers. The use of these messages for this purpose may be prohibited in the future.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference						
Chapter 3 Reference 3.1.2.8.7.4.2  Recommendation	<p><i>Surface system status</i></p> <p><b>Recommendation.</b>— <i>The surface system status message type (Type Code=24) should be the only message used to provide the status or synchronization of surface surveillance systems.</i></p> <p><i>Note.</i>— <i>The surface system status message is specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871). This message will be used only by the surface surveillance system that generated it and will be ignored by other surface systems.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference								
Chapter 3 Reference 3.1.2.8.8.1  Standard	<p>3.1.2.8.8 EXTENDED SQUITTER MILITARY APPLICATION, DOWNLINK FORMAT 19 10011 AF:3</p> <p><i>Note.</i>— <i>This format supports the broadcast of extended squitter ADS-B messages in support of military applications. A separate format is used to distinguish these extended squitters from the standard ADS-B message set broadcast using DF = 17 or 18.</i></p> <p><i>Military format.</i> The format used for DF = 19 shall be a 112-bit downlink format containing the following fields:</p> <table border="0" data-bbox="357 1055 903 1234"> <thead> <tr> <th style="text-align: left;"><i>Field</i></th> <th style="text-align: left;"><i>Reference</i></th> </tr> </thead> <tbody> <tr> <td>DF downlink format</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>AF control field</td> <td>3.1.2.8.8.2</td> </tr> </tbody> </table>	<i>Field</i>	<i>Reference</i>	DF downlink format	3.1.2.3.2.1.2	AF control field	3.1.2.8.8.2	CAR Part 91 Appendix A, A.22.	No Difference		
<i>Field</i>	<i>Reference</i>										
DF downlink format	3.1.2.3.2.1.2										
AF control field	3.1.2.8.8.2										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.8.2  Standard	<i>Application field.</i> This 3-bit (6-8) downlink field in DF = 19 shall be used to define the format of the 112-bit transmission. Code 0 to 7 = Reserved	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.9.1  Standard	<i>3.1.2.8.9 EXTENDED SQUITTER MAXIMUM TRANSMISSION RATE</i>  The maximum total number of full power extended squitters (DF = 17, 18 and 19) emitted by any extended squitter installation shall not exceed the following; a) 6.2 messages per second averaged over 60 seconds for nominal aircraft operations with no emergency and no ACAS RA activity, while not exceeding 11 messages being transmitted in any 1-second interval; or b) 7.4 messages per second averaged over 60 seconds under an emergency and/or ACAS RA condition, while not exceeding 11 messages being transmitted in any 1-second interval.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.9.2  Standard	For installations capable of emitting DF = 19 squitters and in accordance with 3.1.2.8.8, transmission rates for lower power DF = 19 squitters shall be limited to a peak of forty DF = 19 squitters per second, and thirty DF = 19 squitters per second averaged over 10 seconds, provided that the maximum total squitter power-rate product for the sum of full power DF = 17 squitters, full power DF = 18 squitters, full power DF = 19 squitters, and lower power DF = 19 squitters, is maintained at or below a level equivalent to the power sum of 6.2 full power squitters per second averaged over 10 seconds.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.8.9.3  Standard	States shall ensure that the use of low power and higher rate DF = 19 operation (as per 3.1.2.8.9.2) is compliant with the following requirements: a) it is limited to formation or element lead aircraft engaged in formation flight, directing the messages toward wing and other lead aircraft through a directional antenna with a beamwidth of no more than 90 degrees; and b) the type of information contained in the DF = 19 message is limited to the same type of information in the DF = 17 message, that is, information for the sole purpose of safety-of-flight. <i>Note — This low-power, higher squitter rate capability is intended for limited use by State aircraft in coordination with appropriate regulatory bodies.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.8.9.4  Standard	All UF = 19 airborne interrogations shall be included in the interference control provisions of 4.3.2.2.2.2.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.9.1  Standard	3.1.2.9 AIRCRAFT IDENTIFICATION PROTOCOL  <i>Aircraft identification reporting.</i> A ground-initiated Comm-B request (3.1.2.6.11.2) containing RR equals 18 and either DI does not equal 7 or DI equals 7 and RRS equals 0 shall cause the resulting reply to contain the aircraft identification in its MB field.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																				
Chapter 3 Reference 3.1.2.9.1.1  Standard	<p><i>AIS, aircraft identification subfield in MB.</i> The transponder shall report the aircraft identification in the 48-bit (41-88) AIS subfield of MB. The aircraft identification transmitted shall be that employed in the flight plan. When no flight plan is available, the registration marking of the aircraft shall be inserted in this subfield.</p> <p><i>Note.— When the registration marking of the aircraft is used, it is classified as “fixed direct data” (3.1.2.10.5.1.1). When another type of aircraft identification is used, it is classified as “variable direct data” (3.1.2.10.5.1.3).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference																																						
Chapter 3 Reference 3.1.2.9.1.2  Standard	<p><i>Coding of the AIS subfield.</i> The AIS subfield shall be coded as follows:</p> <table border="0" style="margin-left: 40px;"> <tr> <td>33</td> <td>41</td> <td>47</td> <td>53</td> <td>59</td> <td>65</td> </tr> <tr> <td></td> <td>71</td> <td>77</td> <td>83</td> <td></td> <td></td> </tr> <tr> <td>BDS</td> <td>Char. 1</td> <td>Char. 2</td> <td>Char. 3</td> <td>Char. 4</td> <td>Char. 5</td> </tr> <tr> <td></td> <td>Char. 6</td> <td>Char. 7</td> <td>Char. 8</td> <td></td> <td></td> </tr> <tr> <td>40</td> <td>46</td> <td>52</td> <td>58</td> <td>64</td> <td>70</td> </tr> <tr> <td></td> <td>76</td> <td>82</td> <td>88</td> <td></td> <td></td> </tr> </table> <p><i>Note.— Aircraft identification coding provides up to eight characters.</i></p> <p>The BDS code for the aircraft identification message shall be BDS1 equals 2 (33-36) and BDS2 equals 0 (37-40).</p> <p>Each character shall be coded as a 6-bit subset of the International Alphabet Number 5 (IA-5) as illustrated in Table 3-9. The character code shall be transmitted with the high order unit (<i>b</i><sub>6</sub>) first and the reported aircraft identification shall be transmitted with its left-most character first. Characters shall be coded consecutively without intervening SPACE code. Any unused character spaces at the end of the subfield shall contain a SPACE character code.</p>	33	41	47	53	59	65		71	77	83			BDS	Char. 1	Char. 2	Char. 3	Char. 4	Char. 5		Char. 6	Char. 7	Char. 8			40	46	52	58	64	70		76	82	88			CAR Part 91 Appendix A, A.22.	No Difference		
33	41	47	53	59	65																																				
	71	77	83																																						
BDS	Char. 1	Char. 2	Char. 3	Char. 4	Char. 5																																				
	Char. 6	Char. 7	Char. 8																																						
40	46	52	58	64	70																																				
	76	82	88																																						





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.9.1.3  Standard	<i>Aircraft identification capability report.</i> Transponders which respond to a ground-initiated request for aircraft identification shall report this capability in the data link capability report (3.1.2.6.10.2.2.2) by setting bit 33 of the MB subfield to 1.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.9.1.4  Standard	<i>Change of aircraft identification.</i> If the aircraft identification reported in the AIS subfield is changed in flight, the transponder shall report the new identification to the ground by use of the Comm-B broadcast message protocol of 3.1.2.6.11.4 for BDS1 = 2 (33 - 36) and BDS2 = 0 (37 - 40). The transponder shall initiate, generate and announce the revised aircraft identification even if the interface providing flight identification is lost. The transponder shall ensure that the BDS code is set for the aircraft identification report in all cases, including a loss of the interface. In this latter case, bits 42 - 88 shall contain all ZEROS.  <i>Note — The setting of the BDS code by the transponder ensures that a broadcast change of aircraft identification will contain the BDS code for all cases of flight identification failure (e.g. the loss of the interface providing flight identification).</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.10.1</p> <p>Standard</p>	<p>3.1.2.10 ESSENTIAL SYSTEM CHARACTERISTICS OF THE SSR MODE S TRANSPONDER</p> <p><i>Transponder sensitivity and dynamic range.</i> Transponder sensitivity shall be defined in terms of a given interrogation signal input level and a given percentage of corresponding replies. Only correct replies containing the required bit pattern for the interrogation received shall be counted. Given an interrogation that requires a reply according to 3.1.2.4, the minimum triggering level, MTL, shall be defined as the minimum input power level for 90 per cent reply-to-interrogation ratio. The MTL shall be <math>-74 \text{ dBm} \pm 3 \text{ dB}</math> for Mode S interrogations (interrogations using P6), and as defined in 3.1.1.7.5.1 b) for Mode A and C, and inter-mode interrogations. The reply-to-interrogation ratio of a Mode S transponder shall be:</p> <ul style="list-style-type: none"> <li>a) at least 99 per cent for signal input levels between 3 dB above MTL and <math>-21 \text{ dBm}</math>; and</li> <li>b) no more than 10 per cent at signal input levels below <math>-81 \text{ dBm}</math>.</li> </ul> <p><i>Note.— Transponder sensitivity and output power are described in this section in terms of signal level at the terminals of the antenna. This gives the designer freedom to arrange the installation, optimizing cable length and receiver-transmitter design, and does not exclude receiver and/or transmitter components from becoming an integral part of the antenna subassembly.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.1.1  Standard	<p><i>3.1.2.10.1.1 Reply ratio in the presence of interference</i> <i>Note.— The following paragraphs present measures of the performance of the Mode S transponder in the presence of interfering Mode A/C interrogation pulses and low-level in-band CW interference.</i></p> <p><i>Reply ratio in the presence of an interfering pulse.</i> Given a Mode S interrogation which requires a reply (3.1.2.4), the reply ratio of a transponder shall be at least 95 per cent in the presence of an interfering Mode A/C interrogation pulse if the level of the interfering pulse is 6 dB or more below the signal level for Mode S input signal levels between -68 dBm and -21 dBm and the interfering pulse overlaps the <math>P_6</math> pulse of the Mode S interrogation anywhere after the sync phase reversal.</p> <p>Under the same conditions, the reply ratio shall be at least 50 per cent if the interference pulse level is 3 dB or more below the signal level.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.1.2  Standard	<p><i>Reply ratio in the presence of pulse pair interference.</i> Given an interrogation which requires a reply (3.1.2.4), the reply ratio of a transponder shall be at least 90 per cent in the presence of an interfering <math>P_1 - P_2</math> pulse pair if the level of the interfering pulse pair is 9 dB or more below signal level for input signal levels between -68 dBm and -21 dBm and the <math>P_1</math> pulse of the interfering pair occurs no earlier than the <math>P_1</math> pulse of the Mode S signal.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.1.1.3  Standard	<p><i>Reply ratio in the presence of low level asynchronous interference.</i> For all received signals between -65 dBm and -21 dBm and given a Mode S interrogation that requires a reply according to 3.1.2.4 and if no lockout condition is in effect, the transponder shall reply correctly with at least 95 per cent reply ratio in the presence of asynchronous interference. Asynchronous interference shall be taken to be a single Mode A/C interrogation pulse occurring at all repetition rates up to 10 000 Hz at a level 12 dB or more below the level of the Mode S signal.</p> <p><i>Note.— Such pulses may combine with the P<sub>1</sub> and P<sub>2</sub> pulses of the Mode S interrogation to form a valid Mode A/C-only all-call interrogation. The Mode S transponder does not respond to Mode A/C-only all-call interrogations. A preceding pulse may also combine with the P<sub>2</sub> of the Mode S interrogation to form a valid Mode A or Mode C interrogation. However, the P<sub>1</sub> – P<sub>2</sub> pair of the Mode S preamble takes precedence (3.1.2.4.1.1.1). The Mode S decoding process is independent of the Mode A/Mode C decoding process and the Mode S interrogation is accepted.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.1.1.4  Standard	<p><i>Reply ratio in the presence of low-level in-band CW interference.</i> In the presence of non-coherent CW interference at a frequency of 1 030 ±0.2 MHz at signal levels of 20 dB or more below the desired Mode A/C or Mode S interrogation signal level, the transponder shall reply correctly to at least 90 per cent of the interrogations.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.1.1.5.1  Recommendation	<p><i>3.1.2.10.1.1.5 Spurious response</i></p> <p><b>Recommendation.—</b> <i>The response to signals not within the receiver pass band should be at least 60 dB below normal sensitivity.</i></p>	CARs, Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.1.1.5.2  Standard	For equipment certified after 1 January 2011, the spurious Mode A/C reply ratio generated by low level Mode S interrogations shall be no more than: a) an average of 1 per cent in the input interrogation signal range between -81 dBm and the Mode S MTL; and b) a maximum of 3 per cent at any given level in the input interrogation signal range between -81 dBm and the Mode S MTL.  <i>Note — Failure to detect a low level Mode S interrogation can also result in the transponder decoding a three-pulse Mode A/C/S all-call interrogation. This would result in the transponder responding with a Mode S all-call (DF = 11) reply. The above requirement will also control these DF = 11 replies since it places a limit on the probability of failing to correctly detect the Mode S interrogation.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.2  Standard	<i>Transponder peak pulse power.</i> The peak power of each pulse of a reply shall: a) not be less than 18.5 dBW for aircraft not capable of operating at altitudes exceeding 4 570 m (15 000 ft); b) not be less than 21.0 dBW for aircraft capable of operating above 4 570 m (15 000 ft); c) not be less than 21.0 dBW for aircraft with maximum cruising speed exceeding 324 km/h (175 kt); and d) not exceed 27.0 dBW.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.2.1  Standard	<p><i>Inactive state transponder output power.</i> When the transponder is in the inactive state the peak pulse power at 1 090 MHz plus or minus 3 MHz shall not exceed -50 dBm. The inactive state is defined to include the entire period between transmissions less 10-microsecond transition periods preceding the first pulse and following the last pulse of the transmission.</p> <p><i>Note.— Inactive state transponder power is constrained in this way to ensure that an aircraft, when located as near as 185 m (0.1 NM) to a Mode A/C or Mode S interrogator, does not cause interference to that installation. In certain applications of Mode S, airborne collision avoidance for example, where a 1 090 MHz transmitter and receiver are in the same aircraft, it may be necessary to further constrain the inactive state transponder power.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.2.2  Recommendation	<p><i>Spurious emission radiation</i> <b>Recommendation.—</b> <i>CW radiation should not exceed 70 dB below 1 watt.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.3.1  Standard	<p>3.1.2.10.3 SPECIAL CHARACTERISTICS</p> <p><i>Mode S side-lobe suppression</i></p> <p><i>Note.— Side-lobe suppression for Mode S formats occurs when a P<sub>5</sub> pulse overlays the location of the sync phase reversal of P<sub>6</sub>, causing the transponder to fail to recognize the interrogation (3.1.2.4.1.1.3).</i></p> <p>Given a Mode S interrogation that requires a reply, the transponder shall:</p> <ul style="list-style-type: none"> <li>a) at all signal levels between MTL +3 dB and –21 dBm, have a reply ratio of less than 10 per cent if the received amplitude of P<sub>5</sub> exceeds the received amplitude of P<sub>6</sub> by 3 dB or more;</li> <li>b) at all signal levels between MTL +3 dB and –21 dBm, have a reply ratio of at least 99 per cent if the received amplitude of P<sub>6</sub> exceeds the received amplitude of P<sub>5</sub> by 12 dB or more.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.2  Standard	<p><i>Mode S dead time.</i> Dead time shall be defined as the time interval beginning at the end of a reply transmission and ending when the transponder has regained sensitivity to within 3 dB of MTL. Mode S transponders shall not have more than 125 microseconds' dead time.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.3  Standard	<p><i>Mode S receiver desensitization.</i> The transponder's receiver shall be desensitized according to 3.1.1.7.7.1 on receipt of any pulse of more than 0.7 microseconds duration.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.3.3.1  Standard	<i>Recovery from desensitization.</i> Recovery from desensitization shall begin at the trailing edge of each pulse of a received signal and shall occur at the rate prescribed in 3.1.1.7.7.2, provided that no reply or data transfer is made in response to the received signal.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.4.1.1  Standard	3.1.2.10.3.4 Recovery after Mode S interrogations that do not elicit replies  3.1.2.10.3.4.1 Recovery after a single Mode S interrogation  The transponder shall recover sensitivity to within 3 dB of MTL no later than 128 microseconds after receipt of the sync phase reversal following a Mode S interrogation that is not accepted (3.1.2.4.1.2) or that is accepted but requires no reply.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.4.1.2  Recommendation	<b>Recommendation.</b> — <i>The transponder should recover sensitivity to within 3 dB of MTL no later than 45 microseconds after receipt of the sync phase reversal following a Mode S interrogation that is not accepted (3.1.2.4.1.2) or that is accepted but requires no reply.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.4.1.3  Standard	All Mode S transponders installed on or after 1 January 1999 shall recover sensitivity to within 3 dB of MTL no later than 45 microseconds after receipt of the sync phase reversal following a Mode S interrogation that is not accepted (3.1.2.4.1.2) or that is accepted but requires no reply.	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.3.4.2  Standard	<i>Recovery after a Mode S Comm-C interrogation.</i> A Mode S transponder with Comm-C capability shall recover sensitivity to within 3 dB of MTL no later than 45 microseconds after receipt of the sync phase reversal following acceptance of a Comm-C interrogation for which no reply is required.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.5  Standard	<i>Unwanted Mode S replies.</i> Mode S transponders shall not generate unwanted Mode S replies more often than once in 10 seconds. Installation in the aircraft shall be made in such a manner that this standard shall be achieved when all possible interfering equipments installed in the same aircraft are operating at maximum interference levels.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.5.1  Standard	<i>Unwanted Mode S replied in the presence of low-level in-band CW interference.</i> In the presence of non-coherent CW interference at a frequency of 1 030 ±0.2 MHz and at signal levels of -60 dBm or less, and in the absence of valid interrogation signals, Mode S transponders shall not generate unwanted. Mode S replies more often than once per 10 seconds.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.6.1  Standard	3.1.2.10.3.6 Reply rate limiting <i>Note.— Reply rate limiting is prescribed separately for Modes A and C and for Mode S</i>  <i>Mode S reply rate limiting.</i> Reply rate limiting is not required for the Mode S formats of a transponder. If such limiting is incorporated for circuit protection, it shall permit the minimum reply rates required in 3.1.2.10.3.7.2 and 3.1.2.10.3.7.3.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.3.6.2  Standard	<i>Modes A and C reply rate limiting.</i> Reply rate limiting for Modes A and C shall be effected according to 3.1.1.7.9.1. The prescribed sensitivity reduction (3.1.1.7.9.2) shall not affect the Mode S performance of the transponder.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.7.1  Standard	<i>3.1.2.10.3.7 Minimum reply rate capability, Modes A, C and S</i>  All reply rates specified in 3.1.2.10.3.7 shall be in addition to any squitter transmissions that the transponder is required to make.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.7.2  Standard	<i>Minimum reply rate capability, Modes A and C.</i> The minimum reply rate capability for Modes A and C shall be in accordance with 3.1.1.7.9.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.10.3.7.3  Standard</p>	<p><i>Minimum reply rate capability, Mode S.</i> A transponder capable of transmitting only short Mode S replies shall be able to generate replies at the following rates:                      50 Mode S replies in any 1-second interval                      18 Mode S replies in a 100-millisecond interval                      8 Mode S replies in a 25-millisecond interval                      4 Mode S replies in a 1.6-millisecond interval</p> <p>In addition to any downlink ELM transmissions, a level 2, 3 or 4 transponder shall be able to generate as long replies at least:                      16 of 50 Mode S replies in any 1-second interval                      6 of 18 Mode S replies in a 100-millisecond interval                      4 of 8 Mode S replies in a 25-millisecond interval                      2 of 4 Mode S replies in a 1.6-millisecond interval</p> <p>In addition to downlink ELM transmissions, a level 5 transponder shall be able to generate as long replies at least:                      24 of 50 Mode S replies in any 1-second interval                      9 of 18 Mode S replies in a 100-millisecond interval                      6 of 8 Mode S replies in a 25-millisecond interval                      2 of 4 Mode S replies in a 1.6-millisecond interval</p> <p>In addition, a transponder within an ACAS installation shall be able to generate as ACAS coordination replies at least 3 of 50 Mode S replies in any 1-second interval.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 3 Reference 3.1.2.10.3.7.4  Standard</p>	<p><i>Minimum Mode S ELM peak reply rate</i> <i>N1. When a downlink ELM is initialized (3.1.2.7.7.1), the Mode S transponder announces the length (in segments) of the waiting message. The transponder must be able to transmit this number of segments, plus an additional margin to make up for missed replies, during the beam dwell of the ground interrogator.</i> At least once every second a Mode S transponder equipped for ELM downlink operation shall be capable of transmitting in a 25-millisecond interval, at least 25 per cent more segments than have been announced in the initialization (3.1.2.7.7.1). The minimum length downlink ELM capability for level 4 and 5 transponders shall be as specified in 3.1.2.10.5.2.2.2. <i>N2. A transponder capable of processing the maximum length downlink ELM (16 segments) is therefore required to be able to transmit 20 long replies under the above conditions. Level 4 transponders may be built which process less than the maximum message length. These transponders cannot initialize a message length that exceeds their transmitter capability. For example, a transponder that can transmit at most 10 long replies under the above conditions can never announce a message of more than 8 segments.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		
<p>Chapter 3 Reference 3.1.2.10.3.8.1  Standard</p>	<p><i>3.1.2.10.3.8 Reply delay and jitter</i> <i>Note.— After an interrogation has been accepted and if a reply is required, this reply transmission begins after a fixed delay needed to carry out the protocols. Different values for this delay are assigned for Modes A and C, for Mode S and for Modes A/C/S all-call replies.</i>  <i>Reply delay and jitter for Modes A and C. The reply delay and jitter for Modes A and C transactions shall be as prescribed in 3.1.1.7.10.</i></p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.3.8.2  Standard	<i>Reply delay and jitter for Mode S.</i> For all input signal levels between MTL and -21 dBm, the leading edge of the first preamble pulse of the reply (3.1.2.2.5.1.1) shall occur 128 plus or minus 0.25 microsecond after the sync phase reversal (3.1.2.1.5.2.2) of the received $P_6$ . The jitter of the reply delay shall not exceed 0.08 microsecond, peak (99.9 percentile).	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.8.3  Standard	<i>Reply delay and jitter for Modes A/C/S all call.</i> For all input signal levels between MTL +3 dB and - 21 dBm the leading edge of the first preamble pulse of the reply (3.1.2.2.5.1.1) shall occur 128 plus or minus 0.5 microseconds after the leading edge of the $P_4$ pulse of the interrogation (3.1.2.1.5.1.1). Jitter shall not exceed 0.1 microsecond, peak (99.9 percentile). <i>Note.— A peak jitter of 0.1 microsecond is consistent with the jitter prescribed in 3.1.1.7.10.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.9  Standard	<i>Timers.</i> Duration and features of timers shall be as shown in Table 3-10. All timers shall be capable of being restarted. On receipt of any start command, they shall run for their specified times. This shall occur regardless of whether they are in the running or the non-running state at the time that the start command is received. A command to reset a timer shall cause the timer to stop running and to return to its initial state in preparation for a subsequent start command.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.10  Standard	<i>Inhibition of replies.</i> Replies to Mode A/C/S all-call and Mode S-only all-call interrogations shall always be inhibited when the aircraft declares the on-the-ground state. It shall not be possible to inhibit replies to discretely addressed Mode S interrogations regardless of whether the aircraft is airborne or on the ground.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.3.10.1  Recommendation	<b>Recommendation.</b> — <i>Aircraft should provide means to determine the on-the-ground state automatically and provide that information to the transponder.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.3.10.2  Recommendation	<b>Recommendation.</b> — <i>Mode A/C replies should be inhibited when the aircraft is on the ground to prevent interference when in close proximity to an interrogator or other aircraft.</i> <i>Note.</i> — <i>Mode S discretely addressed interrogations do not give rise to such interference and may be required for data link communications with aircraft on the airport surface. Acquisition squitter transmissions may be used for passive surveillance of aircraft on the airport surface.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4  Standard	<i>Transponder antenna system and diversity operation.</i> Mode S transponders equipped for diversity operation shall have two RF ports for operation with two antennas, one antenna on the top and the other on the bottom of the aircraft's fuselage. The received signal from one of the antennas shall be selected for acceptance and the reply shall be transmitted from the selected antenna only.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4.1  Standard	<i>Radiation pattern.</i> The radiation pattern of Mode S antennas when installed on an aircraft shall be nominally equivalent to that of a quarter-wave monopole on a ground plane. <i>Note.</i> — <i>Transponder antennas designed to increase gain at the expense of vertical beamwidth are undesirable because of their poor performance during turns.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.4.2  Standard	<i>Antenna location.</i> The top and bottom antennas shall be mounted as near as possible to the centre line of the fuselage. Antennas shall be located so as to minimize obstruction to their fields in the horizontal plane.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4.2.1  Recommendation	<b>Recommendation.</b> — <i>The horizontal distance between the top and bottom antennas should not be greater than 7.6 m (25 ft).</i>  <i>Note.</i> — <i>This recommendation is intended to support the operation of any diversity transponder (including cables) with any diversity antenna installation and still satisfy the requirement of 3.1.2.10.4.5.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4.3  Standard	<i>Antenna selection.</i> Mode S transponders equipped for diversity operation shall have the capability to evaluate a pulse sequence simultaneously received on both antenna channels to determine individually for each channel if the $P_1$ pulse and the $P_2$ pulse of a Mode S interrogation preamble meet the requirements for a Mode S interrogation as defined in 3.1.2.1 and if the $P_1$ pulse and the $P_3$ pulse of a Mode A, Mode C or intermode interrogation meet the requirements for Mode A and Mode C interrogations as defined in 3.1.1.  <i>Note.</i> — <i>Transponders equipped for diversity operation may optionally have the capability to evaluate additional characteristics of the received pulses of the interrogations in making a diversity channel selection. The transponder may as an option evaluate a complete Mode S interrogation simultaneously received on both channels to determine individually for each channel if the interrogation meets the requirements for Mode S interrogation acceptance as defined in 3.1.2.4.1.2.3.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.4.3.1  Standard	If the two channels simultaneously receive at least a $P_1 - P_2$ pulse pair that meets the requirements for a Mode S interrogation, or a $P_1 - P_3$ pulse pair that meets the requirements for a Mode A or Mode C interrogation, or if the two channels simultaneously accept a complete interrogation, the antenna at which the signal strength is greater shall be selected for the reception of the remainder (if any) of the interrogation and for the transmission of the reply.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4.3.2  Standard	If only one channel receives a pulse pair that meets the requirements for an interrogation, or if only one channel accepts an interrogation, the antenna associated with that channel shall be selected regardless of received signal strength.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4.3.3  Standard	<i>Selection threshold.</i> If antenna selection is based on signal level, it shall be carried out at all signal levels between MTL and -21 dBm.  <i>Note.— Either antenna may be selected if the difference in signal level is less than 3 dB.</i>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.4.3.4  Standard	<i>Received signal delay tolerance.</i> If an interrogation is received at one antenna 0.125 microsecond or less in advance of reception at the other antenna, the interrogations shall be considered to be simultaneous interrogations, and the above antenna selection criteria applied. If an accepted interrogation is received at either antenna 0.375 microsecond or more in advance of reception at the other antenna, the antenna selected for the reply shall be that which received the earlier interrogation. If the relative time of receipt is between 0.125 and 0.375 microsecond, the transponder shall select the antenna for reply either on the basis of the simultaneous interrogation criteria or on the basis of the earlier time of arrival.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4.4  Standard	<i>Diversity transmission channel isolation.</i> The peak RF power transmitted from the selected antenna shall exceed the power transmitted from the non-selected antenna by at least 20 dB.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.4.5  Standard	<i>Reply delay of diversity transponders.</i> The total two-way transmission difference in mean reply delay between the two antenna channels (including the differential delay caused by transponder-to-antenna cables and the horizontal distance along the aircraft centre line between the two antennas) shall not exceed 0.13 microsecond for interrogations of equal amplitude. This requirement shall hold for interrogation signal strengths between MTL +3 dB and -21 dBm. The jitter requirements on each individual channel shall remain as specified for non-diversity transponders.  <i>Note.— This requirement limits apparent jitter caused by antenna switching and by cable delay differences.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.1  Standard	3.1.2.10.5 DATA PROCESSING AND INTERFACES  Direct data. Direct data shall be those which are required for the surveillance protocol of the Mode S system.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.1.1  Standard	Fixed direct data. Fixed direct data are data from the aircraft which do not change in flight and shall be: a) the aircraft address (3.1.2.4.1.2.3.1.1 and 3.1.2.5.2.2.2); b) the maximum airspeed (3.1.2.8.2.2); and c) the registration marking if used for flight identification (3.1.2.9.1.1).	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.1.2  Recommendation	Interfaces for fixed direct data <b>Recommendation.</b> — Interfaces from the transponder to the aircraft should be designed such that the values of the fixed direct data become a function of the aircraft installation rather than of the transponder configuration. <i>Note.</i> — The intent of this recommendation is to encourage an interface technique which permits transponder exchange without manipulation of the transponder itself for setting the fixed direct data.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.1.3  Standard	Variable direct data. Variable direct data are data from the aircraft which can change in flight and shall be: a) the Mode C altitude code (3.1.2.6.5.4); b) the Mode A identity code (3.1.2.6.7.1); c) the on-the-ground condition (3.1.2.5.2.2.1, 3.1.2.6.5.1 and 3.1.2.8.2.1); d) the aircraft identification if different from the registration marking (3.1.2.9.1.1); and e) the SPI condition (3.1.2.6.10.1.3).	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.1.4.1  Standard	3.1.2.10.5.1.4 <i>Interfaces for variable direct data</i>  A means shall be provided, while on the ground or during flight, for the SPI condition to be inserted by the pilot, without the entry or modification of other flight data.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.1.4.2  Standard	A means shall be provided, while on the ground or during flight, for the Mode A identity code to be displayed to the pilot and modified without the entry or modification of other flight data.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.1.4.3  Standard	For transponders of Level 2 and above, a means shall be provided, while on the ground or during flight, for the aircraft identification to be displayed to the pilot and, when containing variable data (3.1.2.10.5.1.3 d)), to be modified without the entry or modification of other flight data. <i>Note.— Implementation of the pilot action for entry of data will be as simple and efficient as possible in order to minimize the time required and reduce the possibility of errors in the data entry.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.1.4.4  Standard	Interfaces shall be included to accept the pressure-altitude and on-the-ground coding. <i>Note.— A specific interface design for the variable direct data is not prescribed.</i>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.2  Standard	<p><i>Indirect data</i></p> <p><i>Note.— Indirect data are those which pass through the transponder in either direction but which do not affect the surveillance function.</i></p> <p>If origins and/or destinations of indirect data are not within the transponder's enclosure, interfaces shall be used for the necessary connections.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.2.1.1  Standard	<p><i>3.1.2.10.5.2.1 The function of interfaces</i></p> <p><i>Note.— Indirect data interfaces for standard transactions serve interrogations which require a reply and the broadcast function. Indirect data interfaces for ELM serve that system and require buffering and protocol circuitry within the transponder. Interface ports can be separate for each direction and for service or can be combined in any manner.</i></p> <p><i>Uplink standard length transaction interface. The uplink standard length transaction interface shall transfer all bits of accepted interrogations, (with the possible exception of the AP field), except for UF = 0, 11 or 16.</i></p> <p><i>Note.— AP can also be transferred to aid in integrity implementation.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.2.1.2  Standard	<p><i>Downlink standard length transaction interface.</i> A transponder which transmits information originating in a peripheral device shall be able to receive bits or bit patterns for insertion at appropriate locations within the transmission. These locations shall not include those into which bit patterns generated internally by the transponder are inserted, nor the AP field of the reply. A transponder which transmits information using the Comm-B format shall have immediate access to requested data in the sense that the transponder shall respond to an interrogation with data requested by that interrogation.</p> <p><i>Note.— This requirement may be met in two ways:</i></p> <ul style="list-style-type: none"> <li><i>a) the transponder may have provisions for internal data and protocol buffering;</i></li> <li><i>b) the transponder may employ a “real time” interface which operates such that uplink data leave the transponder before the corresponding reply is generated and downlink data enter the transponder in time to be incorporated in the reply.</i></li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.2.1.3  Note	<p><i>Extended length message interface</i></p> <p><i>Note.— The ELM interface extracts from, and enters into, the transponder the data exchanged between air and ground by means of the ELM protocol (3.1.2.7).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.2.2.1  Standard	<p>3.1.2.10.5.2.2 <i>Indirect data transaction rates</i></p> <p><i>Standard length transactions.</i> A transponder equipped for information transfer to and from external devices shall be capable of processing the data of at least as many replies as prescribed for minimum reply rates in 3.1.2.10.3.7.2 and uplink data from interrogations being delivered at a rate of at least:</p> <ul style="list-style-type: none"> <li>50 long interrogations in any 1-second interval</li> <li>18 long interrogations in a 100-millisecond interval</li> <li>8 long interrogations in a 25-millisecond interval</li> <li>4 long interrogations in a 1.6-millisecond interval.</li> </ul> <p><i>N1. A transponder capable of reply rates higher than the minimum of 3.1.2.10.3.7.2 need not accept long interrogations after reaching the uplink data processing limits above.</i></p> <p><i>N2. The Mode S reply is the sole means of acknowledging receipt of the data content of a Mode S interrogation. Thus, if the transponder is capable of replying to an interrogation, the Mode S installation must be capable of accepting the data contained in that interrogation regardless of the timing between it and other accepted interrogations. Overlapping Mode S beams from several interrogators could lead to the requirement for considerable data processing and buffering. The minimum described here reduces data processing to a realistic level and the non-acceptance provision provides for notification to the interrogator that data will temporarily not be accepted.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.2.2.2  Standard	<i>Extended length transactions.</i> Level 3 (2.1.5.1.3) and level 4 (2.1.5.1.4) transponders shall be able to transfer data from at least four complete sixteen segment uplink ELMs (3.1.2.7.4) in any four second interval. A level 5 transponder (2.1.5.1.5) shall be able to transfer the data from at least four complete sixteen segment uplink ELMs in any one second interval and shall be capable of accepting at least two complete sixteen segment uplink ELMs with the same II code in a 250 millisecond interval. A level 4 transponder shall be able to transmit at least one four-segment downlink ELM (3.1.2.7.7 and 3.1.2.10.3.7.3) in any one second interval. A level 5 transponder shall be able to transmit at least one sixteen segment downlink ELM in any one second interval.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.2.2.2.1  Recommendation	<b>Recommendation.</b> — <i>Level 3 and level 4 transponders should be able to accept at least two complete sixteen segment uplink ELMs in a 250 millisecond interval.</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.2.3.1  Standard	<b>3.1.2.10.5.2.3 Data formats for standard length transactions and required downlink aircraft parameters (DAPs)</b>  All level 2 and above transponders shall support the following registers: the capability reports (3.1.2.6.10.2); the aircraft identification protocol register 20 {HEX} (3.1.2.9); and for ACAS-equipped aircraft, the active resolution advisory register 30 {HEX} (4.3.8.4.2.2).	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.2.3.2  Standard	Where required, DAPs shall be supported by the registers listed in Table 3-11. The formats and minimum update rates of transponder registers shall be implemented consistently to ensure interoperability.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.2.3.3  Standard	The downlink standard length transaction interface shall deliver downlink aircraft parameters (DAPs) to the transponder which makes them available to the ground. Each DAP shall be packed into the Comm-B format ('MB' field) and can be extracted using either the ground-initiated Comm-B (GICB) protocol, or using MSP downlink channel 3 via the dataflash application.  <i>Note.— The formats and update rates of each register and the dataflash application are specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.3  Standard	<i>Integrity of data content transfer.</i> A transponder which employs data interfaces shall include sufficient protection to ensure error rates of less than one error in $10^3$ messages and less than one undetected error in $10^7$ 112-bit transmissions in both directions between the antenna and each interface port.	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.10.5.4  Standard	<p><i>Message cancellation.</i> The downlink standard length transaction interface and the extended length message interface shall include the capability to cancel a message sent to the transponder for delivery to the ground, but whose delivery cycle has not been completed (i.e. a closeout has not been accomplished by a ground interrogator).</p> <p><i>Note.— One example of the need for this capability is to cancel a message if delivery is attempted when the aircraft is not within coverage of a Mode S ground station. The message must then be cancelled to prevent it from being read and interpreted as a current message when the aircraft re-enters Mode S airspace.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.10.5.5  Standard	<p><i>Air-directed messages.</i> The transfer of this type of message requires all of the actions indicated in 3.1.2.10.5.4 plus the transfer to the transponder of the interrogator identifier of the site that is to receive the message.</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 3 Reference 3.1.2.11.1  Standard	<p><b>3.1.2.11 ESSENTIAL SYSTEM CHARACTERISTICS OF THE GROUND INTERROGATOR</b></p> <p><i>Note.— To ensure that Mode S interrogator action is not detrimental to Mode A/C interrogators, performance limits exist for Mode S interrogators.</i></p> <p><i>Interrogation repetition rates.</i> Mode S interrogators shall use the lowest practicable interrogation repetition rates for all interrogation modes.</p> <p><i>Note.— Accurate azimuth data at low interrogation rates can be obtained with monopulse techniques.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.11.1.1.1  Standard	3.1.2.11.1.1 <i>All-call interrogation repetition rate</i>  The interrogation repetition rate for the Mode A/C/S all-call, used for acquisition, shall be less than 250 per second. This rate shall also apply to the paired Mode S-only and Mode A/C-only all-call interrogations used for acquisition in the multisite mode.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.1.1.2  Standard	<i>Maximum number of Mode S all-call replies triggered by an interrogator.</i> For aircraft that are not locked out, a Mode S interrogator shall not trigger; on average, more than 6 all-call replies per period of 200 ms and no more than 26 all-call replies counted over a period of 18 seconds.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.1.2.1  Standard	3.1.2.11.1.2 <i>Interrogation repetition rate to a single aircraft</i>  <i>Interrogations requiring a reply.</i> Mode S interrogations requiring a reply shall not be transmitted to a single aircraft at intervals shorter than 400 microseconds.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.1.2.2  Standard	<i>Uplink ELM interrogations.</i> The minimum time between the beginning of successive Comm-C interrogations shall be 50 microseconds.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.11.1.3.1  Standard	<p>3.1.2.11.1.3 <i>Transmission rate for selective interrogations</i></p> <p>For all Mode S interrogators, the transmission rate for selective interrogations shall be:</p> <ul style="list-style-type: none"> <li>a) less than 2 400 per second averaged over a 40 -millisecond interval; and</li> <li>b) less than 480 into any 3-degree sector averaged over a 1-second interval.</li> </ul>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.1.3.2  Standard	<p>Additionally, for a Mode S interrogator that has overlapping coverage with the sidelobes of any other Mode S interrogator, the transmission rate for selective interrogations shall be:</p> <ul style="list-style-type: none"> <li>a) less than 1 200 per second averaged over a 4-second interval; and</li> <li>b) less than 1 800 per second averaged over a 1-second interval.</li> </ul> <p><i>Note.— Typical minimum distance to ensure sidelobe separation between interrogators is 35 km.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.2  Recommendation	<p><b>INTERROGATOR-EFFECTIVE RADIATED POWER</b></p> <p><b>Recommendation.—</b> <i>The effective radiated power of all interrogation pulses should be minimized as described in 3.1.1.8.2.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.11.3  Standard	<i>Inactive-state interrogator output power.</i> When the interrogator transmitter is not transmitting an interrogation, its output shall not exceed –5 dBm effective radiated power at any frequency between 960 MHz and 1 215 MHz.  <i>Note.— This constraint ensures that aircraft flying near the interrogator (as close as 1.85 km (1 NM)) will not receive interference that would prevent them from being tracked by another interrogator. In certain instances even smaller interrogator-to-aircraft distances are of significance, for example if Mode S surveillance on the airport surface is used. In such cases a further restraint on inactive state interrogator output power may be necessary.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.3.1  Recommendation	<i>Spurious emission radiation</i> <b>Recommendation.—</b> <i>CW radiation should not exceed 76 dB below 1 watt.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.4  Standard	<i>Tolerances on transmitted signals.</i> In order that the signal-in-space be received by the transponder as described in 3.1.2.1, the tolerances on the transmitted signal shall be as summarized in Table 3-12.	CAR 171.53(a)(1).	No Difference		
Chapter 3 Reference 3.1.2.11.5  Recommendation	<b>SPURIOUS RESPONSE</b> <b>Recommendation.—</b> <i>The response to signals not within the passband should be at least 60 dB below normal sensitivity.</i>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.1.2.11.6  Standard	<p><i>Lockout coordination.</i> A Mode S interrogator shall not be operated using all-call lockout until coordination has been achieved with all other operating Mode S interrogators having any overlapping coverage volume in order to ensure that no interrogator can be denied the acquisition of Mode S-equipped aircraft.</p> <p><i>Note.— This coordination may be via ground network or by the allocation of interrogator identifier (II) codes and will involve regional agreements where coverage overlaps international boundaries.</i></p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																				
Chapter 3 Reference 3.1.2.11.7  Recommendation	<p><i>MOBILE INTERROGATORS</i></p> <p><b>Recommendation.</b>— <i>Mobile interrogators should acquire, whenever possible, Mode S aircraft through the reception of squitters.</i></p> <p><i>Note.</i>— <i>Passive squitter acquisition reduces channel loading and can be accomplished without the need for coordination.</i></p> <p style="text-align: center;"><b>TABLES FOR CHAPTER 3</b></p> <p style="text-align: center;"><b>Table 3-1. Pulse shapes — Mode S and intermode interrogations</b></p> <table border="0" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="text-align: left;"><i>Pulse</i></th> <th style="text-align: center;"><i>Duration time</i></th> <th style="text-align: center;"><i>Duration (Decay</i></th> <th style="text-align: center;"><i>(Rise time)</i></th> </tr> <tr> <td></td> <th style="text-align: center;"><i>Min.</i></th> <th style="text-align: center;"><i>Max.</i></th> <td></td> </tr> <tr> <td></td> <th style="text-align: center;"><i>Min.</i></th> <th style="text-align: center;"><i>Max.</i></th> <td></td> </tr> </thead> <tbody> <tr> <td><i>P<sub>1</sub>, P<sub>2</sub>, P<sub>3</sub>, P<sub>5</sub></i></td> <td style="text-align: center;">0.8</td> <td style="text-align: center;">±0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.2</td> <td></td> </tr> <tr> <td><i>P<sub>4</sub> (short)</i></td> <td style="text-align: center;">0.8</td> <td style="text-align: center;">±0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.2</td> <td></td> </tr> <tr> <td><i>P<sub>4</sub> (long)</i></td> <td style="text-align: center;">1.6</td> <td style="text-align: center;">±0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.2</td> <td></td> </tr> <tr> <td><i>P<sub>6</sub> (short)</i></td> <td style="text-align: center;">16.25</td> <td style="text-align: center;">±0.25</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.2</td> <td></td> </tr> <tr> <td><i>P<sub>6</sub> (long)</i></td> <td style="text-align: center;">30.25</td> <td style="text-align: center;">±0.25</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.2</td> <td></td> </tr> <tr> <td><i>S<sub>i</sub></i></td> <td style="text-align: center;">0.8</td> <td style="text-align: center;">±0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.1</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0.05</td> <td style="text-align: center;">0.2</td> <td></td> </tr> </tbody> </table>	<i>Pulse</i>	<i>Duration time</i>	<i>Duration (Decay</i>	<i>(Rise time)</i>		<i>Min.</i>	<i>Max.</i>			<i>Min.</i>	<i>Max.</i>		<i>P<sub>1</sub>, P<sub>2</sub>, P<sub>3</sub>, P<sub>5</sub></i>	0.8	±0.1			0.05	0.1			0.05	0.2		<i>P<sub>4</sub> (short)</i>	0.8	±0.1			0.05	0.1			0.05	0.2		<i>P<sub>4</sub> (long)</i>	1.6	±0.1			0.05	0.1			0.05	0.2		<i>P<sub>6</sub> (short)</i>	16.25	±0.25			0.05	0.1			0.05	0.2		<i>P<sub>6</sub> (long)</i>	30.25	±0.25			0.05	0.1			0.05	0.2		<i>S<sub>i</sub></i>	0.8	±0.1			0.05	0.1			0.05	0.2		CAR 171.53(a)(1).	No Difference		
<i>Pulse</i>	<i>Duration time</i>	<i>Duration (Decay</i>	<i>(Rise time)</i>																																																																																						
	<i>Min.</i>	<i>Max.</i>																																																																																							
	<i>Min.</i>	<i>Max.</i>																																																																																							
<i>P<sub>1</sub>, P<sub>2</sub>, P<sub>3</sub>, P<sub>5</sub></i>	0.8	±0.1																																																																																							
	0.05	0.1																																																																																							
	0.05	0.2																																																																																							
<i>P<sub>4</sub> (short)</i>	0.8	±0.1																																																																																							
	0.05	0.1																																																																																							
	0.05	0.2																																																																																							
<i>P<sub>4</sub> (long)</i>	1.6	±0.1																																																																																							
	0.05	0.1																																																																																							
	0.05	0.2																																																																																							
<i>P<sub>6</sub> (short)</i>	16.25	±0.25																																																																																							
	0.05	0.1																																																																																							
	0.05	0.2																																																																																							
<i>P<sub>6</sub> (long)</i>	30.25	±0.25																																																																																							
	0.05	0.1																																																																																							
	0.05	0.2																																																																																							
<i>S<sub>i</sub></i>	0.8	±0.1																																																																																							
	0.05	0.1																																																																																							
	0.05	0.2																																																																																							



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																																																							
	<p><b>Table 3-2. Pulse shapes — Mode S replies</b></p> <table border="1"> <thead> <tr> <th rowspan="2">Pulse duration</th> <th>Duration</th> <th>(Rise time)</th> </tr> <tr> <th>(Decay tolerance)</th> <th>Min.</th> </tr> </thead> <tbody> <tr> <td rowspan="3">0.5</td> <td>±0.05</td> <td>0.05</td> </tr> <tr> <td>0.1</td> <td>0.05</td> </tr> <tr> <td>0.2</td> <td></td> </tr> <tr> <td rowspan="3">1.0</td> <td>±0.05</td> <td>0.05</td> </tr> <tr> <td>0.1</td> <td>0.05</td> </tr> <tr> <td>0.2</td> <td></td> </tr> </tbody> </table> <p><b>Table 3-3. Field definitions</b></p> <table border="1"> <thead> <tr> <th>Field Designator</th> <th>Function</th> <th>UF</th> <th>DF</th> <th>Reference</th> </tr> </thead> <tbody> <tr> <td>AA</td> <td>Address announced</td> <td></td> <td>11, 17, 18</td> <td>3.1.2.5.2.2.2</td> </tr> <tr> <td>AC</td> <td>Altitude code</td> <td></td> <td>4, 20</td> <td>3.1.2.6.5.4</td> </tr> <tr> <td>AF</td> <td>Application field</td> <td></td> <td>19</td> <td>3.1.2.8.8.2</td> </tr> <tr> <td>AP</td> <td>Address/parity</td> <td>All</td> <td>0, 4, 5, 16</td> <td>3.1.2.3.2.1.3</td> </tr> <tr> <td></td> <td></td> <td></td> <td>20, 21, 24</td> <td></td> </tr> <tr> <td>AQ</td> <td>Acquisition</td> <td>0</td> <td></td> <td>3.1.2.8.1.1</td> </tr> <tr> <td>CA</td> <td>Capability</td> <td></td> <td>11,17</td> <td>3.1.2.5.2.2.1</td> </tr> <tr> <td>CC</td> <td>Cross-link capability</td> <td></td> <td>0</td> <td>3.1.2.8.2.3</td> </tr> <tr> <td>CF</td> <td>Control field</td> <td></td> <td>18</td> <td>3.1.2.8.7.2</td> </tr> <tr> <td>CL</td> <td>Code label</td> <td>11</td> <td></td> <td>3.1.2.5.2.1.3</td> </tr> <tr> <td>DF</td> <td>Downlink format</td> <td></td> <td>All</td> <td>3.1.2.3.2.1.2</td> </tr> <tr> <td>DI</td> <td>Designator identification</td> <td></td> <td>4, 5,</td> <td>3.1.2.6.1.3</td> </tr> <tr> <td></td> <td></td> <td></td> <td>20, 21</td> <td></td> </tr> <tr> <td>DR</td> <td>Downlink request</td> <td></td> <td>4, 5,</td> <td>3.1.2.6.5.2</td> </tr> <tr> <td></td> <td></td> <td></td> <td>20, 21</td> <td></td> </tr> <tr> <td>DS</td> <td>Data selector</td> <td>0</td> <td></td> <td>3.1.2.8.1.3</td> </tr> <tr> <td>FS</td> <td>Flight status</td> <td></td> <td>4, 5,</td> <td>3.1.2.6.5.1</td> </tr> <tr> <td></td> <td></td> <td></td> <td>20, 21</td> <td></td> </tr> <tr> <td>IC</td> <td>Interrogator code</td> <td>11</td> <td></td> <td>3.1.2.5.2.1.2</td> </tr> </tbody> </table>	Pulse duration	Duration	(Rise time)	(Decay tolerance)	Min.	0.5	±0.05	0.05	0.1	0.05	0.2		1.0	±0.05	0.05	0.1	0.05	0.2		Field Designator	Function	UF	DF	Reference	AA	Address announced		11, 17, 18	3.1.2.5.2.2.2	AC	Altitude code		4, 20	3.1.2.6.5.4	AF	Application field		19	3.1.2.8.8.2	AP	Address/parity	All	0, 4, 5, 16	3.1.2.3.2.1.3				20, 21, 24		AQ	Acquisition	0		3.1.2.8.1.1	CA	Capability		11,17	3.1.2.5.2.2.1	CC	Cross-link capability		0	3.1.2.8.2.3	CF	Control field		18	3.1.2.8.7.2	CL	Code label	11		3.1.2.5.2.1.3	DF	Downlink format		All	3.1.2.3.2.1.2	DI	Designator identification		4, 5,	3.1.2.6.1.3				20, 21		DR	Downlink request		4, 5,	3.1.2.6.5.2				20, 21		DS	Data selector	0		3.1.2.8.1.3	FS	Flight status		4, 5,	3.1.2.6.5.1				20, 21		IC	Interrogator code	11		3.1.2.5.2.1.2				
Pulse duration	Duration		(Rise time)																																																																																																																									
	(Decay tolerance)	Min.																																																																																																																										
0.5	±0.05	0.05																																																																																																																										
	0.1	0.05																																																																																																																										
	0.2																																																																																																																											
1.0	±0.05	0.05																																																																																																																										
	0.1	0.05																																																																																																																										
	0.2																																																																																																																											
Field Designator	Function	UF	DF	Reference																																																																																																																								
AA	Address announced		11, 17, 18	3.1.2.5.2.2.2																																																																																																																								
AC	Altitude code		4, 20	3.1.2.6.5.4																																																																																																																								
AF	Application field		19	3.1.2.8.8.2																																																																																																																								
AP	Address/parity	All	0, 4, 5, 16	3.1.2.3.2.1.3																																																																																																																								
			20, 21, 24																																																																																																																									
AQ	Acquisition	0		3.1.2.8.1.1																																																																																																																								
CA	Capability		11,17	3.1.2.5.2.2.1																																																																																																																								
CC	Cross-link capability		0	3.1.2.8.2.3																																																																																																																								
CF	Control field		18	3.1.2.8.7.2																																																																																																																								
CL	Code label	11		3.1.2.5.2.1.3																																																																																																																								
DF	Downlink format		All	3.1.2.3.2.1.2																																																																																																																								
DI	Designator identification		4, 5,	3.1.2.6.1.3																																																																																																																								
			20, 21																																																																																																																									
DR	Downlink request		4, 5,	3.1.2.6.5.2																																																																																																																								
			20, 21																																																																																																																									
DS	Data selector	0		3.1.2.8.1.3																																																																																																																								
FS	Flight status		4, 5,	3.1.2.6.5.1																																																																																																																								
			20, 21																																																																																																																									
IC	Interrogator code	11		3.1.2.5.2.1.2																																																																																																																								



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	ID Identity 5, 21 3.1.2.6.7.1 KE Control, ELM 24 3.1.2.7.3.1 MA Message, Comm-A 20, 21 3.1.2.6.2.1  MB Message, Comm-B 20, 21 3.1.2.6.6.1 MC Message, Comm-C 24 3.1.2.7.1.3 MD Message, Comm-D 24 3.1.2.7.3.3 ME Message, extended squitter 17, 18 3.1.2.8.6.2 MU Message, ACAS 16 4.3.8.4.2.3 MV Message, ACAS 16 3.1.2.8.3.1, 4.3.8.4.2.4 NC Number of C-segment 24 3.1.2.7.1.2 ND Number of D-segment 24 3.1.2.7.3.2				





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference</p> <p>Definition</p>	<p style="text-align: center;"><b>CHAPTER 4. AIRBORNE COLLISION AVOIDANCE SYSTEM</b></p> <p><i>N1.Guidance material relating to the airborne collision avoidance system is contained in the Airborne Collision Avoidance System (ACAS) Manual (Doc 9863).</i></p> <p><i>N2.Non-SI alternative units are used as permitted by Annex 5, Chapter 3, 3.2.2. In limited cases, to ensure consistency at the level of the logic calculations, units such as ft/s, NM/s and kt/s are used.</i></p> <p><i>N3.The system that is compliant with Chapter 4 in its entirety is the one that incorporates the traffic alert and collision avoidance systems (TCAS) Version 7.1 and therefore meets the RTCA/DO-185B or EUROCAE/ED-143 specification.</i></p> <p><i>N4.Equipment complying with RTCA/DO-185A standards (also known as TCAS Version 7.0) is not compliant with Chapter 4 in its entirety.</i></p> <p style="text-align: center;"><b>4.1 DEFINITIONS RELATING TO AIRBORNE COLLISION AVOIDANCE SYSTEM</b></p> <p><i>ACAS broadcast.</i> A long Mode S air-air surveillance interrogation (UF = 16) with the broadcast address.</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference</p> <p>Definition</p>	<p><i>ACAS I.</i> An ACAS which provides information as an aid to “see and avoid” action but does not include the capability for generating resolution advisories (RAs).</p> <p><i>Note.— ACAS I is not intended for international implementation and standardization by ICAO. Therefore, only ACAS I characteristics required to ensure compatible operation with other ACAS configurations and interference limiting are defined in 4.2.</i></p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		<p>ACAS II equipment carried pursuant to Civil Aviation Rules must meet the requirements of TSO C119b.</p>



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<i>ACAS II.</i> An ACAS which provides vertical resolution advisories (RAs) in addition to traffic advisories (TAs).	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<i>ACAS III.</i> An ACAS which provides vertical and horizontal resolution advisories (RAs) in addition to traffic advisories (TAs).	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<i>Active RAC.</i> An RAC is active if it currently constrains the selection of the RA. RACs that have been received within the last six seconds and have not been explicitly cancelled are active.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<i>Altitude crossing RA.</i> A resolution advisory is altitude crossing if own ACAS aircraft is currently at least 30 m (100 ft) below or above the threat aircraft for upward or downward sense advisories, respectively.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<i>Climb RA.</i> A positive RA recommending a climb but not an increased climb.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<b>Closest approach.</b> The occurrence of minimum range between own ACAS aircraft and the intruder. Thus range at closest approach is the smallest range between the two aircraft and time of closest approach is the time at which this occurs.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Coordination interrogation.</b> A Mode S interrogation (uplink transmission) radiated by ACAS II or III and containing a resolution message.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Coordination reply.</b> A Mode S reply (downlink transmission) acknowledging the receipt of a coordination interrogation by the Mode S transponder that is part of an ACAS II or III installation.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Coordination.</b> The process by which two ACAS-equipped aircraft select compatible resolution advisories (RAs) by the exchange of resolution advisory complements (RACs).	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Corrective RA.</b> A resolution advisory that advises the pilot to deviate from the current flight path.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<b>Cycle.</b> The term “cycle” used in this chapter refers to one complete pass through the sequence of functions executed by ACAS II or ACAS III, nominally once a second.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Descend RA.</b> A positive RA recommending a descent but not an increased descent.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Established track.</b> A track generated by ACAS air-air surveillance that is treated as the track of an actual aircraft.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Increased rate RA.</b> A resolution advisory with a strength that recommends increasing the altitude rate to a value exceeding that recommended by a previous climb or descend RA.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Intruder.</b> An SSR transponder-equipped aircraft within the surveillance range of ACAS for which ACAS has an established track.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<b>Own aircraft.</b> The aircraft fitted with the ACAS that is the subject of the discourse, which ACAS is to protect against possible collisions, and which may enter a manoeuvre in response to an ACAS indication.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Positive RA.</b> A resolution advisory that advises the pilot either to climb or to descend (applies to ACAS II).	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Potential threat.</b> An intruder deserving special attention either because of its close proximity to own aircraft or because successive range and altitude measurements indicate that it could be on a collision or near-collision course with own aircraft. The warning time provided against a potential threat is sufficiently small that a traffic advisory (TA) is justified but not so small that a resolution advisory (RA) would be justified.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Preventive RA.</b> A resolution advisory that advises the pilot to avoid certain deviations from the current flight path but does not require any change in the current flight path.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<p><b>RA sense.</b> The sense of an ACAS II RA is “upward” if it requires climb or limitation of descent rate and “downward” if it requires descent or limitation of climb rate. It can be both upward and downward simultaneously if it requires limitation of the vertical rate to a specified range.</p> <p><i>Note.— The RA sense may be both upward and downward when, having several simultaneous threats, ACAS generates an RA aimed at ensuring adequate separation below some threat(s) and above some other threat (s).</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<p><b>Resolution advisory (RA).</b> An indication given to the flight crew recommending:</p> <ul style="list-style-type: none"> <li>a) a manoeuvre intended to provide separation from all threats; or</li> <li>b) a manoeuvre restriction intended to maintain existing separation.</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<p><b>Resolution advisory complement (RAC).</b> Information provided by one ACAS to another via a Mode S interrogation in order to ensure complementary manoeuvres by restricting the choice of manoeuvres available to the ACAS receiving the RAC.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<p><b>Resolution advisory complements record (RAC record).</b> A composite of all currently active vertical RACs (VRCs) and horizontal RACs (HRCs) that have been received by ACAS. This information is provided by one ACAS to another ACAS or to a Mode S ground station via a Mode S reply.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<b>Resolution advisory strength.</b> The magnitude of the manoeuvre indicated by the RA. An RA may take on several successive strengths before being cancelled. Once a new RA strength is issued, the previous one automatically becomes void.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Resolution message.</b> The message containing the resolution advisory complement (RAC).	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Reversed sense RA.</b> A resolution advisory that has had its sense reversed.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Sensitivity level (S).</b> An integer defining a set of parameters used by the traffic advisory (TA) and collision avoidance algorithms to control the warning time provided by the potential threat and threat detection logic, as well as the values of parameters relevant to the RA selection logic.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Threat.</b> An intruder deserving special attention either because of its close proximity to own aircraft or because successive range and altitude measurements indicate that it could be on a collision or near-collision course with own aircraft. The warning time provided against a threat is sufficiently small that an RA is justified.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<i>Track.</i> A sequence of at least three measurements representing positions that could reasonably have been occupied by an aircraft.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<i>Traffic advisory (TA).</i> An indication given to the flight crew that a certain intruder is a potential threat.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<i>Vertical speed limit (VSL) RA.</i> A resolution advisory advising the pilot to avoid a given range of altitude rates. A VSL RA can be either corrective or preventive.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<i>Warning time.</i> The time interval between potential threat or threat detection and closest approach when neither aircraft accelerates.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.2.1  Standard	<p align="center"><b>4.2 ACAS I GENERAL PROVISIONS AND CHARACTERISTICS</b></p> <p><i>Functional requirements.</i> ACAS I shall perform the following functions:</p> <ul style="list-style-type: none"> <li>a) surveillance of nearby SSR transponder-equipped aircraft; and</li> <li>b) provide indications to the flight crew identifying the approximate position of nearby aircraft as an aid to visual acquisition.</li> </ul> <p><i>Note.— ACAS is intended to operate using Mode A/C interrogations only. Furthermore, it does not coordinate with other ACAS. Therefore, a Mode S transponder is not required as a part of an ACAS I installation.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.2.2  Standard	<i>Signal format.</i> The RF characteristics of all ACAS I signals shall conform to the provisions of Chapter 3, 3.1.1.1 through 3.1.1.6 and 3.1.2.1 through 3.1.2.4.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.2.3.1  Standard	<p align="center"><b>4.2.3 Interference control</b></p> <p><i>Maximum radiated RF power.</i> The effective radiated power of an ACAS I transmission at 0 degree elevation relative to the longitudinal axis of the aircraft shall not exceed 24 dBW.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.2.3.2  Standard	<i>Unwanted radiated power.</i> When ACAS I is not transmitting an interrogation, the effective radiated power in any direction shall not exceed -70 dBm. <i>Note.— This requirement is to ensure that, when not transmitting an interrogation, ACAS I does not radiate RF energy that could interfere with, or reduce the sensitivity of, the SSR transponder or radio equipment in other nearby aircraft or ground facilities.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.2.3.3  Standard	<i>Interference limiting.</i> Each ACAS I interrogator shall control its interrogation rate or power or both in all SSR modes to minimize interference effects (4.2.3.3.3 and 4.2.3.3.4). <i>Note.— These limits are a means of ensuring that all interference effects resulting from these interrogations, together with the interrogations from all other ACAS I, ACAS II and ACAS III interrogators in the vicinity are kept to a low level.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.2.3.3.1  Standard	<i>Determination of own transponder reply rate.</i> ACAS I shall monitor the rate that own transponder replies to interrogations to ensure that the provisions in 4.2.3.3.3 are met.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.2.3.3.2  Standard	<i>Determination of the number of ACAS II and ACAS III interrogators.</i> ACAS I shall count the number of ACAS II and ACAS III interrogators in the vicinity to ensure that the provisions in 4.2.3.3.3 or 4.2.3.3.4 are met. This count shall be obtained by monitoring ACAS broadcasts (UF = 16), (4.3.7.1.2.4) and shall be updated as the number of distinct ACAS aircraft addresses received within the previous 20-s period at a nominal frequency of at least 1 Hz.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																																				
Chapter 4  Reference 4.2.3.3.3	<p><i>Mode A/C ACAS I interference limits.</i> The interrogator power shall not exceed the following limits:</p> <table data-bbox="504 422 882 1218"> <tr> <td><math>n_a</math></td> <td><math>\{ \}</math></td> <td><math>\text{If } f_r \leq 240</math></td> <td><math>\text{If } f_r</math></td> </tr> <tr> <td>&gt;240</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td></td> <td>250</td> <td>118</td> </tr> <tr> <td>1</td> <td></td> <td>250</td> <td>113</td> </tr> <tr> <td>2</td> <td></td> <td>250</td> <td>108</td> </tr> <tr> <td>3</td> <td></td> <td>250</td> <td>103</td> </tr> <tr> <td>4</td> <td></td> <td>250</td> <td>98</td> </tr> <tr> <td>5</td> <td></td> <td>250</td> <td>94</td> </tr> <tr> <td>6</td> <td></td> <td>250</td> <td>89</td> </tr> <tr> <td>7</td> <td></td> <td>250</td> <td>84</td> </tr> <tr> <td>8</td> <td></td> <td>250</td> <td>79</td> </tr> <tr> <td>9</td> <td></td> <td>250</td> <td>74</td> </tr> <tr> <td>10</td> <td></td> <td>245</td> <td>70</td> </tr> <tr> <td>11</td> <td></td> <td>228</td> <td>65</td> </tr> <tr> <td>12</td> <td></td> <td>210</td> <td>60</td> </tr> <tr> <td>13</td> <td></td> <td>193</td> <td>55</td> </tr> <tr> <td>14</td> <td></td> <td>175</td> <td>50</td> </tr> <tr> <td>15</td> <td></td> <td>158</td> <td>45</td> </tr> <tr> <td>16</td> <td></td> <td>144</td> <td>41</td> </tr> <tr> <td>17</td> <td></td> <td>126</td> <td>36</td> </tr> <tr> <td>18</td> <td></td> <td>109</td> <td>31</td> </tr> <tr> <td>19</td> <td></td> <td>91</td> <td>26</td> </tr> <tr> <td>20</td> <td></td> <td>74</td> <td>21</td> </tr> <tr> <td>21</td> <td></td> <td>60</td> <td>17</td> </tr> <tr> <td><math>\geq 22</math></td> <td></td> <td>42</td> <td>12</td> </tr> </table> <p>where:  <math>n_a</math> = number of operating ACAS II and ACAS III equipped aircraft near own (based on ACAS broadcasts received with a transponder receiver threshold of -74 dBm);  <math>\{ \}</math> = average value of the expression within the brackets over last 8 interrogation cycles;</p>	$n_a$	$\{ \}$	$\text{If } f_r \leq 240$	$\text{If } f_r$	>240				0		250	118	1		250	113	2		250	108	3		250	103	4		250	98	5		250	94	6		250	89	7		250	84	8		250	79	9		250	74	10		245	70	11		228	65	12		210	60	13		193	55	14		175	50	15		158	45	16		144	41	17		126	36	18		109	31	19		91	26	20		74	21	21		60	17	$\geq 22$		42	12	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
$n_a$	$\{ \}$	$\text{If } f_r \leq 240$	$\text{If } f_r$																																																																																																						
>240																																																																																																									
0		250	118																																																																																																						
1		250	113																																																																																																						
2		250	108																																																																																																						
3		250	103																																																																																																						
4		250	98																																																																																																						
5		250	94																																																																																																						
6		250	89																																																																																																						
7		250	84																																																																																																						
8		250	79																																																																																																						
9		250	74																																																																																																						
10		245	70																																																																																																						
11		228	65																																																																																																						
12		210	60																																																																																																						
13		193	55																																																																																																						
14		175	50																																																																																																						
15		158	45																																																																																																						
16		144	41																																																																																																						
17		126	36																																																																																																						
18		109	31																																																																																																						
19		91	26																																																																																																						
20		74	21																																																																																																						
21		60	17																																																																																																						
$\geq 22$		42	12																																																																																																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	$P_a(k)$ = peak power radiated from the antenna in all directions of the pulse having the largest amplitude in the group of pulses comprising a single interrogation during the $k$ th Mode A/C interrogation in a 1 s interrogation cycle, W;  $k$ = index number for Mode A/C interrogations, $k = 1, 2, \dots, k_t$ ; $k_t$ = number of Mode A/C interrogations transmitted in a 1 s interrogation cycle; $f_r$ = Mode A/C reply rate of own transponder.				
Chapter 4 Reference 4.2.3.3.4  Standard	<i>Mode S ACAS I interference limits.</i> An ACAS I that uses Mode S interrogations shall not cause greater interference effects than an ACAS I using Mode A/C interrogations only.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference 4.3.1.1  Standard</p>	<p><b>4.3 GENERAL PROVISIONS RELATING TO ACAS II AND ACAS III</b></p> <p><i>N1.The acronym ACAS is used in this section to indicate either ACAS II or ACAS III.</i></p> <p><i>N2.Carriage requirements for ACAS equipment are addressed in Annex 6.</i></p> <p><i>N3.The term “equipped threat” is used in this section to indicate a threat fitted with ACAS II or ACAS III.</i></p> <p><b>4.3.1 Functional requirements</b></p> <p><i>ACAS functions. ACAS shall perform the following functions:</i></p> <ul style="list-style-type: none"> <li>a) surveillance;</li> <li>b) generation of TAs;</li> <li>c) threat detection;</li> <li>d) generation of RAs;</li> <li>e) coordination; and</li> <li>f) communication with ground stations.</li> </ul> <p>The equipment shall execute functions b) through e) on each cycle of operation.</p> <p><i>Note.— Certain features of these functions must be standardized to ensure that ACAS units cooperate satisfactorily with other ACAS units, with Mode S ground stations and with the ATC system. Each of the features that are standardized is discussed below. Certain other features are given herein as recommendations.</i></p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference 4.3.1.1.1  Standard</p>	<p>The duration of a cycle shall not exceed 1.2 s.</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.2.1  Standard	<p><b>4.3.2 Surveillance performance requirements</b></p> <p><i>General surveillance requirements.</i> ACAS shall interrogate SSR Mode A/C and Mode S transponders in other aircraft and detect the transponder replies. ACAS shall measure the range and relative bearing of responding aircraft. Using these measurements and information conveyed by transponder replies, ACAS shall estimate the relative positions of each responding aircraft. ACAS shall include provisions for achieving such position determination in the presence of ground reflections, interference and variations in signal strength.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																		
Chapter 4 Reference 4.3.2.1.1  Standard	<p><i>Track establishment probability.</i> ACAS shall generate an established track, with at least a 0.90 probability that the track is established 30 s before closest approach, on aircraft equipped with transponders when all of the following conditions are satisfied:</p> <ul style="list-style-type: none"> <li>a) the elevation angles of these aircraft are within <math>\pm 10</math> degrees relative to the ACAS aircraft pitch plane;</li> <li>b) the magnitudes of these aircraft's rates of change of altitude are less than or equal to 51 m/s (10 000 ft/min);</li> <li>c) the transponders and antennas of these aircraft meet the Standards of Chapter 3, 3.1.1 and 3.1.2;</li> <li>d) the closing speeds and directions of these aircraft, the local density of SSR transponder-equipped aircraft and the number of other ACAS interrogators in the vicinity (as determined by monitoring ACAS broadcasts, 4.3.7.1.2.4) satisfy the conditions specified in Table 4-1; and</li> <li>e) the minimum slant range is equal to or greater than 300 m (1 000 ft).</li> </ul> <p><b>Table 4-1. ACAS design assumptions</b></p> <table border="1"> <thead> <tr> <th colspan="2">Conditions</th> <th colspan="8">Performance</th> </tr> <tr> <th>Quadrant</th> <th>Forward</th> <th>Side</th> <th>Back</th> <th colspan="2">Maximum traffic density</th> <th colspan="2">Maximum closing speed</th> <th colspan="2">Maximum number of other ACAS within 56 km (30 NM)</th> </tr> <tr> <th></th> <th>m/s</th> <th>kt</th> <th>m/s</th> <th>kt</th> <th>aircraft/ km<sup>2</sup></th> <th>aircraft/ NM<sup>2</sup></th> <th>m/s</th> <th>kt</th> <th>Probability of success</th> </tr> </thead> <tbody> <tr> <td>260</td> <td>500</td> <td>150</td> <td>300</td> <td>93</td> <td>180</td> <td>0.087</td> <td>0.30</td> <td>30</td> <td>0.9</td> </tr> <tr> <td>620</td> <td>1 200</td> <td>390</td> <td>750</td> <td>220</td> <td>430</td> <td>0.017</td> <td>0.06</td> <td>30</td> <td>0.9</td> </tr> </tbody> </table> <p><i>Note.— Table 4-1 shows the design assumption upon which the development of ACAS was based. Operational experience and simulation show that ACAS provides adequate surveillance for collision avoidance even when the maximum number of other ACAS within 56 km (30 NM) is somewhat higher than that shown in Table 4-1. Future ACAS designs will take account of current and expected ACAS</i></p>	Conditions		Performance								Quadrant	Forward	Side	Back	Maximum traffic density		Maximum closing speed		Maximum number of other ACAS within 56 km (30 NM)			m/s	kt	m/s	kt	aircraft/ km <sup>2</sup>	aircraft/ NM <sup>2</sup>	m/s	kt	Probability of success	260	500	150	300	93	180	0.087	0.30	30	0.9	620	1 200	390	750	220	430	0.017	0.06	30	0.9	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Conditions		Performance																																																					
Quadrant	Forward	Side	Back	Maximum traffic density		Maximum closing speed		Maximum number of other ACAS within 56 km (30 NM)																																															
	m/s	kt	m/s	kt	aircraft/ km <sup>2</sup>	aircraft/ NM <sup>2</sup>	m/s	kt	Probability of success																																														
260	500	150	300	93	180	0.087	0.30	30	0.9																																														
620	1 200	390	750	220	430	0.017	0.06	30	0.9																																														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<i>densities.</i>				
Chapter 4 Reference 4.3.2.1.1.1  Standard	ACAS shall continue to provide surveillance with no abrupt degradation in track establishment probability as any one of the condition bounds defined in 4.3.2.1.1 is exceeded.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.2.1.1.2  Standard	ACAS shall not track Mode S aircraft that report that they are on the ground. <i>Note.— A Mode S aircraft may report that it is on the ground by coding in the capability (CA) field in a DF = 11 or DF = 17 transmission (Chapter 3, 3.1.2.5.2.2.1) or by coding in the vertical status (VS) field in a DF = 0 transmission (Chapter 3, 3.1.2.8.2.1). Alternatively, if the aircraft is under Mode S ground surveillance, ground status may be determined by monitoring the flight status (FS) field in downlink formats DF = 4, 5, 20 or 21 (Chapter 3, 3.1.2.6.5.1).</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.2.1.1.3  Recommendation	<b>Recommendation.—</b> ACAS should achieve the required tracking performance when the average SSR Mode A/C asynchronous reply rate from transponders in the vicinity of the ACAS aircraft is 240 replies per second and when the peak interrogation rate received by the individual transponders under surveillance is 500 per second. <i>Note.— The peak interrogation rate mentioned above includes interrogations from all sources.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.2.1.2  Standard	<i>False track probability.</i> The probability that an established Mode A/C track does not correspond in range and altitude, if reported, to an actual aircraft shall be less than 10 <sup>-2</sup> . For an established Mode S track this probability shall be less than 10 <sup>-6</sup> . These limits shall not be exceeded in any traffic environment.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.2.1.3.1  Standard	<b>4.3.2.1.3 RANGE AND BEARING ACCURACY</b>  Range shall be measured with a resolution of 14.5 m (1/128 NM) or better.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.2.1.3.2  Recommendation	<b>Recommendation.</b> — <i>The errors in the relative bearings of the estimated positions of intruders should not exceed 10 degrees rms.</i>  <i>Note.— This accuracy in the relative bearing of intruders is practicable and sufficient as an aid to the visual acquisition of potential threats. In addition, such relative bearing information has been found useful in threat detection, where it can indicate that an intruder is a threat. However, this accuracy is not sufficient as a basis for horizontal RAs, nor is it sufficient for reliable predictions of horizontal miss distance.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.2.2.1  Standard	<b>4.3.2.2 INTERFERENCE CONTROL</b>  <i>Maximum radiated RF power.</i> The effective radiated power of an ACAS transmission at 0 degree elevation relative to the longitudinal axis of the aircraft shall not exceed 27 dBW.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.2.2.1.1  Standard	<i>Unwanted radiated power.</i> When ACAS is not transmitting an interrogation, the effective radiated power in any direction shall not exceed -70 dBm.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.2.2.2  Standard	<i>Interference limiting.</i> Each ACAS interrogator operating below a pressure-altitude of 5 490 m (18 000 ft) shall control its interrogation rate or power or both so as to conform with specific inequalities (4.3.2.2.2.2).	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.2.2.2.1  Standard	<i>Determination of the number of other ACAS.</i> ACAS shall count the number of other ACAS II and III interrogators in the vicinity to ensure that the interference limits are met. This count shall be obtained by monitoring ACAS broadcasts (UF = 16), (4.3.7.1.2.4). Each ACAS shall monitor such broadcast interrogations to determine the number of other ACAS within detection range.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.2.2.2.2  Standard	<p><i>ACAS interference limiting inequalities.</i> ACAS shall adjust its interrogation rate and interrogation power such that the following three inequalities remain true, except as provided in 4.3.2.2.2.2.1.</p> <p>(1)</p> <p>(2)</p> <p>(3)</p> <p>The variables in these inequalities shall be defined as follows:</p> <p><math>i_i</math> = number of interrogations (Mode A/C and Mode S) transmitted in a 1 s interrogation cycle. This shall include all Mode S interrogations used by the ACAS functions, including those in addition to <math>UF = 0</math> and <math>UF = 16</math> interrogations, except as provided in 4.3.2.2.2.2.1; <i>Note.</i> — <math>UF = 19</math> interrogations are included in <math>i_i</math> as specified in 3.1.2.8.9.4.</p> <p><math>i</math> = index number for Mode A/C and Mode S interrogations, <math>i = 1, 2, \dots, i_i</math>;</p> <p><math>\alpha</math> = the minimum of <math>\alpha_1</math> calculated as <math>1/4 [nb/nc]</math> subject to the special conditions given below and <math>\alpha_2</math> calculated as <math>\text{Log}_{10} [na/nb]/\text{Log}_{10} 25</math>, where <math>nb</math> and <math>nc</math> are defined as the number of operating ACAS II and ACAS III equipped aircraft (airborne or on the ground) within 11.2 km (6 NM) and 5.6 km (3 NM) respectively, of own ACAS (based on ACAS surveillance). ACAS aircraft operating on the ground or at or below a radio altitude of 610 m (2 000 ft) AGL shall include both airborne and on-ground ACAS II and ACAS III aircraft in the value for <math>nb</math> and <math>nc</math>. Otherwise, ACAS shall include only airborne ACAS II and ACAS III aircraft in the value for <math>nb</math> and <math>nc</math>. The values of <math>\alpha</math>, <math>\alpha_1</math> and <math>\alpha_2</math> are further constrained to a minimum of 0.5 and a maximum of 1.0.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>In addition;  IF[(<math>n_b \leq 1</math>) OR (<math>n_b \leq 4</math> AND <math>n_c \leq 2</math> AND <math>n_a &gt; 25</math>)] THEN <math>a_1 = 1.0</math>,  IF [(<math>n_c &gt; 2</math>) AND (<math>n_b &gt; 2n_c</math>) AND (<math>n_a &lt; 40</math>)] THEN <math>a_1 = 0.5</math>;</p> <p><math>p(i)</math> = peak power radiated from the antenna in all directions of the pulse having the largest amplitude in the group of pulses comprising a single interrogation during the <math>i</math>th interrogation in a 1 s interrogation cycle, W;  <math>m(i)</math> = duration of the mutual suppression interval for own transponder associated with the <math>i</math>th interrogation in a 1 s interrogation cycle, s;  <math>B</math> = beam sharpening factor (ratio of 3 dB beam width to beamwidth resulting from interrogation side-lobe suppression). For ACAS interrogators that employ transmitter side-lobe suppression (SLS), the appropriate beamwidth shall be the extent in azimuth angle of the Mode A/C replies from one transponder as limited by SLS, averaged over the transponder population;  { } see 4.2.3.3.3  <math>P_a(k)</math> "  <math>k</math> "  <math>kt</math> "  <math>n_a</math> "</p> <p><i>Note.— RA and ACAS broadcasts (4.3.6.2.1 and 4.3.7.1.2.4) are interrogations.</i></p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.2.2.2.2.1  Standard	<i>Transmissions during RAs.</i> All air-to-air coordination interrogations shall be transmitted at full power and these interrogations shall be excluded from the summations of Mode S interrogations in the left-hand terms of inequalities (1) and (2) in 4.3.2.2.2.2 for the duration of the RA.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.2.2.2.2.2  Standard	<i>Transmissions from ACAS units on the ground.</i> Whenever the ACAS aircraft indicates that it is on the ground, ACAS interrogations shall be limited by setting the number of other ACAS II and III aircraft ( <i>n<sub>a</sub></i> ) count in the interference limiting inequalities to a value that is three times the value obtained based on ACAS broadcasts received with a transponder receiver threshold of -74 dBm. Whenever Mode A/C interrogation power is reduced because of interference limiting, the Mode A/C interrogation power in the forward beam shall be reduced first until the forward sequence matches the right and left sequences. The forward, right and left interrogation powers shall then sequentially be reduced until they match the rear interrogation power. Further reduction of Mode A/C power shall be accomplished by sequentially reducing the forward, side and rear interrogation powers.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.2.2.2.2.3  Standard	<i>Transmissions from ACAS units above 5 490 m (18 000 ft) altitude.</i> Each ACAS interrogator operating above a pressure-altitude of 5 490 m (18 000 ft) shall control its interrogation rate or power or both such that inequalities (1) and (3) in 4.3.2.2.2.2 remain true when <i>n<sub>a</sub></i> and <i>a</i> are equal to 1, except as provided in 4.3.2.2.2.1.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.3.1  Standard	<p align="center"><b>4.3.3 Traffic advisories (TAs)</b></p> <p><i>TA function.</i> ACAS shall provide TAs to alert the flight crew to potential threats. Such TAs shall be accompanied by an indication of the approximate relative position of potential threats to facilitate visual acquisition.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.3.1.1  Standard	<p>Display of potential threats. If potential threats are shown on a traffic display, they shall be displayed in amber or yellow.</p> <p><i>N1. These colours are generally considered suitable for indicating a cautionary condition.</i></p> <p><i>N2. Additional information assisting in the visual acquisition such as vertical trend and relative altitude may be displayed as well.</i></p> <p><i>N3. Traffic situational awareness is improved when tracks can be supplemented by display of heading information (e.g. as extracted from received ADS-B messages).</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.3.2  Recommendation	<p align="center">PROXIMATE TRAFFIC DISPLAY</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.3.2.1  Standard	<p><b>Recommendation.</b>— <i>While any RA and/or TA are displayed, proximate traffic within 11 km (6 NM) range and, if altitude reporting, ±370 m (1 200 ft) altitude should be displayed. This proximate traffic should be distinguished (e.g. by colour or symbol type) from threats and potential threats, which should be more prominently displayed.</i></p>	CARs, Part 121 Appendix B, B.11; CARs, Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.3.2.2  Standard	<b>Recommendation.</b> — <i>While any RA and/or TA are displayed, visual acquisition of the threats and/or potential threat should not be adversely affected by the display of proximate traffic or other data (e.g contents of received ADS-B messages) unrelated to collision avoidance.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.3.3  Standard	<i>TAs as RA precursors.</i> The criteria for TAs shall be such that they are satisfied before those for an RA.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.3.3.1  Standard	<i>TA warning time.</i> For intruders reporting altitude, the nominal TA warning time shall not be greater than (T+20 s) where T is the nominal warning time for the generation of the resolution advisory.  <i>Note.— Ideally, RAs would always be preceded by a TA but this is not always possible, e.g. the RA criteria might be already satisfied when a track is first established, or a sudden and sharp manoeuvre by the intruder could cause the TA lead time to be less than a cycle.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.4.1  Standard	<b>4.3.4 Threat detection</b>  <i>Declaration of threat.</i> ACAS shall evaluate appropriate characteristics of each intruder to determine whether or not it is a threat.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.4.1.1  Standard	<i>Intruder characteristics.</i> As a minimum, the characteristics of an intruder that are used to identify a threat shall include: a) tracked altitude; b) tracked rate of change of altitude; c) tracked slant range; d) tracked rate of change of slant range; and e) sensitivity level of intruder's ACAS, $S_i$ . For an intruder not equipped with ACAS II or ACAS III, $S_i$ shall be set to 1.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.4.1.2  Standard	<i>Own aircraft characteristics.</i> As a minimum, the characteristics of own aircraft that are used to identify a threat shall include: a) altitude; b) rate of change of altitude; and c) sensitivity level of own ACAS (4.3.4.3).	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.4.2  Standard	<i>Sensitivity levels.</i> ACAS shall be capable of operating at any of a number of sensitivity levels. These shall include: a) $S = 1$ , a "standby" mode in which the interrogation of other aircraft and all advisories are inhibited; b) $S = 2$ , a "TA only" mode in which RAs are inhibited; and c) $S = 3-7$ , further levels that enable the issue of RAs that provide the warning times indicated in Table 4-2 as well as TAs.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.4.3  Standard	<i>Selection of own sensitivity level (So).</i> The selection of own ACAS sensitivity level shall be determined by sensitivity level control (SLC) commands which shall be accepted from a number of sources as follows: a) SLC command generated automatically by ACAS based on altitude band or other external factors; b) SLC command from pilot input; and c) SLC command from Mode S ground stations.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.4.3.1  Standard	<i>Permitted SLC command codes.</i> As a minimum, the acceptable SLC command codes shall include:  <i>Coding</i>  for SLC based on altitude band 2-7 for SLC from pilot input 0,1,2 for SLC from Mode S ground stations 0,2-6	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.4.3.2  Standard	<i>Altitude-band SLC command.</i> Where ACAS selects an SLC command based on altitude, hysteresis shall be applied to the nominal altitude thresholds at which SLC command value changes are required as follows: for a climbing ACAS aircraft the SLC command shall be increased at the appropriate altitude threshold plus the hysteresis value; for a descending ACAS aircraft the SLC command shall be decreased at the appropriate altitude threshold minus the hysteresis value.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																	
Chapter 4 Reference 4.3.4.3.3  Standard	<p><i>Pilot SLC command.</i> For the SLC command set by the pilot the value 0 shall indicate the selection of the “automatic” mode for which the sensitivity level selection shall be based on the other commands.</p> <p style="text-align: center;"><b>Table 4-2</b></p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 20px;"><i>Sensitivity level</i></td> <td style="padding-right: 20px; text-align: center;">2</td> <td style="padding-right: 20px; text-align: center;">3</td> <td style="text-align: center;">4</td> </tr> <tr> <td></td> <td style="text-align: center;">5</td> <td style="text-align: center;">6</td> <td style="text-align: center;">7</td> </tr> </table> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 20px;">Nominal warning time</td> <td style="padding-right: 20px;">no RAs</td> <td style="text-align: center;">15s</td> </tr> <tr> <td></td> <td style="text-align: center;">20s</td> <td style="text-align: center;">25s</td> </tr> <tr> <td></td> <td style="text-align: center;">30s</td> <td style="text-align: center;">35s</td> </tr> </table>	<i>Sensitivity level</i>	2	3	4		5	6	7	Nominal warning time	no RAs	15s		20s	25s		30s	35s	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Sensitivity level</i>	2	3	4																			
	5	6	7																			
Nominal warning time	no RAs	15s																				
	20s	25s																				
	30s	35s																				
Chapter 4 Reference 4.3.4.3.4  Standard	<p><i>Mode S ground station SLC command.</i> For SLC commands transmitted via Mode S ground stations (4.3.8.4.2.1.1), the value 0 shall indicate that the station concerned is not issuing an SLC command and that sensitivity level selection shall be based on the other commands, including non-0 commands from other Mode S ground stations. ACAS shall not process an uplinked SLC value of 1.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																			
Chapter 4 Reference 4.3.4.3.4.1  Standard	<p><i>ATS selection of SLC command code.</i> ATS authorities shall ensure that procedures are in place to inform pilots of any ATS selected SLC command code other than 0 (4.3.4.3.1).</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																			
Chapter 4 Reference 4.3.4.3.5  Standard	<p><i>Selection rule.</i> Own ACAS sensitivity level shall be set to the smallest non-0 SLC command received from any of the sources listed in 4.3.4.3.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																			



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.4.4  Standard	<i>Selection of parameter values for RA generation.</i> When the sensitivity level of own ACAS is 3 or greater, the parameter values used for RA generation that depend on sensitivity level shall be based on the greater of the sensitivity level of own ACAS, $S_o$ , and the sensitivity level of the intruder's ACAS, $S_i$ .	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.4.5  Standard	<i>Selection of parameter values for TA generation.</i> The parameter values used for TA generation that depend on sensitivity level shall be selected on the same basis as those for RAs (4.3.4.4) except when an SLC command with a value of 2 ("TA only" mode) has been received from either the pilot or a Mode S ground station. In this case, the parameter values for TA generation shall retain the values they would have had in the absence of the SLC command from the pilot or Mode S ground station.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.1  Standard	<b>4.3.5 Resolution advisories (RAs)</b>  <i>RA generation.</i> For all threats, ACAS shall generate an RA except where it is not possible to select an RA that can be predicted to provide adequate separation either because of uncertainty in the diagnosis of the intruder's flight path or because there is a high risk that a manoeuvre by the threat will negate the RA.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.1.1  Standard	<i>Display of threats.</i> If threats are shown on a traffic display, they shall be displayed in red. <i>Note. — This colour is generally considered suitable for indicating a warning condition.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.5.1.2  Standard	<i>RA cancellation.</i> Once an RA has been generated against a threat or threats it shall be maintained or modified until tests that are less stringent than those for threat detection indicate on two consecutive cycles that the RA may be cancelled, at which time it shall be cancelled.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.2  Standard	<i>RA selection.</i> ACAS shall generate the RA that is predicted to provide adequate separation from all threats and that has the least effect on the current flight path of the ACAS aircraft consistent with the other provisions in this chapter.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.3  Standard	<i>RA effectiveness.</i> The RA shall not recommend or continue to recommend a manoeuvre or manoeuvre restriction that, considering the range of probable threat trajectories, is more likely to reduce separation than increase it, subject to the provisions in 4.3.5.5.1.1 and 4.3.5.6. <i>Note.— See also 4.3.5.8.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.5.3.1  Standard	New ACAS installations after 1 January 2014 shall monitor own aircraft's vertical rate to verify compliance with the RA sense. If non-compliance is detected, ACAS shall stop assuming compliance, and instead shall assume the observed vertical rate.  <i>N1.This overcomes the retention of an RA sense that would work only if followed. The revised vertical rate assumption is more likely to allow the logic to select the opposite sense when it is consistent with the non-complying aircraft's vertical rate.</i>  <i>N2.Equipment complying with RTCA/DO-185 or DO-185A standards (also known as TCAS Version 6.04A or TCAS Version 7.0) do not comply with this requirement.</i>  <i>N3.Compliance with this requirement can be achieved through the implementation of traffic alert and collision avoidance system (TCAS) Version 7.1 as specified in RTCA/DO-185B or EUROCAE/ED-143.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.5.3.2  Standard	<b>Recommendation.</b> — <i>All ACAS should be compliant with the requirement in 4.3.5.3.1.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.5.3.3  Standard	After 1 January 2017, all ACAS units shall comply with the requirements stated in 4.3.5.3.1.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.5.4  Standard	<i>Aircraft capability.</i> The RA generated by ACAS shall be consistent with the performance capability of the aircraft.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.4.1  Standard	<i>Proximity to the ground..</i> Descend RAs shall not be generated or maintained when own aircraft is below 300 m (1 000 ft) AGL.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.4.2  Standard	ACAS shall not operate in sensitivity levels 3-7 when own aircraft is below 300 m (1 000 ft) AGL.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.5  Standard	<i>Reversals of sense.</i> ACAS shall not reverse the sense of an RA from one cycle to the next, except as permitted in 4.3.5.5.1 to ensure coordination or when the predicted separation at closest approach for the existing sense is inadequate.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.5.5.1  Standard	<i>Sense reversals against equipped threats.</i> If an RAC received from an equipped threat is incompatible with the current RA sense, ACAS shall modify the RA sense to conform with the received RAC if own aircraft address is higher in value than that of the threat.  <i>Note.— 4.3.6.1.3 requires that the own ACAS RAC for the threat is also reversed.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.5.1.1  Standard	ACAS shall not modify an RA sense in a way that makes it incompatible with an RAC received from an equipped threat if own aircraft address is higher in value than that of the threat.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.6  Standard	<i>RA strength retention.</i> Subject to the requirement that a descend RA is not generated at low altitude (4.3.5.4.1), an RA shall not be modified if the time to closest approach is too short to achieve a significant response or if the threat is diverging in range.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.7  Standard	<i>Weakening an RA.</i> An RA shall not be weakened if it is likely that it would subsequently need to be strengthened.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.5.8  Standard	<p><i>ACAS-equipped threats.</i> The RA shall be compatible with all the RACs transmitted to threats (4.3.6.1.3). If an RAC is received from a threat before own ACAS generates an RAC for that threat, the RA generated shall be compatible with the RAC received unless such an RA is more likely to reduce separation than increase it and own aircraft address is lower in value than that of the threat.</p> <p><i>Note.— In encounters with more than one threat where it is necessary to pass above some threats and below other threats, this standard can be interpreted as referring to the whole duration of the RA. Specifically, it is permissible to retain an RA to climb (descend) towards a threat that is above (below) own aircraft provided there is a calculated intention to provide adequate separation from all threats by subsequently levelling-off.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.9  Standard	<p><i>Encoding of ARA subfield.</i> On each cycle of an RA, the RA sense, strength and attributes shall be encoded in the active RA (ARA) subfield (4.3.8.4.2.2.1.1). If the ARA subfield has not been refreshed for an interval of 6 s, it shall be set to 0, along with the MTE subfield in the same message (4.3.8.4.2.2.1.3).</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.5.10  Standard	<p><i>System response time.</i> The system delay from receipt of the relevant SSR reply to presentation of an RA sense and strength to the pilot shall be as short as possible and shall not exceed 1.5 s.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.6.1.1  Standard	<p align="center"><b>4.3.6 Coordination and communication</b></p> <p align="center">4.3.6.1 PROVISIONS FOR COORDINATION WITH ACAS-EQUIPPED THREATS</p> <p><i>Multi-aircraft coordination.</i> In a multi-aircraft situation, ACAS shall coordinate with each equipped threat individually.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.2  Standard	<i>Data protection during coordination.</i> ACAS shall prevent simultaneous access to stored data by concurrent processes, in particular, during resolution message processing.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.6.1.3  Standard	<p><i>Coordination interrogation.</i> Each cycle ACAS shall transmit a coordination interrogation to each equipped threat, unless generation of an RA is delayed because it is not possible to select an RA that can be predicted to provide adequate separation (4.3.5.1). The resolution message transmitted to a threat shall include an RAC selected for that threat. If an RAC has been received from the threat before ACAS selects an RAC for that threat, the selected RAC shall be compatible with the received RAC unless no more than three cycles have elapsed since the RAC was received, the RAC is altitude-crossing, and own aircraft address is lower in value than that of the threat in which case ACAS shall select its RA independently. If an RAC received from an equipped threat is incompatible with the RAC own ACAS has selected for that threat, ACAS shall modify the selected RAC to be compatible with the received RAC if own aircraft address is higher in value than that of the threat.</p> <p><i>Note.— The RAC included in the resolution message is in the form of a vertical RAC (VRC) for ACAS II (4.3.8.4.2.3.2.2) and a vertical RAC (VRC) and/or horizontal RAC (HRC) for ACAS III.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.3.1  Standard	<p><i>Coordination termination.</i> Within the cycle during which an intruder ceases to be a reason for maintaining the RA, ACAS shall send a resolution message to that intruder by means of a coordination interrogation. The resolution message shall include the cancellation code for the last RAC sent to that intruder while it was a reason for maintaining the RA.</p> <p><i>Note.— During an encounter with a single threat, the threat ceases to be a reason for the RA when the conditions for cancelling the RA are met. During an encounter with multiple threats, a threat ceases to be a reason for the RA when the conditions for cancelling the RA are met in respect of that threat, even though the RA may have to be maintained because of other threats.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.6.1.3.2  Standard	ACAS coordination interrogations shall be transmitted until a coordination reply is received from the threat, up to a maximum of not less than six and not more than twelve attempts. The successive interrogations shall be nominally equally spaced over a period of 100 ±5 ms. If the maximum number of attempts is made and no reply is received, ACAS shall continue its regular processing sequence.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.3.3  Standard	ACAS shall provide parity protection (4.3.8.4.2.3.2.6 and 4.3.8.4.2.3.2.7) for all fields in the coordination interrogation that convey RAC information. <i>Note.— This includes the vertical RAC (VRC), the cancel vertical RAC (CVC), the horizontal RAC (HRC) and the cancel horizontal RAC (CHC).</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.3.4  Standard	Whenever own ACAS reverses its sense against an equipped threat, the resolution message that is sent on the current and subsequent cycles to that threat shall contain both the newly selected RAC and the cancellation code for the RAC sent before the reversal.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.3.5  Standard	When a vertical RA is selected, the vertical RAC (VRC) (4.3.8.4.2.3.2.2) that own ACAS includes in a resolution message to the threat shall be as follows: a) “do not pass above” when the RA is intended to provide separation above the threat; b) “do not pass below” when the RA is intended to provide separation below the threat.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.6.1.4  Standard	<p><i>Resolution message processing.</i> Resolution messages shall be processed in the order in which they are received and with delay limited to that required to prevent possible concurrent access to stored data and delays due to the processing of previously received resolution messages. Resolution messages that are being delayed shall be temporarily queued to prevent possible loss of messages. Processing a resolution message shall include decoding the message and updating the appropriate data structures with the information extracted from the message.</p> <p><i>Note.— According to 4.3.6.1.2, resolution message processing must not access any data whose usage is not protected by the coordination lock state.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.4.1  Standard	An RAC or an RAC cancellation received from another ACAS shall be rejected if the encoded sense bits indicate the existence of a parity error or if undefined value(s) are detected in the resolution message. An RAC or an RAC cancellation received without parity errors and without undefined resolution message values shall be considered valid.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.4.2  Standard	<i>RAC storage.</i> A valid RAC received from another ACAS shall be stored or shall be used to update the previously stored RAC corresponding to that ACAS. A valid RAC cancellation shall cause the previously stored RAC to be deleted. A stored RAC that has not been updated for an interval of 6 s shall be deleted.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.1.4.3  Standard	<i>RAC record update.</i> A valid RAC or RAC cancellation received from another ACAS shall be used to update the RAC record. If a bit in the RAC record has not been refreshed for an interval of 6 s by any threat, that bit shall be set to 0.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.6.2.1  Standard	<p>4.3.6.2 PROVISIONS FOR ACAS COMMUNICATION WITH GROUND STATIONS</p> <p><i>Air-initiated downlink of ACAS RAs.</i> When an ACAS RA exists, ACAS shall:</p> <ul style="list-style-type: none"> <li>a) transfer to its Mode S transponder an RA report for transmission to the ground in a Comm-B reply (4.3.11.4.1); and</li> <li>b) transmit periodic RA broadcasts (4.3.7.3.2).</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.2.2  Standard	<p><i>Sensitivity level control (SLC) command.</i> ACAS shall store SLC commands from Mode S ground stations. An SLC command received from a Mode S ground station shall remain effective until replaced by an SLC command from the same ground station as indicated by the site number contained in the IIS subfield of the interrogation. If an existing stored command from a Mode S ground station is not refreshed within 4 minutes, or if the SLC command received has the value 15 (4.3.8.4.2.1.1), the stored SLC command for that Mode S ground station shall be set to 0.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.6.3.1  Standard	<p>4.3.6.3 PROVISIONS FOR DATA TRANSFER BETWEEN ACAS AND ITS MODE S TRANSPONDER</p> <p><i>Data transfer from ACAS to its Mode S transponder:</i></p> <ul style="list-style-type: none"> <li>a) ACAS shall transfer RA information to its Mode S transponder for transmission in an RA report (4.3.8.4.2.2.1) and in a coordination reply (4.3.8.4.2.4.2);</li> <li>b) ACAS shall transfer current sensitivity level to its Mode S transponder for transmission in a sensitivity level report (4.3.8.4.2.5); and</li> <li>c) ACAS shall transfer capability information to its Mode S transponder for transmission in a data link capability report (4.3.8.4.2.2.2).</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.6.3.2  Standard	<p><i>Data transfer from Mode S transponder to its ACAS:</i></p> <ul style="list-style-type: none"> <li>a) ACAS shall receive from its Mode S transponder sensitivity level control commands (4.3.8.4.2.1.1) transmitted by Mode S ground stations;</li> <li>b) ACAS shall receive from its Mode S transponder ACAS broadcast messages (4.3.8.4.2.3.3) transmitted by other ACAS; and</li> <li>c) ACAS shall receive from its Mode S transponder resolution messages (4.3.8.4.2.3.2) transmitted by other ACAS for air-air coordination purposes.</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.7.1.1.1  Standard	<p align="center"><b>4.3.7 ACAS protocols</b></p> <p align="center">4.3.7.1 SURVEILLANCE PROTOCOLS</p> <p><i>4.3.7.1.1 Surveillance of Mode A/C transponders.</i></p> <p>ACAS shall use the Mode C-only all-call interrogation (Chapter 3, 3.1.2.1.5.1.2) for surveillance of aircraft equipped with Mode A/C transponders.</p>	CARs, Part 121 Appendix B, B.11; CARs, Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.7.1.1.2  Standard	Using a sequence of interrogations with increasing power, surveillance interrogations shall be preceded by an S <sub>1</sub> -pulse (Chapter 3,3.1.1.7.4.3) to reduce interference and improve Mode A/C target detection.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.7.1.2.1  Standard	<p><i>4.3.7.1.2 SURVEILLANCE OF MODE S TRANSPONDERS</i></p> <p><i>Detection.</i> ACAS shall monitor 1 090 MHz for Mode S acquisition squitters (DF = 11). ACAS shall detect the presence and determine the address of Mode S-equipped aircraft using their Mode S acquisition squitters (DF = 11) or extended squitters (DF = 17).</p> <p><i>N1.</i> It is acceptable to acquire individual aircraft using either acquisition or extended squitters (DF = 11 or DF = 17), and to monitor for both squitters. However, ACAS must monitor for acquisition squitters because, at any time, not all aircraft will transmit the extended squitter.</p> <p><i>N2.</i> If, in the future, it becomes permitted for aircraft not to transmit the acquisition squitter, relying instead on continual transmission of the extended squitter, it would become essential for all ACAS units to monitor for both the acquisition and the extended squitters.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference 4.3.7.1.2.2</p> <p><b>Standard</b></p>	<p><i>Surveillance interrogations.</i> On first receipt of a 24-bit aircraft address from an aircraft that is determined to be within the reliable surveillance range of ACAS based on reception reliability and that is within an altitude band 3 050 m (10 000 ft) above and below own aircraft, ACAS shall transmit a short air-air interrogation (UF = 0) for range acquisition. Surveillance interrogations shall be transmitted at least once every five cycles when this altitude condition is satisfied. Surveillance interrogations shall be transmitted each cycle if the range of the detected aircraft is less than 5.6 km (3 NM) or the calculated time to closest approach is less than 60 s, assuming that both the detected and own aircraft proceed from their current positions with unaccelerated motion and that the range at closest approach equals 5.6 km (3 NM). Surveillance interrogations shall be suspended for a period of five cycles if:</p> <ul style="list-style-type: none"> <li>a) a reply was successfully received; and</li> <li>b) own aircraft and intruder aircraft are operating below a pressure-altitude of 5 490 m (18 000 ft); and</li> <li>c) the range of the detected aircraft is greater than 5.6 km (3 NM) and the calculated time to closest approach exceeds 60 seconds, assuming that both the detected and own aircraft proceed from their current positions with unaccelerated motion and that the range at closest approach equals 5.6 km (3 NM).</li> </ul>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.7.1.2.2.1  Standard	<p><i>Range acquisition interrogations.</i> ACAS shall use the short air-air surveillance format (UF = 0) for range acquisition. ACAS shall set AQ = 1 (Chapter 3, 3.1.2.8.1.1) and RL = 0 (Chapter 3, 3.1.2.8.1.2) in an acquisition interrogation.</p> <p>N1. <i>Setting AQ = 1 results in a reply with bit 14 of the RI field equal to 1 and serves as an aid in distinguishing the reply to own interrogation from replies elicited from other ACAS units (4.3.7.1.2.2.2).</i></p> <p>N2. <i>In the acquisition interrogation RL is set to 0 to command a short acquisition reply (DF = 0).</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.7.1.2.2.2  Standard	<p><i>Tracking interrogations.</i> ACAS shall use the short air-air surveillance format (UF = 0) with RL = 0 and AQ = 0 for tracking interrogations.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.7.1.2.3  Standard	<p><i>Surveillance replies.</i> These protocols are described in 4.3.11.3.1.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.7.1.2.4  Standard	<p><i>ACAS broadcast.</i> An ACAS broadcast shall be made nominally every 8 to 10 s at full power from the top antenna. Installations using directional antennas shall operate such that complete circular coverage is provided nominally every 8 to 10 s.</p> <p><i>Note.— A broadcast causes other Mode S transponders to accept the interrogation without replying and to present the interrogation content containing the MU field at the transponder output data interface. The UDS1 = 3, UDS2 = 2 combination identifies the data as an ACAS broadcast containing the 24-bit address of the interrogating ACAS aircraft. This provides each ACAS with a means of determining the number of other ACAS within its detection range for limiting interference. The format of the MU field is described in 4.3.8.4.2.3.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.7.2.1  Standard	<p>4.3.7.2 AIR-AIR COORDINATION PROTOCOLS</p> <p><i>Coordination interrogations.</i> ACAS shall transmit UF = 16 interrogations (Chapter 3, 3.1.2.3.2, Figure 3-7) with AQ = 0 and RL = 1 when another aircraft reporting RI = 3 or 4 is declared a threat (4.3.4). The MU field shall contain the resolution message in the subfields specified in 4.3.8.4.2.3.2.</p> <p><i>N1.A UF = 16 interrogation with AQ = 0 and RL = 1 is intended to cause a DF = 16 reply from the other aircraft.</i></p> <p><i>N2.An aircraft reporting RI = 3 or RI = 4 is an aircraft equipped with an operating ACAS which has vertical only or vertical and horizontal resolution capability, respectively.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.7.2.2  Standard	<i>Coordination reply.</i> These protocols are described in 4.3.11.3.2.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.7.3.1  Standard	4.3.7.3 PROTOCOLS FOR ACAS COMMUNICATION WITH GROUND STATIONS  <i>RA reports to Mode S ground stations.</i> These protocols are described in 4.3.11.4.1.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.7.3.2  Standard	<i>RA broadcasts.</i> RA broadcasts shall be transmitted at full power from the bottom antenna at jittered, nominally 8 s intervals for the period that the RA is indicated. The RA broadcast shall include the MU field as specified in 4.3.8.4.2.3.4. The RA broadcast shall describe the most recent RA that existed during the preceding 8 s period. Installations using directional antennas shall operate such that complete circular coverage is provided nominally every 8 s and the same RA sense and strength is broadcast in each direction.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.7.3.3  Standard	<i>Data link capability report.</i> These protocols are described in 4.3.11.4.2.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.7.3.4  Standard	<i>ACAS sensitivity level control.</i> ACAS shall act upon an SLC command if and only if TMS (Chapter 3, 3.1.2.6.1.4.1) has the value 0 and DI is either 1 or 7 in the same interrogation.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.1  Standard	<b>4.3.8 Signal formats</b>  The RF characteristics of all ACAS signals shall conform to the Standards of Chapter 3, 3.1.1.1 through 3.1.1.6, 3.1.2.1 through 3.1.2.3, 3.1.2.5 and 3.1.2.8.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.2  Note	RELATIONSHIP BETWEEN ACAS AND MODE S SIGNAL FORMATS  <i>Note.— ACAS uses Mode S transmissions for surveillance and communications. ACAS air-air communication functions permit RA decisions to be coordinated with ACAS-equipped threats. ACAS air-ground communication functions permit the reporting of RAs to ground stations and the uplinking of commands to ACAS-equipped aircraft to control parameters of the collision avoidance algorithms.</i>		Not Applicable		Compliance data not required for Notes.
Chapter 4 Reference 4.3.8.3  Standard	<i>Signal format conventions.</i> The data encoding of all ACAS signals shall conform to the Standards of Chapter 3, 3.1.2.3. <i>Note.— In air-air transmissions used by ACAS, interrogations transmitted at 1 030 MHz are designated as uplink transmissions and contain uplink format (UF) codes. Replies received at 1 090 MHz are designated as downlink transmissions and contain downlink format (DF) codes.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 4  Reference 4.3.8.4.1.1  Standard	<p style="text-align: center;">4.3.8.4 FIELD DESCRIPTION</p> <p><i>N1.Note.— The air-air surveillance and communication formats which are used by ACAS but not fully described in Chapter 3, 3.1.2 are given in Figure 4-1.</i></p> <p style="text-align: center;"><b>Figure 4-1. Surveillance and communication formats used by ACAS</b></p> <p><i>N2.This section defines the Mode S fields (and their subfields) that are processed by ACAS to accomplish ACAS functions. Some of the ACAS fields (those also used for other SSR Mode S functions) are described with unassigned ACAS codes in Chapter 3, 3.1.2.6. Such codes are assigned in 4.3.8.4.1. Fields and subfields used only by ACAS equipment are assigned in 4.3.8.4.2.</i></p> <p><i>N3.The bit numbering convention used in 4.3.8.4 reflects the bit numbering within the entire uplink or downlink format rather than the bits within individual fields or subfields.</i></p> <p><i>4.3.8.4.1 FIELDS AND SUBFIELDS INTRODUCED IN CHAPTER 3, 3.1.2</i></p> <p><i>Note.— Codes for mission fields and subfields that are designated “reserved for ACAS” in Chapter 3, 3.1.2, are specified in this section.</i></p> <p><i>DR (downlink request). The significance of the coding of the downlink request field shall be as follows:</i></p> <p style="margin-left: 40px;"><i>Coding</i></p> <table style="margin-left: 40px; border: none;"> <tr> <td style="padding-right: 20px;">0-1</td> <td>See Chapter 3, 3.1.2.6.5.2</td> </tr> <tr> <td>2</td> <td>ACAS message available</td> </tr> <tr> <td>3</td> <td>Comm-B message available and ACAS message available</td> </tr> <tr> <td>4-5</td> <td>See Chapter 3, 3.1.2.6.5.2</td> </tr> <tr> <td>6</td> <td>Comm-B broadcast message 1</td> </tr> </table>	0-1	See Chapter 3, 3.1.2.6.5.2	2	ACAS message available	3	Comm-B message available and ACAS message available	4-5	See Chapter 3, 3.1.2.6.5.2	6	Comm-B broadcast message 1	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
0-1	See Chapter 3, 3.1.2.6.5.2														
2	ACAS message available														
3	Comm-B message available and ACAS message available														
4-5	See Chapter 3, 3.1.2.6.5.2														
6	Comm-B broadcast message 1														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	available and ACAS message available 7 Comm-B broadcast message 2 available and ACAS message available 8-31 See Chapter 3, 3.1.2.6.5.2				
Chapter 4 Reference 4.3.8.4.1.2  Standard	<p><i>RI (air-air reply information)</i>. The significance of the coding in the RI field shall be as follows:</p> <p><i>Coding</i></p> <p>0 No operating ACAS</p> <p>1 Not assigned</p> <p>2 ACAS with resolution capability inhibited</p> <p>3 ACAS with vertical-only resolution capability</p> <p>4 ACAS with vertical and horizontal resolution capability</p> <p>5-7 Not assigned</p> <p>8-15 See Chapter 3, 3.1.2.8.2.2</p> <p>Bit 14 of the reply format containing this field shall replicate the AQ bit of the interrogation. The RI field shall report “no operating ACAS” (RI = 0) if the ACAS unit has failed or is in standby. The RI field shall report “ACAS with resolution capability inhibited” (RI = 2) if sensitivity level is 2 or TA only mode has been selected.</p> <p><i>Note.— Codes 0-7 in the RI field indicate that the reply is a tracking reply and also give the ACAS capability of the interrogated aircraft. Codes 8-15 indicate that the reply is an acquisition reply and also give the maximum true airspeed capability of the interrogated aircraft.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference								
Chapter 4 Reference 4.3.8.4.1.3  Standard	<p><i>RR (reply request).</i> The significance of the coding in the reply request field shall be as follows:</p> <p style="padding-left: 40px;"><i>Coding</i></p> <table style="margin-left: 40px; border: none;"> <tr> <td style="padding-right: 20px;">0-18</td> <td>See Chapter 3, 3.1.2.6.1.2</td> </tr> <tr> <td>19</td> <td>Transmit a resolution advisory report</td> </tr> <tr> <td colspan="2"> </td> </tr> <tr> <td>20-31</td> <td>See Chapter 3, 3.1.2.6.1.2</td> </tr> </table>	0-18	See Chapter 3, 3.1.2.6.1.2	19	Transmit a resolution advisory report			20-31	See Chapter 3, 3.1.2.6.1.2	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
0-18	See Chapter 3, 3.1.2.6.1.2												
19	Transmit a resolution advisory report												
20-31	See Chapter 3, 3.1.2.6.1.2												
Chapter 4 Reference 4.3.8.4.2.1.1  Standard	<p><i>4.3.8.4.2 ACAS FIELDS AND SUBFIELDS</i></p> <p><i>Note.— The following paragraphs describe the location and coding of those fields and subfields that are not defined in Chapter 3, 3.1.2 but are used by aircraft equipped with ACAS.</i></p> <p><i>4.3.8.4.2.1 Subfield in MA</i></p> <p><i>ADS (A-definition subfield).</i> This 8-bit (33-40) subfield shall define the remainder of MA.</p> <p><i>Note.— For convenience of coding, ADS is expressed in two groups of four bits each, ADS1 and ADS2.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference										
Chapter 4 Reference 4.3.8.4.2.1.2  Standard	When ADS1 = 0 and ADS2 = 5, the following subfield shall be contained in MA:	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																														
<p>Chapter 4 Reference 4.3.8.4.2.1.3</p> <p><b>Standard</b></p>	<p><i>SLC (ACAS sensitivity level control (SLC) command).</i> This 4-bit (41-44) subfield shall denote a sensitivity level command for own ACAS.</p> <p><i>Coding</i></p> <table border="0"> <tr><td>0</td><td>No command issued</td></tr> <tr><td>1</td><td>Not assigned</td></tr> <tr><td>2</td><td>Set ACAS sensitivity level to 2</td></tr> <tr><td>3</td><td>Set ACAS sensitivity level to 3</td></tr> <tr><td>4</td><td>Set ACAS sensitivity level to 4</td></tr> <tr><td>5</td><td>Set ACAS sensitivity level to 5</td></tr> <tr><td>6</td><td>Set ACAS sensitivity level to 6</td></tr> <tr><td>7-14</td><td>Not assigned</td></tr> <tr><td>15</td><td>Cancel previous SLC command from this ground station</td></tr> </table> <p><i>Note.— Structure of MA for a sensitivity level control command:</i></p> <table border="0"> <tr><td>33</td><td>37</td><td>41 45</td></tr> <tr><td>ADS1 = 0</td><td>ADS2 = 5</td><td>SLC</td></tr> <tr><td>---- 44 ----</td><td></td><td></td></tr> <tr><td>36</td><td>40</td><td>44 88</td></tr> </table>	0	No command issued	1	Not assigned	2	Set ACAS sensitivity level to 2	3	Set ACAS sensitivity level to 3	4	Set ACAS sensitivity level to 4	5	Set ACAS sensitivity level to 5	6	Set ACAS sensitivity level to 6	7-14	Not assigned	15	Cancel previous SLC command from this ground station	33	37	41 45	ADS1 = 0	ADS2 = 5	SLC	---- 44 ----			36	40	44 88	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
0	No command issued																																		
1	Not assigned																																		
2	Set ACAS sensitivity level to 2																																		
3	Set ACAS sensitivity level to 3																																		
4	Set ACAS sensitivity level to 4																																		
5	Set ACAS sensitivity level to 5																																		
6	Set ACAS sensitivity level to 6																																		
7-14	Not assigned																																		
15	Cancel previous SLC command from this ground station																																		
33	37	41 45																																	
ADS1 = 0	ADS2 = 5	SLC																																	
---- 44 ----																																			
36	40	44 88																																	
<p>Chapter 4 Reference 4.3.8.4.2.2.1</p> <p><b>Standard</b></p>	<p><i>4.3.8.4.2.2 Subfields in MB</i></p> <p><i>Subfields in MB for an RA report.</i> When BDS1=3 and BDS2=0, the subfields indicated below shall be contained in MB.</p> <p><i>Note.— The requirements for communication of information relating to the current or recent RAs is described in 4.3.11.4.1.</i></p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>																																





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																	
Chapter 4  Reference 4.3.8.4.2.2.1.1  Standard	<p><i>ARA (active RAs)</i>. This 14-bit (41-54) subfield shall indicate the characteristics of the RA, if any, generated by the ACAS associated with the transponder transmitting the subfield (4.3.6.2.1 a)). The bits in ARA shall have meanings determined by the value of the MTE subfield (4.3.8.4.2.2.1.4) and, for vertical RAs, the value of bit 41 of ARA. The meaning of bit 41 of ARA shall be as follows:</p> <p><i>Coding</i></p> <p>0            There is more than one threat and the RA is intended to provide separation below some threat(s) and above some other threat(s) or no RA has been generated (when MTE = 0)</p> <p>1            Either there is only one threat or the RA is intended to provide separation in the same direction for all threats</p> <p>When ARA bit 41 = 1 and MTE = 0 or 1, bits 42-47 shall have the following meanings:</p> <table border="0" data-bbox="373 927 911 1490"> <thead> <tr> <th><i>Bit</i></th> <th><i>Coding</i></th> <th></th> </tr> </thead> <tbody> <tr> <td>42</td> <td>0</td> <td>RA is preventive</td> </tr> <tr> <td></td> <td>1</td> <td>RA is corrective</td> </tr> <tr> <td>43</td> <td>0</td> <td>Upward sense RA has been generated</td> </tr> <tr> <td></td> <td>1</td> <td>Downward sense RA has been generated</td> </tr> <tr> <td>44</td> <td>0</td> <td>RA is not increased rate</td> </tr> <tr> <td></td> <td>1</td> <td>RA is increased rate</td> </tr> <tr> <td>45</td> <td>0</td> <td>RA is not a sense reversal</td> </tr> <tr> <td></td> <td>1</td> <td>RA is a sense reversal</td> </tr> <tr> <td>46</td> <td>0</td> <td>RA is not altitude crossing</td> </tr> <tr> <td></td> <td>1</td> <td>RA is altitude crossing</td> </tr> </tbody> </table>	<i>Bit</i>	<i>Coding</i>		42	0	RA is preventive		1	RA is corrective	43	0	Upward sense RA has been generated		1	Downward sense RA has been generated	44	0	RA is not increased rate		1	RA is increased rate	45	0	RA is not a sense reversal		1	RA is a sense reversal	46	0	RA is not altitude crossing		1	RA is altitude crossing	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Bit</i>	<i>Coding</i>																																					
42	0	RA is preventive																																				
	1	RA is corrective																																				
43	0	Upward sense RA has been generated																																				
	1	Downward sense RA has been generated																																				
44	0	RA is not increased rate																																				
	1	RA is increased rate																																				
45	0	RA is not a sense reversal																																				
	1	RA is a sense reversal																																				
46	0	RA is not altitude crossing																																				
	1	RA is altitude crossing																																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																									
	<p>47            0            RA is vertical speed limit</p> <p>                 1            RA is positive</p> <p>48-54        Reserved for ACAS III</p> <p>When ARA bit 41 = 0 and MTE = 1, bits 42-47 shall have the following meanings:</p> <table border="0"> <tr> <td style="padding-right: 20px;"><i>Bit</i></td> <td style="padding-right: 20px;"><i>Coding</i></td> <td></td> </tr> <tr> <td>42</td> <td>0</td> <td>RA does not require a correction in the upward sense</td> </tr> <tr> <td></td> <td>1</td> <td>RA requires a correction in the upward sense</td> </tr> <tr> <td>43</td> <td>0</td> <td>RA does not require a positive climb</td> </tr> <tr> <td></td> <td>1</td> <td>RA requires a positive climb</td> </tr> <tr> <td>44</td> <td>0</td> <td>RA does not require a correction in the downward sense</td> </tr> <tr> <td></td> <td>1</td> <td>RA requires a correction in the downward sense</td> </tr> <tr> <td>45</td> <td>0</td> <td>RA does not require a positive descend</td> </tr> <tr> <td></td> <td>1</td> <td>RA requires a positive descend</td> </tr> <tr> <td>46</td> <td>0</td> <td>RA does not require a crossing</td> </tr> <tr> <td></td> <td>1</td> <td>RA requires a crossing</td> </tr> <tr> <td>47</td> <td>0</td> <td>RA is not a sense</td> </tr> <tr> <td>reversal</td> <td>1</td> <td>RA is a senses reversal</td> </tr> <tr> <td>48-54</td> <td></td> <td>Reserved for ACAS III</td> </tr> </table>	<i>Bit</i>	<i>Coding</i>		42	0	RA does not require a correction in the upward sense		1	RA requires a correction in the upward sense	43	0	RA does not require a positive climb		1	RA requires a positive climb	44	0	RA does not require a correction in the downward sense		1	RA requires a correction in the downward sense	45	0	RA does not require a positive descend		1	RA requires a positive descend	46	0	RA does not require a crossing		1	RA requires a crossing	47	0	RA is not a sense	reversal	1	RA is a senses reversal	48-54		Reserved for ACAS III			
<i>Bit</i>	<i>Coding</i>																																													
42	0	RA does not require a correction in the upward sense																																												
	1	RA requires a correction in the upward sense																																												
43	0	RA does not require a positive climb																																												
	1	RA requires a positive climb																																												
44	0	RA does not require a correction in the downward sense																																												
	1	RA requires a correction in the downward sense																																												
45	0	RA does not require a positive descend																																												
	1	RA requires a positive descend																																												
46	0	RA does not require a crossing																																												
	1	RA requires a crossing																																												
47	0	RA is not a sense																																												
reversal	1	RA is a senses reversal																																												
48-54		Reserved for ACAS III																																												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
	<p><i>Note.— When ARA bit 41 = 0 and MTE = 0, no vertical RA has been generated.</i></p>														
<p>Chapter 4 Reference 4.3.8.4.2.2.1.2  Standard</p>	<p><i>RAC (RACs record).</i> This 4-bit (55-58) subfield shall indicate all the currently active RACs, if any, received from other ACAS aircraft. The bits in RAC shall have the following meanings:</p> <table data-bbox="373 630 829 792"> <tr> <td><i>Bit</i></td> <td><i>Resolution advisory complement</i></td> </tr> <tr> <td>55</td> <td>Do not pass below</td> </tr> <tr> <td>56</td> <td>Do not pass above</td> </tr> <tr> <td>57</td> <td>Do not turn left</td> </tr> <tr> <td>58</td> <td>Do not turn right</td> </tr> </table> <p>A bit set to 1 shall indicate that the associated RAC is active. A bit set to 0 shall indicate that the associated RAC is inactive.</p>	<i>Bit</i>	<i>Resolution advisory complement</i>	55	Do not pass below	56	Do not pass above	57	Do not turn left	58	Do not turn right	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<i>Bit</i>	<i>Resolution advisory complement</i>														
55	Do not pass below														
56	Do not pass above														
57	Do not turn left														
58	Do not turn right														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference 4.3.8.4.2.2.1.3</p> <p>Standard</p>	<p><i>RAT (RA terminated indicator).</i> This 1-bit (59) subfield shall indicate when an RA previously generated by ACAS has ceased being generated.</p> <p><i>Coding</i></p> <p>0 ACAS is currently generating the RA indicated in the ARA subfield</p> <p>1 The RA indicated by the ARA subfield has been terminated (4.3.11.4.1)</p> <p><i>N1.</i>After an RA has been terminated by ACAS, it is still required to be reported by the Mode S transponder for 18±1 s (4.3.11.4.1). The RA terminated indicator may be used, for example, to permit timely removal of an RA indication from an air traffic controller's display, or for assessments of RA duration within a particular airspace.</p> <p><i>N2.</i>RAs may terminate for a number of reasons: normally, when the conflict has been resolved and the threat is diverging in range; or when the threat's Mode S transponder for some reason ceases to report altitude during the conflict. The RA terminated indicator is used to show that the RA has been removed in each of these cases.</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference 4.3.8.4.2.2.1.4</p> <p>Standard</p>	<p><i>MTE (multiple threat encounter).</i> This 1-bit (60) subfield shall indicate whether two or more simultaneous threats are currently being processed by the ACAS threat resolution logic.</p> <p><i>Coding</i></p> <p>0 One threat is being processed by the resolution logic (when ARA bit 41 = 1); or no threat is being processed by the resolution logic (when ARA bit 41 = 0)</p> <p>1 Two or more simultaneous threats are being processed by the resolution logic</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.8.4.2.2.1.5  Standard	<p><i>TTI (threat type indicator subfield)</i>. This 2-bit subfield (61-62) shall define the type of identity data contained in the TID subfield.</p> <p><i>Coding</i></p> <p>0 No identity data in TID</p> <p>1 TID contains a Mode S transponder address</p> <p>2 TID contains altitude, range and bearing data</p> <p>3 Not assigned</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.2.1.6  Standard	<p><i>TID (threat identity data subfield)</i>. This 26-bit subfield (63-88) shall contain the Mode S address of the threat or the altitude, range, and bearing if the threat is not Mode S equipped. If two or more threats are simultaneously processed by the ACAS resolution logic, TID shall contain the identity or position data for the most recently declared threat. If TTI = 1, TID shall contain in bits 63-86 the aircraft address of the threat, and bits 87 and 88 shall be set to 0. If TTI = 2, TID shall contain the following three subfields.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																
Chapter 4 Reference 4.3.8.4.2.2.1.6.1  Standard	<p><i>TIDA (threat identity data altitude subfield)</i>. This 13-bit subfield (63-75) shall contain the most recently reported Mode C altitude code of the threat.</p> <p><i>Coding</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;"></td> <td style="width: 10%;">Bit</td> <td style="width: 10%;">63</td> <td style="width: 10%;">64</td> <td style="width: 10%;">65</td> <td style="width: 10%;">66</td> <td style="width: 10%;">67</td> <td style="width: 10%;">68</td> </tr> <tr> <td></td> <td></td> <td>69</td> <td>70</td> <td>71</td> <td>72</td> <td>73</td> <td>74</td> </tr> <tr> <td></td> <td></td> <td>75</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>Mode C code bit</td> <td>C1</td> <td>A1</td> <td>C2</td> <td>A2</td> <td>C4</td> <td>A4</td> </tr> <tr> <td></td> <td></td> <td>0</td> <td>B1</td> <td>D1</td> <td>B2</td> <td>D2</td> <td>B4</td> </tr> <tr> <td></td> <td></td> <td>D4</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>		Bit	63	64	65	66	67	68			69	70	71	72	73	74			75							Mode C code bit	C1	A1	C2	A2	C4	A4			0	B1	D1	B2	D2	B4			D4						CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
	Bit	63	64	65	66	67	68																																														
		69	70	71	72	73	74																																														
		75																																																			
	Mode C code bit	C1	A1	C2	A2	C4	A4																																														
		0	B1	D1	B2	D2	B4																																														
		D4																																																			
Chapter 4 Reference 4.3.8.4.2.2.1.6.2  Standard	<p><i>TIDR (threat identity data range subfield)</i>. This 7-bit subfield (76-82) shall contain the most recent threat range estimated by ACAS.</p> <p><i>Coding (n)</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;"></td> <td style="width: 10%;"><i>n</i></td> <td style="width: 80%;"><i>Estimated range (NM)</i></td> </tr> <tr> <td></td> <td>0</td> <td>No range estimate available</td> </tr> <tr> <td></td> <td>1</td> <td>Less than 0.05</td> </tr> <tr> <td></td> <td>2-126</td> <td><math>(n-1)/10 \pm 0.05</math></td> </tr> <tr> <td></td> <td>127</td> <td>Greater than 12.55</td> </tr> </table>		<i>n</i>	<i>Estimated range (NM)</i>		0	No range estimate available		1	Less than 0.05		2-126	$(n-1)/10 \pm 0.05$		127	Greater than 12.55	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																																			
	<i>n</i>	<i>Estimated range (NM)</i>																																																			
	0	No range estimate available																																																			
	1	Less than 0.05																																																			
	2-126	$(n-1)/10 \pm 0.05$																																																			
	127	Greater than 12.55																																																			



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																
Chapter 4 Reference 4.3.8.4.2.2.1.6.3  Standard	<p><i>TIDB (threat identity data bearing subfield)</i>. This 6-bit subfield (83-88) shall contain the most recent estimated bearing of the threat aircraft, relative to the ACAS aircraft heading.</p> <p><i>Coding (n)</i></p> <table border="0"> <tr> <td><i>n</i></td> <td><i>Estimated bearing (degrees)</i></td> </tr> <tr> <td>0</td> <td>No bearing estimate available</td> </tr> <tr> <td>1-60</td> <td>Between 6(n-1) and 6n</td> </tr> <tr> <td>61-63</td> <td>Not assigned</td> </tr> </table> <p><i>Note.— Structure of MB for an RA report:</i></p> <table border="0"> <tr> <td>33</td> <td>37</td> <td>41</td> <td>55</td> <td>59</td> <td></td> </tr> <tr> <td></td> <td>60</td> <td>61</td> <td>63</td> <td></td> <td></td> </tr> <tr> <td>BDS1=3</td> <td>BDS2=0</td> <td>ARA</td> <td>RAC</td> <td>RAT</td> <td>MTE TTI=1 TID</td> </tr> <tr> <td>36</td> <td>40</td> <td>54</td> <td>58</td> <td>88</td> <td>59</td> </tr> <tr> <td></td> <td>60</td> <td>62</td> <td></td> <td></td> <td></td> </tr> <tr> <td>33</td> <td>37</td> <td>41</td> <td>55</td> <td>59</td> <td></td> </tr> <tr> <td></td> <td>60</td> <td>61</td> <td>63</td> <td>76</td> <td></td> </tr> <tr> <td></td> <td>83</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>BDS1=3</td> <td>BDS2=0</td> <td>ARA</td> <td>RAC</td> <td>RAT</td> <td>MTE TTI=2 TIDA TIDR TIDB</td> </tr> <tr> <td>36</td> <td>40</td> <td>54</td> <td>58</td> <td>82</td> <td>59</td> </tr> <tr> <td></td> <td>60</td> <td>62</td> <td>75</td> <td></td> <td></td> </tr> <tr> <td></td> <td>88</td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	<i>n</i>	<i>Estimated bearing (degrees)</i>	0	No bearing estimate available	1-60	Between 6(n-1) and 6n	61-63	Not assigned	33	37	41	55	59			60	61	63			BDS1=3	BDS2=0	ARA	RAC	RAT	MTE TTI=1 TID	36	40	54	58	88	59		60	62				33	37	41	55	59			60	61	63	76			83					BDS1=3	BDS2=0	ARA	RAC	RAT	MTE TTI=2 TIDA TIDR TIDB	36	40	54	58	82	59		60	62	75				88					CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>n</i>	<i>Estimated bearing (degrees)</i>																																																																																				
0	No bearing estimate available																																																																																				
1-60	Between 6(n-1) and 6n																																																																																				
61-63	Not assigned																																																																																				
33	37	41	55	59																																																																																	
	60	61	63																																																																																		
BDS1=3	BDS2=0	ARA	RAC	RAT	MTE TTI=1 TID																																																																																
36	40	54	58	88	59																																																																																
	60	62																																																																																			
33	37	41	55	59																																																																																	
	60	61	63	76																																																																																	
	83																																																																																				
BDS1=3	BDS2=0	ARA	RAC	RAT	MTE TTI=2 TIDA TIDR TIDB																																																																																
36	40	54	58	82	59																																																																																
	60	62	75																																																																																		
	88																																																																																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																				
<p>Chapter 4 Reference 4.3.8.4.2.2.2</p> <p>Standard</p>	<p><i>Subfields in MB for the data link capability report. When BDS1 = 1 and BDS2 = 0, the following bit patterns shall be provided to the transponder for its data link capability report:</i></p> <table border="0"> <tr> <td><i>Bit</i></td> <td><i>Coding</i></td> <td></td> </tr> <tr> <td>48</td> <td>0 ACAS failed or on standby</td> <td></td> </tr> <tr> <td></td> <td>1 ACAS operating</td> <td></td> </tr> <tr> <td>69</td> <td>0 Hybrid surveillance not operational</td> <td></td> </tr> <tr> <td></td> <td>1 Hybrid surveillance fitted and operational</td> <td></td> </tr> <tr> <td>70</td> <td>0 ACAS generating TAs only</td> <td></td> </tr> <tr> <td></td> <td>1 ACAS generating TAs and RAs</td> <td></td> </tr> <tr> <td>Bit 72</td> <td>Bit 71</td> <td>ACAS version</td> </tr> <tr> <td>0</td> <td>0</td> <td>RTCA/DO-185 (pre ACAS)</td> </tr> <tr> <td>0</td> <td>1</td> <td>RTCA/DO-185A</td> </tr> <tr> <td>1</td> <td>0</td> <td>RTCA/DO-185B &amp; EUROCAE ED 143</td> </tr> <tr> <td>1</td> <td>1</td> <td>Reserved for future versions (see Note 3)</td> </tr> </table> <p><b>N1.</b> <i>A summary of the MB subfields for the data link capability report structure is described in Chapter 3, 3.1.2.6.10.2.2.</i></p> <p><b>N2.</b> <i>The use of hybrid surveillance to limit ACAS active interrogations is described in 4.5.1. The ability only to support decoding of DF = 17 extended squitter messages is not sufficient to set bit 72.</i></p> <p><b>N3.</b> <i>Future versions of ACAS will be identified using part numbers and software version numbers specified in registers E5<sub>16</sub> and E6<sub>16</sub>.</i></p>	<i>Bit</i>	<i>Coding</i>		48	0 ACAS failed or on standby			1 ACAS operating		69	0 Hybrid surveillance not operational			1 Hybrid surveillance fitted and operational		70	0 ACAS generating TAs only			1 ACAS generating TAs and RAs		Bit 72	Bit 71	ACAS version	0	0	RTCA/DO-185 (pre ACAS)	0	1	RTCA/DO-185A	1	0	RTCA/DO-185B & EUROCAE ED 143	1	1	Reserved for future versions (see Note 3)	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.</p>	<p>No Difference</p>		
<i>Bit</i>	<i>Coding</i>																																								
48	0 ACAS failed or on standby																																								
	1 ACAS operating																																								
69	0 Hybrid surveillance not operational																																								
	1 Hybrid surveillance fitted and operational																																								
70	0 ACAS generating TAs only																																								
	1 ACAS generating TAs and RAs																																								
Bit 72	Bit 71	ACAS version																																							
0	0	RTCA/DO-185 (pre ACAS)																																							
0	1	RTCA/DO-185A																																							
1	0	RTCA/DO-185B & EUROCAE ED 143																																							
1	1	Reserved for future versions (see Note 3)																																							





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.8.4.2.3  Standard	<i>MU field.</i> This 56-bit (33-88) field of long air-air surveillance interrogations (Figure 4-1) shall be used to transmit resolution messages, ACAS broadcasts and RA broadcasts.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.3.1  Standard	<i>UDS (U-definition subfield).</i> This 8-bit (33-40) subfield shall define the remainder of MU. <i>Note.— For convenience in coding, UDS is expressed in two groups of four bits each, UDS1 and UDS2.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.3.2  Standard	<i>Subfields in MU for a resolution message.</i> When UDS1 = 3 and UDS2 = 0 the following subfields shall be contained in MU:	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.3.2.1  Standard	<i>MTB (multiple threat bit).</i> This 1-bit (42) subfield shall indicate the presence or absence of multiple threats. <i>Coding</i> 0 Interrogating ACAS has one threat 1 Interrogating ACAS has more than one threat	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference								
Chapter 4 Reference 4.3.8.4.2.3.2.2  Standard	<p><i>VRC (vertical RAC)</i>. This 2-bit (45-46) subfield shall denote a vertical RAC relating to the addressed aircraft.</p> <p><i>Coding</i></p> <table border="0"> <tr> <td>0</td> <td>No vertical RAC sent</td> </tr> <tr> <td>1</td> <td>Do not pass below</td> </tr> <tr> <td>2</td> <td>Do not pass above</td> </tr> <tr> <td>3</td> <td>Not assigned</td> </tr> </table>	0	No vertical RAC sent	1	Do not pass below	2	Do not pass above	3	Not assigned	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
0	No vertical RAC sent												
1	Do not pass below												
2	Do not pass above												
3	Not assigned												
Chapter 4 Reference 4.3.8.4.2.3.2.3  Standard	<p><i>CVC (cancel vertical RAC)</i>. This 2-bit (43-44) subfield shall denote the cancellation of a vertical RAC previously sent to the addressed aircraft. This subfield shall be set to 0 for a new threat.</p> <p><i>Coding</i></p> <table border="0"> <tr> <td>0</td> <td>No cancellation</td> </tr> <tr> <td>1</td> <td>Cancel previously sent "Do not pass below"</td> </tr> <tr> <td>2</td> <td>Cancel previously sent "Do not pass above"</td> </tr> <tr> <td>3</td> <td>Not assigned</td> </tr> </table>	0	No cancellation	1	Cancel previously sent "Do not pass below"	2	Cancel previously sent "Do not pass above"	3	Not assigned	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
0	No cancellation												
1	Cancel previously sent "Do not pass below"												
2	Cancel previously sent "Do not pass above"												
3	Not assigned												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.8.4.2.3.2.4  Standard	<p><i>HRC (horizontal RAC)</i>. This 3-bit (50-52) subfield shall denote a horizontal RAC relating to the addressed aircraft.</p> <p><i>Coding</i></p> <p>0 No horizontal RAC or no horizontal resolution capability</p> <p>1 Other ACAS sense is turn left; do not turn left</p> <p>2 Other ACAS sense is turn left; do not turn right</p> <p>3 Not assigned</p> <p>4 Not assigned</p> <p>5 Other ACAS sense is turn right; do not turn left</p> <p>6 Other ACAS sense is turn right; do not turn right</p> <p>7 Not assigned</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.3.2.5  Standard	<p><i>CHC (cancel horizontal RAC)</i>. This 3-bit (47-49) subfield shall denote the cancellation of a horizontal RAC previously sent to the addressed aircraft. This subfield shall be set to 0 for a new threat.</p> <p><i>Coding</i></p> <p>0 No cancellation or no horizontal resolution capability</p> <p>1 Cancel previously sent "Do not turn left"</p> <p>2 Cancel previously sent "Do not turn right"</p> <p>3-7 Not assigned</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																																																																																																																										
Chapter 4  Reference 4.3.8.4.2.3.2.6   Standard	<p>VSB (vertical sense bits subfield). This 4-bit (61-64) subfield shall be used to protect the data in the CVC and VRC subfields. For each of the 16 possible combinations of bits 43-46 the following VSB code shall be transmitted:</p> <table border="1" data-bbox="373 500 926 1503"> <thead> <tr> <th></th> <th>C</th> <th>VC</th> <th>V</th> <th>RC</th> <th></th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>VC</td> <td>V</td> <td>RC</td> <td></td> </tr> <tr> <td></td> <td></td> <td colspan="4">VSB</td> </tr> <tr> <td><i>Coding</i></td> <td>43</td> <td>44</td> <td>45</td> <td>46</td> <td>61</td> </tr> <tr> <td></td> <td>62</td> <td>63</td> <td>64</td> <td></td> <td></td> </tr> <tr> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> </tr> <tr> <td>1</td> <td>0</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>0</td> <td></td> <td></td> </tr> <tr> <td>2</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>4</td> <td>0</td> <td>1</td> <td>0</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>5</td> <td>0</td> <td>1</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>6</td> <td>0</td> <td>1</td> <td>1</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>0</td> <td></td> <td></td> </tr> <tr> <td>7</td> <td>0</td> <td>1</td> <td>1</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>0</td> <td></td> <td></td> </tr> <tr> <td>8</td> <td>1</td> <td>0</td> <td>0</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>9</td> <td>1</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>10</td> <td>1</td> <td>0</td> <td>1</td> <td>0</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>0</td> <td></td> <td></td> </tr> <tr> <td>11</td> <td>1</td> <td>0</td> <td>1</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>0</td> <td></td> <td></td> </tr> <tr> <td>12</td> <td>1</td> <td>1</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>0</td> <td></td> <td></td> </tr> </tbody> </table>		C	VC	V	RC				VC	V	RC				VSB				<i>Coding</i>	43	44	45	46	61		62	63	64			0	0	0	0	0	0		0	0	0			1	0	0	0	1	1		1	1	0			2	0	0	1	0	0		1	1	1			3	0	0	1	1	1		0	0	1			4	0	1	0	0	1		0	1	1			5	0	1	0	1	0		1	0	1			6	0	1	1	0	1		1	0	0			7	0	1	1	1	0		0	1	0			8	1	0	0	0	1		1	0	1			9	1	0	0	1	0		0	1	1			10	1	0	1	0	1		0	1	0			11	1	0	1	1	0		1	0	0			12	1	1	0	0	0		1	1	0			CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
	C	VC	V	RC																																																																																																																																																																																											
		VC	V	RC																																																																																																																																																																																											
		VSB																																																																																																																																																																																													
<i>Coding</i>	43	44	45	46	61																																																																																																																																																																																										
	62	63	64																																																																																																																																																																																												
0	0	0	0	0	0																																																																																																																																																																																										
	0	0	0																																																																																																																																																																																												
1	0	0	0	1	1																																																																																																																																																																																										
	1	1	0																																																																																																																																																																																												
2	0	0	1	0	0																																																																																																																																																																																										
	1	1	1																																																																																																																																																																																												
3	0	0	1	1	1																																																																																																																																																																																										
	0	0	1																																																																																																																																																																																												
4	0	1	0	0	1																																																																																																																																																																																										
	0	1	1																																																																																																																																																																																												
5	0	1	0	1	0																																																																																																																																																																																										
	1	0	1																																																																																																																																																																																												
6	0	1	1	0	1																																																																																																																																																																																										
	1	0	0																																																																																																																																																																																												
7	0	1	1	1	0																																																																																																																																																																																										
	0	1	0																																																																																																																																																																																												
8	1	0	0	0	1																																																																																																																																																																																										
	1	0	1																																																																																																																																																																																												
9	1	0	0	1	0																																																																																																																																																																																										
	0	1	1																																																																																																																																																																																												
10	1	0	1	0	1																																																																																																																																																																																										
	0	1	0																																																																																																																																																																																												
11	1	0	1	1	0																																																																																																																																																																																										
	1	0	0																																																																																																																																																																																												
12	1	1	0	0	0																																																																																																																																																																																										
	1	1	0																																																																																																																																																																																												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																				
	<table border="0"> <tr> <td>13</td> <td>1</td> <td>1</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td></td> <td></td> </tr> <tr> <td>14</td> <td>1</td> <td>1</td> <td>1</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1</td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>1</td> <td>1</td> <td>1</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>1</td> <td></td> <td></td> </tr> </table> <p><i>Note.— The rule used to generate the VSB subfield bit setting is a distance 3 Hamming code augmented with a parity bit, producing the ability to detect up to three errors in the eight transmitted bits.</i></p>	13	1	1	0	1	1		0	0	0			14	1	1	1	0	0		0	0	1			15	1	1	1	1	1		1	1	1						
13	1	1	0	1	1																																				
	0	0	0																																						
14	1	1	1	0	0																																				
	0	0	1																																						
15	1	1	1	1	1																																				
	1	1	1																																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																
Chapter 4 Reference 4.3.8.4.2.3.2.7  Standard	<p><i>HSB (horizontal sense bits subfield)</i>. This 5-bit (56-60) subfield shall be used to protect the data in the CHC and HRC subfields. For each of the 64 possible combinations of bits 47-52 the following HSB code shall be transmitted:</p> <table border="1" data-bbox="315 454 903 1494"> <thead> <tr> <th></th> <th>CH</th> <th>C</th> <th>HR</th> <th>C</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>1</td> <td>0</td> <td>0</td> <td>0</td> <td>1</td> </tr> <tr> <td>2</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>3</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td>4</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>5</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td>6</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>7</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td>8</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>9</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>10</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>11</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td>12</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td>13</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td>14</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> </tr> </tbody> </table>		CH	C	HR	C	0	0	0	0	0	1	0	0	0	1	2	0	0	1	0	3	0	0	1	1	4	0	0	1	0	5	0	0	1	1	6	0	0	1	0	7	0	0	1	1	8	0	0	1	0	9	0	0	1	0	10	0	0	1	0	11	0	0	1	1	12	0	0	1	0	13	0	0	1	1	14	0	0	1	0	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
	CH	C	HR	C																																																																																	
0	0	0	0	0																																																																																	
1	0	0	0	1																																																																																	
2	0	0	1	0																																																																																	
3	0	0	1	1																																																																																	
4	0	0	1	0																																																																																	
5	0	0	1	1																																																																																	
6	0	0	1	0																																																																																	
7	0	0	1	1																																																																																	
8	0	0	1	0																																																																																	
9	0	0	1	0																																																																																	
10	0	0	1	0																																																																																	
11	0	0	1	1																																																																																	
12	0	0	1	0																																																																																	
13	0	0	1	1																																																																																	
14	0	0	1	0																																																																																	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS								State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	Standard or Recommended Practice											
	0	0	1	0								
15	0	0	1	1	1	1	0					
	1	0	0	1								
16	0	1	0	0	0	0	1					
	0	1	0	1								
17	0	1	0	0	0	1	1					
	1	1	1	0								
18	0	1	0	0	1	0	0					
	0	1	1	0								
19	0	1	0	0	1	1	0					
	1	1	0	1								
20	0	1	0	1	0	0	0					
	1	0	0	1								
21	0	1	0	1	0	1	0					
	0	0	1	0								
22	0	1	0	1	1	0	1					
	1	0	1	0								
23	0	1	0	1	1	1	1					
	0	0	0	1								
24	0	1	1	0	0	0	1					
	1	0	0	0								
25	0	1	1	0	0	1	1					
	0	0	1	1								
26	0	1	1	0	1	0	0					
	1	0	1	1								
27	0	1	1	0	1	1	0					
	0	0	0	0								
28	0	1	1	1	0	0	0					
	0	1	0	0								
29	0	1	1	1	0	1	0					
	1	1	1	1								
30	0	1	1	1	1	0	1					
	0	1	1	1								
31	0	1	1	1	1	1	1					
	1	1	0	0								
32	1	0	0	0	0	0	1					
	1	0	0	1								



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																
	<table border="0"> <tr> <td>33</td> <td>1</td> <td>0</td> <td>0</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>34</td> <td>1</td> <td>0</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>0</td> <td>1</td> <td>0</td> <td></td> <td></td> <td></td> </tr> <tr> <td>35</td> <td>1</td> <td>0</td> <td>0</td> <td>0</td> <td>1</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>0</td> <td>0</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>36</td> <td>1</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td></td> <td>0</td> <td>1</td> <td>0</td> <td>1</td> <td></td> <td></td> <td></td> </tr> <tr> <td>37</td> <td>1</td> <td>0</td> <td>0</td> <td>1</td> <td>0</td> <td>1</td> <td>0</td> </tr> <tr> <td></td> <td>1</td> <td>1</td> <td>1</td> <td>0</td> <td></td> <td></td> <td></td> </tr> </table>	33	1	0	0	0	0	1	1		0	0	1	0				34	1	0	0	0	1	0	0		1	0	1	0				35	1	0	0	0	1	1	0		0	0	0	1				36	1	0	0	1	0	0	0		0	1	0	1				37	1	0	0	1	0	1	0		1	1	1	0							
33	1	0	0	0	0	1	1																																																																														
	0	0	1	0																																																																																	
34	1	0	0	0	1	0	0																																																																														
	1	0	1	0																																																																																	
35	1	0	0	0	1	1	0																																																																														
	0	0	0	1																																																																																	
36	1	0	0	1	0	0	0																																																																														
	0	1	0	1																																																																																	
37	1	0	0	1	0	1	0																																																																														
	1	1	1	0																																																																																	
<p>Chapter 4 Reference 4.3.8.4.2.3.2.8</p> <p>Standard</p>	<p><i>MID (Aircraft address).</i> This 24-bit (65-88) subfield shall contain the 24-bit aircraft address of the interrogating ACAS aircraft.</p> <p><i>Note.— Structure of MU for a resolution message:</i></p> <table border="0"> <tr> <td>33</td> <td>37</td> <td>41</td> <td>42</td> <td>43</td> <td>45</td> <td>47</td> </tr> <tr> <td></td> <td>50</td> <td>53</td> <td>56</td> <td>61</td> <td>65</td> <td></td> </tr> <tr> <td>UDS1=3</td> <td>UDS2=0</td> <td>-1-</td> <td>MTB</td> <td>CVC</td> <td>VRC</td> <td>CHC</td> </tr> <tr> <td></td> <td></td> <td></td> <td>HRC</td> <td>-3-</td> <td>HSB</td> <td></td> </tr> <tr> <td colspan="7">VSB MID</td> </tr> <tr> <td>36</td> <td>40</td> <td>41</td> <td>42</td> <td>44</td> <td>46</td> <td>49</td> </tr> <tr> <td></td> <td>52</td> <td>55</td> <td>60</td> <td>64</td> <td>88</td> <td></td> </tr> </table>	33	37	41	42	43	45	47		50	53	56	61	65		UDS1=3	UDS2=0	-1-	MTB	CVC	VRC	CHC				HRC	-3-	HSB		VSB MID							36	40	41	42	44	46	49		52	55	60	64	88		<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>																																	
33	37	41	42	43	45	47																																																																															
	50	53	56	61	65																																																																																
UDS1=3	UDS2=0	-1-	MTB	CVC	VRC	CHC																																																																															
			HRC	-3-	HSB																																																																																
VSB MID																																																																																					
36	40	41	42	44	46	49																																																																															
	52	55	60	64	88																																																																																
<p>Chapter 4 Reference 4.3.8.4.2.3.3</p> <p>Standard</p>	<p><i>Subfield in MU for an ACAS broadcast.</i> When UDS1 = 3 and UDS2 = 2, the following subfield shall be contained in MU:</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>																																																																																		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference															
Chapter 4 Reference 4.3.8.4.2.3.3.1  Standard	<p><i>MID (Aircraft address)</i>. This 24-bit (65-88) subfield shall contain the 24-bit aircraft address of the interrogating ACAS aircraft.</p> <p><i>Note.— Structure of MU for an ACAS broadcast:</i></p> <table style="margin-left: 40px;"> <tr> <td style="text-align: right;">33</td> <td style="text-align: center;">37</td> <td style="text-align: left;">41</td> </tr> <tr> <td></td> <td style="text-align: center;">65</td> <td></td> </tr> <tr> <td style="text-align: right;">UDS1 = 3</td> <td style="text-align: center;">UDS2 = 2</td> <td style="text-align: left;">-----24----- MID</td> </tr> <tr> <td style="text-align: right;">36</td> <td style="text-align: center;">40</td> <td style="text-align: left;">64</td> </tr> <tr> <td></td> <td style="text-align: center;">88</td> <td></td> </tr> </table>	33	37	41		65		UDS1 = 3	UDS2 = 2	-----24----- MID	36	40	64		88		CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
33	37	41																		
	65																			
UDS1 = 3	UDS2 = 2	-----24----- MID																		
36	40	64																		
	88																			
Chapter 4 Reference 4.3.8.4.2.3.4  Standard	<p><i>Subfields in MU for an RA broadcast</i>. When UDS1 = 3 and UDS2 = 1, the following subfields shall be contained in MU:</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																	
Chapter 4 Reference 4.3.8.4.2.3.4.1  Standard	<p><i>ARA (active RAs)</i>. This 14-bit (41-54) subfield shall be coded as defined in 4.3.8.4.2.2.1.1.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																	
Chapter 4 Reference 4.3.8.4.2.3.4.2  Standard	<p><i>RAC (RACs record)</i>. This 4-bit (55-58) subfield shall be coded as defined in 4.3.8.4.2.2.1.2.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.8.4.2.3.4.3  Standard	<i>RAT (RA terminated indicator)</i> . This 1-bit (59) subfield shall be coded as defined in 4.3.8.4.2.2.1.3.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.3.4.4  Standard	<i>MTE (multiple threat encounter)</i> . This 1-bit (60) subfield shall be coded as defined in 4.3.8.4.2.2.1.4.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.3.4.5  Standard	<i>AID (Mode A identity code)</i> . This 13-bit (63-75) subfield shall denote the Mode A identity code of the reporting aircraft.  <i>Coding</i>  Bit                    63    64    65    66    67 68    69    70    71    72 73    74    75  Mode A code bit    A4    A2    A1    B4    B2 B1    0    C4    C2    C1 D4    D2    D1	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																																														
Chapter 4 Reference 4.3.8.4.2.3.4.6  Standard	<p><i>CAC (Mode C altitude code).</i> This 13-bit (76-88) subfield shall denote the Mode C altitude code of the reporting aircraft.</p> <p><i>Coding</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">Bit</td> <td style="width: 10%;">76</td> <td style="width: 10%;">77</td> <td style="width: 10%;">78</td> <td style="width: 10%;">79</td> <td style="width: 10%;">80</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>81</td> <td>82</td> <td>83</td> <td>84</td> <td>85</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>86</td> <td>87</td> <td>88</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Mode C code bit</td> <td>C1</td> <td>A1</td> <td>C2</td> <td>A2</td> <td>C4</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>A4</td> <td>0</td> <td>B1</td> <td>D1</td> <td>B2</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>D2</td> <td>B4</td> <td>D4</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table> <p><i>Note.— Structure of MU for an RA broadcast:</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">33</td> <td style="width: 10%;">37</td> <td style="width: 10%;">41</td> <td style="width: 10%;">55</td> <td style="width: 10%;">59</td> <td style="width: 10%;">60</td> <td style="width: 10%;">61</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>63</td> <td>76</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>UDS1=3</td> <td>UDS2=1</td> <td>ARA</td> <td>RAC</td> <td>RAT</td> <td>MTE</td> <td>-2-</td> <td>AID</td> <td>CAC</td> <td></td> </tr> <tr> <td>36</td> <td>40</td> <td>54</td> <td>58</td> <td>59</td> <td>60</td> <td>62</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>75</td> <td>88</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </table>	Bit	76	77	78	79	80						81	82	83	84	85						86	87	88							Mode C code bit	C1	A1	C2	A2	C4						A4	0	B1	D1	B2						D2	B4	D4							33	37	41	55	59	60	61					63	76								UDS1=3	UDS2=1	ARA	RAC	RAT	MTE	-2-	AID	CAC		36	40	54	58	59	60	62					75	88								CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Bit	76	77	78	79	80																																																																																																														
	81	82	83	84	85																																																																																																														
	86	87	88																																																																																																																
Mode C code bit	C1	A1	C2	A2	C4																																																																																																														
	A4	0	B1	D1	B2																																																																																																														
	D2	B4	D4																																																																																																																
33	37	41	55	59	60	61																																																																																																													
	63	76																																																																																																																	
UDS1=3	UDS2=1	ARA	RAC	RAT	MTE	-2-	AID	CAC																																																																																																											
36	40	54	58	59	60	62																																																																																																													
	75	88																																																																																																																	
Chapter 4 Reference 4.3.8.4.2.4  Standard	<p><i>MV field.</i> This 56-bit (33-88) field of long air-air surveillance replies (Figure 4-1) shall be used to transmit air-air coordination reply messages.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																																																																																																																
Chapter 4 Reference 4.3.8.4.2.4.1  Standard	<p><i>VDS (V-definition subfield).</i> This 8-bit (33-40) subfield shall define the remainder of MV.</p> <p><i>Note.— For convenience in coding, VDS is expressed in two groups of four bits each, VDS1 and VDS2.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																																																																																																																



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.8.4.2.4.2  Standard	<i>Subfields in MV for a coordination reply.</i> When VDS1 = 3 and VDS2 = 0, the following subfields shall be contained in MV:	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.4.2.1  Standard	<i>ARA (active RAs).</i> This 14-bit (41-54) subfield shall be coded as defined in 4.3.8.4.2.2.1.1.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.4.2.2  Standard	<i>RAC (RACs record).</i> This 4-bit (55-58) subfield shall be coded as defined in 4.3.8.4.2.2.1.2.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.8.4.2.4.2.3  Standard	<i>RAT (RA terminated indicator).</i> This 1-bit (59) subfield shall be coded as defined in 4.3.8.4.2.2.1.3.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																									
Chapter 4 Reference 4.3.8.4.2.4.2.4  Standard	<p><i>MTE (multiple threat encounter)</i>. This 1-bit (60) subfield shall be coded as defined in 4.3.8.4.2.2.1.4.</p> <p><i>Note.— Structure of MV for a coordination reply:</i></p> <table border="0" style="margin-left: 40px;"> <tr> <td>33</td> <td>37</td> <td>41</td> <td>55</td> <td>59</td> </tr> <tr> <td></td> <td>60</td> <td>61</td> <td></td> <td></td> </tr> <tr> <td>VDS1=3</td> <td>VDS2=0</td> <td>ARA RAC RAT</td> <td>MTE -28-</td> <td></td> </tr> <tr> <td></td> <td>36</td> <td>40</td> <td>54</td> <td>58</td> </tr> <tr> <td></td> <td>59</td> <td>60</td> <td>88</td> <td></td> </tr> </table>	33	37	41	55	59		60	61			VDS1=3	VDS2=0	ARA RAC RAT	MTE -28-			36	40	54	58		59	60	88		CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
33	37	41	55	59																										
	60	61																												
VDS1=3	VDS2=0	ARA RAC RAT	MTE -28-																											
	36	40	54	58																										
	59	60	88																											
Chapter 4 Reference 4.3.8.4.2.5  Standard	<p><i>SL (sensitivity level report)</i>. This 3-bit (9-11) downlink field shall be included in both short and long air-air reply formats (DF = 0 and 16). This field shall denote the sensitivity level at which ACAS is currently operating.</p> <p><i>Coding</i></p> <table border="0" style="margin-left: 40px;"> <tr> <td>0</td> <td>ACAS inoperative</td> </tr> <tr> <td>1</td> <td>ACAS is operating at sensitivity level 1</td> </tr> <tr> <td>2</td> <td>ACAS is operating at sensitivity level 2</td> </tr> <tr> <td>3</td> <td>ACAS is operating at sensitivity level 3</td> </tr> <tr> <td>4</td> <td>ACAS is operating at sensitivity level 4</td> </tr> <tr> <td>5</td> <td>ACAS is operating at sensitivity level 5</td> </tr> <tr> <td>6</td> <td>ACAS is operating at sensitivity level 6</td> </tr> <tr> <td>7</td> <td>ACAS is operating at sensitivity level 7</td> </tr> </table>	0	ACAS inoperative	1	ACAS is operating at sensitivity level 1	2	ACAS is operating at sensitivity level 2	3	ACAS is operating at sensitivity level 3	4	ACAS is operating at sensitivity level 4	5	ACAS is operating at sensitivity level 5	6	ACAS is operating at sensitivity level 6	7	ACAS is operating at sensitivity level 7	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference											
0	ACAS inoperative																													
1	ACAS is operating at sensitivity level 1																													
2	ACAS is operating at sensitivity level 2																													
3	ACAS is operating at sensitivity level 3																													
4	ACAS is operating at sensitivity level 4																													
5	ACAS is operating at sensitivity level 5																													
6	ACAS is operating at sensitivity level 6																													
7	ACAS is operating at sensitivity level 7																													



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.8.4.2.6  Standard	<p><i>CC: Cross-link capability.</i> This 1-bit (7) downlink field shall indicate the ability of the transponder to support the cross-link capability, i.e. decode the contents of the DS field in an interrogation with UF equals 0 and respond with the contents of the specified GICB register in the corresponding reply with DF equals 16.</p> <p>Coding 0 signifies that the transponder cannot support the cross-link capability. 1 signifies that the transponder supports the cross-link capability.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.3.9.1  Standard	<p><b>4.3.9 ACAS equipment characteristics</b></p> <p><i>Interfaces.</i> As a minimum, the following input data shall be provided to the ACAS:</p> <ul style="list-style-type: none"> <li>a) aircraft address code;</li> <li>b) air-air and ground-air Mode S transmissions received by the Mode S transponder for use by ACAS (4.3.6.3.2);</li> <li>c) own aircraft's maximum cruising true airspeed capability (Chapter 3, 3.1.2.8.2.2);</li> <li>d) pressure-altitude; and</li> <li>e) radio altitude.</li> </ul> <p><i>Note.— Specific requirements for additional inputs for ACAS II and III are listed in the appropriate sections below.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.2  Standard	<p><i>Aircraft antenna system.</i> ACAS shall transmit interrogations and receive replies via two antennas, one mounted on the top of the aircraft and the other on the bottom of the aircraft. The top-mounted antenna shall be directional and capable of being used for direction finding.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.9.2.1  Standard	<i>Polarization.</i> Polarization of ACAS transmissions shall be nominally vertical.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.2.2  Standard	<i>Radiation pattern.</i> The radiation pattern in elevation of each antenna when installed on an aircraft shall be nominally equivalent to that of a quarter-wave monopole on a ground plane.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.2.3.1  Standard	4.3.9.2.3 ANTENNA SELECTION  <i>Squitter reception.</i> ACAS shall be capable of receiving squitters via the top and bottom antennas.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.2.3.2  Standard	<i>Interrogations.</i> ACAS interrogations shall not be transmitted simultaneously on both antennas.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.3  Standard	<i>Pressure altitude source.</i> The altitude data for own aircraft provided to ACAS shall be obtained from the source that provides the basis for own Mode C or Mode S reports and they shall be provided at the finest quantization available.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.9.3.1  <b>Recommendation</b>	<b>Recommendation.</b> — <i>A source providing a resolution finer than 7.62 m (25 ft) should be used.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.3.2  <b>Standard</b>	Where a source providing a resolution finer than 7.62 m (25 ft) is not available, and the only altitude data available for own aircraft is Gilham encoded, at least two independent sources shall be used and compared continuously in order to detect encoding errors.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.3.3  <b>Recommendation</b>	<b>Recommendation.</b> — <i>Two altitude data sources should be used and compared in order to detect errors before provision to ACAS.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.9.3.4  <b>Standard</b>	The provisions of 4.3.10.3 shall apply when the comparison of the two altitude data sources indicates that one of the sources is in error.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.10.1  Standard	<p style="text-align: center;"><b>4.3.10 Monitoring</b></p> <p><i>Monitoring function.</i> ACAS shall continuously perform a monitoring function in order to provide a warning if any of the following conditions at least are satisfied:</p> <ul style="list-style-type: none"> <li>a) there is no interrogation power limiting due to interference control (4.3.2.2.2) and the maximum radiated power is reduced to less than that necessary to satisfy the surveillance requirements specified in 4.3.2; or</li> <li>b) any other failure in the equipment is detected which results in a reduced capability of providing TAs or RAs; or</li> <li>c) data from external sources indispensable for ACAS operation are not provided, or the data provided are not credible.</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.10.2  Standard	<i>Effect on ACAS operation.</i> The ACAS monitoring function shall not adversely affect other ACAS functions.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.10.3  Standard	<p><i>Monitoring response.</i> When the monitoring function detects a failure (4.3.10.1), ACAS shall:</p> <ul style="list-style-type: none"> <li>a) indicate to the flight crew that an abnormal condition exists;</li> <li>b) prevent any further ACAS interrogations; and</li> <li>c) cause any Mode S transmission containing own aircraft's resolution capability to indicate that ACAS is not operating.</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference						
<p>Chapter 4 Reference 4.3.11.1</p> <p>Standard</p>	<p><b>4.3.11 Requirements for a Mode S transponder used in conjunction with ACAS</b></p> <p><i>Transponder capabilities.</i> In addition to the minimum transponder capabilities defined in Chapter 3, 3.1, the Mode S transponder used in conjunction with ACAS shall have the following capabilities:</p> <ul style="list-style-type: none"> <li>a) ability to handle the following formats:  <table border="0" style="margin-left: 20px;"> <tr> <td style="padding-right: 20px;"><i>Format No.</i></td> <td><i>Format name</i></td> </tr> <tr> <td>UF = 16</td> <td>Long air-air surveillance interrogation</td> </tr> <tr> <td>DF = 16</td> <td>Long air-air surveillance reply</td> </tr> </table> </li> <li>b) ability to receive long Mode S interrogations (UF = 16) and generate long Mode S replies (DF = 16) at a continuous rate of 16.6 ms (60 per second);</li> <li>c) means for delivering the ACAS data content of all accepted interrogations addressed to the ACAS equipment;</li> <li>d) antenna diversity (as specified in Chapter 3, 3.1.2.10.4);</li> <li>e) mutual suppression capability; and</li> <li>f) inactive state transponder output power restriction.</li> </ul> <p>When the Mode S transponder transmitter is in the inactive state, the peak pulse power at 1 090 MHz <math>\pm</math>3 MHz at the terminals of the Mode S transponder antenna shall not exceed -70 dBm.</p>	<i>Format No.</i>	<i>Format name</i>	UF = 16	Long air-air surveillance interrogation	DF = 16	Long air-air surveillance reply	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<i>Format No.</i>	<i>Format name</i>										
UF = 16	Long air-air surveillance interrogation										
DF = 16	Long air-air surveillance reply										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.11.2.1  Standard	<p><b>4.3.11.2 DATA TRANSFER BETWEEN ACAS AND ITS MODE S TRANSPONDER</b></p> <p><i>Data transfer from ACAS to its Mode S transponder:</i></p> <ul style="list-style-type: none"> <li>a) The Mode S transponder shall receive from its ACAS RA information for transmission in an RA report (4.3.8.4.2.2.1) and in a coordination reply (4.3.8.4.2.4.2);</li> <li>b) the Mode S transponder shall receive from its ACAS current sensitivity level for transmission in a sensitivity level report (4.3.8.4.2.5);</li> <li>c) the Mode S transponder shall receive from its ACAS capability information for transmission in a data link capability report (4.3.8.4.2.2.2) and for transmission in the RI field of air-air downlink formats DF = 0 and DF = 16 (4.3.8.4.1.2); and</li> <li>d) the Mode S transponder shall receive from its ACAS an indication that RAs are enabled or inhibited for transmission in the RI field of downlink formats 0 and 16.</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.11.2.2  Standard	<p>Data transfer from Mode S transponder to its ACAS:</p> <ul style="list-style-type: none"> <li>a) The Mode S transponder shall transfer to its ACAS received sensitivity level control commands (4.3.8.4.2.1.1) transmitted by Mode S stations;</li> <li>b) the Mode S transponder shall transfer to its ACAS received ACAS broadcast messages (4.3.8.4.2.3.3) transmitted by other ACASs;</li> <li>c) the Mode S transponder shall transfer to its ACAS received resolution messages (4.3.8.4.2.3.2) transmitted by other ACASs for air-air coordination purposes; and</li> <li>d) the Mode S transponder shall transfer to its ACAS own aircraft's Mode A identity data for transmission in an RA broadcast (4.3.8.4.2.3.4.5).</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.11.3.1  Standard	4.3.11.3 COMMUNICATION OF ACAS INFORMATION TO OTHER ACAS  <i>Surveillance reply.</i> The ACAS Mode S transponder shall use the short (DF = 0) or long (DF = 16) surveillance formats for replies to ACAS surveillance interrogations. The surveillance reply shall include the VS field as specified in Chapter 3, 3.1.2.8.2, the RI field as specified in Chapter 3, 3.1.2.8.2 and in 4.3.8.4.1.2, and the SL field as specified in 4.3.8.4.2.5.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.11.3.2  Standard	<i>Coordination reply.</i> The ACAS Mode S transponder shall transmit a coordination reply upon receipt of a coordination interrogation from an equipped threat subject to the conditions of 4.3.11.3.2.1. The coordination reply shall use the long air-air surveillance reply format, DF = 16, with the VS field as specified in Chapter 3, 3.1.2.8.2, the RI field as specified in Chapter 3, 3.1.2.8.2 and in 4.3.8.4.1.2, the SL field as specified in 4.3.8.4.2.5 and the MV field as specified in 4.3.8.4.2.4. Coordination replies shall be transmitted even if the minimum reply rate limits of the transponder (Chapter 3, 3.1.2.10.3.7.2) are exceeded.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.11.3.2.1  Standard	The ACAS Mode S transponder shall reply with a coordination reply to a coordination interrogation received from another ACAS if and only if the transponder is able to deliver the ACAS data content of the interrogation to its associated ACAS.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference 4.3.11.4.1</p> <p>Standard</p>	<p>4.3.11.4 COMMUNICATION OF ACAS INFORMATION TO GROUND STATIONS</p> <p><i>RA reports to Mode S ground stations. During the period of an RA and for 18±1 s following the end of the RA, the ACAS Mode S transponder shall indicate that it has an RA report by setting the appropriate DR field code in replies to a Mode S sensor as specified in 4.3.8.4.1.1. The RA report shall include the MB field as specified in 4.3.8.4.2.2.1. The RA report shall describe the most recent RA that existed during the preceding 18±1 s period.</i></p> <p><i>N1.The last sentence of 4.3.11.4.1 means that for 18±1 s following the end of the RA, all MB subfields in the RA report with the exception of bit 59 (RA terminated indicator) will retain the information reported at the time the RA was last active.</i></p> <p><i>N2.Upon receipt of a reply with DR = 2, 3, 6 or 7, a Mode S ground station may request downlink of the RA report by setting RR = 19 and either DI = 7, or DI = 7 and RRS =0 in a surveillance or Comm-A interrogation to the ACAS aircraft. When this interrogation is received, the transponder replies with a Comm-B reply whose MB field contains the RA report.</i></p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference 4.3.11.4.2</p> <p>Standard</p>	<p><i>Data link capability report. The presence of an ACAS shall be indicated by its Mode S transponder to a ground station in the Mode S data link capability report.</i></p> <p><i>Note.— This indication causes the transponder to set codes in a data link capability report as specified in 4.3.8.4.2.2.2.</i></p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.3.12.1  Recommendation	<p style="text-align: center;"><b>4.3.12 Indications to the flight crew</b></p> <p style="text-align: center;">CORRECTIVE AND PREVENTIVE RAs</p> <p><b>Recommendation.</b>— <i>Indications to the flight crew should distinguish between preventive and corrective RAs.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.3.12.2  Recommendation	<p style="text-align: center;">ALTITUDE CROSSING RAs</p> <p><b>Recommendation.</b>— <i>If ACAS generates an altitude crossing RA, a specific indication should be given to the flight crew that it is crossing.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																								
<p>Chapter 4 Reference</p> <p>Definition</p>	<p><b>4.4 PERFORMANCE OF THE ACAS II COLLISION AVOIDANCE LOGIC</b></p> <p><i>Note.— Caution is to be observed when considering potential improvements to the reference ACAS II system described in Section 4 of the guidance material in the Attachment since changes may affect more than one aspect of the system performance. It is essential that alternative designs would not degrade the performances of other designs and that such compatibility is demonstrated with a high degree of confidence.</i></p> <p><b>4.4.1 Definitions relating to the performance of the collision avoidance logic</b></p> <p><i>Note.— The notation <math>[t_1, t_2]</math> is used to indicate the interval between <math>t_1</math> and <math>t_2</math>.</i></p> <p><b>Altitude layer.</b> Each encounter is attributed to one of six altitude layers as follows:</p> <table border="0" data-bbox="323 938 850 1133"> <tr> <td style="padding-right: 20px;"><i>Layer</i></td> <td style="padding-right: 20px;"><i>1</i></td> <td style="padding-right: 20px;"><i>2</i></td> <td><i>3</i></td> </tr> <tr> <td></td> <td><i>4</i></td> <td><i>5</i></td> <td><i>6</i></td> </tr> <tr> <td style="padding-right: 20px;"><i>from</i></td> <td></td> <td>2 300 ft</td> <td>5 000 ft</td> </tr> <tr> <td></td> <td>10 000 ft</td> <td>20 000 ft</td> <td>41 000 ft</td> </tr> <tr> <td style="padding-right: 20px;"><i>to</i></td> <td>2 300 ft</td> <td>5 000 ft</td> <td>10 000 ft</td> </tr> <tr> <td></td> <td>20 000 ft</td> <td>41 000 ft</td> <td></td> </tr> </table> <p>The altitude layer of an encounter is determined by the average altitude of the two aircraft at closest approach.</p> <p><i>Note.— For the purposes of defining the performance of the collision avoidance logic, there is no need to specify the physical basis of the altitude measurement or the relationship between altitude and ground level.</i></p>	<i>Layer</i>	<i>1</i>	<i>2</i>	<i>3</i>		<i>4</i>	<i>5</i>	<i>6</i>	<i>from</i>		2 300 ft	5 000 ft		10 000 ft	20 000 ft	41 000 ft	<i>to</i>	2 300 ft	5 000 ft	10 000 ft		20 000 ft	41 000 ft		<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<i>Layer</i>	<i>1</i>	<i>2</i>	<i>3</i>																										
	<i>4</i>	<i>5</i>	<i>6</i>																										
<i>from</i>		2 300 ft	5 000 ft																										
	10 000 ft	20 000 ft	41 000 ft																										
<i>to</i>	2 300 ft	5 000 ft	10 000 ft																										
	20 000 ft	41 000 ft																											



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<b>Approach angle.</b> The difference in the ground headings of the two aircraft at closest approach, with 180 degrees defined as head on and 0 degrees defined as parallel.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Crossing encounter.</b> An encounter in which the altitude separation of the two aircraft exceeds 100 ft at the beginning and at the end of the encounter window, and the relative vertical position of two aircraft at the end of the encounter window is reversed from that at the beginning of the encounter window.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Encounter class.</b> Encounters are classified according to whether or not the aircraft are transitioning at the beginning and end of the encounter window, and whether or not the encounter is crossing.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Encounter window.</b> The time interval [ $tca - 40$ s, $tca + 10$ s].	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Encounter.</b> For the purposes of defining the performance of the collision avoidance logic, an encounter consists of two simulated aircraft trajectories. The horizontal coordinates of the aircraft represent the actual position of the aircraft but the vertical coordinate represents an altimeter measurement of altitude.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<b>Horizontal miss distance (hmd).</b> The minimum horizontal separation observed in an encounter.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Level aircraft.</b> An aircraft that is not transitioning.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Original rate.</b> The original rate of an ACAS-equipped aircraft at any time is its altitude rate at the same time when it followed the original trajectory.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Original trajectory.</b> The original trajectory of an ACAS-equipped aircraft is that followed by the aircraft in the same encounter when it was not ACAS equipped.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Required rate.</b> For the standard pilot model, the required rate is that closest to the original rate consistent with the RA.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<p><b>tca.</b> Nominally, the time of closest approach. For encounters in the standard encounter model (4.4.2.6), a reference time for the construction of the encounter at which various parameters, including the vertical and horizontal separation (<i>vmd</i> and <i>hmd</i>), are specified.</p> <p><i>Note.— Encounters in the standard encounter model (4.4.2.6) are constructed by building the trajectories of the two aircraft outwards starting at tca. When the process is complete, tca may not be the precise time of closest approach and differences of a few seconds are acceptable.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<p><b>Transitioning aircraft.</b> An aircraft having an average vertical rate with a magnitude exceeding 400 feet per minute (ft/min), measured over some period of interest.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<p><b>Turn extent.</b> A heading difference defined as an aircraft's ground heading at the end of a turn minus its ground heading at the beginning of the turn.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<p><b>Vertical miss distance (vmd).</b> Notionally, the vertical separation at closest approach. For encounters in the standard encounter model (4.4.2.6), by construction the vertical separation at the time <i>tca</i>.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4  Reference 4.4.2.1  Standard	<p><b>4.4.2 Conditions under which the requirements apply</b></p> <p>The following assumed conditions shall apply to the performance requirements specified in 4.4.3 and 4.4.4:</p> <ul style="list-style-type: none"> <li>a) range and bearing measurements and an altitude report are available for the intruder each cycle as long as it is within 14 NM, but not when the range exceeds 14 NM;</li> <li>b) the errors in the range and bearing measurements conform to standard range and bearing error models (4.4.2.2 and 4.4.2.3);</li> <li>c) the intruder's altitude reports, which are its Mode C replies, are expressed in 100 ft quanta;</li> <li>d) an altitude measurement that has not been quantized and is expressed with a precision of 1 ft or better is available for own aircraft;</li> <li>e) errors in the altitude measurements for both aircraft are constant throughout any particular encounter;</li> <li>f) the errors in the altitude measurements for both aircraft conform to a standard altimetry error model (4.4.2.4);</li> <li>g) the pilot responses to RAs conform to a standard pilot model (4.4.2.5);</li> <li>h) the aircraft operate in an airspace in which close encounters, including those in which ACAS generates an RA, conform to a standard encounter model (4.4.2.6);</li> <li>i) ACAS-equipped aircraft are not limited in their ability to perform the manoeuvres required by their RAs; and</li> <li>j) as specified in 4.4.2.7:                         <ul style="list-style-type: none"> <li>1) the intruder involved in each encounter is not equipped (4.4.2.7 a)); or</li> <li>2) the intruder is ACAS-equipped but follows a trajectory identical to that in the unequipped encounter (4.4.2.7 b)); or</li> </ul> </li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>3) the intruder is equipped with an ACAS having a collision avoidance logic identical to that of own ACAS (4.4.2.7 c)).</p> <p><i>Note.— The phrase “altitude measurement” refers to a measurement by an altimeter prior to any quantization.</i></p>				
<p>Chapter 4 Reference 4.4.2.1.1</p> <p><b>Standard</b></p>	<p>The performance of the collision avoidance logic shall not degrade abruptly as the statistical distribution of the altitude errors or the statistical distributions of the various parameters that characterize the standard encounter model or the response of pilots to the advisories are varied, when surveillance reports are not available on every cycle or when the quantization of the altitude measurements for the intruder is varied or the altitude measurements for own aircraft are quantized.</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference 4.4.2.2</p> <p><b>Standard</b></p>	<p style="text-align: center;">STANDARD RANGE ERROR MODEL</p> <p>The errors in the simulated range measurements shall be taken from a Normal distribution with mean 0 ft and standard deviation 50 ft.</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference 4.4.2.3</p> <p><b>Standard</b></p>	<p style="text-align: center;">STANDARD BEARING ERROR MODEL</p> <p>The errors in the simulated bearing measurements shall be taken from a Normal distribution with mean 0.0 degrees and standard deviation 10.0 degrees.</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																		
Chapter 4 Reference 4.4.2.4.1  Standard	4.4.2.4 STANDARD ALTIMETRY ERROR MODEL  The errors in the simulated altitude measurements shall be assumed to be distributed as a Laplacian distribution with zero mean having probability density	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																																																				
Chapter 4 Reference 4.4.2.4.2  Standard	The parameter $\lambda$ required for the definition of the statistical distribution of altimeter error for each aircraft shall have one of two values, $\lambda_1$ and $\lambda_2$ , which depend on the altitude layer of the encounter as follows:  <table border="1" data-bbox="294 792 924 1055"> <thead> <tr> <th>Layer</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> </tr> </thead> <tbody> <tr> <td></td> <td>5</td> <td>6</td> <td></td> <td></td> </tr> <tr> <td></td> <td><i>m</i></td> <td><i>ft</i></td> <td><i>m</i></td> <td><i>ft</i></td> </tr> <tr> <td></td> <td><i>ft</i></td> <td><i>m</i></td> <td><i>ft</i></td> <td><i>m</i></td> </tr> <tr> <td><math>\lambda_1</math></td> <td>10</td> <td>35</td> <td>11</td> <td>38</td> </tr> <tr> <td></td> <td>58</td> <td>22</td> <td>72</td> <td>28</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>94</td> </tr> <tr> <td><math>\lambda_2</math></td> <td>18</td> <td>60</td> <td>18</td> <td>60</td> </tr> <tr> <td></td> <td>87</td> <td>30</td> <td>101</td> <td>30</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>101</td> </tr> </tbody> </table>	Layer	1	2	3	4		5	6				<i>m</i>	<i>ft</i>	<i>m</i>	<i>ft</i>		<i>ft</i>	<i>m</i>	<i>ft</i>	<i>m</i>	$\lambda_1$	10	35	11	38		58	22	72	28					94	$\lambda_2$	18	60	18	60		87	30	101	30					101	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Layer	1	2	3	4																																																			
	5	6																																																					
	<i>m</i>	<i>ft</i>	<i>m</i>	<i>ft</i>																																																			
	<i>ft</i>	<i>m</i>	<i>ft</i>	<i>m</i>																																																			
$\lambda_1$	10	35	11	38																																																			
	58	22	72	28																																																			
				94																																																			
$\lambda_2$	18	60	18	60																																																			
	87	30	101	30																																																			
				101																																																			
Chapter 4 Reference 4.4.2.4.3  Standard	For an aircraft equipped with ACAS the value of $\lambda$ shall be $\lambda_1$ .	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																																																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																			
Chapter 4 Reference 4.4.2.4.4  Standard	For aircraft not equipped with ACAS, the value of $\lambda$ shall be selected randomly using the following probabilities: <table style="margin-left: 40px; border-collapse: collapse;"> <tr> <td style="padding-right: 10px;"><i>Layer</i></td> <td style="padding-right: 10px;"><i>1</i></td> <td style="padding-right: 10px;"><i>2</i></td> <td style="padding-right: 10px;"><i>3</i></td> <td style="padding-right: 10px;"><i>4</i></td> <td style="padding-right: 10px;"><i>5</i></td> <td style="padding-right: 10px;"><i>6</i></td> </tr> <tr> <td>prob(<math>\lambda_1</math>)</td> <td>0.391</td> <td>0.320</td> <td>0.345</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0.610</td> <td>0.610</td> <td>0.610</td> <td></td> <td></td> <td></td> </tr> <tr> <td>prob(<math>\lambda_2</math>)</td> <td>0.609</td> <td>0.680</td> <td>0.655</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>0.390</td> <td>0.390</td> <td>0.390</td> <td></td> <td></td> <td></td> </tr> </table>	<i>Layer</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>	<i>6</i>	prob( $\lambda_1$ )	0.391	0.320	0.345					0.610	0.610	0.610				prob( $\lambda_2$ )	0.609	0.680	0.655					0.390	0.390	0.390				CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Layer</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>	<i>5</i>	<i>6</i>																																		
prob( $\lambda_1$ )	0.391	0.320	0.345																																					
	0.610	0.610	0.610																																					
prob( $\lambda_2$ )	0.609	0.680	0.655																																					
	0.390	0.390	0.390																																					



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.2.5  Standard	<p style="text-align: center;">STANDARD PILOT MODEL</p> <p>The standard pilot model used in the assessment of the performance of the collision avoidance logic shall be that:</p> <ul style="list-style-type: none"> <li>a) any RA is complied with by accelerating to the required rate (if necessary) after an appropriate delay;</li> <li>b) when the aircraft's current rate is the same as its original rate and the original rate complies with the RA, the aircraft continues at its original rate, which is not necessarily constant due to the possibility of acceleration in the original trajectory;</li> <li>c) when the aircraft is complying with the RA, its current rate is the same as the original rate and the original rate changes and consequently becomes inconsistent with the RA, the aircraft continues to comply with the RA;</li> <li>d) when an initial RA requires a change in altitude rate, the aircraft responds with an acceleration of 0.25 g after a delay of 5 s from the display of the RA;</li> <li>e) when an RA is modified and the original rate complies with the modified RA, the aircraft returns to its original rate (if necessary) with the acceleration specified in g) after the delay specified in h);</li> <li>f) when an RA is modified and the original rate does not comply with the modified RA, the aircraft responds to comply with the RA with the acceleration specified in g) after the delay specified in h);</li> <li>g) the acceleration used when an RA is modified is 0.25 g unless the modified RA is a reversed sense RA or an increased rate RA in which case the acceleration is 0.35 g;</li> <li>h) the delay used when an RA is modified is 2.5 s unless this results in the acceleration starting earlier than 5 s from the initial RA in which case the acceleration starts 5 s from the initial RA; and</li> <li>i) when an RA is cancelled, the aircraft returns to its</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	original rate (if necessary) with an acceleration of 0.25 g after a delay of 2.5 s.				
Chapter 4 Reference 4.4.2.6.1.1  Standard	4.4.2.6 STANDARD ENCOUNTER MODEL  4.4.2.6.1 ELEMENTS OF THE STANDARD ENCOUNTER MODEL  In order to calculate the effect of ACAS on the risk of collision (4.4.3) and the compatibility of ACAS with air traffic management (ATM) (4.4.4), sets of encounters shall be created for each of: <ul style="list-style-type: none"> <li>a) the two aircraft address orderings;</li> <li>b) the six altitude layers;</li> <li>c) nineteen encounter classes; and</li> <li>d) nine or ten <i>vmd</i> bins as specified in 4.4.2.6.2.4.</li> </ul> The results for these sets shall be combined using the relative weightings given in 4.4.2.6.2.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.4.2.6.1.1.1  Standard	Each set of encounters shall contain at least 500 independent, randomly generated encounters.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference 4.4.2.6.1.1.2</p> <p>Standard</p>	<p>The two aircraft trajectories in each encounter shall be constructed with the following randomly selected characteristics:</p> <ul style="list-style-type: none"> <li>a) in the vertical plane:                             <ul style="list-style-type: none"> <li>1) a <i>vmd</i> from within the appropriate <i>vmd</i> bin;</li> <li>2) a vertical rate for each aircraft at the beginning of the encounter window, <math>z_1</math> and at the end of the encounter window, <math>z_2</math></li> <li>3) a vertical acceleration; and</li> <li>4) a start time for the vertical acceleration; and</li> </ul> </li> <li>b) and in the horizontal plane:                             <ul style="list-style-type: none"> <li>5) an <i>hmd</i>;</li> <li>6) an approach angle;</li> <li>7) a speed for each aircraft at closest approach;</li> <li>8) a decision for each aircraft whether or not it turns;</li> <li>9) the turn extent; the bank angle; and the turn end time;</li> <li>10) a decision for each aircraft whether or not its speed changes; and</li> <li>11) the magnitude of the speed change.</li> </ul> </li> </ul> <p><i>Note.— It is possible for the selections made for the various characteristics of an encounter to be irreconcilable. When this occurs, the problem can be resolved by discarding either the selection for a particular characteristic or the whole encounter, as most appropriate.</i></p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																				
Chapter 4 Reference 4.4.2.6.1.3  Standard	Two models shall be used for the statistical distribution of <i>hmd</i> (4.4.2.6.4.1). For calculations of the effect of ACAS on the risk of collision (4.4.3), <i>hmd</i> shall be constrained to be less than 500 ft. For calculations of the compatibility of ACAS with ATM (4.4.4), <i>hmd</i> shall be selected from a larger range of values (4.4.2.6.4.1.2). <i>Note.— 4.4.2.6.2 and 4.4.2.6.3 specify vertical characteristics for the aircraft trajectories in the standard encounter model that depend on whether the hmd is constrained to be small (“for calculating risk ratio”) or can take larger values (“for ATM compatibility”). Otherwise, the characteristics of the encounters in the vertical and horizontal planes are independent.</i>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																						
Chapter 4 Reference 4.4.2.6.2.1  Standard	4.4.2.6.2 ENCOUNTER CLASSES AND WEIGHTS  <i>Aircraft address.</i> Each aircraft shall be equally likely to have the higher aircraft address.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																						
Chapter 4 Reference 4.4.2.6.2.2  Standard	<i>Altitude layers.</i> The relative weights of the altitude layers shall be as follows: <table data-bbox="323 1094 924 1224"> <tr> <td><i>Layer</i></td> <td><i>1</i></td> <td><i>2</i></td> <td><i>3</i></td> <td><i>4</i></td> </tr> <tr> <td></td> <td><i>5</i></td> <td><i>6</i></td> <td></td> <td></td> </tr> <tr> <td>prob(layer)</td> <td>0.13</td> <td>0.25</td> <td>0.32</td> <td></td> </tr> <tr> <td></td> <td>0.22</td> <td>0.07</td> <td>0.01</td> <td></td> </tr> </table>	<i>Layer</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>		<i>5</i>	<i>6</i>			prob(layer)	0.13	0.25	0.32			0.22	0.07	0.01		CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Layer</i>	<i>1</i>	<i>2</i>	<i>3</i>	<i>4</i>																					
	<i>5</i>	<i>6</i>																							
prob(layer)	0.13	0.25	0.32																						
	0.22	0.07	0.01																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																				
Chapter 4  Reference 4.4.2.6.2.3.1  Standard	<p>4.4.2.6.2.3 <i>Encounter classes</i></p> <p>The encounters shall be classified according to whether the aircraft are level (L) or transitioning (T) at the beginning (<i>before tca</i>) and end (after <i>tca</i>) of the encounter window and whether or not the encounter is crossing, as follows:</p> <table border="0" style="margin-left: 40px;"> <tr> <td></td> <td style="text-align: center;"><i>Aircraft No. 1</i></td> <td style="text-align: center;"><i>Aircraft No. 2</i></td> <td></td> </tr> <tr> <td style="text-align: center;"><i>Class</i></td> <td style="text-align: center;"><i>before tca</i></td> <td style="text-align: center;"><i>after tca</i></td> <td style="text-align: center;"><i>before tca</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>after tca</i></td> <td style="text-align: center;"><i>Crossing</i></td> <td></td> </tr> </table> <table border="0" style="margin-left: 40px;"> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T T yes</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L T yes</td> </tr> <tr> <td style="text-align: center;">3</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T L yes</td> </tr> <tr> <td style="text-align: center;">4</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T T yes</td> </tr> <tr> <td style="text-align: center;">5</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T T yes</td> </tr> <tr> <td style="text-align: center;">6</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T L yes</td> </tr> <tr> <td style="text-align: center;">7</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T</td> <td style="text-align: center;">L T yes</td> </tr> <tr> <td style="text-align: center;">8</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T L yes</td> </tr> <tr> <td style="text-align: center;">9</td> <td style="text-align: center;">T</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T L yes</td> </tr> <tr> <td style="text-align: center;">10</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L L no</td> </tr> <tr> <td style="text-align: center;">11</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T T no</td> </tr> <tr> <td style="text-align: center;">12</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L T no</td> </tr> <tr> <td style="text-align: center;">13</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">T L no</td> </tr> <tr> <td style="text-align: center;">14</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T</td> <td style="text-align: center;">T T no</td> </tr> </table>		<i>Aircraft No. 1</i>	<i>Aircraft No. 2</i>		<i>Class</i>	<i>before tca</i>	<i>after tca</i>	<i>before tca</i>		<i>after tca</i>	<i>Crossing</i>		1	L	L	T T yes	2	L	L	L T yes	3	L	L	T L yes	4	T	T	T T yes	5	L	T	T T yes	6	T	T	T L yes	7	L	T	L T yes	8	L	T	T L yes	9	T	L	T L yes	10	L	L	L L no	11	L	L	T T no	12	L	L	L T no	13	L	L	T L no	14	T	T	T T no	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
	<i>Aircraft No. 1</i>	<i>Aircraft No. 2</i>																																																																							
<i>Class</i>	<i>before tca</i>	<i>after tca</i>	<i>before tca</i>																																																																						
	<i>after tca</i>	<i>Crossing</i>																																																																							
1	L	L	T T yes																																																																						
2	L	L	L T yes																																																																						
3	L	L	T L yes																																																																						
4	T	T	T T yes																																																																						
5	L	T	T T yes																																																																						
6	T	T	T L yes																																																																						
7	L	T	L T yes																																																																						
8	L	T	T L yes																																																																						
9	T	L	T L yes																																																																						
10	L	L	L L no																																																																						
11	L	L	T T no																																																																						
12	L	L	L T no																																																																						
13	L	L	T L no																																																																						
14	T	T	T T no																																																																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	15      L            T            T T no 16      T            T            T L no 17      L            T            L T no 18      L            T            T L no 19      T            L            T L no				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																																
Chapter 4 Reference 4.4.2.6.2.3.2	<p>The relative weights of the encounter classes shall depend on layer as follows:</p> <p style="text-align: center;"><i>for calculating risk ratio for ATM compatibility</i></p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;"><i>Class</i></td> <td style="width: 40%;"><i>Layers 1-3</i></td> <td style="width: 40%;"><i>Layers 4-6</i></td> </tr> <tr> <td><b>Standard</b></td> <td><i>Layers 1-3</i></td> <td><i>Layers 4-6</i></td> </tr> <tr><td>1</td><td>0.00502</td><td>0.00319</td></tr> <tr><td></td><td>0.06789</td><td>0.07802</td></tr> <tr><td>2</td><td>0.00030</td><td>0.00018</td></tr> <tr><td></td><td>0.00408</td><td>0.00440</td></tr> <tr><td>3</td><td>0.00049</td><td>0.00009</td></tr> <tr><td></td><td>0.00664</td><td>0.00220</td></tr> <tr><td>4</td><td>0.00355</td><td>0.0027</td></tr> <tr><td></td><td>0.04798</td><td>0.06593</td></tr> <tr><td>5</td><td>0.00059</td><td>0.00022</td></tr> <tr><td></td><td>0.00791</td><td>0.00549</td></tr> <tr><td>6</td><td>0.00074</td><td>0.00018</td></tr> <tr><td></td><td>0.00995</td><td>0.00440</td></tr> <tr><td>7</td><td>0.00002</td><td>0.00003</td></tr> <tr><td></td><td>0.00026</td><td>0.00082</td></tr> <tr><td>8</td><td>0.00006</td><td>0.00003</td></tr> <tr><td></td><td>0.00077</td><td>0.00082</td></tr> <tr><td>9</td><td>0.00006</td><td>0.00003</td></tr> <tr><td></td><td>0.00077</td><td>0.00082</td></tr> <tr><td>10</td><td>0.36846</td><td>0.10693</td></tr> <tr><td></td><td>0.31801</td><td>0.09011</td></tr> <tr><td>11</td><td>0.26939</td><td>0.41990</td></tr> <tr><td></td><td>0.23252</td><td>0.35386</td></tr> <tr><td>12</td><td>0.06476</td><td>0.02217</td></tr> <tr><td></td><td>0.05590</td><td>0.01868</td></tr> <tr><td>13</td><td>0.07127</td><td>0.22038</td></tr> <tr><td></td><td>0.06151</td><td>0.18571</td></tr> <tr><td>14</td><td>0.13219</td><td>0.08476</td></tr> <tr><td></td><td>0.11409</td><td>0.07143</td></tr> <tr><td>15</td><td>0.02750</td><td>0.02869</td></tr> <tr><td></td><td>0.02374</td><td>0.02418</td></tr> </table>	<i>Class</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>	<b>Standard</b>	<i>Layers 1-3</i>	<i>Layers 4-6</i>	1	0.00502	0.00319		0.06789	0.07802	2	0.00030	0.00018		0.00408	0.00440	3	0.00049	0.00009		0.00664	0.00220	4	0.00355	0.0027		0.04798	0.06593	5	0.00059	0.00022		0.00791	0.00549	6	0.00074	0.00018		0.00995	0.00440	7	0.00002	0.00003		0.00026	0.00082	8	0.00006	0.00003		0.00077	0.00082	9	0.00006	0.00003		0.00077	0.00082	10	0.36846	0.10693		0.31801	0.09011	11	0.26939	0.41990		0.23252	0.35386	12	0.06476	0.02217		0.05590	0.01868	13	0.07127	0.22038		0.06151	0.18571	14	0.13219	0.08476		0.11409	0.07143	15	0.02750	0.02869		0.02374	0.02418	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Class</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>																																																																																																			
<b>Standard</b>	<i>Layers 1-3</i>	<i>Layers 4-6</i>																																																																																																			
1	0.00502	0.00319																																																																																																			
	0.06789	0.07802																																																																																																			
2	0.00030	0.00018																																																																																																			
	0.00408	0.00440																																																																																																			
3	0.00049	0.00009																																																																																																			
	0.00664	0.00220																																																																																																			
4	0.00355	0.0027																																																																																																			
	0.04798	0.06593																																																																																																			
5	0.00059	0.00022																																																																																																			
	0.00791	0.00549																																																																																																			
6	0.00074	0.00018																																																																																																			
	0.00995	0.00440																																																																																																			
7	0.00002	0.00003																																																																																																			
	0.00026	0.00082																																																																																																			
8	0.00006	0.00003																																																																																																			
	0.00077	0.00082																																																																																																			
9	0.00006	0.00003																																																																																																			
	0.00077	0.00082																																																																																																			
10	0.36846	0.10693																																																																																																			
	0.31801	0.09011																																																																																																			
11	0.26939	0.41990																																																																																																			
	0.23252	0.35386																																																																																																			
12	0.06476	0.02217																																																																																																			
	0.05590	0.01868																																																																																																			
13	0.07127	0.22038																																																																																																			
	0.06151	0.18571																																																																																																			
14	0.13219	0.08476																																																																																																			
	0.11409	0.07143																																																																																																			
15	0.02750	0.02869																																																																																																			
	0.02374	0.02418																																																																																																			



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	16      0.03578      0.06781 0.03088      0.05714 17      0.00296      0.00098 0.00255      0.00082 18      0.00503      0.00522 0.00434      0.00440 19      0.01183      0.03651 0.01021      0.03077				
Chapter 4 Reference 4.4.2.6.2.4.1  Standard	4.4.2.6.2.4 <i>vmd bins</i>  The <i>vmd</i> of each encounter shall be taken from one of ten <i>vmd</i> bins for the non-crossing encounter classes, and from one of nine or ten <i>vmd</i> bins for the crossing encounter classes. Each <i>vmd</i> bin shall have an extent of 100 ft for calculating risk ratio, or an extent of 200 ft for calculating compatibility with ATM. The maximum <i>vmd</i> shall be 1 000 ft for calculating risk ratio, and 2 000 ft otherwise.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																												
Chapter 4 Reference 4.4.2.6.2.4.2  Standard	<p>For non-crossing encounter classes, the relative weights of the <i>vmd</i> bins shall be as follows:</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="text-align: right;"><i>vmd bin</i></td> <td style="text-align: center;"><i>for calculating risk ratio</i></td> <td style="text-align: center;"><i>for</i></td> <td style="text-align: center;"><i>ATM compatibility</i></td> </tr> <tr> <td>1</td> <td style="text-align: center;">0.013</td> <td style="text-align: center;">0.128</td> <td></td> </tr> <tr> <td>2</td> <td style="text-align: center;">0.026</td> <td style="text-align: center;">0.135</td> <td></td> </tr> <tr> <td>3</td> <td style="text-align: center;">0.035</td> <td style="text-align: center;">0.209</td> <td></td> </tr> <tr> <td>4</td> <td style="text-align: center;">0.065</td> <td style="text-align: center;">0.171</td> <td></td> </tr> <tr> <td>5</td> <td style="text-align: center;">0.100</td> <td style="text-align: center;">0.160</td> <td></td> </tr> <tr> <td>6</td> <td style="text-align: center;">0.161</td> <td style="text-align: center;">0.092</td> <td></td> </tr> <tr> <td>7</td> <td style="text-align: center;">0.113</td> <td style="text-align: center;">0.043</td> <td></td> </tr> <tr> <td>8</td> <td style="text-align: center;">0.091</td> <td style="text-align: center;">0.025</td> <td></td> </tr> <tr> <td>9</td> <td style="text-align: center;">0.104</td> <td style="text-align: center;">0.014</td> <td></td> </tr> <tr> <td>10</td> <td style="text-align: center;">0.091</td> <td style="text-align: center;">0.009</td> <td></td> </tr> </table> <p><i>Note.— The weights for the vmd bins do not sum to 1.0. The weights specified are based on an analysis of encounters captured in ATC ground radar data. The missing proportion reflects the fact that the encounters captured included some with vmd exceeding the maximum vmd in the model.</i></p>	<i>vmd bin</i>	<i>for calculating risk ratio</i>	<i>for</i>	<i>ATM compatibility</i>	1	0.013	0.128		2	0.026	0.135		3	0.035	0.209		4	0.065	0.171		5	0.100	0.160		6	0.161	0.092		7	0.113	0.043		8	0.091	0.025		9	0.104	0.014		10	0.091	0.009		CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>vmd bin</i>	<i>for calculating risk ratio</i>	<i>for</i>	<i>ATM compatibility</i>																																														
1	0.013	0.128																																															
2	0.026	0.135																																															
3	0.035	0.209																																															
4	0.065	0.171																																															
5	0.100	0.160																																															
6	0.161	0.092																																															
7	0.113	0.043																																															
8	0.091	0.025																																															
9	0.104	0.014																																															
10	0.091	0.009																																															



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																				
Chapter 4 Reference 4.4.2.6.2.4.3  Standard	For the crossing classes, the relative weights of the <i>vmd</i> bins shall be as follows:  <table border="0" style="margin-left: 40px;"> <tr> <td style="padding-right: 20px;"><i>vmd bin</i></td> <td style="padding-right: 20px;"><i>for calculating risk ratio</i></td> <td><i>for</i></td> </tr> <tr> <td colspan="3" style="text-align: center;"><i>ATM compatibility</i></td> </tr> <tr><td>1</td><td>0</td><td>0.064</td></tr> <tr><td>2</td><td>0.026</td><td>0.144</td></tr> <tr><td>3</td><td>0.036</td><td>0.224</td></tr> <tr><td>4</td><td>0.066</td><td>0.183</td></tr> <tr><td>5</td><td>0.102</td><td>0.171</td></tr> <tr><td>6</td><td>0.164</td><td>0.098</td></tr> <tr><td>7</td><td>0.115</td><td>0.046</td></tr> <tr><td>8</td><td>0.093</td><td>0.027</td></tr> <tr><td>9</td><td>0.106</td><td>0.015</td></tr> <tr><td>10</td><td>0.093</td><td>0.010</td></tr> </table> <p style="margin-left: 40px;"><i>Note.— For the crossing classes, vmd must exceed 100 ft so that the encounter qualifies as a crossing encounter. Thus, for the calculation of risk ratio there is no vmd bin 1, and for calculations of the compatibility with ATM vmd bin 1 is limited to [100 ft, 200 ft].</i></p>	<i>vmd bin</i>	<i>for calculating risk ratio</i>	<i>for</i>	<i>ATM compatibility</i>			1	0	0.064	2	0.026	0.144	3	0.036	0.224	4	0.066	0.183	5	0.102	0.171	6	0.164	0.098	7	0.115	0.046	8	0.093	0.027	9	0.106	0.015	10	0.093	0.010	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>vmd bin</i>	<i>for calculating risk ratio</i>	<i>for</i>																																							
<i>ATM compatibility</i>																																									
1	0	0.064																																							
2	0.026	0.144																																							
3	0.036	0.224																																							
4	0.066	0.183																																							
5	0.102	0.171																																							
6	0.164	0.098																																							
7	0.115	0.046																																							
8	0.093	0.027																																							
9	0.106	0.015																																							
10	0.093	0.010																																							
Chapter 4 Reference 4.4.2.6.3.1  Standard	<p style="margin-left: 40px;"><i>4.4.2.6.3 CHARACTERISTICS OF THE AIRCRAFT TRAJECTORIES IN THE VERTICAL PLANE</i></p> <p style="margin-left: 40px;"><i>vmd.</i> The <i>vmd</i> for each encounter shall be selected randomly from a distribution that is uniform in the interval covered by the appropriate <i>vmd</i> bin.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																																						





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference												
Chapter 4 Reference 4.4.2.6.3.2.1  Standard	4.4.2.6.3.2 <i>Vertical rate</i>  For each aircraft in each encounter, either the vertical rate shall be constant ( $\dot{z}$ ) or the vertical trajectory shall be constructed so that the vertical rate at $tca - 35$ s is $\dot{z}_1$ , and the vertical rate at $tca + 5$ s is $\dot{z}_2$ . Each vertical rate, $\dot{z}$ , $\dot{z}_1$ or $\dot{z}_2$ , shall be determined by first selecting randomly an interval within which it lies and then selecting the precise value from a distribution that is uniform over the interval selected.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference														
Chapter 4 Reference 4.4.2.6.3.2.2  Standard	The intervals within which the vertical rates lie shall depend on whether the aircraft is level, i.e. marked "L" in 4.4.2.6.2.3.1, or transitioning, i.e. marked "T" in 4.4.2.6.2.3.1, and shall be as follows:  <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center; width: 50%;"><i>L</i></td> <td style="text-align: center; width: 50%;"><i>T</i></td> </tr> <tr> <td style="text-align: center;">[240 ft/min, 400 ft/min] 6000 ft/min]</td> <td style="text-align: center;">[3200 ft/min, 400 ft/min,</td> </tr> <tr> <td style="text-align: center;">[80 ft/min, 240 ft/min] 3200 ft/min]</td> <td style="text-align: center;">[400 ft/min,</td> </tr> <tr> <td style="text-align: center;">[-80 ft/min, 80 ft/min] 400 ft/min]</td> <td style="text-align: center;">[-400 ft/min,</td> </tr> <tr> <td style="text-align: center;">[-240 ft/min, 80 ft/min] ft/min, 400 ft/min]</td> <td style="text-align: center;">[-3 200</td> </tr> <tr> <td style="text-align: center;">[-400 ft/min, 240 ft/min] ft/min, 3200 ft/min]</td> <td style="text-align: center;">[-6 000</td> </tr> </table>	<i>L</i>	<i>T</i>	[240 ft/min, 400 ft/min] 6000 ft/min]	[3200 ft/min, 400 ft/min,	[80 ft/min, 240 ft/min] 3200 ft/min]	[400 ft/min,	[-80 ft/min, 80 ft/min] 400 ft/min]	[-400 ft/min,	[-240 ft/min, 80 ft/min] ft/min, 400 ft/min]	[-3 200	[-400 ft/min, 240 ft/min] ft/min, 3200 ft/min]	[-6 000	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>L</i>	<i>T</i>																
[240 ft/min, 400 ft/min] 6000 ft/min]	[3200 ft/min, 400 ft/min,																
[80 ft/min, 240 ft/min] 3200 ft/min]	[400 ft/min,																
[-80 ft/min, 80 ft/min] 400 ft/min]	[-400 ft/min,																
[-240 ft/min, 80 ft/min] ft/min, 400 ft/min]	[-3 200																
[-400 ft/min, 240 ft/min] ft/min, 3200 ft/min]	[-6 000																



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference												
Chapter 4 Reference 4.4.2.6.3.2.3  Standard	For aircraft that are level over the entire encounter window, the vertical rate $\dot{z}$ shall be constant. The probabilities for the intervals within which $\dot{z}$ lies shall be as follows:  <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;"><math>\dot{z}</math> (ft/min)</td> <td style="text-align: center;"><math>prob(\dot{z})</math></td> </tr> <tr> <td style="text-align: center;">[240 ft/min, 400 ft/min]</td> <td style="text-align: center;">0.0382</td> </tr> <tr> <td style="text-align: center;">[80 ft/min, 240 ft/min]</td> <td style="text-align: center;">0.0989</td> </tr> <tr> <td style="text-align: center;">[80 ft/min, 80 ft/min]</td> <td style="text-align: center;">0.7040</td> </tr> <tr> <td style="text-align: center;">[-240 ft/min, 80 ft/min]</td> <td style="text-align: center;">0.1198</td> </tr> <tr> <td style="text-align: center;">[-400 ft/min, 240 ft/min]</td> <td style="text-align: center;">0.0391</td> </tr> </table>	$\dot{z}$ (ft/min)	$prob(\dot{z})$	[240 ft/min, 400 ft/min]	0.0382	[80 ft/min, 240 ft/min]	0.0989	[80 ft/min, 80 ft/min]	0.7040	[-240 ft/min, 80 ft/min]	0.1198	[-400 ft/min, 240 ft/min]	0.0391	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
$\dot{z}$ (ft/min)	$prob(\dot{z})$																
[240 ft/min, 400 ft/min]	0.0382																
[80 ft/min, 240 ft/min]	0.0989																
[80 ft/min, 80 ft/min]	0.7040																
[-240 ft/min, 80 ft/min]	0.1198																
[-400 ft/min, 240 ft/min]	0.0391																



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																								
Chapter 4 Reference 4.4.2.6.3.2.4  Standard	<p>For aircraft that are not level over the entire encounter window, the intervals for <math>z_1</math> and <math>z_2</math> shall be determined jointly by random selection using joint probabilities that depend on altitude layer and on whether the aircraft is transitioning at the beginning of the encounter window (Rate-to-Level), at the end of the encounter window (Level-to-Rate) or at both the beginning and the end (Rate-to-Rate). The joint probabilities for the vertical rate intervals shall be as follows:</p> <p>for aircraft with Rate-to-Level trajectories in layers 1 to 3,</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"><i>z<sub>2</sub> interval</i></td> <td colspan="3" style="text-align: center;"><i>joint probability of z<sub>1</sub> and z<sub>2</sub> interval</i></td> </tr> <tr> <td>[240 ft/min, 400 ft/min]</td> <td style="text-align: center;">0.0019</td> <td style="text-align: center;">0.0169</td> <td style="text-align: center;">0.0131</td> </tr> <tr> <td></td> <td style="text-align: center;">0.1554</td> <td style="text-align: center;">0.0000</td> <td></td> </tr> <tr> <td>[80 ft/min, 240 ft/min]</td> <td style="text-align: center;">0.0000</td> <td style="text-align: center;">0.0187</td> <td style="text-align: center;">0.0019</td> </tr> <tr> <td></td> <td style="text-align: center;">0.1086</td> <td style="text-align: center;">0.0000</td> <td></td> </tr> <tr> <td>[-80 ft/min, 80 ft/min]</td> <td style="text-align: center;">0.0037</td> <td style="text-align: center;">0.1684</td> <td style="text-align: center;">0.0094</td> </tr> <tr> <td></td> <td style="text-align: center;">0.1124</td> <td style="text-align: center;">0.0075</td> <td></td> </tr> <tr> <td>[-240 ft/min, -80 ft/min]</td> <td style="text-align: center;">0.0037</td> <td style="text-align: center;">0.1461</td> <td style="text-align: center;">0.0094</td> </tr> <tr> <td></td> <td style="text-align: center;">0.0243</td> <td style="text-align: center;">0.0037</td> <td></td> </tr> <tr> <td>[-400 ft/min, -240 ft/min]</td> <td style="text-align: center;">0.0000</td> <td style="text-align: center;">0.1742</td> <td style="text-align: center;">0.0094</td> </tr> <tr> <td></td> <td style="text-align: center;">0.0094</td> <td style="text-align: center;">0.0019</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">-6 000 ft/min</td> <td style="text-align: center;">-3 200 ft/min</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">-400 ft/min</td> <td style="text-align: center;">400 ft/min</td> <td style="text-align: center;">3</td> </tr> <tr> <td>200 ft/min</td> <td style="text-align: center;">6 000 ft/min</td> <td style="text-align: center;"><math>z_1</math></td> <td></td> </tr> </table> <p>for aircraft with Rate-to-Level trajectories in layers 4 to 6,</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"><i>z<sub>2</sub> interval</i></td> <td colspan="3" style="text-align: center;"><i>joint probability of z<sub>1</sub> and z<sub>2</sub> interval</i></td> </tr> <tr> <td>[240 ft/min, 400 ft/min]</td> <td style="text-align: center;">0.0105</td> <td style="text-align: center;">0.0035</td> <td style="text-align: center;">0.0000</td> </tr> <tr> <td></td> <td style="text-align: center;">0.1010</td> <td style="text-align: center;">0.0105</td> <td></td> </tr> <tr> <td>[80 ft/min, 240 ft/min]</td> <td style="text-align: center;">0.0035</td> <td style="text-align: center;">0.0418</td> <td style="text-align: center;">0.0035</td> </tr> <tr> <td></td> <td style="text-align: center;">0.1776</td> <td style="text-align: center;">0.0279</td> <td></td> </tr> <tr> <td>[-80 ft/min, 80 ft/min]</td> <td style="text-align: center;">0.0279</td> <td style="text-align: center;">0.1219</td> <td style="text-align: center;">0.0000</td> </tr> <tr> <td></td> <td style="text-align: center;">0.2403</td> <td style="text-align: center;">0.0139</td> <td></td> </tr> <tr> <td>[-240 ft/min, -80 ft/min]</td> <td style="text-align: center;">0.0035</td> <td style="text-align: center;">0.0767</td> <td style="text-align: center;">0.0000</td> </tr> </table>	<i>z<sub>2</sub> interval</i>	<i>joint probability of z<sub>1</sub> and z<sub>2</sub> interval</i>			[240 ft/min, 400 ft/min]	0.0019	0.0169	0.0131		0.1554	0.0000		[80 ft/min, 240 ft/min]	0.0000	0.0187	0.0019		0.1086	0.0000		[-80 ft/min, 80 ft/min]	0.0037	0.1684	0.0094		0.1124	0.0075		[-240 ft/min, -80 ft/min]	0.0037	0.1461	0.0094		0.0243	0.0037		[-400 ft/min, -240 ft/min]	0.0000	0.1742	0.0094		0.0094	0.0019			-6 000 ft/min	-3 200 ft/min			-400 ft/min	400 ft/min	3	200 ft/min	6 000 ft/min	$z_1$		<i>z<sub>2</sub> interval</i>	<i>joint probability of z<sub>1</sub> and z<sub>2</sub> interval</i>			[240 ft/min, 400 ft/min]	0.0105	0.0035	0.0000		0.1010	0.0105		[80 ft/min, 240 ft/min]	0.0035	0.0418	0.0035		0.1776	0.0279		[-80 ft/min, 80 ft/min]	0.0279	0.1219	0.0000		0.2403	0.0139		[-240 ft/min, -80 ft/min]	0.0035	0.0767	0.0000	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>z<sub>2</sub> interval</i>	<i>joint probability of z<sub>1</sub> and z<sub>2</sub> interval</i>																																																																																												
[240 ft/min, 400 ft/min]	0.0019	0.0169	0.0131																																																																																										
	0.1554	0.0000																																																																																											
[80 ft/min, 240 ft/min]	0.0000	0.0187	0.0019																																																																																										
	0.1086	0.0000																																																																																											
[-80 ft/min, 80 ft/min]	0.0037	0.1684	0.0094																																																																																										
	0.1124	0.0075																																																																																											
[-240 ft/min, -80 ft/min]	0.0037	0.1461	0.0094																																																																																										
	0.0243	0.0037																																																																																											
[-400 ft/min, -240 ft/min]	0.0000	0.1742	0.0094																																																																																										
	0.0094	0.0019																																																																																											
	-6 000 ft/min	-3 200 ft/min																																																																																											
	-400 ft/min	400 ft/min	3																																																																																										
200 ft/min	6 000 ft/min	$z_1$																																																																																											
<i>z<sub>2</sub> interval</i>	<i>joint probability of z<sub>1</sub> and z<sub>2</sub> interval</i>																																																																																												
[240 ft/min, 400 ft/min]	0.0105	0.0035	0.0000																																																																																										
	0.1010	0.0105																																																																																											
[80 ft/min, 240 ft/min]	0.0035	0.0418	0.0035																																																																																										
	0.1776	0.0279																																																																																											
[-80 ft/min, 80 ft/min]	0.0279	0.1219	0.0000																																																																																										
	0.2403	0.0139																																																																																											
[-240 ft/min, -80 ft/min]	0.0035	0.0767	0.0000																																																																																										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>0.0488 0.0105</p> <p>[−400 ft/min, −240 ft/min]      0.0105    0.0453    0.0035</p> <p>0.0174 0.0000</p> <p>−6 000 ft/min      −3 200 ft/min</p> <p>−400 ft/min      400 ft/min      3</p> <p>200 ft/min      6 000 ft/min      <math>\dot{z}_1</math></p> <p>for aircraft with Level-to-Rate trajectories in layers 1 to 3, <i>z</i><sub>2</sub> interval      joint probability of <math>\dot{z}_1</math> and <i>z</i><sub>2</sub> interval</p> <p>[3 200 ft/min, 6000 ft/min]      0.0000    0.0000    0.0000</p> <p>0.0000 0.0000</p> <p>[400 ft/min, 3200 ft/min]      0.0074    0.0273    0.0645</p> <p>0.0720 0.1538</p> <p>[−400 ft/min, 400 ft/min]      0.0000    0.0000    0.0000</p> <p>0.0000 0.0000</p> <p>[−3 200 ft/min, −400 ft/min]      0.2978    0.2084    0.1365</p> <p>0.0273 0.005</p> <p>[−6 000ft/min, −3 200ft/min]      0.0000    0.0000    0.0000</p> <p>0.0000 0.0000</p> <p>−400 ft/min      −240 ft/min      −80</p> <p>ft/min      80 ft/min      240 ft/min      400</p> <p>ft/min      <math>\dot{z}_1</math></p> <p>for aircraft with Level-to-Rate trajectories in layers 4 to 6, <i>z</i><sub>2</sub> interval      joint probability of <math>\dot{z}_1</math> and <i>z</i><sub>2</sub> interval</p> <p>[3 200 ft/min, 6 000 ft/min]      0.0000    0.0000    0.0000</p> <p>0.0000 0.0192</p> <p>[400 ft/min, 3 200 ft/min]      0.0000    0.0000    0.0962</p> <p>0.0577 0.1154</p> <p>[−400 ft/min, 400 ft/min]      0.0000    0.0000    0.0000</p> <p>0.0000 0.0000</p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 4 Reference 4.4.2.6.3.2.5  Standard	For a Rate-to-Rate track, if line $ \dot{z}_2 - \dot{z}_1  < 566$ ft/min then the track shall be constructed with a constant rate equal to $\dot{z}_1$ .	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference												
Chapter 4 Reference 4.4.2.6.3.3.1  Standard	4.4.2.6.3.3 <i>Vertical acceleration</i>  Subject to 4.4.2.6.3.2.5, for aircraft that are not level over the entire encounter window, the rate shall be constant and equal to $\dot{z}_1$ over at least the interval $[tca - 40 \text{ s}, tca - 35 \text{ s}]$ at the beginning of the encounter window, and shall be constant and equal to $\dot{z}_2$ over at least the interval $[tca + 5 \text{ s}, tca + 10 \text{ s}]$ at the end of the encounter window. The vertical acceleration shall be constant in the intervening period.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference												
Chapter 4 Reference 4.4.2.6.3.3.2  Standard	The vertical acceleration() shall be modelled as follows: $= (A\dot{z}_2 - \dot{z}_1) + \varepsilon$ where the parameter $A$ is case-dependent as follows: <table data-bbox="462 1039 903 1315" style="margin-left: 100px;"> <tr> <td style="text-align: right;"><i>Case</i></td> <td style="text-align: left;"><i>A(s-l)</i></td> </tr> <tr> <td style="text-align: right;">Rate-to-Level</td> <td style="text-align: left;">Layers 1-3 Layers 4-6</td> </tr> <tr> <td style="text-align: right;">Level-to-Rate</td> <td style="text-align: left;">0.071 0.059</td> </tr> <tr> <td style="text-align: right;">Rate-to-Rate</td> <td style="text-align: left;">0.089 0.075</td> </tr> <tr> <td style="text-align: right;">Rate-to-Rate</td> <td style="text-align: left;">0.083 0.072</td> </tr> </table> and the error $\varepsilon$ is selected randomly using the following probability density:	<i>Case</i>	<i>A(s-l)</i>	Rate-to-Level	Layers 1-3 Layers 4-6	Level-to-Rate	0.071 0.059	Rate-to-Rate	0.089 0.075	Rate-to-Rate	0.083 0.072	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Case</i>	<i>A(s-l)</i>														
Rate-to-Level	Layers 1-3 Layers 4-6														
Level-to-Rate	0.071 0.059														
Rate-to-Rate	0.089 0.075														
Rate-to-Rate	0.083 0.072														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.2.6.3.4  Standard	<i>Acceleration start time.</i> The acceleration start time shall be distributed uniformly in the time interval [ $tca - 35$ s, $tca - 5$ s] and shall be such that $\dot{z}_2$ is achieved no later than $tca + 5$ s.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.4.2.6.4.1.1  Standard	4.4.2.6.4 CHARACTERISTICS OF THE AIRCRAFT TRAJECTORIES IN THE HORIZONTAL PLANE  4.4.2.6.4.1 Horizontal miss distance  For calculations of the effect of ACAS on the risk of collision (4.4.3), hmd shall be uniformly distributed in the range [0, 500 ft].	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																																																																																						
Chapter 4 Reference 4.4.2.6.4.1.2  Standard	<p>For calculations concerning the compatibility of ACAS with ATM (4.4.4), <i>hmd</i> shall be distributed so that the values of <i>hmd</i> have the following cumulative probabilities:</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;"><i>cumulative probability</i></td> <td colspan="2" style="text-align: center;"><i>cumulative probability</i></td> <td></td> </tr> <tr> <td style="text-align: left;"><i>hmd (ft)</i></td> <td style="text-align: center;"><i>Layers 1-3</i></td> <td style="text-align: center;"><i>Layers 4-6</i></td> <td style="text-align: center;"><i>Layers 4-6</i></td> <td style="text-align: right;"><i>hmd (ft)</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>Layers 1-3</i></td> <td style="text-align: center;"><i>Layers 4-6</i></td> <td></td> <td></td> </tr> <tr> <td>0</td> <td style="text-align: center;">0.000</td> <td style="text-align: center;">0.000</td> <td></td> <td style="text-align: right;">17013</td> </tr> <tr> <td></td> <td style="text-align: center;">0.999</td> <td style="text-align: center;">0.868</td> <td></td> <td></td> </tr> <tr> <td>1215</td> <td style="text-align: center;">0.152</td> <td style="text-align: center;">0.125</td> <td></td> <td style="text-align: right;">18228</td> </tr> <tr> <td></td> <td style="text-align: center;">1.000</td> <td style="text-align: center;">0.897</td> <td></td> <td></td> </tr> <tr> <td>2430</td> <td style="text-align: center;">0.306</td> <td style="text-align: center;">0.195</td> <td></td> <td style="text-align: right;">19443</td> </tr> <tr> <td></td> <td style="text-align: center;">0.916</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3646</td> <td style="text-align: center;">0.482</td> <td style="text-align: center;">0.260</td> <td></td> <td style="text-align: right;">20659</td> </tr> <tr> <td></td> <td style="text-align: center;">0.927</td> <td></td> <td></td> <td></td> </tr> <tr> <td>4860</td> <td style="text-align: center;">0.631</td> <td style="text-align: center;">0.322</td> <td></td> <td style="text-align: right;">21874</td> </tr> <tr> <td></td> <td style="text-align: center;">0.939</td> <td></td> <td></td> <td></td> </tr> <tr> <td>6076</td> <td style="text-align: center;">0.754</td> <td style="text-align: center;">0.398</td> <td></td> <td style="text-align: right;">23089</td> </tr> <tr> <td></td> <td style="text-align: center;">0.946</td> <td></td> <td></td> <td></td> </tr> <tr> <td>7921</td> <td style="text-align: center;">0.859</td> <td style="text-align: center;">0.469</td> <td></td> <td style="text-align: right;">24304</td> </tr> <tr> <td></td> <td style="text-align: center;">0.952</td> <td></td> <td></td> <td></td> </tr> <tr> <td>8506</td> <td style="text-align: center;">0.919</td> <td style="text-align: center;">0.558</td> <td></td> <td style="text-align: right;">25520</td> </tr> <tr> <td></td> <td style="text-align: center;">0.965</td> <td></td> <td></td> <td></td> </tr> <tr> <td>9722</td> <td style="text-align: center;">0.954</td> <td style="text-align: center;">0.624</td> <td></td> <td style="text-align: right;">26735</td> </tr> <tr> <td></td> <td style="text-align: center;">0.983</td> <td></td> <td></td> <td></td> </tr> <tr> <td>10937</td> <td style="text-align: center;">0.972</td> <td style="text-align: center;">0.692</td> <td></td> <td style="text-align: right;">27950</td> </tr> <tr> <td></td> <td style="text-align: center;">0.993</td> <td></td> <td></td> <td></td> </tr> <tr> <td>12152</td> <td style="text-align: center;">0.982</td> <td style="text-align: center;">0.753</td> <td></td> <td style="text-align: right;">29165</td> </tr> <tr> <td></td> <td style="text-align: center;">0.996</td> <td></td> <td></td> <td></td> </tr> <tr> <td>13367</td> <td style="text-align: center;">0.993</td> <td style="text-align: center;">0.801</td> <td></td> <td style="text-align: right;">30381</td> </tr> <tr> <td></td> <td style="text-align: center;">0.999</td> <td></td> <td></td> <td></td> </tr> <tr> <td>14582</td> <td style="text-align: center;">0.998</td> <td style="text-align: center;">0.821</td> <td></td> <td style="text-align: right;">31596</td> </tr> <tr> <td></td> <td style="text-align: center;">1.000</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15798</td> <td style="text-align: center;">0.999</td> <td style="text-align: center;">0.848</td> <td></td> <td></td> </tr> </table>	<i>cumulative probability</i>		<i>cumulative probability</i>			<i>hmd (ft)</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>	<i>Layers 4-6</i>	<i>hmd (ft)</i>		<i>Layers 1-3</i>	<i>Layers 4-6</i>			0	0.000	0.000		17013		0.999	0.868			1215	0.152	0.125		18228		1.000	0.897			2430	0.306	0.195		19443		0.916				3646	0.482	0.260		20659		0.927				4860	0.631	0.322		21874		0.939				6076	0.754	0.398		23089		0.946				7921	0.859	0.469		24304		0.952				8506	0.919	0.558		25520		0.965				9722	0.954	0.624		26735		0.983				10937	0.972	0.692		27950		0.993				12152	0.982	0.753		29165		0.996				13367	0.993	0.801		30381		0.999				14582	0.998	0.821		31596		1.000				15798	0.999	0.848			CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>cumulative probability</i>		<i>cumulative probability</i>																																																																																																																																																									
<i>hmd (ft)</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>	<i>Layers 4-6</i>	<i>hmd (ft)</i>																																																																																																																																																							
	<i>Layers 1-3</i>	<i>Layers 4-6</i>																																																																																																																																																									
0	0.000	0.000		17013																																																																																																																																																							
	0.999	0.868																																																																																																																																																									
1215	0.152	0.125		18228																																																																																																																																																							
	1.000	0.897																																																																																																																																																									
2430	0.306	0.195		19443																																																																																																																																																							
	0.916																																																																																																																																																										
3646	0.482	0.260		20659																																																																																																																																																							
	0.927																																																																																																																																																										
4860	0.631	0.322		21874																																																																																																																																																							
	0.939																																																																																																																																																										
6076	0.754	0.398		23089																																																																																																																																																							
	0.946																																																																																																																																																										
7921	0.859	0.469		24304																																																																																																																																																							
	0.952																																																																																																																																																										
8506	0.919	0.558		25520																																																																																																																																																							
	0.965																																																																																																																																																										
9722	0.954	0.624		26735																																																																																																																																																							
	0.983																																																																																																																																																										
10937	0.972	0.692		27950																																																																																																																																																							
	0.993																																																																																																																																																										
12152	0.982	0.753		29165																																																																																																																																																							
	0.996																																																																																																																																																										
13367	0.993	0.801		30381																																																																																																																																																							
	0.999																																																																																																																																																										
14582	0.998	0.821		31596																																																																																																																																																							
	1.000																																																																																																																																																										
15798	0.999	0.848																																																																																																																																																									



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																
Chapter 4 Reference 4.4.2.6.4.2  Standard	<p><i>Approach angle.</i> The cumulative distribution for the horizontal approach angle shall be as follows:</p> <table border="1"> <thead> <tr> <th><i>approach angle (deg.)</i></th> <th><i>cumulative probability Layers 1-3</i></th> <th><i>cumulative probability Layers 4-6</i></th> <th><i>approach angle (deg.)</i></th> </tr> </thead> <tbody> <tr><td>0</td><td>0.00</td><td>0.00</td><td>100</td></tr> <tr><td></td><td>0.28</td><td></td><td></td></tr> <tr><td>10</td><td>0.14</td><td>0.05</td><td>110</td></tr> <tr><td></td><td>0.31</td><td></td><td></td></tr> <tr><td>20</td><td>0.17</td><td>0.06</td><td>120</td></tr> <tr><td></td><td>0.35</td><td></td><td></td></tr> <tr><td>30</td><td>0.18</td><td>0.08</td><td>130</td></tr> <tr><td></td><td>0.43</td><td></td><td></td></tr> <tr><td>40</td><td>0.19</td><td>0.08</td><td>140</td></tr> <tr><td></td><td>0.50</td><td></td><td></td></tr> <tr><td>50</td><td>0.21</td><td>0.10</td><td>150</td></tr> <tr><td></td><td>0.59</td><td></td><td></td></tr> <tr><td>60</td><td>0.23</td><td>0.13</td><td>160</td></tr> <tr><td></td><td>0.66</td><td></td><td></td></tr> <tr><td>70</td><td>0.25</td><td>0.14</td><td>170</td></tr> <tr><td></td><td>0.79</td><td></td><td></td></tr> <tr><td>80</td><td>0.28</td><td>0.19</td><td>180</td></tr> <tr><td></td><td>1.00</td><td></td><td></td></tr> <tr><td>90</td><td>0.32</td><td>0.22</td><td></td></tr> </tbody> </table>	<i>approach angle (deg.)</i>	<i>cumulative probability Layers 1-3</i>	<i>cumulative probability Layers 4-6</i>	<i>approach angle (deg.)</i>	0	0.00	0.00	100		0.28			10	0.14	0.05	110		0.31			20	0.17	0.06	120		0.35			30	0.18	0.08	130		0.43			40	0.19	0.08	140		0.50			50	0.21	0.10	150		0.59			60	0.23	0.13	160		0.66			70	0.25	0.14	170		0.79			80	0.28	0.19	180		1.00			90	0.32	0.22		CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>approach angle (deg.)</i>	<i>cumulative probability Layers 1-3</i>	<i>cumulative probability Layers 4-6</i>	<i>approach angle (deg.)</i>																																																																																		
0	0.00	0.00	100																																																																																		
	0.28																																																																																				
10	0.14	0.05	110																																																																																		
	0.31																																																																																				
20	0.17	0.06	120																																																																																		
	0.35																																																																																				
30	0.18	0.08	130																																																																																		
	0.43																																																																																				
40	0.19	0.08	140																																																																																		
	0.50																																																																																				
50	0.21	0.10	150																																																																																		
	0.59																																																																																				
60	0.23	0.13	160																																																																																		
	0.66																																																																																				
70	0.25	0.14	170																																																																																		
	0.79																																																																																				
80	0.28	0.19	180																																																																																		
	1.00																																																																																				
90	0.32	0.22																																																																																			





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																																																																																
Chapter 4  Reference 4.4.2.6.4.3  Standard	<p><i>Aircraft speed.</i> The cumulative distribution for each aircraft's horizontal ground speed at closest approach shall be as follows:</p> <table border="0" data-bbox="275 435 938 1352"> <tr> <td style="text-align: right;"><i>ground</i></td> <td style="text-align: center;"><i>cumulative probability</i></td> <td style="text-align: center;"><i>ground</i></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>cumulative probability</i></td> <td></td> <td></td> </tr> <tr> <td style="text-align: right;"><i>speed (kt)</i></td> <td style="text-align: center;"><i>Layers 1-3</i></td> <td style="text-align: center;"><i>Layers 4-6</i></td> <td style="text-align: right;"><i>speed (kt)</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>Layers 1-3</i></td> <td style="text-align: center;"><i>Layers 4-6</i></td> <td></td> </tr> <tr><td>45</td><td>0.000</td><td></td><td>325 0.977</td></tr> <tr><td></td><td>0.528</td><td></td><td></td></tr> <tr><td>50</td><td>0.005</td><td></td><td>350 0.988</td></tr> <tr><td></td><td>0.602</td><td></td><td></td></tr> <tr><td>75</td><td>0.024</td><td>0.000</td><td>375 0.997</td></tr> <tr><td></td><td>0.692</td><td></td><td></td></tr> <tr><td>100</td><td>0.139</td><td>0.005</td><td>400 0.998</td></tr> <tr><td></td><td>0.813</td><td></td><td></td></tr> <tr><td>125</td><td>0.314</td><td>0.034</td><td>425 0.999</td></tr> <tr><td></td><td>0.883</td><td></td><td></td></tr> <tr><td>150</td><td>0.486</td><td>0.064</td><td>450 1.000</td></tr> <tr><td></td><td>0.940</td><td></td><td></td></tr> <tr><td>175</td><td>0.616</td><td>0.116</td><td>475</td></tr> <tr><td></td><td>0.972</td><td></td><td></td></tr> <tr><td>200</td><td>0.700</td><td>0.171</td><td>500</td></tr> <tr><td></td><td>0.987</td><td></td><td></td></tr> <tr><td>225</td><td>0.758</td><td>0.211</td><td>525</td></tr> <tr><td></td><td>0.993</td><td></td><td></td></tr> <tr><td>250</td><td>0.821</td><td>0.294</td><td>550</td></tr> <tr><td></td><td>0.998</td><td></td><td></td></tr> <tr><td>275</td><td>0.895</td><td>0.361</td><td>575</td></tr> <tr><td></td><td>0.999</td><td></td><td></td></tr> <tr><td>300</td><td>0.949</td><td>0.427</td><td>600</td></tr> <tr><td></td><td>1.000</td><td></td><td></td></tr> </table>	<i>ground</i>	<i>cumulative probability</i>	<i>ground</i>			<i>cumulative probability</i>			<i>speed (kt)</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>	<i>speed (kt)</i>		<i>Layers 1-3</i>	<i>Layers 4-6</i>		45	0.000		325 0.977		0.528			50	0.005		350 0.988		0.602			75	0.024	0.000	375 0.997		0.692			100	0.139	0.005	400 0.998		0.813			125	0.314	0.034	425 0.999		0.883			150	0.486	0.064	450 1.000		0.940			175	0.616	0.116	475		0.972			200	0.700	0.171	500		0.987			225	0.758	0.211	525		0.993			250	0.821	0.294	550		0.998			275	0.895	0.361	575		0.999			300	0.949	0.427	600		1.000			CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>ground</i>	<i>cumulative probability</i>	<i>ground</i>																																																																																																																			
	<i>cumulative probability</i>																																																																																																																				
<i>speed (kt)</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>	<i>speed (kt)</i>																																																																																																																		
	<i>Layers 1-3</i>	<i>Layers 4-6</i>																																																																																																																			
45	0.000		325 0.977																																																																																																																		
	0.528																																																																																																																				
50	0.005		350 0.988																																																																																																																		
	0.602																																																																																																																				
75	0.024	0.000	375 0.997																																																																																																																		
	0.692																																																																																																																				
100	0.139	0.005	400 0.998																																																																																																																		
	0.813																																																																																																																				
125	0.314	0.034	425 0.999																																																																																																																		
	0.883																																																																																																																				
150	0.486	0.064	450 1.000																																																																																																																		
	0.940																																																																																																																				
175	0.616	0.116	475																																																																																																																		
	0.972																																																																																																																				
200	0.700	0.171	500																																																																																																																		
	0.987																																																																																																																				
225	0.758	0.211	525																																																																																																																		
	0.993																																																																																																																				
250	0.821	0.294	550																																																																																																																		
	0.998																																																																																																																				
275	0.895	0.361	575																																																																																																																		
	0.999																																																																																																																				
300	0.949	0.427	600																																																																																																																		
	1.000																																																																																																																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																								
Chapter 4 Reference 4.4.2.6.4.4  Standard	<p><i>Horizontal manoeuvre probabilities.</i> For each aircraft in each encounter, the probability of a turn, the probability of a speed change given a turn, and the probability of a speed change given no turn shall be as follows:</p> <table border="0" style="margin-left: 40px;"> <tr> <td style="text-align: right;"><i>Layer</i></td> <td style="text-align: right;"><i>Prob(turn)</i></td> <td style="text-align: right;"><i>Prob(speed change)</i></td> <td></td> </tr> <tr> <td></td> <td style="text-align: right;"><i>given a turn</i></td> <td style="text-align: right;"><i>Prob(speed change)</i></td> <td style="text-align: right;"><i>given no turn</i></td> </tr> <tr> <td>1</td> <td style="text-align: right;">0.31</td> <td style="text-align: right;">0.20</td> <td style="text-align: right;">0.5</td> </tr> <tr> <td>2</td> <td style="text-align: right;">0.29</td> <td style="text-align: right;">0.20</td> <td style="text-align: right;">0.25</td> </tr> <tr> <td>3</td> <td style="text-align: right;">0.22</td> <td style="text-align: right;">0.10</td> <td style="text-align: right;">0.15</td> </tr> <tr> <td>4, 5, 6</td> <td style="text-align: right;">0.16</td> <td style="text-align: right;">0.05</td> <td style="text-align: right;">0.10</td> </tr> </table>	<i>Layer</i>	<i>Prob(turn)</i>	<i>Prob(speed change)</i>			<i>given a turn</i>	<i>Prob(speed change)</i>	<i>given no turn</i>	1	0.31	0.20	0.5	2	0.29	0.20	0.25	3	0.22	0.10	0.15	4, 5, 6	0.16	0.05	0.10	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Layer</i>	<i>Prob(turn)</i>	<i>Prob(speed change)</i>																											
	<i>given a turn</i>	<i>Prob(speed change)</i>	<i>given no turn</i>																										
1	0.31	0.20	0.5																										
2	0.29	0.20	0.25																										
3	0.22	0.10	0.15																										
4, 5, 6	0.16	0.05	0.10																										
Chapter 4 Reference 4.4.2.6.4.4.1  Standard	Given a speed change, the probability of a speed increase shall be 0.5 and the probability of a speed decrease shall be 0.5.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																										



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																											
Chapter 4 Reference 4.4.2.6.4.5  Standard	<p><i>Turn extent.</i> The cumulative distribution for the extent of any turn shall be as follows:</p> <p style="text-align: center;"><i>cumulative probability</i></p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><i>Turn extent (deg.)</i></th> <th style="text-align: left;"><i>Layers 1-3</i></th> <th style="text-align: left;"><i>Layers 4-6</i></th> </tr> </thead> <tbody> <tr><td>15</td><td>0.00</td><td>0.00</td></tr> <tr><td>30</td><td>0.43</td><td>0.58</td></tr> <tr><td>60</td><td>0.75</td><td>0.90</td></tr> <tr><td>90</td><td>0.88</td><td>0.97</td></tr> <tr><td>120</td><td>0.95</td><td>0.99</td></tr> <tr><td>150</td><td>0.98</td><td>1.00</td></tr> <tr><td>180</td><td>0.99</td><td></td></tr> <tr><td>210</td><td>1.00</td><td></td></tr> </tbody> </table>	<i>Turn extent (deg.)</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>	15	0.00	0.00	30	0.43	0.58	60	0.75	0.90	90	0.88	0.97	120	0.95	0.99	150	0.98	1.00	180	0.99		210	1.00		CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>Turn extent (deg.)</i>	<i>Layers 1-3</i>	<i>Layers 4-6</i>																														
15	0.00	0.00																														
30	0.43	0.58																														
60	0.75	0.90																														
90	0.88	0.97																														
120	0.95	0.99																														
150	0.98	1.00																														
180	0.99																															
210	1.00																															
Chapter 4 Reference 4.4.2.6.4.5.1  Standard	The direction of the turn shall be random, with the probability of a left turn being 0.5 and the probability of a right turn being 0.5.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference																													



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																											
Chapter 4 Reference 4.4.2.6.4.6	<p><i>Bank angle.</i> An aircraft's bank angle during a turn shall not be less than 15 degrees. The probability that it equals 15 degrees shall be 0.79 in layers 1-3 and 0.54 in layers 4-5. The cumulative distribution for larger bank angles shall be as follows:</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 30%; text-align: center;"><i>probability</i></td> <td style="width: 30%; text-align: center;"><i>cumulative</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>Bank angle (deg.)</i></td> <td style="text-align: center;"><i>Layers 1-3</i> <i>Layers 4-6</i></td> </tr> <tr> <td style="text-align: center;">15</td> <td></td> <td style="text-align: center;">0.79 0.54</td> </tr> <tr> <td style="text-align: center;">25</td> <td></td> <td style="text-align: center;">0.96 0.82</td> </tr> <tr> <td style="text-align: center;">35</td> <td></td> <td style="text-align: center;">0.99 0.98</td> </tr> <tr> <td style="text-align: center;">50</td> <td></td> <td style="text-align: center;">1.00 1.00</td> </tr> </table>		<i>probability</i>	<i>cumulative</i>		<i>Bank angle (deg.)</i>	<i>Layers 1-3</i> <i>Layers 4-6</i>	15		0.79 0.54	25		0.96 0.82	35		0.99 0.98	50		1.00 1.00	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference											
	<i>probability</i>	<i>cumulative</i>																														
	<i>Bank angle (deg.)</i>	<i>Layers 1-3</i> <i>Layers 4-6</i>																														
15		0.79 0.54																														
25		0.96 0.82																														
35		0.99 0.98																														
50		1.00 1.00																														
Chapter 4 Reference 4.4.2.6.4.7	<p><i>Turn end time.</i> The cumulative distribution for each aircraft's turn end time shall be as follows:</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;"></td> <td style="width: 30%; text-align: center;"><i>Turn end time (seconds before tca)</i></td> <td style="width: 30%; text-align: center;"><i>cumulative</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>Layers 1-3</i> <i>Layers 4-6</i></td> <td style="text-align: center;"><i>probability</i></td> </tr> <tr> <td style="text-align: center;">0</td> <td></td> <td style="text-align: center;">0.42 0.28</td> </tr> <tr> <td style="text-align: center;">5</td> <td></td> <td style="text-align: center;">0.64 0.65</td> </tr> <tr> <td style="text-align: center;">10</td> <td></td> <td style="text-align: center;">0.77 0.76</td> </tr> <tr> <td style="text-align: center;">15</td> <td></td> <td style="text-align: center;">0.86 0.85</td> </tr> <tr> <td style="text-align: center;">20</td> <td></td> <td style="text-align: center;">0.92 0.94</td> </tr> <tr> <td style="text-align: center;">25</td> <td></td> <td style="text-align: center;">0.98 0.99</td> </tr> <tr> <td style="text-align: center;">30</td> <td></td> <td style="text-align: center;">1.00 1.00</td> </tr> </table>		<i>Turn end time (seconds before tca)</i>	<i>cumulative</i>		<i>Layers 1-3</i> <i>Layers 4-6</i>	<i>probability</i>	0		0.42 0.28	5		0.64 0.65	10		0.77 0.76	15		0.86 0.85	20		0.92 0.94	25		0.98 0.99	30		1.00 1.00	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
	<i>Turn end time (seconds before tca)</i>	<i>cumulative</i>																														
	<i>Layers 1-3</i> <i>Layers 4-6</i>	<i>probability</i>																														
0		0.42 0.28																														
5		0.64 0.65																														
10		0.77 0.76																														
15		0.86 0.85																														
20		0.92 0.94																														
25		0.98 0.99																														
30		1.00 1.00																														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.2.6.4.8  Standard	<i>Speed change.</i> A constant acceleration or deceleration shall be randomly selected for each aircraft performing a speed change in a given encounter, and shall be applied for the duration of the encounter. Accelerations shall be uniformly distributed between 2 kt/s and 6 kt/s. Decelerations shall be uniformly distributed between 1 kt/s and 3 kt/s.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.2.7  Standard	<p style="text-align: center;"><b>ACAS EQUIPAGE OF THE INTRUDER</b></p> <p>The performance requirements specified in 4.4.3 and 4.4.4 each apply to three distinct situations in which the following conditions concerning the intruder's ACAS and trajectory shall apply:</p> <ul style="list-style-type: none"> <li>a) where the intruder involved in each encounter is not equipped (4.4.2.1 j) 1)), it follows a trajectory identical to that which it follows when own aircraft is not equipped;</li> <li>b) where the intruder is ACAS-equipped but follows a trajectory identical to that in the unequipped encounter (4.4.2.1 j) 2)): <ul style="list-style-type: none"> <li>1) it follows the identical trajectory regardless of whether or not there is an RA;</li> <li>2) the intruder ACAS generates an RA and transmits an RAC that is received immediately after any RA is first announced to the pilot of own aircraft;</li> <li>3) the sense of the RAC generated by the intruder ACAS and transmitted to own aircraft is opposite to the sense of the first RAC selected and transmitted to the intruder by own aircraft (4.3.6.1.3);</li> <li>4) the RAC transmitted by the intruder is received by own aircraft; and</li> <li>5) the requirements apply both when own aircraft has the lower aircraft address and when the intruder aircraft has the lower aircraft address; and</li> </ul> </li> <li>c) where the intruder is equipped with an ACAS having a collision avoidance logic identical to that of own ACAS (4.4.2.1 j) 3)): <ul style="list-style-type: none"> <li>6) the conditions relating to the performance of own aircraft, ACAS and pilot apply equally to the intruder aircraft, ACAS and pilot;</li> <li>7) RACs transmitted by one aircraft are received by the other; and</li> </ul> </li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	8) the requirements apply both when own aircraft has the lower aircraft address and when the intruder aircraft has the lower aircraft address.				
Chapter 4 Reference 4.4.2.8  Recommendation	<p align="center"><b>COMPATIBILITY BETWEEN DIFFERENT COLLISION AVOIDANCE LOGIC DESIGNS</b></p> <p><b>Recommendation.</b>— <i>When considering alternative collision avoidance logic designs, certification authorities should verify that:</i></p> <p>a) <i>the performances of the alternative design are acceptable in encounters involving ACAS units that use existing designs; and</i></p> <p>b) <i>the performances of the existing designs are not degraded by the use of the alternative design.</i></p> <p><i>Note.</i>— <i>To address the compatibility between different collision avoidance logic designs, the conditions described in 4.4.2.7 b) are the most severe that can be anticipated in this respect.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.4.3  Standard	<p align="center"><b>Reduction in the risk of collision</b></p> <p>Under the conditions of 4.4.2, the collision avoidance logic shall be such that the expected number of collisions is reduced to the following proportions of the number expected in the absence of ACAS:</p> <p>a) when the intruder is not ACAS equipped 0.18;</p> <p>b) when the intruder is equipped but does not respond 0.32; and</p> <p>c) when the intruder is equipped and responds 0.04.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference												
Chapter 4 Reference 4.4.4.1.1  Standard	<p><b>4.4.4 Compatibility with air traffic management (ATM)</b></p> <p>4.4.4.1 NUISANCE ALERT RATE</p> <p>Under the conditions of 4.4.2, the collision avoidance logic shall be such that the proportion of RAs which are a “nuisance” (4.4.4.1.2) shall not exceed:</p> <p>.06 when own aircraft’s vertical rate at the time the RA is first issued is less than 400 ft/min; or</p> <p>.08 when own aircraft’s vertical rate at the time the RA is first issued exceeds 400 ft/min.</p> <p><i>Note.— This requirement is not qualified by the ACAS equipage of the intruder (4.4.2.7) since it has negligible effect on the occurrence and frequency of nuisance RAs.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference														
Chapter 4 Reference 4.4.4.1.2  Standard	<p>An RA shall be considered a “nuisance” for the purposes of 4.4.4.1.1 unless, at some point in the encounter in the absence of ACAS, the horizontal separation and the vertical separation are simultaneously less than the following values:</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 20px;"><i>separation</i></td> <td style="padding-right: 20px;"><i>horizontal</i></td> <td></td> </tr> <tr> <td></td> <td><i>vertical separation</i></td> <td></td> </tr> <tr> <td><i>above FL100</i></td> <td>2.0 NM</td> <td>750 ft</td> </tr> <tr> <td><i>below FL100</i></td> <td>1.2 NM</td> <td>750 ft</td> </tr> </table>	<i>separation</i>	<i>horizontal</i>			<i>vertical separation</i>		<i>above FL100</i>	2.0 NM	750 ft	<i>below FL100</i>	1.2 NM	750 ft	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
<i>separation</i>	<i>horizontal</i>																
	<i>vertical separation</i>																
<i>above FL100</i>	2.0 NM	750 ft															
<i>below FL100</i>	1.2 NM	750 ft															





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.4.2  Standard	<p style="text-align: center;">COMPATIBLE SENSE SELECTION</p> <p>Under the conditions of 4.4.2, the collision avoidance logic shall be such that the proportion of encounters in which following the RA results in an altitude separation at closest approach with the opposite sign to that occurring in the absence of ACAS shall not exceed the following values:</p> <ul style="list-style-type: none"> <li>a) when the intruder is not ACAS equipped 0.08;</li> <li>b) when the intruder is equipped but does not respond 0.08; and</li> <li>c) when the intruder is equipped and responds 0.12.</li> </ul>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.4.3.1  Standard	<p>4.4.4.3 DEVIATIONS CAUSED BY ACAS</p> <p>Under the conditions of 4.4.2, the collision avoidance logic shall be such that the number of RAs resulting in “deviations” (4.4.4.3.2) greater than the values indicated shall not exceed the following proportions of the total number of RAs:</p> <p style="text-align: right;"><i>wh</i></p> <p><i>en own aircraft’s vertical rate at the time the RA is first issued</i></p> <p style="text-align: right;"><i>is less than 400ft/min</i> <i>exceeds 400ft/min</i></p> <p><i>when the intruder is not ACAS equipped,</i></p> <p style="text-align: right;"><i>for deviations ≥300 ft</i></p> <p style="text-align: right;">0.1</p> <p>5</p> <p style="text-align: right;">0.2</p> <p>3</p> <p style="text-align: right;"><i>for deviations ≥600 ft</i></p> <p style="text-align: right;">0.0</p> <p>4</p> <p style="text-align: right;">0.1</p> <p>3</p> <p style="text-align: right;"><i>for deviations ≥1 000 ft</i></p> <p style="text-align: right;">0.0</p> <p>1</p> <p style="text-align: right;">0.0</p> <p>7</p> <p><i>when the intruder is equipped but does not respond,</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<i>for deviations <math>\geq 300</math> ft</i>		0.2		
	3		0.3		
	5		0.0		
	<i>for deviations <math>\geq 600</math> ft</i>		0.1		
	6		0.0		
	6		0.0		
	<i>for deviations <math>\geq 1\ 000</math> ft</i>		0.0		
	2		0.0		
	7				
	<i>when the intruder is equipped and responds,</i>				
	<i>for deviations <math>\geq 300</math> ft</i>		0.1		
	1		0.2		
	3		0.0		
	<i>for deviations <math>\geq 600</math> ft</i>		0.1		
	2		0.0		
	2		0.0		
	<i>for deviations <math>\geq 1\ 000</math> ft</i>		0.0		
	1		0.0		
	6				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.4.3.2  Standard	For the purposes of 4.4.4.3.1, the “deviation” of the equipped aircraft from the original trajectory shall be measured in the interval from the time at which the RA is first issued until the time at which, following cancellation of the RA, the equipped aircraft has recovered its original altitude rate. The deviation shall be calculated as the largest altitude difference at any time in this interval between the trajectory followed by the equipped aircraft when responding to its RA and its original trajectory.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.4.5  Recommendation	<p style="text-align: center;"><b>Relative value of conflicting objectives</b></p> <p><b>Recommendation.</b>— <i>The collision avoidance logic should be such as to reduce as much as practicable the risk of collision (measured as defined in 4.4.3) and limit as much as practicable the disruption to ATM (measured as defined in 4.4.4).</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference</p> <p>Definition</p>	<p><b>4.5 ACAS USE OF EXTENDED SQUITTER</b></p> <p><b>4.5.1 ACAS hybrid surveillance using extended squitter position data</b></p> <p><i>Note.— Hybrid surveillance is the technique used by ACAS to take advantage of passive position information available via extended squitter DF = 17. Using hybrid surveillance, ACAS validates the position provided by extended squitter through direct active range measurement. An initial validation is performed at track initiation. Revalidation is performed once every 60 seconds for targets that do not meet the conditions in altitude or range. Revalidation is performed once per 10 seconds if the intruder becomes a near threat in altitude or range. Finally, regular active surveillance is performed once per second on intruders that become a near threat in both altitude and range. In this manner, passive surveillance (once validated) is used for non-threatening intruders thus lowering the ACAS interrogation rate. Active surveillance is used whenever an intruder becomes a near threat in order to preserve ACAS independence as an independent safety monitor.</i></p> <p>4.5.1.1 DEFINITIONS</p> <p><i>Active surveillance.</i> The process of tracking an intruder by using the information gained from the replies to own ACAS interrogations.</p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference  Definition	<b>Hybrid surveillance.</b> The process of using active surveillance to validate and monitor other aircraft being tracked principally using passive surveillance in order to preserve ACAS independence.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Initial acquisition.</b> The process of starting the formation of a new track upon receipt of a squitter from a Mode S aircraft for which there is no track by making an active interrogation.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Passive surveillance.</b> The process of tracking another aircraft without interrogating it, by using the other aircraft's extended squitters. ACAS uses the information obtained to monitor the need for active surveillance, but not for any other purpose.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference  Definition	<b>Validation.</b> The process of verifying the relative position of an intruder using passive information by comparing it to the relative position obtained by active interrogation.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.5.1.2  Standard	An ACAS equipped to receive extended squitter airborne position messages for passive surveillance of non-threatening intruders shall utilize this passive position information in the following manner.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.5.1.3.1  Standard	<p style="text-align: center;">4.5.1.3 PASSIVE SURVEILLANCE</p> <p><i>Validation.</i> To validate the position of an intruder reported by extended squitter, ACAS shall determine the relative range and relative bearing as computed from the position and geographical heading of own aircraft and the intruder's position as reported in the extended squitter. This derived range and relative bearing and the altitude reported in the squitter shall be compared to the range, relative bearing and altitude determined by active ACAS interrogation of the aircraft. Differences between the derived and measured range and relative bearing and the squitter and reply altitude shall be computed and used in tests to determine whether the extended squitter data is valid. If these tests are satisfied the passive position shall be considered to be validated and the track shall be maintained on passive data unless it is a near threat as described in 4.5.1.4. If any of these validation tests fail, active surveillance shall be used to track the intruder.</p> <p><i>Note. — Suitable tests for validating extended squitter data information for the purposes of ACAS hybrid surveillance can be found in RTCA/DO-300.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.5.1.3.2  Standard	<p><i>Supplementary active interrogations.</i> In order to ensure that an intruder's track is updated at least as frequently as required in the absence of extended squitter data (4.3.7.1.2.2), each time a track is updated using squitter information the time at which an active interrogation would next be required shall be calculated. An active interrogation shall be made at that time if a further squitter has not been received before the interrogation is due.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.5.1.4  Standard	<p><i>Near threat.</i> An intruder shall be tracked under active surveillance if it is a near threat, as determined by separate tests on the range and altitude of the aircraft. These tests shall be such that an intruder is considered a near threat before it becomes a potential threat, and thus triggers a traffic advisory as described in 4.3.3. These tests shall be performed once per second. All near threats, potential threats and threats shall be tracked using active surveillance.</p> <p><i>Note.— Suitable tests for determining that an intruder is a near threat can be found in RTCA/DO-300.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.5.1.5  Standard	<p><i>Revalidation and monitoring.</i> If an aircraft is being tracked using passive surveillance, periodic active interrogations shall be performed to validate and monitor the extended squitter data as required in 4.5.1.3.1. The default rates of revalidation shall be once per minute for non-threat and once per 10 seconds for a near threat. The tests required in 4.5.1.3.1 shall be performed for each interrogation, and active surveillance shall be used to track the intruder if these revalidation tests fail.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.5.1.6  Standard	<p><i>Full active surveillance.</i> If the following condition is met for a track being updated via passive surveillance data:</p> <p>a) <math> a  \leq 10\,000</math> ft and both;</p> <p>b) <math> a  \leq 3\,000</math> ft or <math> a - 3\,000 \text{ ft}  /    \leq 60</math> s; and</p> <p>c) <math>r \leq 3</math> NM or <math>(r - 3 \text{ NM}) /    \leq 60</math> s;</p> <p>where: <math>a</math> = intruder altitude separation in ft</p> <p><math>  </math> = altitude rate estimate in ft/s</p> <p><math>r</math> = intruder slant range in NM</p> <p><math>  </math> = range rate estimate in NM/s</p> <p>the aircraft shall be declared an active track and shall be updated on active range measurements once per second for as long as the above condition is met.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.5.1.6.1  Standard	All near threats, potential threats and threats shall be tracked using active surveillance.	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 4 Reference 4.5.1.6.2  Standard	<p>A track under active surveillance shall transition to passive surveillance if it is neither a near, potential threat nor a threat. The tests used to determine it is no longer a near threat shall be similar to those used in 4.5.1.4 but with larger thresholds in order to have hysteresis which prevents the possibility of frequent transitions between active and passive surveillance.</p> <p><i>Note.— Suitable tests for determining that an intruder is no longer a near threat can be found in RTCA/DO-300.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.5.2.1  Standard	<p><b>4.5.2 ACAS operation with an improved receiver MTL</b></p> <p><i>Note.— Applications of extended squitter that are independent of ACAS might be implemented (for convenience) using the ACAS receiver. The use of an improved receiver minimum triggering level (MTL) will make it possible to receive extended squitters from ranges of up to 60 NM and beyond in support of such applications.</i></p> <p>An ACAS operating with a receiver having a MTL more sensitive than -74 dBm shall implement the capabilities specified in the following paragraphs.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		
Chapter 4 Reference 4.5.2.2  Standard	<p><i>Dual minimum triggering levels.</i> The ACAS receiver shall be capable of setting an indication for each squitter reception as to whether the reply would have been detected by an ACAS operating with a conventional MTL (-74 dBm). Squitter receptions received at the conventional MTL shall be passed to the ACAS surveillance function for further processing. Squitter receptions that do not meet this condition shall be not be passed to the ACAS surveillance function.</p> <p><i>N1.Extended squitters containing position report information will be disseminated for display in connection with an extended squitter application.</i></p> <p><i>N2.Use of the conventional MTL for the ACAS surveillance function preserves the current operation of ACAS surveillance when operating with a receiver with an improved MTL.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.5.2.3  Standard	<p><i>Dual or re-triggerable reply processor.</i> The ACAS Mode S reply processing function shall:</p> <ul style="list-style-type: none"> <li>a) use separate reply processors for Mode S reply formats received at or above the conventional MTL and a separate reply processor for Mode S reply formats received below the conventional MTL; or,</li> <li>b) use a Mode S reply processor that will re-trigger if it detects a Mode S preamble that is 2 to 3 dB stronger than the reply that is currently being processed.</li> </ul> <p><i>Note.— Care must be taken to ensure that low-level squitters (i.e. those below the conventional MTL) do not interfere with the processing of acquisition squitters for ACAS. This could happen if the low-level squitter is allowed to capture the reply processor. This can be prevented by using a separate reply processor for each function, or by requiring the reply processor to be re-triggered by a higher level squitter.</i></p> <hr style="width: 10%; margin-left: auto; margin-right: auto;"/>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B,B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 5 Reference 5.1.1.1</p> <p>Standard</p>	<p align="center"><b>CHAPTER 5. MODE S EXTENDED SQUITTER</b></p> <p><b>N1.</b> <i>A functional model of Mode S extended squitter systems supporting ADS-B and/or TIS-B is depicted in Figure 5-1.</i></p> <p><b>N2.</b> <i>Airborne systems transmit ADS-B messages (ADS-B OUT) and may also receive ADS-B and TIS-B messages (ADS-B IN and TIS-B IN). Ground systems (i.e. ground stations) transmit TIS-B (as an option) and receive ADS-B messages.</i></p> <p><b>N3.</b> <i>Although not explicitly depicted in the functional model presented in Figure 5-1, extended squitter systems installed on aerodrome surface vehicles or fixed obstacles may transmit ADS-B messages (ADS-B OUT).</i></p> <p align="center"><b>5.1 MODE S EXTENDED SQUITTER TRANSMITTING SYSTEM CHARACTERISTICS</b></p> <p><i>Note.— Many of the requirements associated with the transmission of Mode S extended squitter are included in Chapter 2 and Chapter 3 for Mode S transponder and non-transponder devices using the message formats defined in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871). The provisions presented within the following subsections are focused on requirements applicable to specific classes of airborne and ground transmitting systems that are supporting the applications of ADS-B and TIS-B.</i></p> <p align="center"><b>5.1.1 ADS-B OUT requirements</b></p> <p>Aircraft, surface vehicles and fixed obstacles supporting an ADS-B capability shall incorporate the ADS-B message generation function and the ADS-B message exchange function (transmit) as depicted in Figure 5-1.</p>	<p>CAR Part 91 Appendix A, A.22.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.1.1.1  Standard	ADS-B transmissions from aircraft shall include position, aircraft identification and type, airborne velocity, periodic status and event driven messages including emergency/priority information.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.1.1.1.2  Recommendation	<p><b>Recommendation.</b>— <i>Extended squitter transmitting equipment should use formats and protocols of the latest version available.</i></p> <p><i>N1.The data formats and protocols for messages transferred via extended squitter are specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i></p> <p><i>N2.Some States and/or regions require extended squitter version 2 to be transmitted by specific dates.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.1.2  Standard	<p><i>Extended squitter ADS-B transmission requirements.</i> Mode S extended squitter transmitting equipment shall be classified according to the unit's range capability and the set of parameters that it is capable of transmitting consistent with the following definition of general equipment classes and the specific equipment classes defined in Tables 5-1 and 5-2:</p> <ul style="list-style-type: none"> <li>a) Class A extended squitter airborne systems support an interactive capability incorporating both an extended squitter transmission capability (i.e. ADS-B OUT) with a complementary extended squitter reception capability (i.e. ADS-B IN) in support of onboard ADS-B applications;</li> <li>b) Class B extended squitter systems provide a transmission only (i.e. ADS-B OUT without an extended squitter reception capability) for use on aircraft, surface vehicles, or fixed obstructions; and</li> <li>c) Class C extended squitter systems have only a reception capability and thus have no transmission requirements.</li> </ul>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.1.3  Standard	<p><i>Class A extended squitter system requirements. Class A extended squitter airborne systems shall have transmitting and receiving subsystem characteristics of the same class (i.e. A0, A1, A2, or A3) as specified in 5.1.1.1 and 5.2.1.2.</i></p> <p><i>Note.— Class A transmitting and receiving subsystems of the same specific class (e.g. Class A2) are designed to complement each other with their functional and performance capabilities. The minimum air-to-air range that extended squitter transmitting and receiving systems of the same class are designed to support are:</i></p> <ul style="list-style-type: none"> <li><i>a) A0-to-A0 nominal air-to-air range is 10 NM;</i></li> <li><i>b) A1-to-A1 nominal air-to-air range is 20 NM;</i></li> <li><i>c) A2-to-A2 nominal air-to-air range is 40 NM; and</i></li> <li><i>d) A3-to-A3 nominal air-to-air range is 90 NM.</i></li> </ul> <p><i>The above ranges are design objectives and the actual effective air-to-air range of the Class A extended squitter systems may be larger in some cases (e.g. in environments with low levels of 1 090 MHz fruit) and shorter in other cases (e.g. in environments with very high levels of 1 090 MHz fruit).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.1.1.4.1  Recommendation	<p>5.1.1.4 CONTROL OF ADS-B OUT OPERATION</p> <p><b>Recommendation.</b>— <i>Protection against reception of corrupted data from the source providing the position should be satisfied by error detection on the data inputs and the appropriate maintenance of the installation.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.1.1.4.2  Standard	<p>If an independent control of the ADS-B OUT function is provided, then the operational state of the ADS-B OUT function shall be indicated to the flight crew, at all times.</p> <p><i>Note.— There is no requirement for an independent control for the ADS-B OUT function.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.2.1  Standard	<p align="center"><b>5.1.2 TIS-B OUT requirements</b></p> <p>Ground stations supporting a TIS-B capability shall incorporate the TIS-B message generation function and the TIS-B message exchange function (transmit).</p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.1.2.2  Standard	<p>The extended squitter messages for TIS-B shall be transmitted by an extended squitter ground station when connected to an appropriate source of surveillance data.</p> <p><i>N1. Extended squitter messages for TIS-B are specified in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</i></p> <p><i>N2. Ground stations supporting TIS-B use an extended squitter transmission capability. The characteristics of such ground stations, in terms of transmitter power, antenna gain, transmission rates, etc., are to be tailored to the desired TIS-B service volume of the specific ground station assuming airborne users are equipped with (at least) Class A1 receiving systems.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.1.2.3  Recommendation	<p><b>Recommendation.</b>— <i>The maximum transmission rates and effective radiated power of the transmissions should be controlled to avoid unacceptable levels of RF interference to other 1 090 MHz systems (i.e. SSR and ACAS).</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.1  Standard	<p><b>5.2 MODE S EXTENDED SQUITTER RECEIVING SYSTEM CHARACTERISTICS (ADS-B IN AND TIS-B IN)</b></p> <p><i>N1. The paragraphs herein describe the required capabilities for 1 090 MHz receivers used for the reception of Mode S extended squitter transmissions that convey ADS-B and/or TIS-B messages. Airborne receiving systems support ADS-B and TIS-B reception while ground receiving systems support only ADS-B reception.</i></p> <p><i>N2. Detailed technical provisions for Mode S extended squitter receivers can be found within RTCA DO-260B/EUROCAE ED-102A, "Minimum Operational Performance Standards for 1 090 MHz Extended Squitter Automatic Dependent Surveillance – Broadcast (ADS-B) and Traffic Information Services – Broadcast (TIS-B)."</i></p> <p><b>5.2.1 Mode S extended squitter receiving system functional requirements</b></p> <p>Mode S extended squitter receiving systems shall perform the message exchange function (receive) and the report assembler function.</p> <p><i>Note.— The extended squitter receiving system receives ADS-B Mode S extended squitter messages and outputs ADS-B reports to client applications. Airborne receiving systems also receive TIS-B extended squitter messages and output TIS-B reports to client applications. This functional model (shown in Figure 5-1) depicts both airborne and ground 1 090 MHz ADS-B receiving systems.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.2  Standard	<p><i>Mode S extended squitter receiver classes.</i> The required functionality and performance characteristics for the Mode S extended squitter receiving system will vary depending on the ADS-B and TIS-B client applications to be supported and the operational use of the system. Airborne Mode S extended squitter receivers shall be consistent with the definition of receiving system classes shown in Table 5-3.</p> <p><i>Note.— Different equipment classes of Mode S extended squitter installations are possible. The characteristics of the receiver associated with a given equipment class are intended to be appropriate to support the required level of operational capability. Equipment classes A0 through A3 are applicable to those Mode S extended airborne installations that include a Mode S extended squitter transmission (ADS-OUT) and reception (ADS-B IN) capability. Equipment classes B0 through B3 are applicable to Mode S extended installations with only a transmission (ADS-B OUT) capability and includes equipment classes applicable to airborne, surface vehicles and fixed obstructions. Equipment classes C1 through C3 are applicable to Mode S extended squitter ground receiving systems.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.2.2.1  Standard	<p><b>5.2.2 Message exchange function</b></p> <p>The message exchange function shall include the 1 090 MHz receiving antenna and the radio equipment (receiver/demodulator/decoder/data buffer) sub-functions.</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.2  Standard	<i>Message exchange functional characteristics.</i> The airborne Mode S extended squitter receiving system shall support the reception and decoding of all extended squitter messages as listed in Table 5-3. The ground ADS-B extended squitter receiving system shall, as a minimum, support the reception and decoding of all of the extended squitter message types that convey information needed to support the generation of the ADS-B reports of the types required by the client ATM ground applications.	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.2.2.3  Standard	<i>Required message reception performance.</i> The airborne Mode S extended squitter receiver/demodulation/decoder shall employ the reception techniques and have a receiver minimum trigger threshold level (MTL) as listed in Table 5-3 as a function of the airborne receiver class. The reception technique and MTL for extended squitter ground receiver shall be selected to provide the reception performance (i.e. range and update rates) as required by the client ATM ground applications.	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.4  Standard	<p><i>Enhanced reception techniques.</i> Class A1, A2 and A3 airborne receiving systems shall include the following features to provide improved probability of Mode S extended squitter reception in the presence of multiple overlapping Mode A/C fruit and/or in the presence of an overlapping stronger Mode S fruit, as compared to the performance of the standard reception technique required for Class A0 airborne receiving systems:</p> <ul style="list-style-type: none"> <li>a) Improved Mode S extended squitter preamble detection.</li> <li>b) Enhanced error detection and correction.</li> <li>c) Enhanced bit and confidence declaration techniques applied to the airborne receiver classes as shown below: <ul style="list-style-type: none"> <li>1) Class A1 – Performance equivalent to or better than the use of the “Centre Amplitude” technique.</li> <li>2) Class A2 – Performance equivalent to or better than the use of the “Multiple Amplitude Samples” baseline technique, where at least 8 samples are taken for each Mode S bit position and are used in the decision process.</li> <li>3) Class A3 – Performance equivalent to or better than the use of the “Multiple Amplitude Samples” baseline technique, where at least 10 samples are taken for each Mode S bit position and are used in the decision process.</li> </ul> </li> </ul> <p><i>N1.The above enhanced reception techniques are as defined in RTCA DO-260B/EUROCAE ED-102A, Appendix I.</i></p> <p><i>N2.The performance provided for each of the above enhanced reception techniques when used in a high fruit environment (i.e. with multiple overlapping Mode A/C fruit) is expected to be at least equivalent to that provided by the use of the techniques described in RTCA DO-260B/EUROCAE ED-102A, Appendix I.</i></p> <p><i>N3.It is considered appropriate for ground extended squitter receiving systems to employ the enhanced reception</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<i>techniques equivalent to those specified for airborne Class A2 or A3 receiving systems.</i>				
Chapter 5 Reference 5.2.3.1  Standard	<p style="text-align: center;"><b>5.2.3 Report assembler function</b></p> <p>The report assembler function shall include the message decoding, report assembly, and output interface sub-functions.</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 5 Reference 5.2.3.2</p> <p>Standard</p>	<p>When an extended squitter message is received, the message shall be decoded and the applicable ADS-B report(s) of the types defined in 5.2.3.3 shall be generated within 0.5 seconds.</p> <p><i>N1.Two configurations of extended squitter airborne receiving systems, which include the reception portion of the ADS-B message exchange function and the ADS-B/TIS-B report assembly function, are allowed:</i></p> <p><i>a) Type I extended squitter receiving systems receive ADS-B and TIS-B messages and produce application-specific subsets of ADS-B and TIS-B reports. Type I extended squitter receiving systems are customized to the particular client applications using ADS-B and TIS-B reports. Type I extended squitter receiving systems may additionally be controlled by an external entity to produce installation-defined subsets of the reports that those systems are capable of producing.</i></p> <p><i>b) Type II extended squitter receiving systems receive ADS-B and TIS-B messages and are capable of producing complete ADS-B and TIS-B reports in accordance with the equipment class. Type II extended squitter receiving systems may be controlled by an external entity to produce installation-defined subsets of the reports that those systems are capable of producing.</i></p> <p><i>N2.Extended squitter ground receiving systems receive ADS-B messages and produce either application-specific subsets or complete ADS-B reports based on the needs of the ground service provider, including the client applications to be supported.</i></p> <p><i>N3.The extended squitter message reception function may be physically partitioned into hardware separate from those that implement the report assembly function.</i></p>	<p>CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 5 Reference 5.2.3.3.1  Standard</p>	<p>5.2.3.3 ADS-B REPORT TYPES</p> <p>N1. <i>The ADS-B report refers to the restructuring of ADS-B message data received from Mode S extended squitter broadcasts into various reports that can be used directly by a set of client applications. Five ADS-B report types are defined by the following subparagraphs for output to client applications. Additional information on the ADS-B report contents and the applicable mapping from extended squitter messages to ADS-B reports can be found in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871) and RTCA DO-260B/EUROCAE ED-102A.</i></p> <p>N2. <i>The use of precision (e.g. GNSS UTC measured time) versus non-precision (e.g. internal receiving system clock) time sources as the basis for the reported time of applicability is described in 5.2.3.5.</i></p> <p><i>State vector report.</i> The state vector report shall contain time of applicability, information about an airborne or vehicle's current kinematic state (e.g. position, velocity), as well as a measure of the integrity of the navigation data, based on information received in airborne or ground position, airborne velocity, identification and category, aircraft operational status and target state and status extended squitter messages. Since separate messages are used for position and velocity, the time of applicability shall be reported individually for the position related report parameters and the velocity related report parameters. Also, the state vector report shall include a time of applicability for the estimated position and/or estimated velocity information (i.e. not based on a message with updated position or velocity information) when such estimated position and/or velocity information is included in the state vector report.</p> <p><i>Note.— Specific requirements for the customization of this type of report may vary according to the needs of the client applications of each participant (ground or airborne). The state vector data is the most dynamic of the four ADS-B reports; hence, the applications require frequent</i></p>	<p>CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<i>updates of the state vector to meet the required accuracy for the operational dynamics of the typical airborne or ground operations of airborne and surface vehicles.</i>				
Chapter 5 Reference 5.2.3.3.2  Standard	<p><i>Mode status report.</i> The mode status report shall contain time of applicability and current operational information about the transmitting participant, including airborne/vehicle address, call sign, ADS-B version number, airborne/vehicle length and width information, state vector quality information, and other information based on information received in aircraft operational status, target state and status, aircraft identification and category, airborne velocity and aircraft status extended squitter messages. Each time that a mode status report is generated, the report assembler function shall update the report time of applicability. Parameters for which valid data is not available shall either be indicated as invalid or omitted from the mode status report.</p> <p><i>N1. Specific requirements for the customization of this type of report may vary according to the needs of the client applications of each participant (ground or airborne).</i></p> <p><i>N2. The age of the information being reported within the various data elements of a mode status report may vary as a result of the information having been received within different extended squitter messages at different times.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.3.3  Standard	<p><i>Air referenced velocity report.</i> Air referenced velocity reports shall be generated when air referenced velocity information is received in airborne velocity extended squitter messages. The air referenced velocity report shall contain time of applicability, airspeed and heading information. Only certain classes of extended squitter receiving systems, as defined in 5.2.3.5, are required to generate air referenced velocity reports. Each time that an individual mode status report is generated, the report assembly function shall update the report time of applicability.</p> <p><i>N1.The air referenced velocity report contains velocity information that is received in airborne velocity messages along with additional information received in airborne identification and category extended squitter messages. Air referenced velocity reports are not generated when ground referenced velocity information is being received in the airborne velocity extended squitter messages.</i></p> <p><i>N2.Specific requirements for the customization of this type of report may vary according to the needs of the client applications of each participant (ground or airborne).</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.2.3.3.4  Standard	<p><i>Resolution advisory (RA) report.</i> The RA report shall contain time of applicability and the contents of an active ACAS resolution advisory (RA) as received in a Type=28 and Subtype=2 extended squitter message.</p> <p><i>Note.— The RA report is only intended to be generated by ground receiving subsystems when supporting a ground ADS-B client application(s) requiring active RA information. An RA report will nominally be generated each time a Type=28, Subtype=2 extended squitter message is received.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.3.5  Note	<p><i>TARGET STATE REPORT</i></p> <p><i>Note.— The target state report will be generated when information is received in target state and status messages, along with additional information received in airborne identification and category extended squitter messages. The target state and status message is defined in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871). Specific requirements for the customization of this type of report may vary according to the needs of the client applications of each participant (ground or airborne).</i></p>		Not Applicable		Compliance dat not required for Notes.
Chapter 5 Reference 5.2.3.4.1  Standard	<p>5.2.3.4 TIS-B REPORT TYPES</p> <p>As TIS-B messages are received by airborne receiving systems, the information shall be reported to client applications. Each time that an individual TIS-B report is generated, the report assembly function shall update the report time of applicability to the current time.</p> <p>N1.The TIS-B message formats are defined in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</p> <p>N2.The TIS-B report refers to the restructuring of TIS-B message data received from ground Mode S extended squitter broadcasts into reports that can be used by a set of client applications. Two ADS-B report types are defined by the following subparagraphs for output to client applications. Additional information on the TIS-B report contents and the applicable mapping from extended squitter messages to ADS-B reports can be found in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871).</p> <p>N3.The use of precision (e.g. GNSS UTC measured time) versus non-precision (e.g. internal receiving system clock) time sources as the basis for the reported time of applicability is described in 5.2.3.5.</p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.4.2  Standard	<i>TIS-B target report.</i> All received information elements, other than position, shall be reported directly, including all reserved fields for the TIS-B fine format messages and the entire message content of any received TIS-B management message. The reporting format is not specified in detail, except that the information content reported shall be the same as the information content received.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.2.3.4.3  Standard	When a TIS-B position message is received, it is compared with tracks to determine whether it can be decoded into target position (i.e. correlated to an existing track). If the message is decoded into target position, a report shall be generated within 0.5 seconds. The report shall contain the received position information with a time of applicability, the most recently received velocity measurement with a time of applicability, the estimated position and velocity applicable to a common time of applicability, airborne/vehicle address, and all other information in the received message. The estimated values shall be based on the received position information and the track history of the target.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.2.3.4.4  Standard	When a TIS-B velocity message is received, if it is correlated to a complete track, a report shall be generated, within 0.5 seconds of the message reception. The report shall contain the received velocity information with a time of applicability, the estimated position and velocity applicable to a common time of applicability, airborne/vehicle address, and all other information in the received message. The estimated values shall be based on the received ground reference velocity information and the track history of the target.	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.4.5  Standard	<i>TIS-B management report.</i> The entire message content of any received TIS-B management message shall be reported directly to the client applications. The information content reported shall be the same as the information content received.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.2.3.4.5.1  Standard	The contents of any received TIS-B management message shall be reported bit-for-bit to the client applications.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.2.3.5  Standard	REPORT TIME OF APPLICABILITY The receiving system shall use a local source of reference time as the basis for reporting the time of applicability, as defined for each specific ADS-B and TIS-B report type (see 5.2.3.3 and 5.2.3.4).	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.5.1  Standard	<p><i>Precision time reference.</i> Receiving systems intended to generate ADS-B and/or TIS-B reports based on the reception of surface position messages, airborne position messages, and/or TIS-B messages shall use GNSS UTC measured time for the purpose of generating the report time applicability for the following cases of received messages:</p> <ul style="list-style-type: none"> <li>a) version zero (0) ADS-B messages, as defined in 3.1.2.8.6.2, when the navigation uncertainty category (NUC) is 8 or 9; or</li> <li>b) version one (1) or version two (2) ADS-B or TIS-B messages, as defined in 3.1.2.8.6.2 and 3.1.2.8.7 respectively, when the navigation integrity category (NIC) is 10 or 11;</li> </ul> <p>UTC measured time data shall have a minimum range of 300 seconds and a resolution of 0.0078125 (1/128) seconds.</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.5.2.1  Standard	<p>5.2.3.5.2 <i>NON-PRECISION LOCAL TIME REFERENCE</i></p> <p>For receiving systems not intended to generate ADS-B and/or TIS-B reports based on reception of ADS-B or TIS-B messages meeting the NUC or NIC criteria as indicated in 5.2.3.5.1, a non-precision time source shall be allowed. In such cases, where there is no appropriate precision time source available, the receiving system shall establish an appropriate internal clock or counter having a maximum clock cycle or count time of 20 milliseconds. The established cycle or clock count shall have a minimum range of 300 seconds and a resolution of 0.0078125 (1/128) seconds.</p> <p><i>Note.— The use of a non-precision time reference as described above is intended to allow the report time of applicability to accurately reflect the time intervals applicable to reports within a sequence. For example the applicable time interval between state vector reports could be accurately determined by a client application, even though the absolute time (e.g. UTC measured time) would not be indicated by the report.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.2.3.6.1  Standard	<p>5.2.3.6 REPORTING REQUIREMENTS</p> <p><i>Reporting requirements for Type I Mode S extended squitter airborne receiving systems. As a minimum, the report assembler function associated with Type I Mode S extended squitter receiving systems, as defined in 5.2.3, shall support that subset of ADS-B and TIS-B reports and report parameters, that are required by the specific client applications being served by that receiving system.</i></p>	CAR Part 91 Appendix A, A.22.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.6.2  Standard	<i>Reporting requirements for Type II Mode S extended squitter airborne receiving systems.</i> The report assembler function associated with Type II receiving systems, as defined in 5.2.3, shall generate ADS-B and TIS-B reports according to the class of the receiving system as shown in Table 5-4 when the prerequisite ADS-B and/or TIS-B messages are being received.	CAR Part 91 Appendix A, A.22.	No Difference		
Chapter 5 Reference 5.2.3.6.3  Standard	<i>Reporting requirements for Mode S extended squitter ground receiving systems.</i> As a minimum, the report assembler function associated with Mode S extended squitter ground receiving systems, as defined in 5.2.3, shall support that subset of ADS-B reports and report parameters, that are required by the specific client applications being served by that receiving system.	CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.2.4  Standard	<p style="text-align: center;"><b>Interoperability</b></p> <p>The Mode S extended squitter receiving system shall provide interoperability between the different versions of extended squitter ADS-B message formats.</p> <p><i>N1.All defined ADS-B versions and their corresponding message formats are contained in the Technical Provisions for Mode S Services and Extended Squitter (Doc 9871) and are identified by a version number.</i></p> <p><i>N2.ADS-B message formats are defined with backward compatibility with previous versions. An extended squitter receiver can recognize and decode signals of its own version, as well as the message formats from lower versions. The receiver, however, can decode the portion of messages received from a higher version transponder according to its own capability.</i></p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.1  Standard	<p style="text-align: center;">INITIAL MESSAGE DECODING</p> <p>The Mode S extended squitter receiving system shall, upon acquiring a new ADS-B target, initially apply the decoding provisions applicable to version 0 (zero) ADS-B messages until or unless an aircraft operational status message is received indicating that a higher version message format is in use.</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.2.4.2  Standard	<p style="text-align: center;">APPLYING VERSION NUMBER</p> <p>The Mode S extended squitter receiving system shall decode the version number information conveyed in the aircraft operational status message and shall apply the corresponding decoding rules for the reported version, up to the highest version supported by the receiving system, for the decoding of the subsequent extended squitter ADS-B messages from that specific aircraft or vehicle.</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		
Chapter 5 Reference 5.2.4.3  Standard	<p style="text-align: center;">HANDLING OF RESERVED MESSAGE SUBFIELDS</p> <p>The Mode S extended squitter receiving system shall ignore the contents of any message subfield defined as reserved.</p> <p><i>Note.— This provision supports interoperability between message versions by allowing the definition of additional parameters that will be ignored by earlier receiver versions and correctly decoded by newer receiver versions.</i></p> <p style="text-align: center;">_____</p>	CAR Part 91 Appendix A, A.22; CAR 171.53(a)(1).	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 6 Reference</p> <p>Definition</p>	<p style="text-align: center;"><b>CHAPTER 6. MULTILATERATION SYSTEMS</b></p> <p><b>N1.</b> <i>Multilateration (MLAT) systems use the time difference of arrival (TDOA) of the transmissions of an SSR transponder (or the extended squitter transmissions of a non-transponder device) between several ground receivers to determine the position of the aircraft (or ground vehicle). A multilateration system can be:</i></p> <ul style="list-style-type: none"> <li><i>a) passive, using transponder replies to other interrogations or spontaneous squitter transmissions;</i></li> <li><i>b) active, in which case the system itself interrogates aircraft in the coverage area; or</i></li> <li><i>c) a combination of a) and b).</i></li> </ul> <p><b>N2.</b> <i>Material contained in EUROCAE ED-117 - MOPS for Mode S Multilateration Systems for Use in A-SMGCS and ED-142 - Technical Specifications for Wide Area Multilateration System (WAM) provides a good basis for planning, implementation and satisfactory operation of MLAT systems for most applications.</i></p> <p style="text-align: center;"><b>6.1 DEFINITIONS</b></p> <p><b>Multilateration (MLAT) System.</b> A group of equipment configured to provide position derived from the secondary surveillance radar (SSR) transponder signals (replies or squitters) primarily using time difference of arrival (TDOA) techniques. Additional information, including identification, can be extracted from the received signals.</p>	<p>CAR 171.53(a)(1).</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference  Definition	<b>Time Difference of Arrival (TDOA).</b> The difference in relative time that a transponder signal from the same aircraft (or ground vehicle) is received at different receivers.	CAR 171.53(a)(1).	No Difference		
Chapter 6 Reference 6.2.1  Standard	<b>6.2 FUNCTIONAL REQUIREMENTS</b>  Radio frequency characteristics, structure and data contents of signals used in 1 090 MHz MLAT systems shall conform to the provisions of Chapter 3.	CAR 171.53(a)(1).	No Difference		
Chapter 6 Reference 6.2.2  Standard	An MLAT system used for air traffic surveillance shall be capable of determining aircraft position and identity. <i>N1. Depending on the application, either two- or three-dimensional position of the aircraft may be required.</i> <i>N2. Aircraft identity may be determined from:</i> a) Mode A code contained in Mode A or Mode S replies; or b) Aircraft identification contained in Mode S replies or extended squitter identity and category message. <i>N3. Other aircraft information can be obtained by analysing transmissions of opportunity (i.e. squitters or replies to other ground interrogations) or by direct interrogation by the MLAT system.</i>	CAR 171.53(a)(1).	No Difference		
Chapter 6 Reference 6.2.3  Standard	Where an MLAT system is equipped to decode additional position information contained in transmissions, it shall report such information separately from the aircraft position calculated based to TDOA.	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.1  Standard	<p align="center"><b>6.3 PROTECTION OF THE RADIO FREQUENCY ENVIRONMENT</b></p> <p><i>Note. — This section only applies to active MLAT systems.</i></p> <p>In order to minimize system interferences the effective radiated power of active interrogators shall be reduced to the lowest value consistent with the operationally required range of each individual interrogator site.</p> <p><i>Note. — Guidance material on power consideration is contained in the Aeronautical Surveillance Manual (Doc 9924).</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 6 Reference 6.3.2  Standard	<p>An active MLAT system shall not use active interrogations to obtain information that can be obtained by passive reception within each required update period.</p> <p><i>Note — Transponder occupancy will be increased by the use of omnidirectional antennas. It is particularly significant for Mode S selective interrogations because of their higher transmission rate. All Mode S transponders will be occupied decoding each selective interrogation not just the addressed transponder.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 6 Reference 6.3.3  Standard	<p>An active MLAT system consisting of a set of transmitters shall be considered as a single Mode S interrogator.</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.3.4  Standard	<p>The set of transmitters used by all active MLAT systems in any part of the airspace shall not cause any transponder to be impacted such that its occupancy, because of the aggregate of all MLAT 1 030 MHz interrogations, is greater than 2 per cent at any time.</p> <p><i>N1. This represents a minimum requirement. Some regions may impose stricter requirements.</i></p> <p><i>N2. For an MLAT system using only Mode S interrogations, 2 per cent is equivalent to no more than 400 Mode S interrogations per second received by any aircraft from all systems using MLAT technology.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 6 Reference 6.3.5  Standard	<p>Active MLAT systems shall not use Mode S All-Call interrogations.</p> <p><i>Note. — Mode S aircraft can be acquired by the reception of acquisition squitter or extended squitter even in airspace where there are no active interrogators.</i></p>	CAR 171.53(a)(1).	No Difference		
Chapter 6 Reference 6.4.1  Standard	<p style="text-align: center;"><b>6.4 PERFORMANCE REQUIREMENTS</b></p> <p>The performance characteristics of the MLAT system used for air traffic surveillance shall be such that the intended operational service(s) can be satisfactorily supported.</p> <p style="text-align: center;">_____</p>	CAR 171.53(a)(1).	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 7 Reference 7.1.1.1.1</p> <p>Standard</p>	<p style="text-align: center;"><b>CHAPTER 7. TECHNICAL REQUIREMENTS FOR AIRBORNE SURVEILLANCE APPLICATIONS</b></p> <p><i>N1. Airborne surveillance applications are based on aircraft receiving and using ADB-B message information transmitted by other aircraft/vehicles or ground stations. The capability of an aircraft to receive and use ADS-B/TIS-B message information is referred to as ADS-B/TIS-B IN.</i></p> <p><i>N2. Initial airborne surveillance applications use ADS-B messages on 1 090 MHz extended squitter to provide airborne traffic situational awareness (ATSA) and are expected to include "In-trail procedures" and "Enhanced visual separation on approach".</i></p> <p><i>N3. Detailed description of aforementioned applications can be found in RTCA/DO-289 and DP-312.</i></p> <p style="text-align: center;"><b>7.1 GENERAL REQUIREMENTS</b></p> <p style="text-align: center;"><b>7.1.1 Traffic data functions</b></p> <p><i>Note. — The aircraft transmitting ADS-B messages used by other aircraft for airborne surveillance applications is referred to as the reference aircraft.</i></p> <p style="text-align: center;"><b>7.1.1.1 IDENTIFYING THE REFERENCE AIRCRAFT</b></p> <p>The system shall support a function to identify unambiguously each reference aircraft relevant to the application.</p>	<p>CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.1.1.2.1  Standard	<p><b>7.1.1.2 TRACKING THE REFERENCE AIRCRAFT</b></p> <p>The system shall support a function to monitor the movements and behaviour of each reference aircraft relevant to the application.</p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 7 Reference 7.1.1.3.1  Recommendation	<p><b>7.1.1.3 TRAJECTORY OF THE REFERENCE AIRCRAFT</b></p> <p><b>Recommendation.</b> — <i>The system should support a computational function to predict the future position of a reference aircraft beyond simple extrapolation.</i></p> <p><i>Note.</i> — <i>It is anticipated that this function will be required for future applications.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 7 Reference 7.1.2.1  Standard	<p><b>7.1.2 Displaying traffic</b></p> <p><i>Note.</i> — <i>Provisions contained in this section apply to cases wherein tracks generated by ACAS and by reception of ADS-B/TIS-B IN messages are shown on a single display.</i></p> <p>The system shall display only one track for each distinct aircraft on a given display.</p> <p><i>Note.</i> — <i>This is to ensure that tracks established by ACAS and ADS-B/TIS-B IN are properly correlated and mutually validated before being displayed.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		
Chapter 7 Reference 7.1.2.2  Standard	<p>Where a track generated by ADS-B/TIS-B IN and a track generated by ACAS have been determined to belong to the same aircraft, the track generated by ADS-B/TIS-B IN shall be displayed.</p> <p><i>Note.</i> — <i>At close distances, it is possible that the track generated by ACAS provides better accuracy than the track generated by ADS-B/TIS-B IN. The requirement above ensures the continuity of the display.</i></p>	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.1.2.3  Standard	The display of the tracks shall comply with the requirements of ACAS traffic display. <i>Note. — Section 4.3 addresses colour coding and readability of the display.</i>  _____	CAR Part 121 Appendix B, B.11; CAR Part 125 Appendix B, B.10.	No Difference		

- END -