



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 1 Reference</p> <p>Definition</p>	<p align="center"><b>COMMUNICATION PROCEDURES</b></p> <p align="center"><b>Introduction</b></p> <p><i>The object of the international aeronautical telecommunication service is to ensure the telecommunications and radio aids to air navigation necessary for the safety, regularity and efficiency of international air navigation.</i></p> <p><i>Procedures for the International Aeronautical Telecommunication Service are herein set forth for worldwide use. It is recognized that Supplementary Procedures may be required in certain cases in order to meet particular requirements of the ICAO Regions. Any Supplementary procedure recommended for this purpose must be a requirement peculiar to the region and must not be contained in, nor conflict with, any worldwide Procedure of ICAO.</i></p> <p><i>Where appropriate, specific ITU Radio Regulations have been paraphrased in this document. Users of these Procedures should note that the Radio Regulations Annex of the International Telecommunications Convention is all-embracing in character and, therefore, should be applied in all pertinent cases.</i></p> <p><i>All references to "Radio Regulations" are to the Radio Regulations published by the International Telecommunication Union.</i></p> <p><i>The Communication Procedures are to be used in conjunction with the Abbreviations and Codes of Doc 8400 and with such other codes and abbreviations as may be approved by ICAO for use in communications.</i></p> <p><i>Volume II contains a number of provisions relating to the exchange of information which were developed primarily for low modulation rates utilizing the coded character sets of International Alphabets Nos. 2 and 3. Provisions for International Alphabet No. 5 (IA-5) for use at medium and higher signalling rates are contained in Annex 10, Volume III.</i></p>	<p>Civil Aviation Rules (CAR) Part 1.</p>	<p>No Difference</p>		<p>Note: incorporated by reference in definition of "Aeronautical telecommunication service".</p>



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p style="text-align: center;"><b>CHAPTER 1. DEFINITIONS</b></p> <p>When the following terms are used in this publication, they have the meaning prescribed in this chapter:</p> <p><i>N1.A list of additional specialized communication terms and their definitions is contained in Attachment A.</i></p> <p><i>N2.All references to "Radio Regulations" are to the Radio Regulations published by the International Telecommunication Union (ITU). Radio Regulations are amended from time to time by decisions embodied in the Final Acts of World Radiocommunication Conferences held normally every two to three years. Further information on the ITU processes as they relate to aeronautical radio system frequency use is contained in the Handbook on Radio Frequency Spectrum Requirements for Civil Aviation including statement of approved ICAO policies (Doc 9718).</i></p> <p style="text-align: center;"><b>1.1 Services</b></p> <p><i>Aeronautical broadcasting service.</i> A broadcasting service intended for the transmission of information relating to air navigation.</p>				
Chapter 1 Reference  Definition	<i>Aeronautical fixed service (AFS).</i> A telecommunication service between specified fixed points provided primarily for the safety of air navigation and for the regular, efficient and economical operation of air services.	CAR Part 1.	No Difference		Note: incorporated by reference in definition of "Aeronautical telecommunication service".



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<i>Aeronautical fixed telecommunication network (AFTN)</i> . A worldwide system of aeronautical fixed circuits provided, as part of the aeronautical fixed service, for the exchange of messages and/or digital data between aeronautical fixed stations having the same or compatible communications characteristics.	AIPNZ GEN 2.2.	No Difference		
Chapter 1 Reference  Definition	<i>Aeronautical mobile (R)* service (RR SI.33)</i> . An aeronautical mobile service reserved for communications relating to safety and regularity of flight, primarily along national or international civil air routes.  * route	Airways Corporation of New Zealand (ACNZ) Manual of Air Traffic Services (MATS) RAC 1.	No Difference		
Chapter 1 Reference  Definition	<i>Aeronautical mobile service (RR SI.32)</i> . A mobile service between aeronautical stations and aircraft stations, or between aircraft stations, in which survival craft stations may participate; emergency position-indicating radiobeacon stations may also participate in this service on designated distress and emergency frequencies.	CAR Part 1.	No Difference		Note: incorporated by reference in definition of "Aeronautical telecommunication service".
Chapter 1 Reference  Definition	<i>Aeronautical mobile-satellite (R)* service (RR SI.36)</i> . An aeronautical mobile-satellite service reserved for communications relating to safety and regularity of flights, primarily along national or international civil air routes.  * route	MATS RAC 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<i>Aeronautical mobile-satellite service (RR S1.35).</i> A mobile-satellite service in which mobile earth stations are located on board aircraft; survival craft stations and emergency position-indicating radiobeacon stations may also participate in this service.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<i>Aeronautical radio navigation service (RR S1.46).</i> A radio navigation service intended for the benefit and for the safe operation of aircraft. <i>Note.— The following Radio Regulations are quoted for purposes of reference and/or clarity in understanding of the above definition of the aeronautical radio navigation service:</i> RR S1.10 Radio navigation: Radiodetermination used for the purpose of navigation, including obstruction warning. RR S1.9 Radiodetermination: The determination of the position, velocity and/or other characteristics of an object, or the obtaining of information relating to these parameters, by means of the propagation properties of radio waves.	CAR Part 1.	No Difference		Note: incorporated by reference in definition of "Aeronautical telecommunication service".
Chapter 1 Reference  Definition	<i>Aeronautical telecommunication service.</i> A telecommunication service provided for any aeronautical purpose.	CAR Part 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<i>International telecommunication service.</i> A telecommunication service between offices or stations of different States, or between mobile stations which are not in the same State, or are subject to different States.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>1.2 Stations</b> <i>Aerodrome control radio station.</i> A station providing radio-communication between an aerodrome control tower and aircraft or mobile aeronautical stations.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<i>Aeronautical fixed station.</i> A station in the aeronautical fixed service.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<i>Aeronautical station (RR S1.81).</i> A land station in the aeronautical mobile service. In certain instances, an aeronautical station may be located, for example, on board ship or on a platform at sea.	CAR Part 1.	No Difference		
Chapter 1 Reference  Definition	<i>Aeronautical telecommunication station.</i> A station in the aeronautical telecommunication service.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<i>AFTN communication centre.</i> An AFTN station whose primary function is the relay or retransmission of AFTN traffic from (or to) a number of other AFTN stations connected to it.	CAR Part 1.	No Difference	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<i>AFTN destination station.</i> An AFTN station to which messages and/or digital data are addressed for processing for delivery to the addressee.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<i>AFTN origin station.</i> An AFTN station where messages and/or digital data are accepted for transmission over the AFTN.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<i>AFTN station.</i> A station forming part of the aeronautical fixed telecommunication network (AFTN) and operating as such under the authority or control of a State.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<i>Aircraft station (RR S1.83).</i> A mobile station in the aeronautical mobile service, other than a survival craft station, located on board an aircraft.	CAR Part 1.	No Difference		Note: "Aircraft radio station".



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Air-ground control radio station.</b> An aeronautical telecommunication station having primary responsibility for handling communications pertaining to the operation and control of aircraft in a given area.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Communication centre.</b> An aeronautical fixed station which relays or retransmits telecommunication traffic from (or to) a number of other aeronautical fixed stations directly connected to it.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Mobile surface station.</b> A station in the aeronautical telecommunication service, other than an aircraft station, intended to be used while in motion or during halts at unspecified points.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Network station.</b> An aeronautical station forming part of a radiotelephony network.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Radio direction finding (RR S1.12).</b> Radiodetermination using the reception of radio waves for the purpose of determining the direction of a station or object.	MATS RAC 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Radio direction-finding station (RR S1.91).</b> A radiodetermination station using radio direction finding. <i>Note.— The aeronautical application of radio direction finding is in the aeronautical radio navigation service.</i>	MATS RAC 1.	No Difference		Implicit in definition of "Radio direction finding".
Chapter 1 Reference  Definition	<b>Regular station.</b> A station selected from those forming an en-route air-ground radiotelephony network to communicate with or to intercept communications from aircraft in normal conditions.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Tributary station.</b> An aeronautical fixed station that may receive or transmit messages and/or digital data but which does not relay except for the purpose of serving similar stations connected through it to a communication centre.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>1.3 Communication methods</b> <b>Air-ground communication.</b> Two-way communication between aircraft and stations or locations on the surface of the earth.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Air-to-ground communication.</b> One-way communication from aircraft to stations or locations on the surface of the earth.	MATS RAC 1.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Blind transmission.</b> A transmission from one station to another station in circumstances where two-way communication cannot be established but where it is believed that the called station is able to receive the transmission.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Broadcast.</b> A transmission of information relating to air navigation that is not addressed to a specific station or stations.	CAR Part 1.	No Difference		
Chapter 1 Reference  Definition	<b>Duplex.</b> A method in which telecommunication between two stations can take place in both directions simultaneously.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Ground-to-air communication.</b> One-way communication from stations or locations on the surface of the earth to aircraft.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Interpilot air-to-air communication.</b> Two-way communication on the designated air-to-air channel to enable aircraft engaged in flights over remote and oceanic areas out of range of VHF ground stations to exchange necessary operational information and to facilitate the resolution of operational problems.	MATS RAC 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Non-network communications.</b> Radiotelephony communications conducted by a station of the aeronautical mobile service, other than those conducted as part of a radiotelephony network.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Radiotelephony network.</b> A group of radiotelephony aeronautical stations which operate on and guard frequencies from the same family and which support each other in a defined manner to ensure maximum dependability of air-ground communications and dissemination of air-ground traffic.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Readback.</b> A procedure whereby the receiving station repeats a received message or an appropriate part thereof back to the transmitting station so as to obtain confirmation of correct reception.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Simplex.</b> A method in which telecommunication between two stations takes place in one direction at a time.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Telecommunication (RR S1.3).</b> Any transmission, emission, or reception of signs, signals, writing, images and sounds or intelligence of any nature by wire, radio, optical or other electromagnetic systems.	MATS RAC 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<p style="text-align: center;"><b>1.4 Direction finding</b></p> <p><b>Homing.</b> The procedure of using the direction-finding equipment of one radio station with the emission of another radio station, where at least one of the stations is mobile, and whereby the mobile station proceeds continuously towards the other station.</p>	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<p><b>Radio bearing.</b> The angle between the apparent direction of a definite source of emission of electro-magnetic waves and a reference direction, as determined at a radio direction-finding station. A <i>true</i> radio bearing is one for which the reference direction is that of true North. A <i>magnetic</i> radio bearing is one for which the reference direction is that of magnetic North.</p>	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<p style="text-align: center;"><b>1.5 Teletypewriter systems</b></p> <p><b>Automatic relay installation.</b> A teletypewriter installation where automatic equipment is used to transfer messages from incoming to outgoing circuits. <i>Note.— This term covers both fully automatic and semi-automatic installations.</i></p>	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<p><b>“Torn-tape” relay installation.</b> A teletypewriter installation where messages are received and relayed in teletypewriter tape form and where all operations of relay are performed as the result of operator intervention.</p>		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Fully automatic relay installation.</b> A teletypewriter installation where interpretation of the relaying responsibility in respect of an incoming message and the resultant setting-up of the connections required to effect the appropriate retransmissions is carried out automatically, as well as all other normal operations of relay, thus obviating the need for operator intervention, except for supervisory purposes.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Message field.</b> An assigned area of a message containing specified elements of data.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Semi-automatic relay installation.</b> A teletypewriter installation where interpretation of the relaying responsibility in respect of an incoming message and the resultant setting-up of the connections required to effect the appropriate retransmissions require the intervention of an operator but where all other normal operations of relay are carried out automatically.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Teletypewriter tape.</b> A tape on which signals are recorded in the 5-unit Start-Stop code by completely severed perforations (Chad Type) or by partially severed perforations (Chadless Type) for transmission over teletypewriter circuits.		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<p style="text-align: center;"><b>1.6 Agencies</b></p> <p><i>Aeronautical telecommunication agency.</i> An agency responsible for operating a station or stations in the aeronautical telecommunication service.</p>	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<i>Aircraft operating agency.</i> The person, organization or enterprise engaged in, or offering to engage in, an aircraft operation.	CAR Part 1.	Different in character or other means of compliance	Implicit in definition "operate".	
Chapter 1 Reference  Definition	<p style="text-align: center;"><b>1.7 Frequencies</b></p> <p><i>Primary frequency.</i> The radiotelephony frequency assigned to an aircraft as a first choice for air-ground communication in a radiotelephony network.</p>	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<i>Secondary frequency.</i> The radiotelephony frequency assigned to an aircraft as a second choice for air-ground communication in a radiotelephony network.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<p style="text-align: center;"><b>1.8 Data link communications</b></p> <p><i>Controller-pilot data link communications (CPDLC).</i> A means of communication between controller and pilot, using data link for ATC communications.</p>	MATS RAC 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Current data authority.</b> The designated ground system through which a CPDLC dialogue between a pilot and a controller currently responsible for the flight is permitted to take place.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Downstream data authority.</b> A designated ground system, different from the current data authority, through which the pilot can contact an appropriate ATC unit for the purposes of receiving a downstream clearance.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Free text message element.</b> A message element used to convey information not conforming to any standardized message element in the CPDLC message set.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Next data authority.</b> The ground system so designated by the current data authority through which an onward transfer of communications and control can take place.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Pre-formatted free text message element.</b> A free text message element that is stored within the aircraft system or ground system for selection.	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Standardized free text message element.</b> A message element that uses a defined free text message format, using specific words in a specific order. <i>Note.— Standardized free text message elements may be manually entered by the user or pre-formatted.</i>	CARs.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>1.9 Miscellaneous</b> <b>Aeronautical fixed circuit.</b> A circuit forming part of the aeronautical fixed service (AFS).	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Aeronautical fixed telecommunication network circuit.</b> A circuit forming part of the aeronautical fixed telecommunication network (AFTN).	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Aeronautical telecommunication log.</b> A record of the activities of an aeronautical telecommunication station.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Air-report.</b> A report from an aircraft in flight prepared in conformity with requirements for position, and operational and/ or meteorological reporting. <i>Note.— Details of the AIREP form are given in PANS-ATM (Doc 4444).</i>	MATS RAC 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<i>Altitude.</i> The vertical distance of a level, a point or an object considered as a point, measured from mean sea level (MSL).	CAR Part 1.	No Difference		
Chapter 1 Reference  Definition	<i>ATS direct speech circuit.</i> An aeronautical fixed service (AFS) telephone circuit, for direct exchange of information between air traffic services (ATS) units.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<i>Automatic telecommunication log.</i> A record of the activities of an aeronautical telecommunication station recorded by electrical or mechanical means.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<p><b>Flight level.</b> A surface of constant atmospheric pressure which is related to a specific pressure datum, 1 013.2 hectopascals (hPa), and is separated from other such surfaces by specific pressure intervals.</p> <p><i>N1.A pressure type altimeter calibrated in accordance with the standard atmosphere:</i></p> <ul style="list-style-type: none"> <li>a) when set to a <i>QNH</i> altimeter setting, will indicate altitude;</li> <li>b) when set to a <i>QFE</i> altimeter setting, will indicate height above the <i>QFE</i> reference datum;</li> <li>c) when set to a pressure 1 013.2 hPa, may be used to indicate flight levels.</li> </ul> <p><i>N2.The terms "height" and "altitude", used in Note 1 above, indicate altimetric rather than geometric heights and altitudes.</i></p>	CAR Part 1.	No Difference		
Chapter 1 Reference  Definition	<p><b>Frequency channel.</b> A continuous portion of the frequency spectrum appropriate for a transmission utilizing a specified class of emission.</p> <p><i>Note.— The classification of emissions and information relevant to the portion of the frequency spectrum appropriate for a given type of transmission (bandwidths) is specified in the ITU Radio Regulations, Article S2 and Appendix S1.</i></p>	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<p><b>Height.</b> The vertical distance of a level, a point or an object considered as a point, measured from a specified datum.</p>	CAR Part 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>Human performance.</b> Human capabilities and limitations which have an impact on the safety and efficiency of aeronautical operations.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	Common usage term.
Chapter 1 Reference  Definition	<b>Location indicator.</b> A four-letter code group formulated in accordance with rules prescribed by ICAO and assigned to the location of an aeronautical fixed station.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Meteorological operational channel.</b> A channel of the aeronautical fixed service (AFS), for the exchange of aeronautical meteorological information.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Meteorological operational telecommunication network.</b> An integrated system of meteorological operational channels, as part of the aeronautical fixed service (AFS), for the exchange of aeronautical meteorological information between the aeronautical fixed stations within the network. <i>Note.— “Integrated” is to be interpreted as a mode of operation necessary to ensure that the information can be transmitted and received by the stations within the network in accordance with pre-established schedules.</i>	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<b>NOTAM.</b> A notice distributed by means of telecommunication containing information concerning the establishment, condition or change in any aeronautical facility, service, procedure or hazard, the timely knowledge of which is essential to personnel concerned with flight operations.	CAR Part 1.	No Difference		
Chapter 1 Reference  Definition	<b>Operational control communications.</b> Communications required for the exercise of authority over the initiation, continuation, diversion or termination of a flight in the interest of the safety of the aircraft and the regularity and efficiency of a flight. <i>Note.— Such communications are normally required for the exchange of messages between aircraft and aircraft operating agencies.</i>	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	
Chapter 1 Reference  Definition	<b>Route segment.</b> A route or portion of route usually flown without an intermediate stop.	MATS RAC 1.	No Difference		
Chapter 1 Reference  Definition	<b>Routing Directory.</b> A list in a communication centre indicating for each addressee the outgoing circuit to be used.	CAR Part 1.	Less protective or partially implemented or not implemented	Not specifically defined.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 1 Reference  Definition	<i><b>SNOWTAM.</b></i> A special series NOTAM notifying the presence or removal of hazardous conditions due to snow, ice, slush or standing water associated with snow, slush and ice on the movement area, by means of a specific format.		Not Applicable		
Chapter 2 Reference 2.1  Standard	<p style="text-align: center;"><b>CHAPTER 2. ADMINISTRATIVE PROVISIONS RELATING TO THE INTERNATIONAL AERONAUTICAL TELECOMMUNICATION SERVICE</b></p> <p style="text-align: center;"><b>Division of service</b></p> <p>The international aeronautical telecommunication service shall be divided into four parts:</p> <ol style="list-style-type: none"> <li>1)aeronautical fixed service;</li> <li>2)aeronautical mobile service;</li> <li>3)aeronautical radio navigation service;</li> <li>4)aeronautical broadcasting service.</li> </ol>	CAR Part 1.	No Difference		Note: "Aeronautical telecommunication service".
Chapter 2 Reference 2.2  Standard	<p style="text-align: center;"><b>Telecommunication — Access</b></p> <p>All aeronautical telecommunication stations, including end systems and intermediate systems of the aeronautical telecommunication network (ATN), shall be protected from unauthorized direct or remote access.</p>	CAR 171.55.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.3.1  Standard	<p style="text-align: center;"><b>2.3 Hours of service</b></p> <p>The Competent Authority shall give notification of the normal hours of service of stations and offices of the international aeronautical telecommunication service under its control to the aeronautical telecommunication agencies designated to receive this information by other Administrations concerned.</p>	CAR 171.19; AIPNZ GEN 3.4, 1.5.	No Difference		
Chapter 2 Reference 2.3.2  Standard	Whenever necessary and practicable, the Competent Authority shall give notification of any change in the normal hours of service, before such a change is effected, to the aeronautical telecommunication agencies designated to receive this information by other Administrations concerned. Such changes shall also, whenever necessary, be promulgated in NOTAM.	CAR 171.19; AIPNZ GEN 3.4, 1.5.	No Difference		
Chapter 2 Reference 2.3.3  Standard	If a station of the international aeronautical telecommunication service, or an aircraft operating agency, requests a change in the hours of service of another station, such change shall be requested as soon as possible after the need for change is known. The station or aircraft operating agency requesting the change shall be informed of the result of its request as soon as possible.	CAR 171.19.	No Difference		
Chapter 2 Reference 2.4.1  Standard	<p style="text-align: center;"><b>2.4 Supervision</b></p> <p>Each State shall designate the authority responsible for ensuring that the international aeronautical telecommunication service is conducted in accordance with the Procedures in this Annex.</p>	Civil Aviation (CA) Act 1990.	Less protective or partially implemented or not implemented	The Civil Aviation Authority of New Zealand (CAANZ) is the de facto telecommunications authority. The delegation has yet to be formally ratified by the Minister of Transport.	ICAO USOAP Audit finding ANS/10. Awaiting response from Miniater.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.4.2  Recommendation	<b>Recommendation.</b> — <i>Occasional infringements of the Procedures contained herein, when not serious, should be dealt with by direct communication between the parties immediately interested either by correspondence or by personal contact.</i>	CAR Part 12.	No Difference		Provides for reporting and investigation of incidents.
Chapter 2 Reference 2.4.3  Standard	When a station commits serious or repeated infringements, representations relating to them shall be made to the authority designated in 2.4.1 of the State to which the station belongs by the authority which detects them.	CA Act 1990 s15 and 17.	No Difference		
Chapter 2 Reference 2.4.4  Recommendation	<b>Recommendation.</b> — <i>The authorities designated in 2.4.1 should exchange information regarding the performance of systems of communication, radio navigation, operation and maintenance, unusual transmission phenomena, etc.</i>	CAR Part 171.	Less protective or partially implemented or not implemented	Not specifically mandated.	
Chapter 2 Reference 2.5  Standard	<b>Superfluous transmissions</b> Each State shall ensure that there is no wilful transmission of unnecessary or anonymous signals, messages or data by any station within that State.	Radiocommunications Act 1989. Radiocommunications Regulations. CAR 171.21.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 2 Reference 2.6  Standard	<p style="text-align: center;"><b>Interference</b></p> <p>Before authorizing tests and experiments in any station, each Administration, in order to avoid harmful interference, shall prescribe the taking of all possible precautions, such as the choice of frequency and of time, and the reduction or, if possible, the suppression of radiation. Any harmful interference resulting from tests and experiments shall be eliminated as soon as possible.</p>	CAR 171.53(b) and (c).	No Difference		
Chapter 3 Reference 3.1  Standard	<p style="text-align: center;"><b>CHAPTER 3. GENERAL PROCEDURES FOR THE INTERNATIONAL AERONAUTICAL TELECOMMUNICATION SERVICE</b></p> <p style="text-align: center;"><b>General</b></p> <p>The procedures outlined in this chapter are general in character and shall be applied where appropriate to the other chapters contained in this Volume.</p> <p><i>Note.— Detailed procedures, with special application to the service concerned, are contained in Chapters 4, 5, 6, 7 and 8.</i></p>	CAR 171.75.	No Difference		The rule incorporates the Standards by reference.
Chapter 3 Reference 3.2.1  Standard	<p style="text-align: center;"><b>3.2 Extensions of service and closing down of stations</b></p> <p>Stations of the international aeronautical telecommunication service shall extend their normal hours of service as required to provide for traffic necessary for flight operation.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.2.2  Standard	Before closing down, a station shall notify its intention to all other stations with which it is in direct communication, confirm that an extension of service is not required and advise the time of re-opening if other than its normal hours of service.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.2.3  Standard	When it is working regularly in a network on a common circuit, a station shall notify its intention of closing down either to the control station, if any, or to all stations in the network. It shall continue watch for two minutes and may then close down if it has received no call during this period.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.2.4  Standard	Stations with other than continuous hours of operation, engaged in, or expected to become engaged in distress, urgency, unlawful interference, or interception traffic, shall extend their normal hours of service to provide the required support to those communications.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.1  Standard	<b>3.3 Acceptance, transmission and delivery of messages</b>  Only those messages coming within the categories specified in 4.4.1.1 shall be accepted for transmission by the aeronautical telecommunication service.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.1.1  Standard	The responsibility for determining the acceptability of a message shall rest with the station where the message is filed for transmission.	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.3.1.2  Standard	Once a message is deemed acceptable, it shall be transmitted, relayed and (or) delivered in accordance with the priority classification and without discrimination or undue delay.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.1.3  Recommendation	<b>Recommendation.</b> — <i>The authority in control of any station through which a message is relayed, should make representations at a later date to the authority in control of the accepting station regarding any message which is considered unacceptable.</i>	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.2  Standard	Only messages for stations forming part of the aeronautical telecommunication service shall be accepted for transmission, except where special arrangements have been made with the telecommunication authority concerned.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.2.1  Standard	Acceptance as a single message of a message intended for two or more addresses, whether at the same station or at different stations, shall be permitted subject, however, to the provisions prescribed in 4.4.3.1.2.3.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.3  Standard	Messages handled for aircraft operating agencies shall be accepted only when handed in to the telecommunication station in the form prescribed herein and by an authorized representative of that agency, or when received from that agency over an authorized circuit.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.3.4  Standard	For each station of the aeronautical telecommunication service from which messages are delivered to one or more aircraft operating agencies, a single office for each aircraft operating agency shall be designated by agreement between the aeronautical telecommunication agency and the aircraft operating agency concerned.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.5  Standard	Stations of the international aeronautical telecommunication service shall be responsible for delivery of messages to addressee(s) located within the boundaries of the aerodrome(s) served by that station and beyond those boundaries only to such addressee(s) as may be agreed by special arrangements with the Administrations concerned.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.6  Standard	Messages shall be delivered in the form of a written record, or other permanent means as prescribed by authorities.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.6.1  Recommendation	<b>Recommendation.</b> — <i>In cases where telephone or loudspeaker systems are used without recording facilities for the delivery of messages, a written copy should be provided, as confirmation of delivery, as soon as possible.</i>	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.7  Standard	Messages originated in the aeronautical mobile service by an aircraft in flight and which require transmission over the aeronautical fixed telecommunication network to effect delivery, shall be reprocessed by the aeronautical telecommunication station into the message format prescribed in 4.4.2 prior to transmission on the AFTN.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.3.7.1  Standard	Messages originated in the aeronautical mobile service by an aircraft in flight and which require transmission over the aeronautical fixed service, other than on AFTN circuits, shall also be reprocessed by the aeronautical telecommunication station into the format prescribed in 4.4.2 except where, subject to the provisions of 3.3.5, prior and other arrangements have been made between the aeronautical telecommunication agency and the aircraft operating agency concerned for predetermined distribution of messages from aircraft.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.7.2  Standard	Messages (including air-reports) without specific address containing meteorological information received from an aircraft in flight shall be forwarded without delay to the meteorological office associated with the point of reception.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.7.3  Standard	Messages (including air-reports) without specific address containing air traffic services information from aircraft in flight shall be forwarded without delay to the air traffic services unit associated with the communication station receiving the message.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.3.7.4  PANS	<b>PANS.</b> — <i>When recording the text of air-reports in AIREP form, the data conventions approved by ICAO for this purpose shall be used wherever possible.</i>  <i>Note.— Provisions relating to the composition, including data conventions, of air-reports and to the order and form in which the elements of such reports are transmitted by the aircraft stations and recorded and retransmitted by the aeronautical stations, are contained in the PANS-ATM (Doc.4444).</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.3.7.5  PANS	<b>PANS.</b> — <i>When air-reports in AIREP form are to be retransmitted by telegraphy (including teletypewriting), the text transmitted shall be as recorded in compliance with 3.3.7.4.</i>	CAR 171.75.	No Difference		
Chapter 3 Reference 3.4.1  Standard	<b>3.4 Time system</b>  Universal Co-ordinated Time (UTC) shall be used by all stations in the aeronautical telecommunication service. Midnight shall be designated as 2400 for the end of the day and 0000 for the beginning of the day.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.4.2  Standard	A date-time group shall consist of six figures, the first two figures representing the date of the month and the last four figures the hours and minutes in UTC.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.5.1.1  Standard	<p align="center"><b>3.5 Record of communications</b></p> <p align="center">3.5.1 General</p> <p>A telecommunication log, written or automatic, shall be maintained in each station of the aeronautical telecommunication service except that an aircraft station, when using radiotelephony in direct communication with an aeronautical station, need not maintain a telecommunication log.</p> <p><i>Note.— The telecommunication log will serve as a protection, should the operator's watch activities be investigated. It may be required as legal evidence.</i></p>	CAR 171.75.	No Difference		
Chapter 3 Reference 3.5.1.1.1  Recommendation	<p><b>Recommendation.—</b> <i>Aeronautical stations should record messages at the time of their receipt, except that, if during an emergency the continued manual recording would result in delays in communication, the recording of messages may be temporarily interrupted and completed at the earliest opportunity.</i></p> <p><i>Note.— In the case of radiotelephony operation it would be desirable if voice recording were provided for use during interruption in manual recording.</i></p>	CAR 171.75.	No Difference		
Chapter 3 Reference 3.5.1.1.2  Recommendation	<p><b>Recommendation.—</b> <i>When a record is maintained in an aircraft station, either in a radiotelephone log or elsewhere, concerning distress communications, harmful interference, or interruption to communications, such a record should be associated with information concerning the time and the position, and altitude of the aircraft.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.5.1.2  Standard	In written logs, entries shall be made only by operators on duty except that other persons having knowledge of facts pertinent to the entries may certify in the log the accuracy of operators' entries.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.5.1.3  Standard	All entries shall be complete, clear, correct and intelligible. Superfluous marks or notations shall not be made in the log.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.5.1.4  Standard	In written logs, any necessary correction in the log shall be made only by the person making the initial entry. The correction shall be accomplished by drawing or typing a single line through the incorrect entry, initialling same, recording the time and date of correction. The correct entry shall be made on the next line after the last entry.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.5.1.5  Standard	Telecommunication logs, written or automatic, shall be retained for a period of at least thirty days. When logs are pertinent to inquiries or investigations they shall be retained for longer periods until it is evident that they will be no longer required.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.5.1.6  Standard	The following information shall be entered in written logs: a) the name of the agency operating the station; b) the identification of the station; c) the date; d) the time of opening and closing the station; e) the signature of each operator, with the time the operator assumes and relinquishes a watch; f) the frequencies being guarded and type of watch (continuous or scheduled) being maintained on each frequency; g) except at intermediate mechanical relay stations where the provisions of this paragraph need not be complied with, a record of each communication, test transmission, or attempted communication showing text of communication, time communication completed, station(s) communicated with, and frequency used. The text of the communication may be omitted from the log when copies of the messages handled are available and form part of the log; h) all distress communications and action thereon; i) a brief description of communication conditions and difficulties, including harmful interference. Such entries should include, whenever practicable, the time at which interference was experienced, the character, radio frequency and identification of the interfering signal; j) a brief description of interruption to communications due to equipment failure or other troubles, giving the duration of the interruption and action taken; k) such additional information as may be considered by the operator to be of value as a part of the record of the station's operations.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.6.1  Standard	<p align="center"><b>3.6 Establishment of radiocommunication</b></p> <p>All stations shall answer calls directed to them by other stations in the aeronautical telecommunication service and shall exchange communications on request.</p>	CAR 171.75.	No Difference		
Chapter 3 Reference 3.6.2  Standard	All stations shall radiate the minimum power necessary to ensure a satisfactory service.	CAR 171.75.	No Difference		
Chapter 3 Reference 3.7.1  Standard	<p align="center"><b>3.7 Use of abbreviations and codes</b></p> <p>Abbreviations and codes shall be used in the international aeronautical telecommunication service whenever they are appropriate and their use will shorten or otherwise facilitate communication.</p>	CAR 171.75.	No Difference		
Chapter 3 Reference 3.7.1.1  Standard	<p>Where abbreviations and codes other than those approved by ICAO are contained in the text of messages, the originator shall, if so required by the aeronautical telecommunication station accepting the message for transmission, make available to that station a decode for the abbreviations and codes used.</p> <p><i>Note.— The use of ICAO approved abbreviations and codes wherever appropriate — for example, those contained in PANS-ABC (Doc 8400) — obviates the need for application of the provisions of 3.7.1.1.</i></p>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 3 Reference 3.8  Standard	<p style="text-align: center;"><b>Cancellation of messages</b></p> <p>Messages shall be cancelled by a telecommunication station only when cancellation is authorized by the message originator.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference 4.1.1</p> <p>Standard</p>	<p style="text-align: center;"><b>CHAPTER 4. AERONAUTICAL FIXED SERVICE (AFS)</b></p> <p style="text-align: center;"><b>General</b></p> <p>The aeronautical fixed service shall comprise the following systems and applications that are used for ground-ground (i.e. point-to-point and/or point-to-multipoint) communications in the international aeronautical telecommunication service:</p> <ul style="list-style-type: none"> <li>a) ATS direct speech circuits and networks;</li> <li>b) meteorological operational circuits, networks and broadcast systems;</li> <li>c) the aeronautical fixed telecommunications network (AFTN);</li> <li>d) the common ICAO data interchange network (CIDIN);</li> <li>e) the air traffic services (ATS) message handling services; and</li> <li>f) the inter-centre communications (ICC).</li> </ul> <p><i>N1.Provisions relating to ATS direct speech communications are contained in 4.2.</i></p> <p><i>N2.Provisions relating to meteorological operational channels and meteorological operational telecommunication networks are contained in 4.3.</i></p> <p><i>N3.The AFTN provides a store-and-forward messaging service for the conveyance of text messages in ITA-2 or IA-5 format, using character-oriented procedures. Provisions relating to the AFTN are contained in 4.4.</i></p> <p><i>N4.The CIDIN provides a common transport service for the conveyance of binary or text application messages, in support of the AFTN and OPMET applications. Procedural provisions relating to the CIDIN are contained in 4.5.</i></p> <p><i>N5.The ATS (air traffic services) message handling services (ATSMHS) application allows ATS messages to be exchanged between service users over the aeronautical telecommunication network (ATN) internet communication</i></p>	<p>CAR 171.75.</p>	<p>No Difference</p>		<p>The rule incorporates the Standards by reference.</p>



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p><i>service (ICS). Procedural provisions relating to ATS message handling services are contained in 4.6.</i></p> <p><i>N6.The inter-centre communications applications enable the exchange of information between air traffic service units over the aeronautical telecommunication network (ATN) internet communication service (ICS), in support of notification, coordination, transfer of control, flight planning, airspace management and air traffic flow management. Procedural provisions relating to inter-centre communications are contained in 4.7.</i></p> <p><i>N7.The aeronautical telecommunication network through its ATSMHS and ICC applications enable the transition of existing AFTN and CIDIN users and systems into the ATN architecture.</i></p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.1.2.1  Standard	<p><b>4.1.2</b> Material permitted in AFS messages <i>Note.— The provisions contained in 4.1.2 do not apply to ATS voice communications.</i></p> <p>The following characters are allowed in text messages:  <i>Letters:</i> ABCDEFGHIJKLMNOPQRSTUVWXYZ  <i>Figures:</i> 1 2 3 4 5 6 7 8 9 0  <i>Other signs:</i></p> <ul style="list-style-type: none"> <li>- (hyphen)</li> <li>? (question mark)</li> <li>:</li> <li>( (open bracket)</li> <li>) (close bracket)</li> <li>. (full stop, period, or decimal point)</li> <li>,</li> <li>' (apostrophe)</li> <li>= (double hyphen or equal sign)</li> <li>/ (oblique)</li> <li>+ (plus sign)</li> </ul> <p>Characters other than those listed above shall not be used in messages unless absolutely necessary for understanding of the text. When used, they shall be spelled out in full.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.1.2.2  Standard	<p>For the exchange of messages over the teletypewriter circuits, the following signals of the International Telegraph Alphabet No. 2 (ITA-2) shall be permitted:</p> <p>signals nos. 1 to 3 — in letter and in figure case;</p> <p>signal no. 4 — in letter case only;</p> <p>signal no.5 — in letter and in figure case;</p> <p>signal nos. 6 to 8 — in letter case only;</p> <p>signal no. 9 — in letter and in figure case;</p> <p>signal no. 10 — in letter case only; and</p> <p>signals nos. 11 to 31 — in letter and figure case.</p> <p><i>N1. "Letter case" and "figure case" are to be understood as the shift condition in which the equipment associated with the channel was positioned prior to the reception of the signal.</i></p> <p><i>N2. When using any of the above signals, account is to be taken of, amongst others, the provisions of 4.4.5.3.</i></p> <p><i>N3. The foregoing provisions of 4.1.2.2 are not intended to prevent the use of:</i></p> <p><i>a) figure case of signals nos. 6, 7 and 8 after bilateral agreements between States having telecommunication stations directly connected to each other;</i></p> <p><i>b) figure case of signal no. 10 as the priority alarm (see 4.4.4.3); and</i></p> <p><i>c) figure case of signal no. 4 for operational purposes only and not as part of a message.</i></p> <p><i>a)</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.1.2.3  Standard	For the exchange of messages over the teletypewriter circuits, the following characters of International Alphabet No. 5 (IA-5) shall be permitted: characters 0/1 to 0/3, 0/7 — in the priority alarm ( <i>see</i> 4.4.15.2.2.5), 0/10, 0/11 — in the ending sequence ( <i>see</i> 4.4.15.3.12.1), 0/13; characters 2/0, 2/7 to 2/9, 2/11 to 2/15; characters 3/0 to 3/10, 3/13, 3/15; characters 4/1 to 4/15; characters 5/0 to 5/10; and character 7/15. <i>Note.— The foregoing provisions of 4.1.2.3 are not intended to prevent the use of the full IA-5 after agreement between the Administrations concerned.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.1.2.4  Standard	Roman numerals shall not be employed. If the originator of a message wishes the addressee to be informed that roman figures are intended, the arabic figure or figures shall be written and preceded by the word ROMAN.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.1.2.5  Standard	Messages using the ITA-2 code shall not contain: 1) any uninterrupted sequence of signals nos. 26, 3, 26 and 3 (letter case and figure case) in this order, other than the one in the heading as prescribed in 4.4.2.1.1; and 2) any uninterrupted sequence of four times signal no. 14 (letter case and figure case) other than the one in the ending as prescribed in 4.4.6.1.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.1.2.6  Standard	Messages using IA-5 shall not contain: 1)character 0/1 (SOH) other than the one in the heading as prescribed in 4.4.15.1.1 a); 2)character 0/2 (STX) other than the one in the origin line as prescribed in 4.4.15.2.2.7; 3)character 0/3 (ETX) other than the one in the ending as prescribed in 4.4.15.3.12.1; 4)any uninterrupted sequence of characters 5/10, 4/3, 5/10, 4/3 in this order (ZCZC); 5)any uninterrupted sequence of characters 2/11, 3/10, 2/11, 3/10 in this order (+:+:); 6)any uninterrupted sequence of four times character 4/14 (NNNN); and 7)any uninterrupted sequence of four times character 2/12 (,,,,).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.1.2.7  Standard	The text of messages shall be drafted in plain language or in abbreviations and codes, as prescribed in 3.7. The originator shall avoid the use of plain language when reduction in the length of the text by appropriate abbreviations and codes is practicable. Words and phrases which are not essential, such as expressions of politeness, shall not be used.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.1.2.8  Standard	If the originator of a message wishes alignment functions [ $\leq$ ] to be transmitted at specific places in the text part of such message (see 4.4.5.3 and 4.4.15.3.6), the sequence [ $\leq$ ] shall be written on each of those places.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.2  Note	<p align="center"><b>ATS direct speech circuits</b></p> <p align="center"><i>Note.— Provisions relating to ATS direct speech communications are contained in Chapter 6 of Annex 11.</i></p>		Not Applicable		Compliance data not required for Notes.
Chapter 4 Reference 4.3  Standard	<p align="center"><b>Meteorological operational channels and meteorological operational telecommunication networks</b></p> <p>Meteorological operational channel procedures and meteorological operational communication network procedures shall be compatible with aeronautical fixed telecommunications network (AFTN) procedures.</p> <p><i>Note.— “Compatible” is to be interpreted as a mode of operation ensuring that the information exchanged over the meteorological operational channels also can be exchanged over the aeronautical fixed telecommunication network without harmful effect on the operation of the aeronautical fixed telecommunication network and vice versa.</i></p>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.1  Standard	<p><b>4.4 Aeronautical fixed telecommunication network (AFTN)</b></p> <p>4.4.1 General</p> <p><i>Categories of messages.</i> Subject to the provisions of 3.3, the following categories of message shall be handled by the aeronautical fixed telecommunication network:</p> <ul style="list-style-type: none"> <li>a) distress messages;</li> <li>b) urgency messages;</li> <li>c) flight safety messages;</li> <li>d) meteorological messages;</li> <li>e) flight regularity messages;</li> <li>f) aeronautical information services (AIS) messages;</li> <li>g) aeronautical administrative messages;</li> <li>h) service messages.</li> </ul>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.1  Standard	<p><i>Distress messages (priority indicator SS).</i> This message category shall comprise those messages sent by mobile stations reporting that they are threatened by grave and imminent danger and all other messages relative to the immediate assistance required by the mobile station in distress.</p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.2  Standard	<p><i>Urgency messages (priority indicator DD).</i> This category shall comprise messages concerning the safety of a ship, aircraft or other vehicles, or of some person on board or within sight.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.1.3  Standard	Flight safety messages (priority indicator FF) shall comprise: a) movement and control messages as defined in PANS-ATM (Doc 4444), Chapter 11; b) messages originated by an aircraft operating agency of immediate concern to aircraft in flight or preparing to depart; c) meteorological messages restricted to SIGMET information, special air-reports, AIRMET messages, volcanic ash and tropical cyclone advisory information and amended forecasts.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.4  Standard	Meteorological messages (priority indicator GG) shall comprise: a) messages concerning forecasts, e.g. terminal aerodrome forecasts (TAFs), area and route forecasts; b) messages concerning observations and reports, e.g. METAR, SPECI.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.1.5  Standard	Flight regularity messages (priority indicator GG) shall comprise: a) aircraft load messages required for weight and balance computation; b) messages concerning changes in aircraft operating schedules; c) messages concerning aircraft servicing; d) messages concerning changes in collective requirements for passengers, crew and cargo covered by deviation from normal operating schedules; e) messages concerning non-routine landings; f) messages concerning pre-flight arrangements for air navigation services and operational servicing for non-scheduled aircraft operations, e.g. overflight clearance requests; g) messages originated by aircraft operating agencies reporting an aircraft arrival or departure; h) messages concerning parts and materials urgently required for the operation of aircraft.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.6  Standard	Aeronautical information services (AIS) messages (priority indicator GG) shall comprise: a) messages concerning NOTAMs; b) messages concerning SNOWTAMs.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.1.7  Standard	Aeronautical administrative messages (priority indicator KK) shall comprise: a) messages regarding the operation or maintenance of facilities provided for the safety or regularity of aircraft operations; b) messages concerning the functioning of aeronautical telecommunication services; c) messages exchanged between civil aviation authorities relating to aeronautical services.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.8  Standard	Messages requesting information shall take the same priority indicator as the category of message being requested except where a higher priority is warranted for flight safety.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.9  Standard	<i>Service messages (priority indicator as appropriate).</i> This category shall comprise messages originated by aeronautical fixed stations to obtain information or verification concerning other messages which appear to have been transmitted incorrectly by the aeronautical fixed service, confirming channel-sequence numbers, etc.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.9.1  Standard	Service messages shall be prepared in the format prescribed in 4.4.2 or 4.4.15. In applying the provisions of 4.4.3.1.2 or 4.4.15.2.1.3 to service messages addressed to an aeronautical fixed station identified only by a location indicator, this indicator shall be immediately followed by the ICAO three-letter designator YFY, followed by an appropriate 8th letter.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.1.9.2  Standard	Service messages shall be assigned the appropriate priority indicator.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.9.2.1  Recommendation	<b>Recommendation.</b> — <i>When service messages refer to messages previously transmitted, the priority indicator assigned should be that used for the message(s) to which they refer.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.9.3  Standard	Service messages correcting errors in transmission shall be addressed to all the addressees that will have received the incorrect transmission.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.9.4  Standard	A reply to a service message shall be addressed to the station which originated the initial service message.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.1.9.5  Recommendation	<b>Recommendation.</b> — <i>The text of all service messages should be as concise as possible.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference								
Chapter 4 Reference 4.4.1.1.9.6  Standard	A service message, other than one acknowledging receipt of SS messages, shall be further identified by the use of the abbreviation SVC as the first item in the text.	CAR 171.75.	No Difference										
Chapter 4 Reference 4.4.1.1.9.7  Standard	When a service message refers to a message previously handled, reference to the previous message shall be made by use of the appropriate transmission identification ( <i>see</i> 4.4.2.1.1 b) and 4.4.15.1.1 b)) or the filing time and originator indicator groups ( <i>see</i> 4.4.4 and 4.4.15.2.2) identifying the reference message.	CAR 171.75.	No Difference										
Chapter 4 Reference 4.4.1.2.1  Standard	<p><i>4.4.1.2 Order of priority</i></p> <p>The order of priority for the transmission of messages in the aeronautical fixed telecommunication network shall be as follows:</p> <table data-bbox="441 974 934 1201"> <thead> <tr> <th><i>Transmission priority indicator</i></th> <th><i>Priority</i></th> </tr> </thead> <tbody> <tr> <td>1</td> <td>SS</td> </tr> <tr> <td>2</td> <td>DD FF</td> </tr> <tr> <td>3</td> <td>GG KK</td> </tr> </tbody> </table>	<i>Transmission priority indicator</i>	<i>Priority</i>	1	SS	2	DD FF	3	GG KK	CAR 171.75.	No Difference		
<i>Transmission priority indicator</i>	<i>Priority</i>												
1	SS												
2	DD FF												
3	GG KK												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.2.2  Recommendation	<b>Recommendation.</b> — <i>Messages having the same priority indicator should be transmitted in the order in which they are received for transmission.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.3.1  Standard	<b>4.4.1.3 Routing of messages</b>  All communications shall be routed by the most expeditious route available to effect delivery to the addressee.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.3.2  Standard	Predetermined diversion routing arrangements shall be made, when necessary, to expedite the movement of communication traffic. Each communication centre shall have the appropriate diversion routing lists, agreed to by the Administration(s) operating the communication centres affected and shall use them when necessary.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 4 Reference 4.4.1.3.2.1</p> <p>Recommendation</p>	<p><b>Recommendation.</b>— <i>Diversion routing should be initiated:</i></p> <p>1) <i>in a fully automatic communication centre:</i></p> <p>a) <i>immediately after detection of the circuit outage, when the traffic is to be diverted via a fully automatic communication centre;</i></p> <p>b) <i>within a 10-minute period after detection of the circuit outage, when the traffic is to be diverted via a non-fully automatic communication centre;</i></p> <p>2) <i>in a non-fully automatic communication centre within a 10-minute period after detection of the circuit outage.</i></p> <p><i>Service message notification of the diversion requirement should be provided where no bilateral or multilateral prearranged agreements exist.</i></p>	<p>CAR 171.75.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference 4.4.1.3.3</p> <p>Standard</p>	<p>As soon as it is apparent that it will be impossible to dispose of traffic over the aeronautical fixed service within a reasonable period, and when the traffic is held at the station where it was filed, the originator shall be consulted regarding further action to be taken, unless:</p> <p>a) otherwise agreed between the station concerned and the originator; or</p> <p>b) arrangements exist whereby delayed traffic is automatically diverted to commercial telecommunication services without reference to the originator.</p> <p><i>Note.— The expression “reasonable period” means a period of time such that it seems probable that the traffic will not be delivered to the addressee within any fixed transit period applicable to the category of traffic concerned, or, alternatively, any predetermined period agreed between originators and the telecommunication station concerned.</i></p>	<p>CAR 171.75.</p>	<p>No Difference</p>		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.4.1  Standard	4.4.1.4 <i>Supervision of message traffic</i>  <i>Continuity of message traffic.</i> The receiving station shall check the transmission identification of incoming transmissions to ensure the correct sequence of channel-sequence numbers of all messages received over that channel.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.4.1.1  Standard	When the receiving station detects that one or more channel-sequence numbers are missing, it shall send a complete service message ( <i>see</i> 4.4.1.1.9) to the previous station rejecting receipt of any message that may have been transmitted with such missing number(s). The text of this service message shall comprise the signal QTA, the procedure signal MIS followed by one or more missing transmission identification ( <i>see</i> 4.4.2.1.1.3 and 4.4.15.1.1.4) and the end-of-text signal ( <i>see</i> 4.4.5.6 and 4.4.15.3.12).  <i>Note.— The following examples illustrate application of the above-mentioned procedure. In example 2) the hyphen (-) separator is understood to mean “through” in plain language.</i>  <i>1)when one channel-sequence number is missing:</i> SVC→QTA→MIS→ABC↑123↓<≡ <i>2)when several channel-sequence numbers are missing:</i> SVC→QTA→MIS→ABC↑123-126↓<≡	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.4.1.1.1  Standard	When the provisions of 4.4.1.4.1.1 are applied, the station notified of the missing message(s) condition by the service message shall reassume its responsibility for transmission of the message (or messages) that it had previously transmitted with the transmission identification concerned, and shall retransmit that message (or those messages) with a new (correct in sequence) transmission identification. The receiving station shall synchronize such that the next expected channel-sequence number is the last received channel-sequence number plus one.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.4.1.2  Recommendation	<b>Recommendation.</b> — <i>When the receiving station detects that a message has a channel sequence number less than that expected, it should advise the previous station using a service message with a text comprising:</i> 1) <i>the abbreviation SVC;</i> 2) <i>the procedure signal LR followed by the transmission identification of the received message;</i> 3) <i>the procedure signal EXP followed by the transmission identification expected;</i> 4) <i>the end-of-text signal.</i> <i>Note.— The following example illustrates application of the above-mentioned procedure:</i> SVC→LR→ABC↑123→↓EXP→ABC↑135↓<≡	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.4.1.2.1  Recommendation	<b>Recommendation.</b> — <i>When the provisions of 4.4.1.4.1.2 are applied, the station receiving the out-of- sequence message should synchronize such that the next expected channel-sequence number is the last received channel-sequence number plus one. The previous station should check its outgoing channel-sequence numbers and, if necessary, correct the sequence.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.4.2.1  Standard	<p><b>4.4.1.4.2 Misrouted messages</b> <i>Note.— A message is considered to have been misrouted when it contains no relaying instructions, expressed or implied, on which the receiving station can take action.</i></p> <p>When the receiving station detects that a message has been misrouted to it, it shall either:</p> <ol style="list-style-type: none"> <li>1) send a service message (<i>see</i> 4.4.1.1.9) to the previous station rejecting receipt of the misrouted message; or</li> <li>2) itself assume responsibility for transmission of the message to all addressee indicators.</li> </ol> <p><i>Note.— The procedure of 1) is preferable at stations using “torn-tape” relay” methods or a semi-automatic relay technique with continuous tape. The procedure of 2) may be preferred at stations using fully automatic relay methods or a semi-automatic relay technique without continuous tape.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.4.2.2  Standard	<p>When the provisions of 4.4.1.4.2.1, 1) are applied, the text of the service message shall comprise the abbreviation SVC, the signal QTA, the procedure signal MSR followed by the transmission identification (<i>see</i> 4.4.2.1.1.3 and 4.4.15.1.1.4) of the misrouted message and the end-of-text signal (<i>see</i> 4.4.5.6 and 4.4.15.3.12).</p> <p><i>Note.— the following example illustrates application of the above-mentioned procedure:</i> SVC→QTA→MSR→ABC↑123↓&lt;≡</p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.4.2.3  Standard	<p>When, as a result of the provisions of 4.4.1.4.2.2, a sending station is notified of the misrouted message condition by service message, it shall reassume its responsibility for the message and shall retransmit as necessary on the correct outgoing channel or channels.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.4.3  Standard	When a circuit becomes interrupted and alternative facilities exist, the last channel-sequence numbers sent and received shall be exchanged between the stations concerned. Such exchanges shall take the form of complete service messages (see 4.4.1.1.9) with the text comprising the abbreviation SVC, the procedure signals LR and LS followed by the transmission identifications of the relevant messages and the end-of-text signal (see 4.4.5.6 and 4.4.15.3.12). <i>Note.— The following example illustrates application of the above-mentioned procedure:</i> SVC→LR→ABC↑123↓→LS→BAC↑321↓<≡	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.5.1  Standard	<i>4.4.1.5 Failure of communications</i>  Should communication on any fixed service circuit fail, the station concerned shall attempt to re-establish contact as soon as possible.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.5.2  Recommendation	<b>Recommendation.</b> — <i>If contact cannot be re-established within a reasonable period on the normal fixed service circuit, an appropriate alternative circuit should be used. If possible, attempts should be made to establish communication on any authorized fixed service circuit available.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.5.2.1  Standard	If these attempts fail, use of any available air-ground frequency shall be permitted only as an exceptional and temporary measure when no interference to aircraft in flight is ensured.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.5.2.2  Standard	Where a radio circuit fails due to signal fadeout or adverse propagation conditions, a receiving watch shall be maintained on the regular fixed service frequency normally in use. In order to re-establish contact on this frequency as soon as possible there shall be transmitted: a) the procedure signal DE; b) the identification of the transmitting station transmitted three times; c) the alignment function [ $\llcorner$ ]; d) the letters RY repeated without separation for three lines of page copy; e) the alignment function [ $\llcorner$ ]; f) end-of-message signal (NNNN). The foregoing sequence shall be repeated as required.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.5.2.3  Standard	A station experiencing a circuit or equipment failure shall promptly notify other stations with which it is in direct communication if the failure will affect traffic routing by those stations. Restoration to normal shall also be notified to the same stations.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.5.3  Standard	Where diverted traffic will not be accepted automatically or where a predetermined diversion routing has not been agreed, a temporary diversion routing shall be established by the exchange of service messages. The text of such service messages shall comprise: 1)the abbreviation SVC; 2)the procedure signal QSP; 3)if required, the procedure signal RQ, NO or CNL to request, refuse or cancel a diversion; 4)identification of the routing areas, States, territories, locations, or stations for which the diversion applies; 5)the end-of-text signal. <i>Note.— The following examples illustrate application of the above-mentioned procedures:</i> f) to request a diversion: SVC→QSP→RQ→C→K→BG→BI↓<≡ g) to accept a diversion: SVC→QSP→C→K→BG→BI↓<≡ h) to refuse a diversion: SVC→QSP→NO→C→K→BG→BI↓<≡ i) to cancel a diversion: SVC→QSP→CNL→C→K→BG→BI↓<≡	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.6.1  Standard	4.4.1.6 Long-term retention of AFTN traffic records  Copies of all messages, in their entirety, transmitted by an AFTN origin station shall be retained for a period of at least 30 days. <i>Note.— The AFTN origin station, although responsible for ensuring that AFTN traffic is recorded, is not necessarily the unit where the records are made and retained. By local agreement the State concerned may permit the originators to perform those functions.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.6.2  Standard	AFTN destination stations shall retain, for a period of at least 30 days, a record containing the information necessary to identify all messages received and the action taken thereon. <i>Note.— The provision for identification of messages mentioned in 4.4.1.6.2 may be obtained by recording the heading, address and origin parts of messages.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.6.3  Recommendation	<b>Recommendation.</b> — <i>AFTN communication centres should retain, for a period of at least 30 days, a record containing the information necessary to identify all messages relayed or retransmitted and the action taken thereon.</i> <i>N1.The provision for identification of messages mentioned in 4.4.1.6.3 may be obtained by recording the heading, address and origin parts of messages.</i> <i>N2.Provisions relating to short-term retention of AFTN traffic records in AFTN communication centres are contained in 4.4.1.7.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.7.1  Standard	<b>4.4.1.7 Short-term retention of AFTN traffic records</b>  Except as provided in 4.4.1.7.2, AFTN communication centres shall retain, for a period of at least one hour, a copy of all messages, in their entirety, retransmitted or relayed by that communication centre.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.1.7.2  Standard	In cases where acknowledgement is made between AFTN communication centres, a relay centre shall be considered as having no further responsibility for retransmission or repetition of a message for which it has received positive acknowledgement, and it may be deleted from its records. <i>Note.— Provisions relating to long-term retention of AFTN traffic records in AFTN communication centres are contained in 4.4.1.6.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.1.8.1  Recommendation	<p>4.4.1.8 Test procedures on AFTN channels</p> <p>Recommendation.— Test messages transmitted on AFTN channels for the purpose of testing and repairing lines should consist of the following:</p> <ol style="list-style-type: none"> <li>1)the start-of-message signal;</li> <li>2)the procedure signal QJH;</li> <li>3)the originator indicator;</li> <li>4)three page-copy lines of the sequence of characters RY in ITA-2 or U(5/5) *(2/10) in IA-5; and</li> <li>5)the end-of-message signal.</li> </ol>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference												
Chapter 4 Reference 4.4.2  Standard	<p>Message format — International Telegraph Alphabet No. 2 (ITA-2)</p> <p>All messages, other than those prescribed in 4.4.1.8 and 4.4.9.3, shall comprise the components specified in 4.4.2.1 to 4.4.6.1 inclusive.</p> <p><i>N1. An illustration of the ITA-2 message format is given in Figure 4-1.</i></p> <p><i>N2. In the subsequent Standards relative to message format the following symbols have been used in making reference to the functions assigned to certain signals in the International Telegraph Alphabet No. 2 (see Volume III, Part I, 8.2.1 and Table 8-1):</i></p> <table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><i>Symbol</i></td> <td style="text-align: center;"><i>Signification</i></td> </tr> <tr> <td style="text-align: center;">&lt; <i>(signal no. 27)</i></td> <td style="text-align: center;">CARRIAGE RETURN</td> </tr> <tr> <td style="text-align: center;">≡</td> <td style="text-align: center;">LINE FEED <i>(signal no. 28)</i></td> </tr> <tr> <td style="text-align: center;">↓ 29)</td> <td style="text-align: center;">LETTER SHIFT <i>(signal no.</i></td> </tr> <tr> <td style="text-align: center;">↑ 30)</td> <td style="text-align: center;">FIGURE SHIFT <i>(signal no.</i></td> </tr> <tr> <td style="text-align: center;">→</td> <td style="text-align: center;">SPACE <i>(signal no. 31)</i></td> </tr> </table>	<i>Symbol</i>	<i>Signification</i>	< <i>(signal no. 27)</i>	CARRIAGE RETURN	≡	LINE FEED <i>(signal no. 28)</i>	↓ 29)	LETTER SHIFT <i>(signal no.</i>	↑ 30)	FIGURE SHIFT <i>(signal no.</i>	→	SPACE <i>(signal no. 31)</i>	CAR 171.75.	No Difference		
<i>Symbol</i>	<i>Signification</i>																
< <i>(signal no. 27)</i>	CARRIAGE RETURN																
≡	LINE FEED <i>(signal no. 28)</i>																
↓ 29)	LETTER SHIFT <i>(signal no.</i>																
↑ 30)	FIGURE SHIFT <i>(signal no.</i>																
→	SPACE <i>(signal no. 31)</i>																



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.2.1.1  Standard	<p>4.4.2.1 Heading</p> <p>The heading shall comprise:</p> <ul style="list-style-type: none"> <li>a) start-of-message signal, the characters ZCZC;</li> <li>b) transmission identification comprising:                             <ul style="list-style-type: none"> <li>1) circuit identification;</li> <li>2) channel-sequence number.</li> </ul> </li> <li>c) additional service information (if necessary) comprising:                             <ul style="list-style-type: none"> <li>3) one SPACE;</li> <li>4) no more than ten characters.</li> </ul> </li> <li>d) spacing signal.</li> </ul>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.2.1.1.1  Standard	The circuit identification shall consist of three letters selected and assigned by the transmitting station; the first letter identifying the transmitting, the second letter the receiving end of the circuit and the third letter to identify the channel; where there is only one channel between the transmitting and receiving stations, channel letter A shall be assigned; where more than one channel between stations is provided, the channels shall be identified as A, B, C, etc. in respective order.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.2.1.1.2  Standard	Three-digit channel-sequence numbers from 001 to 000 (representing 1 000) shall be assigned sequentially by telecommunication stations to all messages transmitted directly from one station to another. A separate series of these numbers shall be assigned for each channel and a new series shall be started daily at 0000 hours.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.2.1.1.2.1  Recommendation	<b>Recommendation.</b> — <i>The use of the 4-digit channel-sequence number, to preclude duplication of the same numbers during the 24-hour period, is permitted subject to agreement between the authorities responsible for the operation of the circuit.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.2.1.1.3  Standard	The transmission identification shall be sent over the circuit in the following sequence: a) SPACE [→]; b) transmitting-terminal letter; c) receiving-terminal letter; d) channel-identification letter; e) FIGURE SHIFT [↑]; f) channel-sequence number (3 digits).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.2.1.2  Standard	In teletypewriter operation, the spacing signal, consisting of 5 SPACES [→→→→→] followed by 1 LETTER SHIFT [↓], shall be transmitted immediately following the transmission identification prescribed in 4.4.2.1.1.3. <i>Note.— The examples appearing below illustrate the application of the transmission identification Standard (see 4.4.2.1.1 b) and 4.4.1.1.3):</i> <i>Tape</i>  <i>Page-cop</i>  <i>y</i>  →GLB↑039→→→→→↓      GLB039  <i>(This indicates the 39th message of the day transmitted on Channel B of the circuit from Station G to Station L.)</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.2.1.3  Standard	Optional service information shall be permitted to be inserted following the transmission identification subject to agreement between the authorities responsible for the operation of the circuit. Such additional service information shall be preceded by a SPACE followed by not more than ten characters and shall not contain any alignment functions.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.2.1.4  Recommendation	<b>Recommendation.</b> — <i>To avoid any misinterpretation of the diversion indicator especially when considering the possibility of a partly mutilated heading, the sequence of two consecutive signals no. 22 (in the letter case or in the figure case) should not appear in any other component of the heading.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.3.1  Standard	<p style="text-align: center;"><b>4.4.3 Address</b></p> <p>The address shall comprise:</p> <ul style="list-style-type: none"> <li>a) alignment function [<math>\leq</math>];</li> <li>b) priority indicator;</li> <li>c) addressee indicator(s);</li> <li>d) alignment function [<math>\leq</math>].</li> </ul>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																		
Chapter 4 Reference 4.4.3.1.1  Standard	<p>The priority indicator shall consist of the appropriate two-letter group assigned by the originator in accordance with the following:</p> <table border="0"> <tr> <td><i>Message category</i></td> <td><i>Priority</i></td> </tr> <tr> <td>distress messages (see 4.4.1.1.1)</td> <td>SS</td> </tr> <tr> <td>urgency messages (see 4.4.1.1.2)</td> <td>DD</td> </tr> <tr> <td>flight safety messages (see 4.4.1.1.3)</td> <td>FF</td> </tr> <tr> <td>meteorological messages (see 4.4.1.1.4)</td> <td>GG</td> </tr> <tr> <td>flight regularity messages (see 4.4.1.1.5)</td> <td>GG</td> </tr> <tr> <td>aeronautical information services messages (see 4.4.1.1.6)</td> <td>GG</td> </tr> <tr> <td>aeronautical administrative messages (see 4.4.1.1.7)</td> <td>KK</td> </tr> <tr> <td>service messages (see 4.4.1.1.9.)</td> <td><i>(as appropriate)</i></td> </tr> </table>	<i>Message category</i>	<i>Priority</i>	distress messages (see 4.4.1.1.1)	SS	urgency messages (see 4.4.1.1.2)	DD	flight safety messages (see 4.4.1.1.3)	FF	meteorological messages (see 4.4.1.1.4)	GG	flight regularity messages (see 4.4.1.1.5)	GG	aeronautical information services messages (see 4.4.1.1.6)	GG	aeronautical administrative messages (see 4.4.1.1.7)	KK	service messages (see 4.4.1.1.9.)	<i>(as appropriate)</i>	CAR 171.75.	No Difference		
<i>Message category</i>	<i>Priority</i>																						
distress messages (see 4.4.1.1.1)	SS																						
urgency messages (see 4.4.1.1.2)	DD																						
flight safety messages (see 4.4.1.1.3)	FF																						
meteorological messages (see 4.4.1.1.4)	GG																						
flight regularity messages (see 4.4.1.1.5)	GG																						
aeronautical information services messages (see 4.4.1.1.6)	GG																						
aeronautical administrative messages (see 4.4.1.1.7)	KK																						
service messages (see 4.4.1.1.9.)	<i>(as appropriate)</i>																						
Chapter 4 Reference 4.4.3.1.2  Standard	<p>An addressee indicator, which shall be immediately preceded by a SPACE, except when it is the first address indicator of the second or third line of address shall comprise:</p> <ol style="list-style-type: none"> <li>the four-letter location indicator of the place of destination;</li> <li>the three-letter designator identifying the organization/ function (aeronautical authority, service or aircraft operating agency) addressed;</li> <li>an additional letter, which shall represent a department, division or process within the organization/function addressed. The letter X shall be used to complete the address when explicit identification is not required.</li> </ol> <p>N1. <i>The four-letter location indicators are listed in Doc 7910 — Location Indicators.</i></p> <p>N2. <i>The three-letter designators are listed in Doc 8585 — Designators for Aircraft Operating Agencies, Aeronautical Authorities and Services.</i></p>	CAR 171.75.	No Difference																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.3.1.2.1  Standard	Where a message is to be addressed to an organization that has not been allocated an ICAO three-letter designator of the type prescribed in 4.4.3.1.2, the location indicator of the place of destination shall be followed by the ICAO three-letter designator YYY (or the ICAO three-letter designator YXY in the case of a military service or organization). The name of the addressee organization shall then be included in the first item of the text of the message. The eighth position letter following the ICAO three-letter designator YYY or YXY shall be the filler letter X.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.3.1.2.2  Standard	<p>Where a message is to be addressed to an aircraft in flight and, therefore, requires handling over the AFTN for part of its routing before retransmission over the aeronautical mobile service, the location indicator of the aeronautical station which is to relay the message to the aircraft shall be followed by the ICAO three-letter designator ZZZ. The identification of the aircraft shall then be included in the first item of the text of the message. The eighth position letter following the ICAO three-letter designator ZZZ shall be the filler letter X.</p> <p><i>Note.— The following examples illustrate application of the Standards in 4.4.3.1.2.1 and 4.4.3.1.2.2:</i></p> <p><i>1)addressee indicators (possible types):</i></p> <p><i>LGATZTZX aerodrome control tower (ZTZ) at LGAT</i></p> <p><i>LGATYMYF section (F) of the Meteorological Office (YMY) at LGAT</i></p> <p><i>LGATKLMN department (n) of the aircraft operating agency KLM (KLM) at LGAT</i></p> <p><i>LGATYYYY the aircraft operating agency whose name appears in the beginning of the message text and whose office location is served by LGAT</i></p> <p><i>LGATZZZX the aeronautical station (LGAT) is required to relay this message in the aeronautical mobile service to the aircraft whose identification appears in the beginning of the message text.</i></p> <p><i>2)YYY ICAO three-letter designator:</i></p> <p><i>Example of a message addressed to (say) "Penguin Airlines" at NCRG by the PHNL office of the same aircraft operating agency. The Heading and Ending of the message are not shown in this example of teletypewriter page-copy form.</i></p> <p><i>(Address) GG NCRGYYYY</i></p> <p><i>(Origin) 311521 PHNLYYYX</i></p> <p><i>(Text) AIR PENGUIN FLIGHT 801</i></p> <p><i>CANCELLED</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>3)ZZZ ICAO three-letter designator:  <i>Example of a message addressed to aircraft GABCD via aeronautical station NZAA from Area Control Centre at NZZC. The Heading and Ending of the message are not shown in this example of teletypewriter page-copy form.</i>                      (Address)      FF NZAAZZZX                      (Origin)        031451 NZZCZQZX                      (Text)           GABCD CLR DES 5000FT HK NDB</p>				
<p>Chapter 4 Reference 4.4.3.1.2.3</p> <p><b>Standard</b></p>	<p>The complete address shall be restricted to three lines of page-printing copy and, except as provided in 4.4.14, a separate addressee indicator shall be used for each addressee whether at the same or at different locations.</p>	<p>CAR 171.75.</p>	<p>No Difference</p>		
<p>Chapter 4 Reference 4.4.3.1.2.3.1</p> <p><b>Standard</b></p>	<p>Where messages are offered in page-copy form for transmission and contain more addressee indicators than can be accommodated on three lines of a page-copy, such message shall be converted, before transmission, into two or more messages, each of which shall conform with the provisions of 4.4.3.1.2.3. During such conversion, the addressee indicators shall, in so far as practicable, be positioned in the sequence which will ensure that the minimum number of retransmissions will be required at subsequent communication centres.</p>	<p>CAR 171.75.</p>	<p>No Difference</p>		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.3.1.2.3.2  Standard	On teletypewriter circuits, the completion of each line of addressee indicator groups in the address of a message shall be immediately followed by the alignment function [ $\llcorner$ ].	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4  Standard	Origin The origin shall comprise: a) filing time; b) originator indicator; c) priority alarm (when necessary); d) optional heading field; e) alignment function [ $\llcorner$ ].	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4.1  Standard	The filing time shall comprise the 6-digit date-time group indicating the date and time of filing the message for transmission ( <i>see</i> 3.4.2); in teletypewriter operation, the filing time shall be followed by one LETTER SHIFT [ $\downarrow$ ].	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.4.2  Standard	An originator indicator, which shall be immediately preceded by a SPACE, shall comprise: a) the four-letter location indicator of the place at which the message is originated; b) the three-letter designator identifying the organization/ function (aeronautical authority, service or aircraft operating agency) which originated the message; c) an additional letter which shall represent a department, division or process within the organization/function of the originator. The letter X shall be used to complete the address when explicit identification is not required.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4.2.1  Standard	Where a message is originated by an organization that has not been allocated an ICAO three-letter designator of the type prescribed in 4.4.4.2 b), the location indicator of the place at which the message is originated shall be followed immediately by the ICAO three-letter designator YYY followed by the filler letter X (or the ICAO three-letter designator YXY followed by the filler letter X in the case of a military service or organization). The name of the organization (or military service) shall then be included in the first item in the text of the message.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4.2.2  Standard	Where a message originated by an aircraft in flight requires handling on the AFTN for part of its routing before delivery, the originator indicator shall comprise the location indicator of the aeronautical station responsible for transferring the message to the AFTN, followed immediately by the ICAO three-letter designator ZZZ followed by the filler letter X. The identification of the aircraft shall then be included in the first item in the text of the message.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.4.2.3  Standard	<p>Messages relayed over the AFTN that have been originated in other networks shall use a valid AFTN originator indicator that has been agreed for use by the relay or gateway function linking the AFTN with the external network.</p> <p><i>Note.— The following illustrates the application of 4.4.4.2.2 procedure as it would appear with a message from aircraft KLM153 addressed to the Area Control Centre at CZEG, the message being handled via aeronautical station CYCB. The heading and ending of the message are not shown in this example of teletypewriter page-copy form:</i></p> <p><i>(Address) FF CZEGZRZX</i>  <i>(Origin) 031821 CYCBZZZX</i>  <i>(Text) KLM153 [remainder of text as received from aircraft]</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4.3  Standard	<p>The priority alarm shall be used only for distress messages. When used, it shall consist of the following, in the order stated:</p> <ul style="list-style-type: none"> <li>a) FIGURE SHIFT [↑];</li> <li>b) FIVE transmissions of signal no. 10 (figure case);</li> <li>c) LETTER SHIFT [↓].</li> </ul> <p><i>N1.The figure case of signal no. 10 of the International Telegraph Alphabet No. 2 generally corresponds to the figure case of J of teletypewriter equipment in use on aeronautical fixed service circuits.</i></p> <p><i>N2.Use of the priority alarm will actuate a bell (attention) signal at the receiving teletypewriter station, other than at those fully automatic stations which may provide a similar alarm on receipt of priority indicator SS, thereby alerting supervisory personnel at relay centres and operators at tributary stations, so that immediate attention may be given to the message.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.4.4  Standard	The inclusion of optional data in the origin line shall be permitted provided a total of 69 characters is not exceeded and subject to agreement between the authorities concerned. The presence of the optional data field shall be indicated by one occurrence of the SPACE character immediately preceding optional data.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4.4.1  Recommendation	<b>Recommendation.</b> — <i>When additional addressing information in a message needs to be exchanged between source and destination addresses, it should be conveyed in the optional data field (ODF), using the following specific format:</i> a) <i>characters one and full stop (1.) to indicate the parameter code for the additional address function;</i> b) <i>three modifier characters, followed by an equal sign [=] and the assigned 8-character ICAO address; and</i> c) <i>the character hyphen (-) to terminate the additional address parameter field.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4.4.1.1  Recommendation	<b>Recommendation.</b> — <i>When a separate address for service messages or inquiries is different from the originator indicator, the modifier SVC should be used.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.4.5  Standard	The origin line shall be concluded by an alignment function [ $\leq$ ].	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.5.1  Standard	4.4.5 Text  The text of messages shall be drafted in accordance with 4.1.2.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.2  Standard	When an originator's reference is used, it shall appear at the beginning of the text, except as provided in 4.4.5.2.1 and 4.4.5.2.2.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.2.1  Standard	When the ICAO three-letter designators YXY, YYY or ZZZ comprise the second element of the addressee indicator ( <i>see</i> 4.4.3.1.2.1 and 4.4.3.1.2.2) and it, therefore, becomes necessary to identify in the text the specific addressee of the message, such identification group will precede the originator's reference (if used) and become the first item of the text.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.2.2  Standard	When the ICAO three-letter designators YXY, YYY or ZZZ comprise the second element of the originator indicator ( <i>see</i> 4.4.4.2.1 and 4.4.4.2.2) and it thus becomes necessary to identify in the text the name of the organization (or military service), or the aircraft, which originated the message, such identification shall be inserted in the first item of the text of the message.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.5.2.3  Standard	When applying the provisions of 4.4.5.2.1 and 4.4.5.2.2 to messages where the ICAO three-letter designator(s) YXY, YYY or ZZZ is (are) used to refer to two or more different organizations (or military services), the sequence of further identification in the text shall correspond to the complete sequence used in the address and origin of the message. In such instance, each addressee identification shall be followed immediately by an alignment function. The name of the (YXY, YYY or ZZZ) organization originating the message shall then be preceded with "FROM". "STOP" followed by an alignment function shall then be included in the text at the end of these identifications to precede the remainder of the text wording.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.3  Standard	An alignment function [ $\leq$ ] shall be transmitted at the end of each printed line of the text except for the last ( <i>see</i> 4.4.5.6).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.4  Standard	When it is desired to confirm a portion of the text of a message in teletypewriter operation, such confirmation shall be separated from the last text group by an alignment function [ $\leq$ ], and shall be indicated by the abbreviation CFM followed by the portion being confirmed.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.5  Standard	When it is discovered that an error has been made in the text, the correction shall be separated from the last text group or confirmation, if any, by an alignment function [ $\leq$ ] in the case of teletypewriter circuits. This shall be followed by the abbreviation COR and the correction.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.5.5.1  Standard	Stations shall make all indicated corrections on the page-copy prior to local delivery.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.6  Standard	At the end of the text the following end-of-text signal shall be transmitted: 1 LETTER SHIFT [↓], alignment function [≡].	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.5.7  Standard	The text of the messages entered by the AFTN origin station shall not exceed 1 800 characters in length. <i>N1. Where it is desired that a communication with a text exceeding 1 800 characters be transmitted over the aeronautical fixed telecommunication network, 4.4.5.7 requires that such a communication be entered by the AFTN origin station in the form of separate messages, each text of which does not exceed 1 800 characters. Guidance material for forming separate messages from a single long message is given in Attachment B to Volume II.</i> <i>N2. The character count includes all printing and non-printing characters in the message from, but not including, the alignment function preceding the beginning of the text to, but not including, the end-of-text signal.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4  Reference 4.4.6.1  Standard	<p style="text-align: center;">4.4.6 Ending</p> <p>The ending shall comprise:</p> <p>a) the page-feed sequence consisting of 7 LINE FEEDS [=====];</p> <p style="padding-left: 40px;"><i>Note.— This, together with the 1 LINE FEED of the preceding alignment function, will provide sufficient separation between messages when appearing in page-copy form.</i></p> <p>b) the end-of-message signal, consisting of the letter N (letter case of signal no. 14), appearing FOUR times in undivided sequence.</p> <p style="padding-left: 40px;"><i>Note.— This component, transmitted intact from the moment of the first transmission of the message until ultimate delivery, is required so that connections set up for cross-office transmission, at a semi-automatic or fully automatic relay installation, can be cleared for following message traffic.</i></p> <p>And in addition, on message traffic transmitted to “torn-tape” relay stations only:</p> <p>c) the message-separation signal, consisting of a LETTER SHIFT [↓] transmitted 12 times in uninterrupted sequence.</p> <p style="padding-left: 40px;"><i>Note 1.— Nothing but letter shifts are to be transmitted in message traffic between the end-of-message signal of one message and the start-of-message signal of the next.</i></p> <p style="padding-left: 40px;"><i>Note 2.— The following illustrates the procedures specified in 4.4.2 to 4.4.6.1 inclusive for a message in page-copy form:</i></p> <p style="padding-left: 80px;">(Heading)                    *ZCZC LPA183</p> <p style="padding-left: 80px;">(Address)                    GG LGGGZRZX LGATKLMW</p> <p style="padding-left: 80px;">(Origin)                      201838 EGLLKL MW</p> <p style="padding-left: 80px;">(Text)                        As required</p> <p style="padding-left: 80px;">(Ending)                     (Page feed)</p> <p style="padding-left: 80px;">NNNN**</p>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p><i>*Note 2A.— If this message had been one of a series and there had been no manual paper-feed action between messages by the operator attending the receiving page teletypewriter, the “NNNN” of the preceding message would have appeared here.</i></p> <p><i>**Note 2B.— In the circumstances described in Note 2A, the heading of the next message received would be printed on page-copy at this position.</i></p> <p><i>Note 2C.— In actual station practice, messages would be separated on page-copy by tearing through the page-feed sequence. The end-of-message signal would then appear to have become a component part of the next message. This apparent misplacement is, however, unlikely to give rise to any misunderstanding on the part of communicators or addressees since, in practice, the end-of-message signal has no significance on page-copy.</i></p>				
Chapter 4 Reference 4.4.6.2  Standard	<p>AFTN messages entered by the AFTN origin station shall not exceed 2 100 characters in length.</p> <p><i>Note.— The character count includes all printing and non-printing characters in the message from and including the start-of-message signal (ZCZC) to and including the end-of-message signal (NNNN).</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.7.1  Recommendation	4.4.7 Tape feed  <b>Recommendation.</b> — <i>In “torn-tape” installations, and in “semi-automatic” installations using continuous tape technique, when signals additional to those prescribed in 4.4.6.1 are required to ensure that the tape is adequately advanced from the reperforator at the receiving stations, when the ending of one message is not followed immediately by the start-of-message signal of another message, local arrangements should be made at the receiving station to avoid the need for transmission of these signals by the transmitting station.</i>  <i>Note.</i> — <i>In “torn-tape” stations, a facility is normally necessary whereby the tape can be fed from the receiving reperforator to an extent that permits the receiving operator to tear through the message-separation signal at the correct point, on occasions when the operator is ready to tear the tape but there has been no following message to cause this tape-feed to take place. In semi-automatic stations using continuous-tape techniques, a similar process may be necessary in similar circumstances to advance the tape to an extent that permits the end-of-message signal to reach the transmitter.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.7.1.1  Standard	When the provisions of 4.4.7.1 cannot be applied, arrangements shall be made with the transmitting station for the latter to send, at the end of a single message, or following the last message of a series, an agreed number of LETTER SHIFTS [↓] in addition to the components prescribed in 4.4.6.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.8  Standard	Stripped address When applying the provisions of 4.4.3 or 4.4.15.2.1, an AFTN communication centre shall omit from the address all the addressee indicators not required for: a) onward transmission by the AFTN communication centre to which the message is transmitted; b) local delivery to the addressee(s) by the AFTN destination station; c) onward transmission or local delivery by the aggregate of stations on a multi-point circuit.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.9.1.1  Standard	4.4.9 Teletypewriter operating procedure — general  <i>4.4.9.1 End-of-line functions</i>  A single line of page-copy shall not contain more than a total of 69 characters and/or spaces.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.9.1.2  Standard	One CARRIAGE RETURN [ $\lt$ ] and one LINE FEED IMPULSES [ $\equiv$ ] shall be transmitted between each printed page-line of the text of a message.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.9.2  Standard	<i>Duration of transmissions.</i> For simplex circuits, the transmission of a series of messages in a single transmission shall not continue for longer than approximately five minutes. Action shall be taken to deliver or relay each message correctly received without waiting for the end of the series.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.9.3  Standard	<p><i>Channel-check transmissions.</i> Except as provided in 4.4.9.3.3 and 4.4.9.3.5 the following periodic transmissions shall be sent on teletypewriter circuits:</p> <ol style="list-style-type: none"> <li>1) heading (see 4.4.2.1.1);</li> <li>2) alignment function [<math>\leq</math>];</li> <li>3) the procedure signal CH;</li> <li>4) alignment function [<math>\leq</math>];</li> <li>5) end-of-message signal [NNNN];</li> <li>6) message-separation signal [↓↓↓↓↓↓↓↓↓↓] (if required).</li> </ol> <p>The receiving station shall then check the transmission identification of this incoming transmission to ensure its correct sequence in respect of all messages received over that incoming channel.</p> <p><i>Note.— Application of this procedure provides some measure of assurance that channel continuity is maintained.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.9.3.1  Recommendation	<p><b>Recommendation.—</b> <i>Where a circuit is unoccupied, the transmission specified in 4.4.9.3 should be sent at H + 00, H + 20, H + 40.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.9.3.2  Standard	<p>If a periodic channel check transmission is not received within a tolerance agreed for that channel, a station shall send a service message to the station from which the transmission was expected. The text of this service message shall comprise:</p> <ol style="list-style-type: none"> <li>1)the abbreviation SVC;</li> <li>2)the procedure signal MIS;</li> <li>3)the procedure signal CH;</li> <li>4)(optionally) the time at which the transmission was expected;</li> <li>5)the procedure signal LR;</li> <li>6)the transmission identification of the last message received;</li> <li>7)the end-of-text signal.</li> </ol> <p><i>Note.— The following example illustrates application of the above-mentioned procedure:</i></p> <p>SVC→MIS→CH→[↑1220↓→]LR→ABC↑123↓&lt;≡</p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.9.3.3  Standard	<p>When a teletypewriter channel is equipped with a system of controlled circuit protocol, and following agreement between the Administrations responsible, the transmission specified in 4.4.9.3 shall not be made.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.9.3.4  Standard	<p><i>Channel-check transmissions and station radio identifications.</i> In order to satisfy the requirements of ITU regarding periodic transmission of the station radio identification, those AFTN stations using radioteletypewriter channels may combine the station radio identification transmission with the channel-check transmission specified in 4.4.9.3. In this case the combined transmission shall be sent as follows:</p> <ol style="list-style-type: none"> <li>1) heading (see 4.4.2.1.1);</li> <li>2) alignment function [<math>\leq</math>];</li> <li>3) the procedure signal CH;</li> <li>4) alignment function [<math>\leq</math>];</li> <li>5) the procedure signal DE followed by one SPACE [→] and the assigned ITU radio call sign;</li> <li>6) alignment function [<math>\leq</math>];</li> <li>7) end-of-message signal [NNNN];</li> <li>8) message-separation signal [↓↓↓↓↓↓↓↓↓↓] (if required).</li> </ol> <p><i>Note.— Application of this format will permit this special transmission to be handled by fully automatic switching centres without the intervention of supervisory personnel.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.9.3.4.1  Recommendation	<p><b>Recommendation.—</b> <i>When multichannel radioteletypewriter circuits are used (e.g. MET and AFTN) the station radio call sign transmission should be sent on only one channel of the circuit. The channel chosen should be the one which is the most convenient for this purpose with the identification transmission being sent in conformance with the format used on that channel. When an AFTN channel is chosen the identification transmission should be combined with the channel-check transmission.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.9.3.5  Standard	When a teletypewriter circuit is associated with Automatic Error Correction (ARQ) equipment, and following agreement between the Administrations responsible, the transmissions specified in 4.4.9.3 need not be made: however stations employing radioteletypewriter channels on the AFTN for which the station radio identification is required, shall comply with the provisions of 4.4.9.3.4. <i>Note.— The foregoing is not to be interpreted as implying any ICAO requirement necessitating the installation of Automatic Error Correction (ARQ) equipment on international aeronautical fixed circuits.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1  Standard	4.4.10 Normal teletypewriter transmission procedures  Messages shall be transmitted in accordance with predetermined responsibility for onward relay as agreed between the Administrations responsible for the operation of directly connected stations ( <i>see also</i> 4.4.1.3 and 4.4.1.5.2.3).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.1  Standard	Arising from the responsibility agreements established under the provisions of 4.4.10.1, each station of the AFTN shall employ and, subject to the provisions of 4.4.10.1.1.1, adhere to a Routing Directory which consists of the Routing List.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.10.1.1.1  Standard	When an incoming message contains only identical location indicators in the lines-following-the-heading the receiving station shall accept responsibility for further relay. If possible such relay shall be effected on the normal outgoing circuit to the place of destination of the message; if it is not possible to use the normal circuit, an appropriate alternative outgoing circuit shall be used. When neither of these facilities is in operation, the message shall not be retransmitted over the circuit from which it was received, without prior service message ( <i>see</i> 4.4.1.1.9) notification of this action being given to the station that had made the previous transmission.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.1.2  Recommendation	<b>Recommendation.</b> — <i>An AFTN message originator not capable of handling service messages should agree with the AFTN centre it is connected to on a method of exchanging service messages.</i>  <i>Note.</i> — <i>A method of specifying service address in the optional data field is shown in 4.4.4.4.2 and 4.4.4.4.2.1.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.2  Standard	<i>Form of transmission — teletypewriter operation.</i> All transmissions shall comprise in the following order ( <i>see</i> Figure 4-2).	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.10.1.2.1  Standard	<p><i>Starting pulse.</i> When the receiving station uses equipment fitted with a time-switch to stop the teletypewriter machine motor when the channel is idle, a 20-30 millisecond SPACING IMPULSE shall be transmitted when the channel has been at rest for 30 seconds or more and at least 1.5seconds shall be permitted to elapse before the transmission of the heading.</p> <p>N1.<i>This is equivalent to the transmission of a LETTER SHIFT [↵] followed by a pause (i.e. a continuous MARKING IMPULSE) of at least 1.37 seconds.</i></p> <p>N2.<i>Application of this procedure will allow the receiving equipment to reach synchronization before transmission of the heading is commenced.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.3  Standard	<p><i>Message format.</i> All messages shall be prepared in accordance with the provisions of 4.4.2 (ITA-2 format) or 4.4.15 (IA-5 format).</p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.3.1  Recommendation	<p><b>Recommendation.</b>— <i>The Heading Line, with the exception of the SOH character, should be omitted on circuits employing one of the data link control procedures contained in 8.6.3 and 8.6.4 of Annex 10, Volume III.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.4.1  Standard	<p><b>4.4.10.1.4 Reprocessing procedures</b></p> <p>A message requiring retransmission shall have its previous heading deleted by the station which received such message for relay. The retransmission shall commence with the new heading using the transmission identification for the outgoing channel.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.10.1.4.1.1  Standard	When applying the provisions of 4.4.10.1.4.1, transmission of the address part of the message shall commence at some point during the 5 SPACES, 1 LETTER SHIFT [→→→→→↓] immediately preceding the first alignment function [≡].	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.4.1.2  Standard	At tributary and “torn-tape” relay stations not equipped with automatic numbering machine devices and hence where it is necessary for a small number of additional teletypewriter characters to be perforated on a tape before the start-of-message signal to preclude risk of mutilation of the latter signal during retransmission, such additional characters, as required, shall consist of LETTER SHIFTS [↓]. Subsequent transmission on the outgoing channel shall then commence at a point as close as practicable to the start-of-message signal.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.4.1.3  Standard	At stations where the heading of a message is originated by automatic equipment at the point of and time of transmission on the outgoing channel, but where preparation of the other parts of a message is by the perforation of a tape and where, therefore, it is necessary for a small number of additional teletypewriter characters to be perforated before the alignment function [≡] at the commencement of the address so as to preclude risk of mutilation of this alignment function, such additional characters, as required, shall consist of LETTER SHIFTS [↓] or SPACES [→]. Subsequent transmission on the outgoing channel shall then commence at a point as close as practicable to the first alignment function [≡] of the message.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.10.1.4.2  Standard	At a "torn-tape" station the incoming tapes shall be torn at a position in the message-separation signal component ( <i>see</i> 4.4.6.1 and 4.4.7.1) so that the preceding end-of-message signal remains intact.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.4.2.1  Standard	Following application of the provisions of 4.4.10.1.4.2 the shortened (i.e. less than 12 LETTER SHIFTS [↓]) message-separation signal remaining on the message tape shall be deleted, if necessary by electronic methods, before retransmission to an automatic relay installation. If the retransmission is to another "torn-tape" station then: 1)the shortened message-separation signal shall be reformed to a complete [↓↓↓↓↓↓↓↓↓↓] signal by transmission of the necessary number of additional LETTER SHIFTS [↓]; or 2)the shortened message-separation signal remaining on the tape shall be removed and a new and complete message-separation signal shall be added to the message in the process of retransmission in accordance with the provisions of 4.4.6.1 c).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.5  Standard	When possible in "torn-tape" or semi-automatic installations, a correct tape shall be obtained prior to onward relay; when tape is illegible or mutilated the station shall not relay the message unless good judgement indicates that this is not likely to result in malfunctioning of equipment at subsequent relay stations.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.10.1.6  Standard	<i>Acknowledgement of receipt of messages.</i> In teletypewriter operation and except as provided in 4.4.10.1.6.1, a receiving station shall not transmit acknowledgement of receipt of incoming messages. In lieu thereof the provisions of 4.4.1.4.1 shall be applied.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.6.1  Standard	The receipt of distress messages (priority SS — <i>see</i> 4.4.1.1.1) shall be individually acknowledged by the AFTN destination station sending a service message ( <i>see</i> 4.4.1.1.9) to the AFTN origin station. Such acknowledgement of receipt shall take the format of a complete message addressed to the AFTN origin station, shall be assigned priority indicator SS and the associated priority alarm ( <i>see</i> 4.4.4.3) and shall have a text comprising: 1)the procedure signal R; 2)the origin ( <i>see</i> 4.4.4), without priority alarm, or optional heading information of the message being acknowledged; 3)the end-of-text signal [ $\downarrow \Leftarrow$ ]. <i>Note.— The following example illustrates the application of 4.4.10.1.6.1 procedure:</i> Heading ( <i>see</i> 4.4.2.1.1) $\Leftarrow$ SS $\rightarrow$ LECBZRZX $\Leftarrow$ $\uparrow$ 121322 $\downarrow \rightarrow$ EGLLYFYX (Priority Alarm) $\Leftarrow$ R $\rightarrow$ $\uparrow$ 121319 $\downarrow \rightarrow$ LECBZRZX $\downarrow \Leftarrow$ Ending ( <i>see</i> 4.4.6)	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.10.1.7  Standard	In cases where an addressee of a multi-address message requests a repetition of the message from the origin station, the origin station shall address the repeat of the message only to the addressee requesting the repeat. Under these conditions the procedure signal DUPE shall not be included.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.1  Standard	<p>4.4.11 Action on mutilated or improperly formatted messages detected in teletypewriter relay stations</p> <p>If, before retransmission is commenced, a relay station detects that a message has been mutilated or improperly formatted at some point ahead of the end-of-message signal, and it has reason to believe that this mutilation had occurred before the message had been received by the previous station, it shall send a service message (<i>see</i> 4.4.1.1.9) to the originator as identified by the originator indicator in the origin of the mutilated or improperly formatted message, requesting repetition of the incorrectly received message.</p> <p>N1. <i>The following example illustrates a typical text of a service message in which the foregoing procedure has been applied in respect of a mutilated message having as its origin "141335 CYULACAX":</i></p> <p>SVC→QTA→RPT→↑141335↓→CYULACAX↓&lt;≡</p> <p>N2. <i>This circumstance of detection of a mutilation may only be possible at "torn-tape" relay stations.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.2  Standard	When the provisions of 4.4.11.1 are applied, the originator as identified by the originator indicator in the origin of the mutilated message shall reassume responsibility for the mutilated message, and shall comply with the provisions of 4.4.11.3.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.3  Standard	<p>Following application of the provisions of 4.4.11.2, the following reprocessing shall be accomplished before the unmutated version of the message is transmitted for the second time towards the same addressee or addressees:</p> <ol style="list-style-type: none"> <li>1)insert a new heading;</li> <li>2)remove the ending of the message (see 4.4.6.1);</li> <li>3)insert in lieu thereof the procedure signal DUPE, preceded by at least 1 LETTER SHIFT [↓] and followed by 1 CARRIAGE RETURN, 8 LINE Feeds, end-of-message signal and, if necessary (see 4.4.6 and 4.4.7), the LETTER SHIFTS [↓] of the message-separation signal and tape feed.</li> </ol> <p><i>Note.— The example appearing in Figure 4-3 illustrates the application of this procedure.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.4  Standard	<p>If, before retransmission is commenced, a relay station detects that one or more messages have been mutilated at some point ahead of the end-of-message signal, and it has reason to believe that this mutilation had occurred during or subsequent to its transmission from the previous station, it shall send a service message (see 4.4.1.1.9) to the previous station rejecting the mutilated transmission and requesting a repetition of the incorrectly received message (or messages).</p> <p><i>Note 1.— The following examples illustrate application of the above-mentioned procedure. In example 2) the hyphen (-) separator is understood to mean “through” in plain language.</i></p> <ol style="list-style-type: none"> <li>1)in respect of a single mutilated message: SVC→QTA→RPT→ABC↑123↓&lt;≡</li> <li>2)in respect of several mutilated messages: SVC→QTA→RPT→ABC↑123-126↓&lt;≡</li> </ol> <p><i>Note 2.— This circumstance of detection of a mutilation may only be possible at “torn-tape” relay stations.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.5  Standard	When the provisions of 4.4.11.4 are applied, the station receiving the service message shall reassume responsibility for the referenced message. It shall then retransmit the unmutated copy of the referenced message with a new (i.e. correct in sequence) transmission identification (see 4.4.2.1.1 b)). If that station is not in possession of an unmutated copy of the original message, it shall take the action prescribed in 4.4.11.1.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.6  Standard	If, before retransmission is commenced, a relay station detects that a received message has a recognizable but mutilated end-of-message signal, it shall, where necessary, repair this mutilation before retransmission.  <i>Note.— this circumstance of detection of a mutilation may only be possible at “torn-tape” relay stations and the action prescribed will be essential where messages are being transmitted to a semi-automatic or fully automatic station.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.7  Standard	If, during retransmission of a message, a relay station detects that the message has been mutilated at some point ahead of the end-of-message signal and is able to take action before a correct end-of-message signal has been transmitted, it shall: 1)cancel the transmission by inserting into the channel the sequence ↓≡QTA→QTA↓≡ followed by a complete ending (see 4.4.6); 2)reassume responsibility for the message; 3)comply with the provisions of 4.4.11.1 or 4.4.11.4 as appropriate.  <i>Note.— This circumstance of detection of a mutilation may only be possible at “torn-tape” relay stations or at semi-automatic stations using continuous-tape.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.8  Standard	<p>If, after a message has been transmitted <i>in toto</i>, a station detects that the text or the origin of the message was mutilated or incomplete, it shall transmit to all addressees concerned a service message with the following text, if an un mutilated copy of the message is available in the station: SVC CORRECTION (the origin of the incorrect message) STOP (followed by the correct text).</p> <p><i>Note.— This circumstance of detection of a mutilation or incomplete message may only be possible at "torn-tape" relay stations or at semi-automatic stations using continuous-tape.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.9  Standard	<p>If, after transmission of the text of a message, a relay station detects that the message has an obviously mutilated end-of-message signal, it shall insert a proper end-of-message signal into the channel.</p> <p><i>Note.— This circumstance of detection of a mutilation may only be possible at "torn-tape" relay stations or at semi-automatic stations using continuous-tape.</i></p>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.10  Standard	<p>If, after transmission of the text material of a message, a relay station can detect that there is no complete end-of-message signal, but has no practicable means of discovering whether the irregularity has affected only the end-of-message signal or whether it may have also caused part of the original text to have been lost, it shall insert into the channel the following:</p> <ol style="list-style-type: none"> <li>1) ↓&lt;≡CHECK≡TEXT≡NEW→ENDING→ADDED→</li> <li>2) its own station identification;</li> <li>3) ↓&lt;≡</li> <li>4) a proper ending as prescribed in 4.4.6.1.</li> </ol> <p>N1. <i>On tape copy, this insertion will appear as follows:</i> ↓&lt;≡CHECK≡TEXT≡NEW→ENDING→ADDED→LOW WYFX↓&lt;=====NNNN↓↓↓...</p> <p>N2. <i>On page copy, this insertion will appear as follows:</i> CHECK TEXT NEW ENDING ADDED LOWWYFYX NNNN</p> <p>N3. <i>The staggered presentation on copy is prescribed to ensure that the attention of the addressee is drawn immediately to the insertion.</i></p> <p>N4. <i>The FIGURE SHIFT [^] is included to ensure proper functioning where First Line Monitoring Equipment is used, where the presence of the FIGURE SHIFT in the origin is used to cause disconnection of this equipment and where the missing part of the message includes this FIGURE SHIFT.</i></p> <p>N5. <i>This circumstance of detection of a mutilation may only be relevant to fully automatic stations or stations using semi-automatic methods without continuous-tape.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.11  Recommendation	<b>Recommendation.</b> — <i>Relay stations applying the procedural provisions of 4.4.11.9 or 4.4.11.10 should, if practicable, ensure that the appropriate material therein prescribed is inserted prior to the transmission of a complete start-of-message signal associated with any following message.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.12  Standard	If a relay station detects that a message was received with a completely mutilated address line, it shall send a service message to the previous station rejecting the mutilated transmission.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.12.1  Standard	The text of this service message shall comprise: 1)the abbreviation SVC; 2)the procedure signal QTA; 3)the procedure signal ADS; 4)the transmission identification of the message rejected; 5)the indication CORRUPT; 6)the end-of-text signal. <i>Note.— The following example illustrates application of the above-mentioned procedure:</i> SVC→QTA→ADS→ABC↑123↓→CORRUPT↓<≡	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.12.2  Standard	The station receiving such a service message shall reassume responsibility for the referenced message, and shall retransmit the message with a corrected address line, and a new transmission identification.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.13  Standard	If a relay station detects a received message with an invalid (i.e. length other than 8 letters) or unknown addressee indicator, it shall relay the message to those valid addresses for which it has relay responsibility using the stripped address procedure (see 4.4.8).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.13.1  Standard	<p>In addition, except as in 4.4.11.13.3, the station shall send a service message to the previous station requesting correction of the error. The text of this service message shall comprise:</p> <ol style="list-style-type: none"> <li>1)the abbreviation SVC;</li> <li>2)the procedure signal ADS;</li> <li>3)the transmission identification of the message in error;</li> <li>4)an alignment function;</li> <li>5)the first address line of the message as received;</li> <li>6)an alignment function;</li> <li>7)either: <ol style="list-style-type: none"> <li>h) for an invalid addressee indicator: the indication CHECK;</li> <li>i) for an unknown addressee indicator: the indication UNKNOWN;</li> </ol> </li> <li>10)the invalid or unknown addressee indicator(s);</li> <li>11)the end-of-text signal.</li> </ol> <p><i>Note.— The following examples illustrate the application of the procedure of 4.4.11.13.1:</i></p> <ol style="list-style-type: none"> <li>a) for an invalid addressee indicator: SVC→ADS→ABC↑123↓&lt;=GG→EGLLACAX→EGPKYT YXX→CYAA YFYX→CYQXAFX&lt;=CHECK CYQXAFX↓&lt;=</li> <li>b) for an unknown addressee indicator: SVC→ADS→ABC↑123↓&lt;=GG→EGLLACAX→EGEHYT YX→CYAA YFYX→CYQXACAX&lt;= UNKNOWN→EGEHYTYX↓&lt;=</li> </ol>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.13.2  Standard	A station receiving a service message as prescribed in 4.4.11.13.1 shall, if a correct addressee indicator is available, repeat the message to that addressee only using the stripped address procedure ( <i>see</i> 4.4.8) or, if a correct addressee indicator is not available, act as prescribed in 4.4.11.13.1.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.13.3  Standard	Where the procedure of 4.4.11.13 is applied in the case of an unknown addressee indicator, and if the origin of the message is without fault, the station shall send a service message to the originator. The text of this service message shall comprise: 1)the abbreviation SVC; 2)the procedure signal ADS; 3)the origin of the message in error; 4)an alignment function; 5)the first address line of the message as received; 6)an alignment function; 7)the indication UNKNOWN; 8)the unknown addressee indicator(s); 9)the end-of-text signal. <i>Note.— The following example illustrates application of the above-mentioned procedure:</i> SVC→ADS→↑141335↓ →CYULACAX<=GG→EGLLACAX→EGEHYTYX→CYAAY FYX→ CYQXACAX<=UNKNOWN→EGEHYTYX↓<=	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.13.4  Standard	A station receiving such a service message shall obtain a correct addressee indicator and shall repeat the message to the addressee using the stripped address procedure ( <i>see</i> 4.4.8).	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.14  Standard	When the first relay station detects that a message was received with a mutilated origin line or without any origin, it shall: a) stop processing the message; b) send a service message to the station from which the message was received.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.14.1  Standard	The text of this service message shall comprise: 1)the abbreviation SVC; 2)the procedure signal QTA; 3)the procedure signal OGN; 4)the transmission identification of the message rejected; 5)the indication CORRUPT; 6)the end-of-text signal. <i>Note.— The following example illustrates application of the above-mentioned procedure:</i> SVC→QTA→OGN→ABC↑123↓→CORRUPT↓<≡	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.14.2  Standard	The station receiving a service message as prescribed in 4.4.11.14.1 shall reassume responsibility for the referenced message and shall retransmit the message with a correct origin line and a new transmission identification. <i>Note.— When applying the provisions of 4.4.11.14, the minimum requirements for processing the origin of AFTN messages are:</i> 1)the date-time group consisting of six numeric characters; 2)the originator indicator consisting of eight alpha characters.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.11.15  Standard	When the first relay station detects that a message was received with an incorrect originator indicator, it shall: a) stop processing the message; and b) send a service message to the station from which the message was received.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.15.1  Standard	The text of the service message shall comprise: 1)the abbreviation SVC; 2)the procedure signal QTA; 3)the procedure signal OGN; 4)the transmission identification of the message rejected; 5)the indicator INCORRECT; and 6)the end-of-text signal. <i>Note.— The following ITA-2 example illustrates application of the above-mentioned procedure: SVC→QTA→OGN→ABC↑123↓→INCORRECT↓&lt;≡</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.11.15.2  Standard	The station receiving a service message as prescribed in 4.4.11.15.1 shall resume responsibility for the referenced message and shall retransmit the message with a correct originator indicator and, if applicable, a new transmission identification. <i>Note.— When applying the provisions of 4.4.11.15 the relay centre requirement is as a minimum the first character of the originator indicator verified as the first character of the location indicator of the place at which the message is originated.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.12.1  Standard	4.4.12 Correction of errors during tape preparation  Messages for which tapes are prepared at the origin station shall not be allowed to flow into the AFTN with known uncorrected errors.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.12.2  Standard	Errors made ahead of the text of a message shall be corrected by discarding the incorrect tape and preparing a new one.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.12.3  Standard	Where possible, errors made in the text of a message shall be corrected by back-spacing the tape and eliminating the error by operation of the LETTERS [↓] key over the undesired portion.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.12.4  Standard	Where the action of 4.4.12.3 is not possible, correction to the text shall be made immediately after the error by making the error sign (→E→E→E→), transmitting the last correct word or group and then continuing with the tape preparation.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.12.5  Standard	Where neither the action of 4.4.12.3 nor the action of 4.4.12.4 is possible because the error in the text is not noticed until later in the preparation process (but before the end-of-message signal has been added) the station shall comply with the provisions of 4.4.5.5.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.12.6  Standard	The ending must be typed without error.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.13.1  Standard	4.4.13 Correction of errors during message origination in cases where the message is flowing into the AFTN during preparation  Messages flowing into the AFTN during preparation shall not be terminated with an end-of-message signal if they contain known uncorrected errors.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.13.2  Standard	Where an error is made, in this circumstance, in any part of the message which precedes the text, the unfinished message shall be cancelled by sending the sequence ↓≡QTA→QTA↓≡ followed by a complete ending (see 4.4.6).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.13.3  Standard	Errors made in the text and noticed immediately shall be corrected by making the error sign (→E→E→E→), transmitting the last correct word or group and then continuing with the message.	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.13.4  Standard	In cases where errors are made in the text and not noticed until later in the origination process, the station shall comply with the provisions of 4.4.5.5.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.13.5  Standard	In cases where it becomes obvious, during the origination of the text, that the message should be cancelled, the station shall take the action described in 4.4.13.2.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.14.1  Standard	4.4.14 Predetermined distribution system for AFTN messages  When it has been agreed between the Administrations concerned to make use of a predetermined distribution system for AFTN messages, the system described below shall be used.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.14.2  Standard	<p>The Predetermined Distribution Addressee Indicator (PDAI) shall be constructed as follows:</p> <ul style="list-style-type: none"> <li>a) The first and second letters: The first two letters of the Location Indicator of the communications centre of the State which has agreed to implement the system and which receives messages over a circuit for which it has a predetermined routing responsibility;</li> <li>b) The third and fourth letters: The letters ZZ, indicating a requirement for special distribution;</li> <li>c) The fifth, sixth and seventh letters:                             <ul style="list-style-type: none"> <li>1) The fifth, sixth and seventh letters taken from the series A to Z and denoting the national and/or international distribution list(s) to be used by the receiving AFTN centre;</li> <li>2) "N" and "S", as the fifth letter, are reserved for NOTAM and SNOWTAM respectively (<i>see Appendix 5 to Annex 15</i>);</li> </ul> </li> <li>d) The eighth letter: Either the filler letter "X" or a letter taken from the series A to Z to further define the national and/or international distribution list(s) to be used by the receiving AFTN centre.</li> </ul> <p><i>N1.To avoid conflict with the AFTN start-of-message signal, combinations with ZC or CZ will not be used.</i></p> <p><i>N2.To avoid conflict with the AFTN end-of-message signal, combinations with NN will not be used.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.14.3  PANS	<p><b>PANS.</b>— <i>Predetermined Distribution Addressee Indicators (PDAIs) should be used whenever possible on AFTN messages between States which have agreed to make use of the predetermined distribution system.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.14.4  Standard	AFTN messages carrying Predetermined Distribution Addressee Indicators allocated by the State receiving the message shall be routed to the addressees listed on the associated list of Addressee Indicators described in 4.4.14.5.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.14.5  Standard	States shall send their list of selected Predetermined Distribution Addressee Indicators together with the associated lists of Addressee Indicators to: a) the States from which they will receive AFTN messages for predetermined distribution, to assure correct routing; and b) the States which will originate AFTN messages for predetermined distribution to facilitate the treatment of requests for retransmission and to assist originators in using the Predetermined Distribution Addressee Indicators correctly.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.14.5.1  Standard	The list of Addressee Indicators associated with a Predetermined Distribution Addressee Indicator shall include either: a) Addressee Indicators for national distribution; or b) Addressee Indicators for international distribution; or c) Predetermined Distribution Addressee Indicators for international distribution; or d) any combination of a), b) and c).	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference								
Chapter 4  Reference 4.4.15  Standard	<p>Message format - International Alphabet No. 5 (IA-5)</p> <p>When it has been agreed between the Administrations concerned to use International Alphabet No. 5 (IA-5) the format described in 4.4.15 through 4.4.15.3 shall be used. It shall be the responsibility of Administrations using IA-5 to accommodate adjacent AFTN stations employing ITA-2 code in the format described in 4.4.2.</p> <p>All messages, other than those prescribed in 4.4.1.8 and 4.4.9.3 shall comprise the components specified in 4.4.15.1 to 4.4.15.6 inclusive.</p> <p><i>N1. An illustration of the IA-5 message format is given in Figure 4-4.</i></p> <p><i>N2. In the subsequent standards relative to message format the following symbols have been used in making reference to the functions assigned to certain signals in IA-5. (See Volume III, Part I, 8.6.1 and Tables 8-2 and 8-3.)</i></p> <table border="0" data-bbox="367 885 903 1104"> <thead> <tr> <th style="text-align: left;"><i>Symbol</i></th> <th style="text-align: left;"><i>Signification</i></th> </tr> </thead> <tbody> <tr> <td>&lt;</td> <td>CARRIAGE RETURN (character position 0/13)</td> </tr> <tr> <td>≡</td> <td>LINE FEED (character position 0/10)</td> </tr> <tr> <td>→</td> <td>SPACE (character position 2/0).</td> </tr> </tbody> </table>	<i>Symbol</i>	<i>Signification</i>	<	CARRIAGE RETURN (character position 0/13)	≡	LINE FEED (character position 0/10)	→	SPACE (character position 2/0).	CAR 171.75.	No Difference		
<i>Symbol</i>	<i>Signification</i>												
<	CARRIAGE RETURN (character position 0/13)												
≡	LINE FEED (character position 0/10)												
→	SPACE (character position 2/0).												



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.1.1  Standard	<p><i>4.4.15.1 Heading</i></p> <p>The heading shall comprise:</p> <ul style="list-style-type: none"> <li>a) start-of-heading (SOH) character 0/1;</li> <li>b) transmission identification comprising:                             <ul style="list-style-type: none"> <li>1) circuit or link identification;</li> <li>2) channel-sequence number;</li> </ul> </li> <li>c) additional service information (if necessary) comprising:                             <ul style="list-style-type: none"> <li>3) one SPACE;</li> <li>4) no more than 10 characters.</li> </ul> </li> </ul>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.1.1.1  Standard	<p>On point-to-point circuits or links, the identification shall consist of three letters selected and assigned by the transmitting station; the first letter identifying the transmitting, the second letter the receiving end of the circuit, and the third letter the channel. Where only one channel exists, the letter A shall be assigned. Where more than one channel between stations is provided, the channels shall be identified as A, B, C, etc., in respective order. On multipoint channels, the identification shall consist of three letters selected and assigned by the circuit control or master station.</p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.1.1.2  Standard	<p>Except as provided in 4.4.15.1.1.3 three-digit channel-sequence numbers from 001 to 000 (representing 1 000) shall be assigned sequentially by telecommunication stations to all messages transmitted directly from one station to another. A separate series of these numbers shall be assigned for each channel and a new series shall be started daily at 0000 hours.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.1.1.3  Recommendation	<b>Recommendation.</b> — <i>The expansion of the channel-sequence number to preclude duplication of the same numbers during the 24-hour period should be permitted subject to agreement between the Authorities responsible for the operation of the circuit.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.1.1.4  Standard	The transmission identification shall be sent over the circuit in the following sequence: a) transmitting-terminal letter; b) receiving-terminal letter; c) channel-identification letter; d) channel-sequence number.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.1.1.5  Standard	Additional service information shall be permitted to be inserted following the transmission identification subject to agreement between the Authorities responsible for the operation of the circuit. Such additional service information shall be preceded by a SPACE (→) followed by not more than 10 characters inserted into the heading of message immediately following the last digit of the channel-sequence number and shall not contain any alignment functions. When no such additional service information is added the information in 4.4.15.1.1.4 shall be followed immediately by that of 4.4.15.2.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.1  Standard	4.4.15.2 Address  The address shall comprise: a) alignment function [ $\ll\equiv$ ]; b) priority indicator; c) addressee indicator(s); d) alignment function [ $\ll\equiv$ ].	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																		
Chapter 4 Reference 4.4.15.2.1.1  Standard	<p>The priority indicator shall consist of the appropriate two-letter group assigned by the originator in accordance with the following:</p> <table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><i>Priority indicator</i></td> <td style="text-align: center;"><i>Message category</i></td> </tr> <tr> <td>SS</td> <td>distress messages</td> </tr> <tr> <td>DD</td> <td>urgency messages (<i>see</i> 4.4.1.1.2)</td> </tr> <tr> <td>FF</td> <td>flight safety messages (<i>see</i> 4.4.1.1.3)</td> </tr> <tr> <td>GG</td> <td>meteorological messages (<i>see</i> 4.4.1.1.4)</td> </tr> <tr> <td>GG</td> <td>flight regularity messages (<i>see</i> 4.4.1.1.5)</td> </tr> <tr> <td>GG</td> <td>aeronautical information services messages (<i>see</i> 4.4.1.1.6)</td> </tr> <tr> <td>KK</td> <td>aeronautical administrative messages (<i>see</i> 4.4.1.1.7)</td> </tr> <tr> <td>as appropriate</td> <td>service messages (<i>see</i> 4.4.1.1.9)</td> </tr> </table>	<i>Priority indicator</i>	<i>Message category</i>	SS	distress messages	DD	urgency messages ( <i>see</i> 4.4.1.1.2)	FF	flight safety messages ( <i>see</i> 4.4.1.1.3)	GG	meteorological messages ( <i>see</i> 4.4.1.1.4)	GG	flight regularity messages ( <i>see</i> 4.4.1.1.5)	GG	aeronautical information services messages ( <i>see</i> 4.4.1.1.6)	KK	aeronautical administrative messages ( <i>see</i> 4.4.1.1.7)	as appropriate	service messages ( <i>see</i> 4.4.1.1.9)	CAR 171.75.	No Difference		
<i>Priority indicator</i>	<i>Message category</i>																						
SS	distress messages																						
DD	urgency messages ( <i>see</i> 4.4.1.1.2)																						
FF	flight safety messages ( <i>see</i> 4.4.1.1.3)																						
GG	meteorological messages ( <i>see</i> 4.4.1.1.4)																						
GG	flight regularity messages ( <i>see</i> 4.4.1.1.5)																						
GG	aeronautical information services messages ( <i>see</i> 4.4.1.1.6)																						
KK	aeronautical administrative messages ( <i>see</i> 4.4.1.1.7)																						
as appropriate	service messages ( <i>see</i> 4.4.1.1.9)																						
Chapter 4 Reference 4.4.15.2.1.2  Standard	The order of priority shall be the same as specified in 4.4.1.2.	CAR 171.75.	No Difference																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.2.1.3  Standard	An addressee indicator, which shall be immediately preceded by a SPACE, except when it is the first address indicator of the second or third line of addresses, shall comprise: a) the four-letter location indicator of the place of destination; b) the three-letter designator identifying the organization/ function (aeronautical authority, service or aircraft operating agency) addressed; c) an additional letter, which shall represent a department, division or process within the organization/function addressed. The letter X shall be used to complete the address when explicit identification is not required.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.1.3.1  Standard	Where a message is to be addressed to an organization that has not been allocated an ICAO three-letter designator of the type prescribed in 4.4.15.2.1.3 the location indicator of the place of destination shall be followed by the ICAO three-letter designator YYY (or the ICAO three-letter designator YXY in the case of a military service or organization). The name of the addressee organization shall then be included in the first item in the text of the message. The eighth position letter following the ICAO three-letter designator YYY or YXY shall be the filler letter X.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.1.3.2  Standard	Where a message is to be addressed to an aircraft in flight and, therefore, requires handling over the AFTN for part of its routing before retransmission over the Aeronautical Mobile Service, the location indicator of the aeronautical station which is to relay the message to the aircraft shall be followed by the ICAO three-letter designator ZZZ. The identification of the aircraft shall then be included in the first item of the text of the message. The eighth position letter following the ICAO three-letter designator ZZZ shall be the filler letter X.	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.2.1.4  Standard	The complete address shall be restricted to three lines of page-printing copy, and, except as provided in 4.4.16, a separate addressee indicator shall be used for each addressee whether at the same or different locations.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.1.5  Standard	The completion of the addressee indicator group(s) in the address of a message shall be immediately followed by the alignment function.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.1.6  Standard	Where messages are offered in page-copy form for transmission and contain more addressee indicators than can be accommodated on three lines of a page copy, such messages shall be converted, before transmission, into two or more messages, each of which shall conform with the provisions of 4.4.15.2.1.5. During such conversion, the addressee indicators shall, in so far as practicable, be positioned in the sequence which will ensure that the minimum number of retransmissions will be required at subsequent communication centres.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2  Standard	<i>Origin</i> The origin shall comprise: a) filing time; b) originator indicator; c) priority alarm (when necessary); d) optional heading information; e) alignment function [ $\leq$ ]; f) start-of-text character, character 0/2 (STX).	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.2.2.1  Standard	The filing time shall comprise the 6-digit date-time group indicating the date and time of filing the message for transmission ( <i>see</i> 3.4.2).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2.2  Standard	The originator indicator, which shall be immediately preceded by a SPACE, shall comprise: a) the four-letter location indicator of the place at which the message is originated; b) the three-letter designator identifying the organization/ function (aeronautical authority, service or aircraft operating agency) which originated the message; c) an additional letter which shall represent a department, division or process within the organization/function of the originator. The letter X shall be used to complete the address when explicit identification is not required.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2.3  Standard	Where a message is originated by an organization that has not been allocated an ICAO three-letter designator of the type prescribed in 4.4.15.2.2.2, the location indicator of the place at which the message is originated shall be followed immediately by the ICAO three-letter designator YYY followed by the filler letter X (or the ICAO three-letter designator YXY followed by the filler letter X in the case of a military service or organization). The name of the organization (or military service) shall then be included in the first item in the text of the message.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.2.2.3.1  Standard	Messages relayed over the AFTN that have been originated in other networks shall use a valid AFTN originator indicator that has been agreed for use by the relay or gateway function linking the AFTN with the external network.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2.4  Standard	Where a message originated by an aircraft in flight requires handling on the AFTN for part of its routing before delivery, the originator indicator shall comprise the location indicator of the aeronautical station responsible for transferring the message to the AFTN, followed immediately by the ICAO three-letter designator ZZZ followed by the filler letter X. The identification of the aircraft shall then be included in the first item in the text of the message.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2.5  Standard	The priority alarm shall be used only for distress messages. When used it shall consist of five successive BEL (0/7) characters.  <i>Note.— Use of the priority alarm will actuate a bell (attention) signal at the receiving teletypewriter station, other than at those fully automatic stations which may provide a similar alarm on receipt of priority indicator SS, thereby alerting supervisory personnel at relay centres and operators at tributary stations, so that immediate attention may be given to the message.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2.6  Standard	The inclusion of optional data in the origin line shall be permitted provided a total of 69 characters is not exceeded and subject to agreement between the Administrations concerned. The presence of the optional data field shall be indicated by one occurrence of the SPACE character immediately preceding optional data.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.2.2.6.1  Recommendation	<b>Recommendation.</b> — <i>When additional addressing information in a message needs to be exchanged between source and destination addresses, it should be conveyed in the optional data field (ODF), using the following specific format:</i>  a) <i>characters one and full stop (1.) to indicate the parameter code for the additional address function;</i> b) <i>three modifier characters, followed by an equal sign (=) and the assigned 8-character ICAO address; and</i> c) <i>the character hyphen (-) to terminate the additional address parameter field.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2.6.1.1  Recommendation	<b>Recommendation.</b> — <i>When a separate address for service messages or inquiries is different from the originator indicator, the modifier SVC should be used.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.2.2.7  Standard	The origin line shall be concluded by an alignment function [≡] and the start-of-text (STX) (0/2) character.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.3.1  Standard	4.4.15.3 Text  The text of messages shall be drafted in accordance with 4.1.2 and shall consist of all data between STX and ETX. <i>Note.— When message texts do not require conversion to the ITA-2 code and format and do not conflict with ICAO message types or formats in PANS-ATM (Doc 4444), Administrations may make full use of the characters available in International Alphabet No. 5 (IA-5).</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.2  Standard	When an originator's reference is used, it shall appear at the beginning of the text, except as provided in 4.4.15.3.3 and 4.4.15.3.4.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.3  Standard	When the ICAO three-letter designators YXY, YYY or ZZZ comprise the second element of the addressee indicator ( <i>see</i> 4.4.15.2.1.3.1 and 4.4.15.2.1.3.2) and it, therefore, becomes necessary to identify in the text the specific addressee of the message, such identification group shall precede the originator's reference (if used) and become the first item of the text.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.4  Standard	When the ICAO three-letter designators YXY, YYY or ZZZ comprise the second element of the originator indicator ( <i>see</i> 4.4.15.2.2.3 and 4.4.15.2.2.4) and it thus becomes necessary to identify in the text the name of the organization (or military service) or the aircraft which originated the message, such identification shall be inserted in the first item of the text of the message.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.3.5  Standard	When applying the provisions of 4.4.15.3.3 and 4.4.15.3.4 to messages where the ICAO three-letter designator(s) YXY, YYY, ZZZ refer to two or more different organizations (or military services), the sequence of further identification in the text shall correspond to the complete sequence used in the address and originator indicator of the message. In such instance, each addressee identification shall be followed immediately by an alignment function. The name of the (YXY, YYY or ZZZ) organization originating the message shall then be preceded with "FROM". "STOP" followed by an alignment function shall then be included in the text at the end of this identification and preceding the remainder of text.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.6  Standard	An alignment function shall be transmitted at the end of each printed line of the text. When it is desired to confirm a portion of the text of a message in teletypewriter operation, such confirmation shall be separated from the last text group by an alignment function [ $\Leftarrow$ ], and shall be indicated by the abbreviation CFM followed by the portion being confirmed.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.7  Standard	Where messages are prepared off-line, e.g. by preparation of a paper tape, errors in the text shall be corrected by backspacing and replacing the character in error by character DEL (7/15).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.8  Standard	Corrections to textual errors made in on-line operations shall be corrected by inserting $\rightarrow E \rightarrow E \rightarrow E \rightarrow$ following the error, then retyping the last correct word (or group).	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.3.9  Standard	When it is not discovered until later in the origination process that an error has been made in the text, the correction shall be separated from the last text group, or confirmation, if any, by an alignment function [ $\leq$ ]. This shall be followed by the abbreviation COR and the correction.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.10  Standard	Stations shall make all indicated corrections on the page-copy prior to local delivery or a transfer to a manually operated circuit.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.11  Standard	<p>The text of messages entered by the AFTN origin station shall not exceed 1 800 characters in length. AFTN messages exceeding 1 800 characters shall be entered by the AFTN origin station in the form of separate messages. Guidance material for forming separate messages from a single long message is given in Attachment B to Volume II. When messages or data are transmitted only on medium or high speed circuits the text may be increased to a length that exceeds 1 800 characters as long as performance characteristics of the network or link are not diminished and subject to agreement between the Administrations concerned.</p> <p><i>Note.— The character count includes all printing and non-printing characters in the text from, but not including, the start-of-text signal to, but not including, the first alignment function of the ending.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.3.12.1  Standard	4.4.15.3.12 <i>Ending</i>  The ending of a message shall comprise the following in the order stated: a) an alignment [ $\equiv$ ] function following the last line of text; b) page-feed character, character 0/11 (VT); c) end-of-text character 0/3 (ETX).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.12.1.1  Recommendation	<b>Recommendation.</b> — <i>Station terminal equipment (page printers) on the International Alphabet Number 5 (IA-5) shall be provided with a capability to generate sufficient line feed functions for local station use upon the reception of a VERTICAL TAB character (0/11).</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.12.1.2  Recommendation	<b>Recommendation.</b> — <i>When the message does not transit ITA-2 portions of the AFTN, or where Administrations have made provisions to add automatically the second carriage return before transmission to an ITA-2 circuit, one carriage return in the alignment function and end-of-line function should be permitted subject to agreement between the Administrations concerned.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.3.12.1.3  Standard	Messages entered by the AFTN origin station shall not exceed 2 100 characters in length. <i>Note.</i> — <i>The character count includes all printing and non-printing characters in the message from and including the start-heading character (SOH) to and including the end-of-text character.</i>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.4  Standard	Except as provided in 4.4.15.5 to 4.4.15.6 and 4.4.16, the procedures of 4.4.8 and 4.4.9 to 4.4.13 shall be used for messages using IA-5 code.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.5  Standard	<p><i>Channel-check transmissions.</i> In the case where continuous control of channel condition is not provided the following periodic transmissions shall be sent on teletypewriter circuits:</p> <ul style="list-style-type: none"> <li>1) heading line (<i>see</i> 4.4.15.1.1);</li> <li>2) S alignment function T; X</li> <li>3) the procedure signal CH;</li> <li>4) E alignment function T. X</li> </ul> <p>The receiving station shall then check the transmission identification of this incoming transmission to ensure its correct sequence in respect of all messages received over that incoming channel.</p> <p><i>Note.— Application of this procedure provides some measure of assurance that channel continuity is maintained; however, a continuously controlled channel is much more preferable in that data integrity can also be improved.</i></p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.15.5.1  Recommendation	<b>Recommendation.</b> — <i>Where a circuit is unoccupied and uncontrolled, the transmission identified in 4.4.15.5 should be sent at H + 00, H + 20, H + 40.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.15.6  Standard	The receipt of distress messages (priority indicator SS, <i>see</i> 4.4.1.1.1) shall be individually acknowledged by the AFTN destination station by sending a service message ( <i>see</i> 4.4.1.1.9) to the AFTN origin station. Such acknowledgement of receipt shall take the format of a complete message addressed to the AFTN origin station, shall be assigned priority indicator SS and the associated priority alarm ( <i>see</i> 4.4.15.2.2.5), and shall have a text comprising: 1)the procedure signal R; 2)the origin line ( <i>see</i> 4.4.15.2.2) without priority alarm, or optional heading information of the message being acknowledged; 3)the ending ( <i>see</i> 4.4.15.3.12.1). <i>Note.— The following example illustrates the application of the 4.4.15.6 procedures:</i> Heading ( <i>see</i> 4.4.15.1.1) <=SS → LECBZRZX <= 121322 → EGLLYFYX (Priority Alarm) <= S TR → 121319 → LECBZRZX <= X  Ending ( <i>see</i> 4.4.15.3.12.1).	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.16.1  Standard	4.4.16 Action taken on mutilated messages in IA-5 detected in computerized AFTN relay stations  On channels employing continuous control the mutilation detection and subsequent recovery shall be a function of the link control procedures and shall not require the subsequent sending of service or CHECK TEXT NEW ENDING ADDED messages.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.16.2  Standard	On channels not employing continuous control the relay station shall employ the following procedures:	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.16.2.1  Standard	If, during the reception of a message a relay station detects that the message has been mutilated at some point ahead of the end-of-text character, it shall: 1)cancel the onward routing responsibility for the message; 2)send a service message to the transmitting station requesting a retransmission. <i>Note.— The following example illustrates a typical text of a service message in which the foregoing procedure has been applied in respect of a mutilated message:</i> SVC→QTA→RPT→ABC 123 (ending — see 4.4.15.3.12.1)	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.16.2  Standard	<p>When the provisions of 4.4.16.2.1 are applied, the station receiving the service message shall reassume responsibility for the referenced message with a new (i.e. correct in sequence) transmission identification (<i>see</i> 4.4.15.2.1). If that station is not in possession of an un mutilated copy of the original message, it shall send a message to the originator as identified by the originator indicator in the origin of the mutilated message, requesting repetition of the incorrectly received message.</p> <p><i>Note.— The following example illustrates a typical text of a service message in which the foregoing procedure has been applied in respect of a mutilated message having as its origin "141335 CYULACAX":</i> SVC→QTA→RPT→141335→CYULACAX ( ending — see 4.4.15.3.12.1)</p>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.16.3  Standard	<p>If, after transmission of the text material of a message, a relay station can detect that there is no complete end-of-text character, but has no practical means of discovering whether the irregularity has affected only the end-of-text character, or whether it has also caused part of the original text to have been lost, it shall insert into the channel the following:</p> <ol style="list-style-type: none"> <li>1) &lt;≡CHECK≡TEXT≡NEW→ENDING→ADDED</li> <li>2) its own station identification;</li> <li>3) (ending — <i>see</i> 4.4.15.3.12.1).</li> </ol>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.17  Standard	<p>Transfer of AFTN messages over code and byte independent circuits and networks</p> <p>When AFTN messages are transferred across code and byte independent circuits and networks of the AFS, the following shall apply.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.4.17.1  Standard	Except as provided in 4.4.17.3 the heading line of the message shall be omitted. The message shall start with an alignment function followed by the address.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.17.2  Standard	The message shall end with a complete ending.	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.17.3  Recommendation	<b>Recommendation.</b> — <i>For the purposes of technical supervision, entry centres should be permitted to insert additional data preceding the first alignment function and/or following the ending of the message. Such data may be disregarded by the receiving station.</i>	CAR 171.75.	No Difference		
Chapter 4 Reference 4.4.17.3.1  Standard	When the provisions of 4.4.17.3 are applied, the data added shall not include either carriage return or line feed characters or any of the combinations listed in 4.1.2.4.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.5  Note	<p align="center"><b>Common ICAO Data Interchange Network (CIDIN)</b></p> <p><i>N1.The common ICAO data interchange network (CIDIN), which comprises application entities and communication services for ground-ground message exchange, makes use of protocols based on the International Telegraph and Telephone Consultative Committee (CCITT) X.25 Recommendation to provide code and byte-independent communication facilities.</i></p> <p><i>N2.The principal goals of the CIDIN are to improve the AFTN and to support large message transmission and more demanding applications, such as operational meteorological information (OPMET), between two or multiple ground systems.</i></p> <p><i>N3.Details of CIDIN communication procedures, as implemented in Europe, are shown in the EUR CIDIN Manual.</i></p>		Not Applicable		Compliance data not required for notes.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.6  Standard	<p align="center"><b>ATS Message Handling Services (ATSMHS)</b></p> <p>The ATS message service of the ATS (air traffic services) message handling service (ATSMHS) application shall be used to exchange ATS messages between users over the aeronautical telecommunication network (ATN) internet.</p> <p><i>N1.The ATS message service comprised in the ATS message handling service application aims at providing generic message services over the ATN internet communication service (ICS). It may, in turn, be used as a communication system by user-applications communicating over the ATN. This may be achieved, for example, by means of application programme interfaces to the ATS message service.</i></p> <p><i>N2.The detailed specification of the ATS message handling service application is included in the Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN) (Doc 9705), Sub-volume III.</i></p> <p><i>N3.The ATS message service is provided by the implementation over the ATN internet communication service of the message handling systems specified in ISO/IEC (International Organization for Standardization/International Electrotechnical Commission) 10021 and ITU-T (International Telecommunication Union — Telecommunication Standardization Sector) X.400 and complemented by the additional requirements specified in the Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN) (Doc 9705). The two sets of documents, the ISO/IEC MOTIS (Message-Oriented Text Interchange System) International Standards and the ITU-T X.400 Series of Recommendations (1988 or later) are, in principle, aligned with each other. However, there are a small number of differences. In the above-mentioned document, reference is made to the relevant ISO International Standards and International Standardized Profiles (ISP), where applicable. Where necessary, e.g. for reasons of interworking or to point</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																
	<p>out differences, reference is also made to the relevant X.400 Recommendations.</p> <p>N4.The following types of ATN end systems performing ATS message handling services are defined in the Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN) (Doc 9705), Sub-volume III:</p> <ol style="list-style-type: none"> <li>1)an ATS message server;</li> <li>2)an ATS message user agent;</li> <li>3)an AFTN/AMHS gateway (aeronautical fixed telecommunication network/ATS message handling system); and</li> <li>4)a CIDIN/AMHS gateway (common ICAO data interchange network/ATS message handling system).</li> </ol> <p>Connections may be established over the internet communications service between any pair constituted of these ATN end systems (see Table 4-1).</p> <p><b>Table 4-1 Communications between ATN end systems implementing ATS message handling services</b></p> <table border="1" data-bbox="466 998 915 1474"> <thead> <tr> <th>ATN End System 1</th> <th>ATN End System 2</th> </tr> </thead> <tbody> <tr> <td>ATS Message Server</td> <td>ATS Message Server</td> </tr> <tr> <td>ATS Message Server Gateway</td> <td>AFTN/AMHS</td> </tr> <tr> <td>ATS Message Serer Gateway</td> <td>CIDIN/AMHS</td> </tr> <tr> <td>ATS Message Server Agent</td> <td>ATS Message User Agent</td> </tr> <tr> <td>AFTN/AMHS Gateway Gateway</td> <td>AFTN/AMHS</td> </tr> <tr> <td>CIDIN/AMHS Gateway Gateway</td> <td>CIDIN/AMHS</td> </tr> <tr> <td>CIDIN/AMHS Gateway</td> <td>AFTN/AMHS</td> </tr> </tbody> </table>	ATN End System 1	ATN End System 2	ATS Message Server	ATS Message Server	ATS Message Server Gateway	AFTN/AMHS	ATS Message Serer Gateway	CIDIN/AMHS	ATS Message Server Agent	ATS Message User Agent	AFTN/AMHS Gateway Gateway	AFTN/AMHS	CIDIN/AMHS Gateway Gateway	CIDIN/AMHS	CIDIN/AMHS Gateway	AFTN/AMHS				
ATN End System 1	ATN End System 2																				
ATS Message Server	ATS Message Server																				
ATS Message Server Gateway	AFTN/AMHS																				
ATS Message Serer Gateway	CIDIN/AMHS																				
ATS Message Server Agent	ATS Message User Agent																				
AFTN/AMHS Gateway Gateway	AFTN/AMHS																				
CIDIN/AMHS Gateway Gateway	CIDIN/AMHS																				
CIDIN/AMHS Gateway	AFTN/AMHS																				





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	Gateway				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 4 Reference 4.7  Standard	<p style="text-align: center;"><b>Inter-Centre Communications (ICC)</b></p> <p>The inter-centre communications (ICC) applications set shall be used to exchange ATS messages between air traffic service users over the ATN internet.</p> <p>N1. <i>The ICC applications set enables the exchange of information in support of the following operational services:</i></p> <ul style="list-style-type: none"> <li>a) <i>flight notification;</i></li> <li>b) <i>flight coordination;</i></li> <li>c) <i>transfer of control and communications;</i></li> <li>d) <i>flight planning;</i></li> <li>e) <i>airspace management; and</i></li> <li>f) <i>air traffic flow management.</i></li> </ul> <p>N2. <i>The first of the applications developed for the ICC set is the ATS interfacility data communication (AIDC).</i></p> <p>N3. <i>The AIDC application exchanges information between ATS units (ATSUs) for support of critical air traffic control (ATC) functions, such as notification of flights approaching a flight information region (FIR) boundary, coordination of boundary conditions and transfer of control and communications authority.</i></p> <p>N4. <i>The detailed specification of the AIDC application is included in the Manual of Technical Provisions for the Aeronautical Telecommunication Network (ATN) (Doc 9705), Sub-volume III.</i></p> <p>N5. <i>The AIDC application is strictly an ATC application for exchanging tactical control information between ATS units. It does not support the exchange of information with other offices or facilities.</i></p> <p>N6. <i>The AIDC application supports the following operational services:</i></p> <ul style="list-style-type: none"> <li>g) <i>flight notification;</i></li> <li>h) <i>flight coordination;</i></li> <li>i) <i>transfer of executive control;</i></li> <li>j) <i>transfer of communications; and</i></li> <li>k) <i>transfer of general information (flight-related data or free text messages, i.e. unstructured).</i></li> </ul>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.1  Standard	<p style="text-align: center;"><b>CHAPTER 5. AERONAUTICAL MOBILE SERVICE — VOICE COMMUNICATIONS</b></p> <p style="text-align: center;"><b>5.1 General</b></p> <p><i>Note.— For the purposes of these provisions, the communication procedures applicable to the aeronautical mobile service, as appropriate, also apply to the aeronautical mobile satellite service.</i></p> <p>In all communications the highest standard of discipline shall be observed at all times.</p>	AC91-9 (Radiotelephony Manual).	No Difference		
Chapter 5 Reference 5.1.1.1  Standard	<p>ICAO standardized phraseology shall be used in all situations for which it has been specified. Only when standardized phraseology cannot serve an intended transmission, plain language shall be used.</p> <p><i>Note.— Detailed language proficiency requirements appear in the Appendix to Annex 1.</i></p>	AC91-9.	No Difference		
Chapter 5 Reference 5.1.1.2  Standard	The transmission of messages, other than those specified in 5.1.8, on aeronautical mobile frequencies when the aeronautical fixed services are able to serve the intended purpose, shall be avoided.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.1.3  Recommendation	<b>Recommendation.</b> — <i>In all communications, the consequences of human performance which could affect the accurate reception and comprehension of messages should be taken into consideration.</i> <i>Note.</i> — <i>Guidance material on human performance can be found in the Human Factors Training Manual (Doc 9683).</i>	AC91-9.	No Difference		
Chapter 5 Reference 5.1.2  Standard	Where it is necessary for an aircraft station to send signals for testing or adjustment which are liable to interfere with the working of a neighbouring aeronautical station, the consent of the station shall be obtained before such signals are sent. Such transmissions shall be kept to a minimum.	AC91-9, 4.15.	No Difference		
Chapter 5 Reference 5.1.3  Standard	When it is necessary for a station in the aeronautical mobile service to make test signals, either for the adjustment of a transmitter before making a call or for the adjustment of a receiver, such signals shall not continue for more than 10 seconds and shall be composed of spoken numerals (ONE, TWO, THREE, etc.) in radiotelephony, followed by the radio call sign of the station transmitting the test signals. Such transmissions shall be kept to a minimum.	AC91-9, 4.15.	No Difference		
Chapter 5 Reference 5.1.4  Standard	Except as otherwise provided, the responsibility of establishing communication shall rest with the station having traffic to transmit. <i>Note.</i> — <i>In certain cases when SELCAL is used the procedures respecting the establishment of communications are contained in 5.2.4.</i>	AC91-9, 4.7.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.5  Recommendation	<b>Recommendation.</b> — <i>After a call has been made to the aeronautical station, a period of at least 10 seconds should elapse before a second call is made. This should eliminate unnecessary transmissions while the aeronautical station is getting ready to reply to the initial call.</i>	AC91-9.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.1.6  Standard	When an aeronautical station is called simultaneously by several aircraft stations, the aeronautical station shall decide the order in which aircraft shall communicate.	CAR 171.75.	No Difference		
Chapter 5 Reference 5.1.7  Standard	In communications between aircraft stations, the duration of communication shall be controlled by the aircraft station which is receiving, subject to the intervention of an aeronautical station. If such communications take place on an ATS frequency, prior permission of the aeronautical station shall be obtained. Such requests for permission are not required for brief exchanges.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 5 Reference 5.1.8  Standard</p>	<p>Categories of messages The categories of messages handled by the aeronautical mobile service and the order of priority in the establishment of communications and the transmission of messages shall be in accordance with the following table.</p> <p><i>Message category and order of priority</i> <i>Radiotelephony signal</i></p> <p>a) Distress calls, distress messages and distress traffic MAYDAY</p> <p>b) Urgency messages, including messages preceded by the medical transports signal PAN, PAN or PAN, PAN MEDICAL</p> <p>c) Communications relating to direction finding —</p> <p>d) Flight safety messages —</p> <p>e) Meteorological messages —</p> <p>f) Flight regularity messages —</p> <p><i>N1. Messages concerning acts of unlawful interference constitute a case of exceptional circumstances which may preclude the use of recognized communication procedures used to determine message category and priority.</i></p> <p><i>N2.A NOTAM may qualify for any of the categories or priorities c) to f) inclusive. The decision as to which priority will depend on the contents of the NOTAM and its importance to the aircraft concerned.</i></p>	<p>CAR 171.75.</p>	<p>No Difference</p>		
<p>Chapter 5 Reference 5.1.8.1  Standard</p>	<p><i>Distress messages and distress traffic shall be handled in accordance with the provisions of 5.3.</i></p>	<p>CAR 171.75.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.8.2  Standard	<p><i>Urgency messages and urgency traffic</i>, including messages preceded by the medical transports signal, shall be handled in accordance with the provisions of 5.3.</p> <p><i>Note.— The term “medical transports” is defined in the 1949 Geneva Conventions and Additional Protocols (see also RR S33 Section III) and refers to “any means of transportation by land, water, or air, whether military or civilian, permanent or temporary, assigned exclusively to medical transportation and under the control of a competent authority of a Party to the conflict”.</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.1.8.3  Standard	<p><i>Communications relating to direction finding</i> shall be handled in accordance with Chapter 6.</p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.1.8.4  Standard	<p><i>Flight safety messages</i> shall comprise the following:</p> <ol style="list-style-type: none"> <li>1) movement and control messages [<i>see PANS-ATM (Doc 4444)</i>];</li> <li>2) messages originated by an aircraft operating agency or by an aircraft, of immediate concern to an aircraft in flight;</li> <li>3) meteorological advice of immediate concern to an aircraft in flight or about to depart (individually communicated or for broadcast);</li> <li>4) other messages concerning aircraft in flight or about to depart.</li> </ol>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.8.5  Standard	<i>Meteorological messages</i> shall comprise meteorological information to or from aircraft, other than those in 5.1.8.4, 3).	CAR 171.75.	No Difference		
Chapter 5 Reference 5.1.8.6  Standard	<i>Flight regularity messages</i> shall comprise the following: 1) messages regarding the operation or maintenance of facilities essential for the safety or regularity of aircraft operation; 2) messages concerning the servicing of aircraft; 3) instructions to aircraft operating agency representatives concerning changes in requirements for passengers and crew caused by unavoidable deviations from normal operating schedules. Individual requirements of passengers or crew shall not be admissible in this type of message; 4) messages concerning non-routine landings to be made by the aircraft; 5) messages concerning aircraft parts and materials urgently required; 6) messages concerning changes in aircraft operating schedules.	CAR Part 171.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.1.8.6.1  Standard	Air traffic services units using direct pilot-controller communication channels shall only be required to handle flight regularity messages provided this can be achieved without interference with their primary role and no other channels are available for the handling of such messages. <i>Note.— The messages at 5.1.8.4, 2) and 5.1.8.6, 1) to 6) typify some of the operational control communications defined in Chapter 1.</i>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.8.7  <b>Recommendation</b>	<b>Recommendation.</b> — <i>Messages having the same priority should, in general, be transmitted in the order in which they are received for transmission.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.1.8.8  <b>Standard</b>	Interpilot air-to-air communication shall comprise messages related to any matter affecting safety and regularity of flight. The category and priority of these messages shall be determined on the basis of their content in accordance with 5.1.8.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.1.9.1  <b>Standard</b>	5.1.9 Cancellation of messages  <i>Incomplete transmissions.</i> If a message has not been completely transmitted when instructions to cancel are received, the station transmitting the message shall instruct the receiving station to disregard the incomplete transmission. This shall be effected in radiotelephony by use of an appropriate phrase.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.1.9.2  <b>Recommendation</b>	<i>Complete transmissions</i> <b>Recommendation.</b> — <i>When a completed message transmission is being held pending correction and the receiving station is to be informed to take no forwarding action, or when delivery or onward relay cannot be accomplished, transmission should be cancelled. This should be effected in radiotelephony by the use of an appropriate phrase.</i>	CARs.	Less protective or partially implemented or not implemented	Not specified.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.1.9.3  Standard	The station cancelling a transmission shall be responsible for any further action required.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.2.1.1  PANS	<p style="text-align: center;"><b>5.2 Radiotelephony procedures</b></p> <p><i>Note.— When Selective Calling (SELCAL) equipment is used certain of the following procedures are superseded by those contained in 5.2.4.</i></p> <p style="text-align: center;">5.2.1 General</p> <p><b>PANS.—</b> <i>When a controller or pilot communicates via voice, the response should be via voice. Except as provided by 8.2.12.1, when a controller or pilot communicates via CPDLC, the response should be via CPDLC.</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.2.1  Standard	<p><b>5.2.1.2 Language to be used</b></p> <p>The air-ground radiotelephony communications shall be conducted in the language normally used by the station on the ground or in the English language.</p> <p><i>N1. The language normally used by the station on the ground may not necessarily be the language of the State in which it is located. A common language may be agreed upon regionally as a requirement for stations on the ground in that region.</i></p> <p><i>N2. The level of language proficiency required for aeronautical radiotelephony communications is specified in the Appendix to Annex 1.</i></p>	AIPNZ GEN 3.4, 3.5; CAR 91.755.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.2.2  Standard	The English language shall be available, on request from any aircraft station, at all stations on the ground serving designated airports and routes used by international air services.	AIPNZ GEN 3.4, 3.5; CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.2.3  Standard	The languages available at a given station on the ground shall form part of the Aeronautical Information Publications and other published aeronautical information concerning such facilities.	AIPNZ GEN 3.4, 3.5.	No Difference		
Chapter 5 Reference 5.2.1.3  Standard	<p><i>Word spelling in radiotelephony.</i> When proper names, service abbreviations and words of which the spelling is doubtful are spelled out in radiotelephony the alphabet in Figure 5-1 shall be used.</p> <p>N1.<i>The pronunciation of the words in the alphabet as well as numbers may vary according to the language habits of the speakers. In order to eliminate wide variations in pronunciation, posters illustrating the desired pronunciation are available from ICAO.</i></p> <p>N2.<i>The Spelling Alphabet specified in 5.2.1.3 is also prescribed for use in the Maritime Mobile Service (ITU Radio Regulations, Appendix S14).</i></p>	AC91-9, 4.2.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																																				
Chapter 5 Reference 5.2.1.4.1.1  Standard	<p>5.2.1.4 <i>Transmission of numbers in radiotelephony</i></p> <p>5.2.1.4.1 <i>Transmission of numbers</i></p> <p>All numbers, except as prescribed in 5.2.1.4.1.2, shall be transmitted by pronouncing each digit separately.</p> <p><i>Note.— The following examples illustrate the application of this procedure (see 5.2.1.4.3.1 for pronunciation).</i></p> <table border="0"> <tr> <td><i>aircraft call signs</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>CCA 238</td> <td>Air China two three</td> </tr> <tr> <td>eight</td> <td></td> </tr> <tr> <td>OAL 242</td> <td>Olympic two four two</td> </tr> <tr> <td> <i>flight levels</i></td> <td> <i>transmitted as</i></td> </tr> <tr> <td>FL 180</td> <td>flight level one eight</td> </tr> <tr> <td>zero</td> <td></td> </tr> <tr> <td>FL 200</td> <td>flight level two zero</td> </tr> <tr> <td>zero</td> <td></td> </tr> <tr> <td><i>headings</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>100 degrees</td> <td>heading one zero zero</td> </tr> <tr> <td></td> <td></td> </tr> <tr> <td>080 degrees</td> <td>heading zero eight</td> </tr> <tr> <td>zero</td> <td></td> </tr> <tr> <td><i>wind direction and speed</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>200 degrees 70 knots</td> <td>wind two zero zero</td> </tr> <tr> <td>degrees seven zero knots</td> <td></td> </tr> <tr> <td>160 degrees 18 knots gusting 30 knots</td> <td>wind one six zero</td> </tr> <tr> <td>degrees one eight knots gusting three zero knots</td> <td></td> </tr> <tr> <td><i>transponder codes</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>2400</td> <td>squawk two four zero</td> </tr> <tr> <td>zero</td> <td></td> </tr> <tr> <td>4203</td> <td>squawk four two zero</td> </tr> <tr> <td>three</td> <td></td> </tr> <tr> <td><i>runway</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>27</td> <td>runway two seven</td> </tr> </table>	<i>aircraft call signs</i>	<i>transmitted as</i>	CCA 238	Air China two three	eight		OAL 242	Olympic two four two	 <i>flight levels</i>	 <i>transmitted as</i>	FL 180	flight level one eight	zero		FL 200	flight level two zero	zero		<i>headings</i>	<i>transmitted as</i>	100 degrees	heading one zero zero			080 degrees	heading zero eight	zero		<i>wind direction and speed</i>	<i>transmitted as</i>	200 degrees 70 knots	wind two zero zero	degrees seven zero knots		160 degrees 18 knots gusting 30 knots	wind one six zero	degrees one eight knots gusting three zero knots		<i>transponder codes</i>	<i>transmitted as</i>	2400	squawk two four zero	zero		4203	squawk four two zero	three		<i>runway</i>	<i>transmitted as</i>	27	runway two seven	AC91-9, 4.3.	No Difference		
<i>aircraft call signs</i>	<i>transmitted as</i>																																																								
CCA 238	Air China two three																																																								
eight																																																									
OAL 242	Olympic two four two																																																								
 <i>flight levels</i>	 <i>transmitted as</i>																																																								
FL 180	flight level one eight																																																								
zero																																																									
FL 200	flight level two zero																																																								
zero																																																									
<i>headings</i>	<i>transmitted as</i>																																																								
100 degrees	heading one zero zero																																																								
080 degrees	heading zero eight																																																								
zero																																																									
<i>wind direction and speed</i>	<i>transmitted as</i>																																																								
200 degrees 70 knots	wind two zero zero																																																								
degrees seven zero knots																																																									
160 degrees 18 knots gusting 30 knots	wind one six zero																																																								
degrees one eight knots gusting three zero knots																																																									
<i>transponder codes</i>	<i>transmitted as</i>																																																								
2400	squawk two four zero																																																								
zero																																																									
4203	squawk four two zero																																																								
three																																																									
<i>runway</i>	<i>transmitted as</i>																																																								
27	runway two seven																																																								



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	30 <i>altimeter setting</i> 1010 zero 1000 zero  runway three zero <i>transmitted as</i> QNH one zero one  QNH one zero zero				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																										
Chapter 5 Reference 5.2.1.4.1.2  Standard	<p>All numbers used in the transmission of altitude, cloud height, visibility and runway visual range (RVR) information, which contain whole hundreds and whole thousands, shall be transmitted by pronouncing each digit in the number of hundreds or thousands followed by the word HUNDRED or THOUSAND as appropriate. Combinations of thousands and whole hundreds shall be transmitted by pronouncing each digit in the number of thousands followed by the word THOUSAND followed by the number of hundreds followed by the word HUNDRED.</p> <p><i>Note.— The following examples illustrate the application of this procedure (see 5.2.1.4.3.1 for pronunciation).</i></p> <table data-bbox="273 730 924 1412"> <tr> <td><i>altitude</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>800</td> <td><b>eight hundred</b></td> </tr> <tr> <td>3 400</td> <td><b>three thousand</b></td> </tr> <tr> <td><b>four hundred</b></td> <td></td> </tr> <tr> <td>12 000</td> <td><b>one two thousand</b></td> </tr> <tr> <td> </td> <td></td> </tr> <tr> <td><i>cloud height</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>2 200</td> <td><b>two thousand two</b></td> </tr> <tr> <td><b>hundred</b></td> <td></td> </tr> <tr> <td>4 300</td> <td><b>four thousand</b></td> </tr> <tr> <td><b>three hundred</b></td> <td></td> </tr> <tr> <td><i>visibility</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>1000</td> <td>visibility <b>one</b></td> </tr> <tr> <td><b>thousand</b></td> <td></td> </tr> <tr> <td>700</td> <td>visibility <b>seven</b></td> </tr> <tr> <td><b>hundred</b></td> <td></td> </tr> <tr> <td><i>runway visual range</i></td> <td><i>transmitted as</i></td> </tr> <tr> <td>600</td> <td>RVR <b>six hundred</b></td> </tr> <tr> <td> </td> <td></td> </tr> <tr> <td>1 700</td> <td>RVR <b>one thousand</b></td> </tr> <tr> <td><b>seven hundred</b></td> <td></td> </tr> </table>	<i>altitude</i>	<i>transmitted as</i>	800	<b>eight hundred</b>	3 400	<b>three thousand</b>	<b>four hundred</b>		12 000	<b>one two thousand</b>	 		<i>cloud height</i>	<i>transmitted as</i>	2 200	<b>two thousand two</b>	<b>hundred</b>		4 300	<b>four thousand</b>	<b>three hundred</b>		<i>visibility</i>	<i>transmitted as</i>	1000	visibility <b>one</b>	<b>thousand</b>		700	visibility <b>seven</b>	<b>hundred</b>		<i>runway visual range</i>	<i>transmitted as</i>	600	RVR <b>six hundred</b>	 		1 700	RVR <b>one thousand</b>	<b>seven hundred</b>		AC91-9, 4.3.	No Difference		
<i>altitude</i>	<i>transmitted as</i>																																														
800	<b>eight hundred</b>																																														
3 400	<b>three thousand</b>																																														
<b>four hundred</b>																																															
12 000	<b>one two thousand</b>																																														
<i>cloud height</i>	<i>transmitted as</i>																																														
2 200	<b>two thousand two</b>																																														
<b>hundred</b>																																															
4 300	<b>four thousand</b>																																														
<b>three hundred</b>																																															
<i>visibility</i>	<i>transmitted as</i>																																														
1000	visibility <b>one</b>																																														
<b>thousand</b>																																															
700	visibility <b>seven</b>																																														
<b>hundred</b>																																															
<i>runway visual range</i>	<i>transmitted as</i>																																														
600	RVR <b>six hundred</b>																																														
1 700	RVR <b>one thousand</b>																																														
<b>seven hundred</b>																																															



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 5 Reference 5.2.1.4.1.3  Standard	<p>Numbers containing a decimal point shall be transmitted as prescribed in 5.2.1.4.1.1 with the decimal point in appropriate sequence being indicated by the word DECIMAL.</p> <p><i>N1.The following examples illustrate the application of this procedure:</i></p> <table border="0"> <tr> <td style="padding-right: 40px;"><i>Number</i></td> <td><i>Transmitted as</i></td> </tr> <tr> <td>100.3</td> <td>ONE ZERO ZERO DECIMAL</td> </tr> <tr> <td>THREE</td> <td></td> </tr> <tr> <td>38 143.9</td> <td>THREE EIGHT ONE FOUR</td> </tr> <tr> <td>THREE DECIMAL NINE</td> <td></td> </tr> </table> <p><i>N2.For identification of VHF frequencies the number of digits used after the decimal point are determined on the basis of the channel spacing (5.2.1.7.3.4.3 refers to frequencies separated by 25 kHz, 5.2.1.7.3.4.4 refers to frequencies separated by 8.33 kHz).</i></p> <p><i>N3.The channelling/frequency pairing relationship for 8.33 kHz and 25 kHz is found in Table 4-1 (bis), Volume V.</i></p>	<i>Number</i>	<i>Transmitted as</i>	100.3	ONE ZERO ZERO DECIMAL	THREE		38 143.9	THREE EIGHT ONE FOUR	THREE DECIMAL NINE		AC91-9, 4.3.	No Difference		
<i>Number</i>	<i>Transmitted as</i>														
100.3	ONE ZERO ZERO DECIMAL														
THREE															
38 143.9	THREE EIGHT ONE FOUR														
THREE DECIMAL NINE															
Chapter 5 Reference 5.2.1.4.1.4  PANS	<p>PANS.— When transmitting time, only the minutes of the hour should normally be required. Each digit should be pronounced separately. However, the hour should be included when any possibility of confusion is likely to result.</p> <p><i>Note.— The following example illustrates the application of this procedure when applying the provisions of 5.2.1.2.2:</i></p> <table border="0"> <tr> <td style="padding-right: 40px;"><i>Time</i></td> <td><i>Statement</i></td> </tr> <tr> <td>0920 (9:20 A.M.)</td> <td>TOO ZE-RO or ZE-RO</td> </tr> <tr> <td>NIN-er TOO ZE-RO</td> <td></td> </tr> <tr> <td>1643 (4:43 P.M.)</td> <td>FOW-er TREE or WUN SIX</td> </tr> <tr> <td>FOW-er TREE</td> <td></td> </tr> </table>	<i>Time</i>	<i>Statement</i>	0920 (9:20 A.M.)	TOO ZE-RO or ZE-RO	NIN-er TOO ZE-RO		1643 (4:43 P.M.)	FOW-er TREE or WUN SIX	FOW-er TREE		AC91-9, 4.4.	No Difference		
<i>Time</i>	<i>Statement</i>														
0920 (9:20 A.M.)	TOO ZE-RO or ZE-RO														
NIN-er TOO ZE-RO															
1643 (4:43 P.M.)	FOW-er TREE or WUN SIX														
FOW-er TREE															



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																												
Chapter 5 Reference 5.2.1.4.2.1  Standard	<p>5.2.1.4.2 <i>Verification of numbers</i></p> <p>When it is desired to verify the accurate reception of numbers the person transmitting the message shall request the person receiving the message to read back the numbers.</p>	AC91-9, 4.12.	No Difference																														
Chapter 5 Reference 5.2.1.4.3.1  Standard	<p>5.2.1.4.3 <i>Pronunciation of numbers</i></p> <p>When the language used for communication is English, numbers shall be transmitted using the following pronunciation:</p> <table border="0" data-bbox="352 740 919 1247"> <thead> <tr> <th><i>Numeral or numeral element</i></th> <th><i>Pronunciation</i></th> </tr> </thead> <tbody> <tr><td>0</td><td>ZE-RO</td></tr> <tr><td>1</td><td>WUN</td></tr> <tr><td>2</td><td>TOO</td></tr> <tr><td>3</td><td>TREE</td></tr> <tr><td>4</td><td>FOW-er</td></tr> <tr><td>5</td><td>FIFE</td></tr> <tr><td>6</td><td>SIX</td></tr> <tr><td>7</td><td>SEV-en</td></tr> <tr><td>8</td><td>AIT</td></tr> <tr><td>9</td><td>NIN-er</td></tr> <tr><td>Decimal</td><td>DAY-SEE-MAL</td></tr> <tr><td>Hundred</td><td>HUN-dred</td></tr> <tr><td>Thousand</td><td>TOU-SAND</td></tr> </tbody> </table> <p><i>Note.— The syllables printed in capital letters in the above list are to be stressed; for example, the two syllables in ZE-RO are given equal emphasis, whereas the first syllable of FOW-er is given primary emphasis.</i></p>	<i>Numeral or numeral element</i>	<i>Pronunciation</i>	0	ZE-RO	1	WUN	2	TOO	3	TREE	4	FOW-er	5	FIFE	6	SIX	7	SEV-en	8	AIT	9	NIN-er	Decimal	DAY-SEE-MAL	Hundred	HUN-dred	Thousand	TOU-SAND	AC91-9, 4.3.	No Difference		
<i>Numeral or numeral element</i>	<i>Pronunciation</i>																																
0	ZE-RO																																
1	WUN																																
2	TOO																																
3	TREE																																
4	FOW-er																																
5	FIFE																																
6	SIX																																
7	SEV-en																																
8	AIT																																
9	NIN-er																																
Decimal	DAY-SEE-MAL																																
Hundred	HUN-dred																																
Thousand	TOU-SAND																																





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.5.1  PANS	5.2.1.5 <i>Transmitting technique</i>  PANS.— <i>Each written message should be read prior to commencement of transmission in order to eliminate unnecessary delays in communications.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.5.2  Standard	Transmissions shall be conducted concisely in a normal conversational tone. <i>Note.— See the language proficiency requirements in the Appendix to Annex 1.</i>	AC91-9, 4.1.	No Difference		
Chapter 5 Reference 5.2.1.5.3  PANS	PANS.— <i>Speech transmitting technique should be such that the highest possible intelligibility is incorporated in each transmission. Fulfilment of this aim requires that air crew and ground personnel should:</i> a) <i>enunciate each word clearly and distinctly;</i> b) <i>maintain an even rate of speech not exceeding 100 words per minute. When a message is transmitted to an aircraft and its contents need to be recorded the speaking rate should be at a slower rate to allow for the writing process. A slight pause preceding and following numerals make them easier to understand;</i> c) <i>maintain the speaking volume at a constant level;</i> d) <i>be familiar with the microphone operating techniques particularly in relation to the maintenance of a constant distance from the microphone if a modulator with a constant level is not used;</i> e) <i>suspend speech temporarily it becomes necessary to turn the head away from the microphone.</i>	AC91-9, 4.1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.5.4  Recommendation	<b>Recommendation.</b> — <i>Speech transmitting technique should be adapted to the prevailing communications conditions.</i>	AC91-9, 4.1.	No Difference		
Chapter 5 Reference 5.2.1.5.5  PANS	<b>PANS.</b> — <i>Messages accepted for transmission should be transmitted in plain language or ICAO phraseologies without altering the sense of the message in any way. Approved ICAO abbreviations contained in the text of the message to be transmitted to aircraft should normally be converted into the unabbreviated words or phrases which these abbreviations represent in the language used, except for those which, owing to frequent and common practice, are generally understood by aeronautical personnel.</i>  <i>Note.</i> — <i>The abbreviations which constitute the exceptions mentioned in 5.2.1.5.5 are specifically identified in the abbreviation encode sections of the PANS-ABC (Doc 8400).</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.5.6  PANS	<b>PANS.</b> — <i>To expedite communication, the use of phonetic spelling should be dispensed with, if there is no risk of this affecting correct reception and intelligibility of the message.</i>	AC91-9, 1.3.	No Difference		
Chapter 5 Reference 5.2.1.5.7  PANS	<b>PANS.</b> — <i>The transmission of long messages should be interrupted momentarily from time to time to permit the transmitting operator to confirm that the frequency in use is clear and, if necessary, to permit the receiving operator to request repetition of parts not received.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																		
Chapter 5  Reference 5.2.1.5.8  Standard	<p>The following words and phrases shall be used in radiotelephony communications as appropriate and shall have the meaning ascribed hereunder:</p> <table border="0"> <tr> <td><i>Phrase</i></td> <td><i>Meaning</i></td> </tr> <tr> <td>ACKNOWLEDGE</td> <td>“Let me know that you have received and understood this message.”</td> </tr> <tr> <td>AFFIRM</td> <td>“Yes.”</td> </tr> <tr> <td>APPROVED</td> <td>“Permission for proposed action granted.”</td> </tr> <tr> <td>BREAK</td> <td>“I hereby indicate the separation between portions of the message.” <i>(To be used where there is no clear distinction between the text and other portions of the message.)</i></td> </tr> <tr> <td>BREAK BREAK</td> <td>“I hereby indicate the separation between messages transmitted to different aircraft in a very busy environment.”</td> </tr> <tr> <td>CANCEL</td> <td>“Annul the previously transmitted clearance.”</td> </tr> <tr> <td>CHECK</td> <td>“Examine a system or procedure.” <i>(Not to be used in any other context. No answer is normally expected.)</i></td> </tr> <tr> <td>CLEARED</td> <td>“Authorized to proceed under the conditions specified.”</td> </tr> <tr> <td>CONFIRM</td> <td>“I request verification of: <i>(clearance, instruction, action, information).</i>”</td> </tr> <tr> <td>CONTACT</td> <td>“Establish communications with...”</td> </tr> <tr> <td>CORRECT</td> <td>“True” or “Accurate”.</td> </tr> <tr> <td>CORRECTION</td> <td>“An error has been made in this transmission <i>(or message indicated)</i>, The correct version is ...”</td> </tr> <tr> <td>DISREGARD</td> <td>“Ignore.”</td> </tr> <tr> <td>HOW DO YOU READ</td> <td>“What is the readability of my transmission?” <i>(see 5.2.1.8.4)</i></td> </tr> <tr> <td>I SAY AGAIN</td> <td>“I repeat for clarity or emphasis”.</td> </tr> <tr> <td>MAINTAIN</td> <td>“Continue in accordance with</td> </tr> </table>	<i>Phrase</i>	<i>Meaning</i>	ACKNOWLEDGE	“Let me know that you have received and understood this message.”	AFFIRM	“Yes.”	APPROVED	“Permission for proposed action granted.”	BREAK	“I hereby indicate the separation between portions of the message.” <i>(To be used where there is no clear distinction between the text and other portions of the message.)</i>	BREAK BREAK	“I hereby indicate the separation between messages transmitted to different aircraft in a very busy environment.”	CANCEL	“Annul the previously transmitted clearance.”	CHECK	“Examine a system or procedure.” <i>(Not to be used in any other context. No answer is normally expected.)</i>	CLEARED	“Authorized to proceed under the conditions specified.”	CONFIRM	“I request verification of: <i>(clearance, instruction, action, information).</i> ”	CONTACT	“Establish communications with...”	CORRECT	“True” or “Accurate”.	CORRECTION	“An error has been made in this transmission <i>(or message indicated)</i> , The correct version is ...”	DISREGARD	“Ignore.”	HOW DO YOU READ	“What is the readability of my transmission?” <i>(see 5.2.1.8.4)</i>	I SAY AGAIN	“I repeat for clarity or emphasis”.	MAINTAIN	“Continue in accordance with	AC91-9, 4.5.	No Difference		
<i>Phrase</i>	<i>Meaning</i>																																						
ACKNOWLEDGE	“Let me know that you have received and understood this message.”																																						
AFFIRM	“Yes.”																																						
APPROVED	“Permission for proposed action granted.”																																						
BREAK	“I hereby indicate the separation between portions of the message.” <i>(To be used where there is no clear distinction between the text and other portions of the message.)</i>																																						
BREAK BREAK	“I hereby indicate the separation between messages transmitted to different aircraft in a very busy environment.”																																						
CANCEL	“Annul the previously transmitted clearance.”																																						
CHECK	“Examine a system or procedure.” <i>(Not to be used in any other context. No answer is normally expected.)</i>																																						
CLEARED	“Authorized to proceed under the conditions specified.”																																						
CONFIRM	“I request verification of: <i>(clearance, instruction, action, information).</i> ”																																						
CONTACT	“Establish communications with...”																																						
CORRECT	“True” or “Accurate”.																																						
CORRECTION	“An error has been made in this transmission <i>(or message indicated)</i> , The correct version is ...”																																						
DISREGARD	“Ignore.”																																						
HOW DO YOU READ	“What is the readability of my transmission?” <i>(see 5.2.1.8.4)</i>																																						
I SAY AGAIN	“I repeat for clarity or emphasis”.																																						
MAINTAIN	“Continue in accordance with																																						



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>the condition(s) specified” or in its literal sense, e.g. “Maintain VFR”.</p> <p>MONITOR                      “Listen out on (frequency)”.</p> <p>NEGATIVE                      “No” or “Permission not granted” or “That is not correct” or “Not Capable”.</p> <p>OVER                              “My transmission is ended, and I expect a response from you.”</p> <p style="text-align: center;"><i>Note.— Not normally used in VHF communications.</i></p> <p>OUT                                “This exchange of transmissions is ended and no response is expected”</p> <p style="text-align: center;"><i>Note.— Not normally used in VHF communications.</i></p> <p>READ BACK                      “Repeat all, or the specified part, of this message back to me exactly as received.”</p> <p>RECLEARED                      “A change has been made to your last clearance and this new clearance supersedes your previous clearance or part thereof.”</p> <p>REPORT                            “Pass me the following information...”</p> <p>REQUEST                         “I should like to know...” or “I wish to obtain...”.”</p> <p>ROGER                             “I have received all of your last transmission.”</p> <p style="text-align: center;"><i>Note.— Under no circumstances to be used in reply to a question requiring “READ BACK” or a direct answer in the affirmative (AFFIRM) or negative (NEGATIVE).</i></p> <p>SAY AGAIN                        “Repeat all, or the following part, of your last transmission.”</p> <p>SPEAK SLOWER                      “Reduce your rate of speech.”</p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p><i>Note.— For normal rate of speech, see 5.2.1.5.3 b).</i> STANDBY “Wait and I will call you.”</p> <p><i>Note.— The caller would normally re-establish contact if the delay is lengthy. STANDBY is not an approval or denial.</i> UNABLE “I cannot comply with your request, instruction, or clearance.”</p> <p><i>Note.— UNABLE is normally followed by a reason.</i> WILCO <i>(Abbreviation for “will comply”.)</i> “I understand your message and will comply with it.”</p> <p>WORDS TWICE a) <i>As a request:</i> “Communication is difficult. Please send every word, or group of words, twice.”</p> <p>b) <i>As information:</i> “Since communication is difficult, every word, or group of words, in this message will be sent twice.”</p>				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.6.1  Standard	<p>5.2.1.6 <i>Composition of messages</i></p> <p>Messages handled entirely by the aeronautical mobile service shall comprise the following parts in the order stated:</p> <p>a) call indicating the addressee and the originator (<i>see</i> 5.2.1.7.3);</p> <p>b) text (<i>see</i> 5.2.1.6.2.1.1).</p> <p><i>Note.— The following examples illustrate the application of this procedure:</i></p> <p>(<i>call</i>) NEW YORK RADIO SWISSAIR ONE ONE ZERO</p> <p>(<i>text</i>) REQUEST SELCAL CHECK</p> <p><i>or</i></p> <p>(<i>call</i>) SWISSAIR ONE ONE ZERO NEW YORK RADIO</p> <p>(<i>text</i>) CONTACT SAN JUAN ON FIVE SIX</p>	AC 91-9.	No Difference		
Chapter 5 Reference 5.2.1.6.2  Standard	Messages requiring handling by the AFTN for part of their routing and similarly messages which are not handled in accordance with predetermined distribution arrangements ( <i>see</i> 3.3.7.1) shall be composed as follows:	CAR 171.75; AC91-9.	No Difference		
Chapter 5 Reference 5.2.1.6.2.1  Standard	<p><i>When originated in an aircraft:</i></p> <p>1) call (<i>see</i> 5.2.1.7.3);</p> <p>2) the word FOR;</p> <p>3) the name of the organization addressed;</p> <p>4) the name of the station of destination;</p> <p>5) the text.</p>	AC91-9.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.6.2.1.1  Standard	The text shall be as short as practicable to convey the necessary information; full use shall be made of ICAO phraseologies. <i>Note.— The following example illustrates the application of this procedure:</i> <i>(call)</i> BOSTON RADIO SWISSAIR ONE TWO EIGHT <i>(address)</i> FOR SWISSAIR BOSTON <i>(text)</i> NUMBER ONE ENGINE CHANGE REQUIRED	AC91-9.	No Difference		
Chapter 5 Reference 5.2.1.6.2.2  Standard	<i>When addressed to an aircraft.</i> When a message, prepared in accordance with 4.4.2, is retransmitted by an aeronautical station to an aircraft in flight, the heading and address of the AFTN message format shall be omitted during the retransmission on the aeronautical mobile service.	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.6.2.2.1  Standard	When the provisions of 5.2.1.6.2.2 are applied, the aeronautical mobile service message transmission shall comprise: a) the text [incorporating any corrections (COR) contained in the AFTN message]; b) the word FROM; c) the name of the originating organization and its location (taken from the origin section of the AFTN message).	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.6.2.2.2  PANS	<p><b>PANS.</b>— <i>When the text of a message to be transmitted by an aeronautical station to an aircraft in flight contains approved ICAO abbreviations, these abbreviations should normally be converted during the transmission of the message into the unabbreviated words or phrases which the abbreviations represent in the language used, except for those which, owing to frequent or common practice, are generally understood by aeronautical personnel.</i></p> <p><i>Note.</i>— <i>The abbreviations which constitute the exceptions mentioned in 5.2.1.6.2.2.2 are specifically identified in the abbreviations encode sections of the PANS-ABC (Doc 8400).</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.7.1.1  Standard	<p><b>5.2.1.7 Calling</b></p> <p><b>5.2.1.7.1 Radiotelephony call signs for aeronautical stations</b></p> <p><i>Note.</i>— <i>The formation of call signs as specified in ITU Radio Regulations S19 Section III and Section VII.</i></p> <p>Aeronautical stations in the aeronautical mobile service shall be identified by:</p> <ul style="list-style-type: none"> <li>a) the name of the location; and</li> <li>b) the unit or service available.</li> </ul>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																										
Chapter 5 Reference 5.2.1.7.1.2  Standard	<p>The unit or service shall be identified in accordance with the table below except that the name of the location or the unit/service may be omitted provided satisfactory communication has been established.</p> <table border="0" style="width: 100%;"> <tr> <td style="text-align: left;"><i>Unit/service available</i></td> <td style="text-align: right;"><i>Call</i></td> </tr> <tr> <td style="text-align: left;"><i>sign suffix</i></td> <td></td> </tr> <tr> <td>area control centre</td> <td style="text-align: right;">CONT</td> </tr> <tr> <td>ROL approach control</td> <td style="text-align: right;">APPR</td> </tr> <tr> <td>OACH approach control radar arrivals</td> <td style="text-align: right;">ARRIV</td> </tr> <tr> <td>AL approach control radar departures</td> <td style="text-align: right;">DEPA</td> </tr> <tr> <td>RTURE aerodrome control</td> <td style="text-align: right;">TOWE</td> </tr> <tr> <td>R surface movement control</td> <td style="text-align: right;">GROU</td> </tr> <tr> <td>ND radar (in general)</td> <td style="text-align: right;">RADA</td> </tr> <tr> <td>R precision approach radar</td> <td style="text-align: right;">PRECI</td> </tr> <tr> <td>SION direction-finding station</td> <td style="text-align: right;">HOME</td> </tr> <tr> <td>R flight information service</td> <td style="text-align: right;">INFOR</td> </tr> <tr> <td>MATION</td> <td></td> </tr> </table>	<i>Unit/service available</i>	<i>Call</i>	<i>sign suffix</i>		area control centre	CONT	ROL approach control	APPR	OACH approach control radar arrivals	ARRIV	AL approach control radar departures	DEPA	RTURE aerodrome control	TOWE	R surface movement control	GROU	ND radar (in general)	RADA	R precision approach radar	PRECI	SION direction-finding station	HOME	R flight information service	INFOR	MATION		AC91-9.	No Difference		Additionally, aerodrome flight information service units may use "FLIGHT SERVICE" (applies to only one location in New Zealand).
<i>Unit/service available</i>	<i>Call</i>																														
<i>sign suffix</i>																															
area control centre	CONT																														
ROL approach control	APPR																														
OACH approach control radar arrivals	ARRIV																														
AL approach control radar departures	DEPA																														
RTURE aerodrome control	TOWE																														
R surface movement control	GROU																														
ND radar (in general)	RADA																														
R precision approach radar	PRECI																														
SION direction-finding station	HOME																														
R flight information service	INFOR																														
MATION																															



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	clearance delivery  DELIV  ERY apron control  APRO  N company dispatch  DISPA  TCH aeronautical dispatch  RADIO				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																		
Chapter 5 Reference 5.2.1.7.2.1.1  Standard	<p>5.2.1.7.2 Radiotelephony call signs for aircraft</p> <p>5.2.1.7.2.1 Full call signs</p> <p>An aircraft radiotelephony call sign shall be one of the following types:</p> <p>Type a) — the characters corresponding to the registration marking of the aircraft; or</p> <p>Type b) — the telephony designator of the aircraft operating agency, followed by the last four characters of the registration marking of the aircraft;</p> <p>Type c) — the telephony designator of the aircraft operating agency, followed by the flight identification.</p> <p>N1. The name of the aircraft manufacturer or of the aircraft model may be used as a radiotelephony prefix to the Type a) call sign (see Table 5-1).</p> <p>N2. The telephony designators referred to in Types b) and c) are contained in doc 8585 — Designators for Aircraft Operating Agencies, Aeronautical Authorities and Services.</p> <p>N3. Any of the foregoing call signs may be inserted in field 7 of the ICAO flight plan as the aircraft identification. Instructions on the completion of the flight plan form are contained in PANS-ATM, Doc 4444.</p> <p><b>Table 5-1. Examples of full call signs and abbreviated call signs</b> (see 5.2.1.7.2.1 and 5.2.1.7.2.2)</p> <table border="0" style="width: 100%; text-align: center;"> <tr> <td></td> <td>Type a)</td> <td>Type b)</td> </tr> <tr> <td>Type c)</td> <td></td> <td></td> </tr> <tr> <td>Full call sign</td> <td>N57826 *Cessna FABCD</td> <td>*Citation FABCD</td> </tr> <tr> <td></td> <td>VARIG PVMA</td> <td>SCANDINAVIAN 937</td> </tr> <tr> <td>Abbreviated call sign</td> <td>N26 or N826</td> <td>CESSNA</td> </tr> <tr> <td></td> <td>CD or CESSNA BCD</td> <td>CITATION CD or</td> </tr> </table>		Type a)	Type b)	Type c)			Full call sign	N57826 *Cessna FABCD	*Citation FABCD		VARIG PVMA	SCANDINAVIAN 937	Abbreviated call sign	N26 or N826	CESSNA		CD or CESSNA BCD	CITATION CD or	CAR 91.249.	No Difference		
	Type a)	Type b)																					
Type c)																							
Full call sign	N57826 *Cessna FABCD	*Citation FABCD																					
	VARIG PVMA	SCANDINAVIAN 937																					
Abbreviated call sign	N26 or N826	CESSNA																					
	CD or CESSNA BCD	CITATION CD or																					



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>CITATION BCD VARIG MA or VARIG VMA (no abbreviated form)</p> <p>*Examples illustrate the application of Note 1 to 5.2.1.7.2.1.1.</p>				
<p>Chapter 5 Reference 5.2.1.7.2.2.1  Standard</p>	<p>5.2.1.7.2.2 <i>Abbreviated call signs</i></p> <p>The aircraft radiotelephony call signs shown in 5.2.1.7.2.1.1, with the exception of Type c), may be abbreviated in the circumstances prescribed in 5.2.1.7.3.3.1. Abbreviated call signs shall be in the following form:</p> <p>Type a) — the first character of the registration and at least the last two characters of the call sign;</p> <p>Type b) — the telephony designator of the aircraft operating agency, followed by the last two characters of the call sign;</p> <p>Type c) — no abbreviated form.</p> <p><i>Note.— Either the name of the aircraft manufacturer or of the aircraft model may be used in place of the first character in Type a).</i></p>	<p>CAR 91.249.</p>	<p>More Exacting or Exceeds</p>	<p>Abbreviated call signs types (a) and (b) are not permitted.</p>	
<p>Chapter 5 Reference 5.2.1.7.3.1  Standard</p>	<p>5.2.1.7.3 <i>Radiotelephony procedures</i></p> <p>An aircraft shall not change the type of its radiotelephony call sign during flight, except temporarily on the instruction of an air traffic control unit in the interests of safety.</p>	<p>CAR 91.249; AC91-9, 4.2.2.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.7.3.1.1  Standard	Except for reasons of safety no transmission shall be directed to an aircraft during take-off, during the last part of the final approach or during the landing roll.	CAR 171.75; AC91-9, 5.1.1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																		
Chapter 5 Reference 5.2.1.7.3.2.1  Standard	<p>5.2.1.7.3.2 <i>Establishment of radiotelephony communications</i></p> <p>Full radiotelephony call signs shall always be used when establishing communication. The calling procedure of an aircraft establishing communication shall be in accordance with Table 5-2.</p> <p><b>Table 5-2. Radiotelephony calling procedure*</b> (<i>see 5.2.1.7.3.2.1</i>)</p> <table data-bbox="323 662 940 912"> <tr> <td></td> <td><i>Type a)</i></td> <td><i>Type b)</i></td> </tr> <tr> <td></td> <td><i>Type c)</i></td> <td></td> </tr> <tr> <td>Designation of the station called</td> <td>NEW YORK RADIO</td> <td>NEW YORK RADIO</td> </tr> <tr> <td></td> <td>NEW YORK RADIO</td> <td>NEW YORK RADIO</td> </tr> <tr> <td>Designation of the station calling</td> <td>GABCD**</td> <td>SPEEDBIRD ABCD**</td> </tr> <tr> <td></td> <td>SPEEDBIRD ABCD**</td> <td>AEROFLOT 321**</td> </tr> </table> <p>* <i>In certain cases where the call is initiated by the aeronautical station, the call may be effected by transmission of coded tone signals.</i></p> <p>** <i>With the exception of the telephony designators and the type of aircraft, each character in the call sign shall be spoken separately. When individual letters are spelled out, the radiotelephony spelling alphabet prescribed in 5.2.1.3 shall be used. Numbers are to be spoken in accordance with 5.2.1.4.</i></p>		<i>Type a)</i>	<i>Type b)</i>		<i>Type c)</i>		Designation of the station called	NEW YORK RADIO	NEW YORK RADIO		NEW YORK RADIO	NEW YORK RADIO	Designation of the station calling	GABCD**	SPEEDBIRD ABCD**		SPEEDBIRD ABCD**	AEROFLOT 321**	AC91-9, 4.7.	No Difference		
	<i>Type a)</i>	<i>Type b)</i>																					
	<i>Type c)</i>																						
Designation of the station called	NEW YORK RADIO	NEW YORK RADIO																					
	NEW YORK RADIO	NEW YORK RADIO																					
Designation of the station calling	GABCD**	SPEEDBIRD ABCD**																					
	SPEEDBIRD ABCD**	AEROFLOT 321**																					



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																
Chapter 5 Reference 5.2.1.7.3.2.2  PANS	<p><b>PANS.</b>— Stations having a requirement to transmit information to all stations likely to intercept should preface such transmission by the general call ALL STATIONS, followed by the identification of the calling station.</p> <p>Note.— No reply is expected to such general calls unless individual stations are subsequently called to acknowledge receipt.</p>	AC91-9, 4.3.	No Difference																		
Chapter 5 Reference 5.2.1.7.3.2.3  Standard	<p>The reply to the above calls shall be in accordance with Table 5-3. The use of the calling aeronautical station's call sign followed by the answering aeronautical station's call sign shall be considered the invitation to proceed with transmission by the station calling.</p> <p><b>Table 5-3 Radiotelephony reply procedure</b> (see 5.2.1.7.3.2.3)</p> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"></td> <td style="width: 50%; text-align: center;">Type a)                      Type b)</td> </tr> <tr> <td style="width: 50%;"></td> <td style="width: 50%; text-align: center;">Type c)</td> </tr> <tr> <td style="width: 50%;">Designation of the station called</td> <td style="width: 50%;">GABCD*</td> </tr> <tr> <td></td> <td>SPEEDBIRD ABCD*</td> </tr> <tr> <td></td> <td>AEROFLOT 321*</td> </tr> <tr> <td style="width: 50%;">Designation of the station calling</td> <td style="width: 50%;">NEW YORK RADIO</td> </tr> <tr> <td></td> <td>NEW YORK RADIO</td> </tr> <tr> <td></td> <td>NEW YORK RADIO</td> </tr> </table> <p>* With the exception of the telephony designators and the type of aircraft, each character in the call sign shall be spoken separately. When individual letters are spelled out, the radiotelephony spelling alphabet prescribed in 5.2.1.3 shall be used. Numbers are to be spoken in accordance with 5.2.1.4.</p>		Type a)                      Type b)		Type c)	Designation of the station called	GABCD*		SPEEDBIRD ABCD*		AEROFLOT 321*	Designation of the station calling	NEW YORK RADIO		NEW YORK RADIO		NEW YORK RADIO	AC91-9, 4.7.	No Difference		
	Type a)                      Type b)																				
	Type c)																				
Designation of the station called	GABCD*																				
	SPEEDBIRD ABCD*																				
	AEROFLOT 321*																				
Designation of the station calling	NEW YORK RADIO																				
	NEW YORK RADIO																				
	NEW YORK RADIO																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.7.3.2.4  PANS	<p><b>PANS.</b>— <i>When a station is called but is uncertain of the identification of the calling station, it should reply by transmitting the following:</i> STATION CALLING...(station called) SAY AGAIN YOUR CALL SIGN</p> <p><i>Note.</i>— <i>The following example illustrates the application of this procedure:</i> (CAIRO station replying) STATION CALLING CAIRO (pause) SAY AGAIN YOUR CALL SIGN</p>	AC91-9, 4.7.5.	No Difference		
Chapter 5 Reference 5.2.1.7.3.2.5  Standard	Communications shall commence with a call and a reply when it is desired to establish contact, except that, when it is certain that the station called will receive the call, the calling station may transmit the message, without waiting for a reply from the station called.	AC91.9, 4.7.	No Difference		
Chapter 5 Reference 5.2.1.7.3.2.6  Standard	<p>Interpilot air-to-air communication shall be established on the air-to-air channel 123.45 MHz by either a directed call to a specific aircraft station or a general call, taking into account conditions pertaining to use of this channel.</p> <p><i>Note.</i>— <i>For conditions on use of air-to-air channels see Annex 10, Volume V, 4.1.3.2.1, also Volume II, 5.2.2.1.1.4.</i></p>	AIPNZ GEN 3.4, 3.3.13.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.7.3.2.6.1  PANS	<b>PANS.</b> — <i>As the aircraft may be guarding more than one frequency, the initial call should include the distinctive channel identification "INTERPILOT".</i> <i>Note.— The following examples illustrate the application of this calling procedure.</i> CLIPPER 123 — SABENA 901 — INTERPILOT — DO YOU READ <i>or</i> ANY AIRCRAFT VICINITY OF 30 NORTH 160 EAST — JAPANAIR 401 — INTERPILOT — OVER	AC91-9.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.2.1.7.3.3.1  Standard	<b>5.2.1.7.3.3 Subsequent radiotelephony communications</b>  Abbreviated radiotelephony call signs, as prescribed in 5.2.1.7.2.2, shall be used only after satisfactory communication has been established and provided that no confusion is likely to arise. An aircraft station shall use its abbreviated call sign only after it has been addressed in this manner by the aeronautical station.	CAR 91.249.	No Difference		
Chapter 5 Reference 5.2.1.7.3.3.2  Standard	After contact has been established, continuous two-way communication shall be permitted without further identification or call until termination of the contact.	AC91-9, 4.7.	No Difference		
Chapter 5 Reference 5.2.1.7.3.3.3  Standard	In order to avoid any possible confusion, when issuing ATC clearances and reading back such clearances, controllers and pilots shall always add the call sign of the aircraft to which the clearance applies.	AC91-9, 4.12.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.7.3.4.1  PANS	5.2.1.7.3.4 <i>Indication of transmitting channel</i>  PANS.— <i>As the aeronautical station operator generally guards more than one frequency, the call should be followed by an indication of the frequency used, unless other suitable means of identifying the frequency are known to exist.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.7.3.4.2  PANS	PANS.— <i>When no confusion is likely to arise, only the first two digits of the High Frequency (in kHz) need be used to identify the transmitting channel.</i>  <i>Note.— The following example illustrates the application of this procedure:</i>  <i>(PAA 325 calling Kingston on 8 871 kHz)</i> KINGSTON CLIPPER THREE TWO FIVE — ON EIGHT EIGHT	AC91-9, 4.3.2.	Less protective or partially implemented or not implemented	Not specified.	Note: standard practice.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																
Chapter 5 Reference 5.2.1.7.3.4.3  PANS	<p><b>PANS.</b>— <i>Except as specified in 5.2.1.7.3.4.4 all six digits of the numerical designator should be used to identify the transmitting channel in VHF radiotelephony communications, except in the case of both the fifth and sixth digits being zeros, in which case only the first four digits should be used.</i></p> <p><i>N1.The following examples illustrate the application of the procedure in 5.2.1.7.3.4.3:</i></p> <table border="0"> <tr> <td><i>Channel</i></td> <td><i>Transmitted as</i></td> </tr> <tr> <td> </td> <td> </td> </tr> <tr> <td><i>118.000</i></td> <td><i>ONE ONE EIGHT DECIMAL ZERO</i></td> </tr> <tr> <td><i>118.005</i></td> <td><i>ONE ONE EIGHT DECIMAL ZERO ZERO FIVE</i></td> </tr> <tr> <td><i>118.010</i></td> <td><i>ONE ONE EIGHT DECIMAL ZERO ONE ZERO</i></td> </tr> <tr> <td><i>118.025</i></td> <td><i>ONE ONE EIGHT DECIMAL ZERO TWO FIVE</i></td> </tr> <tr> <td><i>118.050</i></td> <td><i>ONE ONE EIGHT DECIMAL ZERO FIVE ZERO</i></td> </tr> <tr> <td><i>118.100</i></td> <td><i>ONE ONE EIGHT DECIMAL ONE</i></td> </tr> </table> <p><i>N2.Caution must be exercised with respect to the indication of transmitting channels in VHF radiotelephony communications when all six digits of the numerical designator are used in airspace where communication channels are separated by 25 kHz, because on aircraft installations with a channel separation capability of 25 kHz or more, it is only possible to select the first five digits of the numerical designator on the radio management panel.</i></p> <p><i>N3.The numerical designator corresponds to the channel identification in Annex 10, Volume V, Table 4-1 (bis).</i></p>	<i>Channel</i>	<i>Transmitted as</i>	 	 	<i>118.000</i>	<i>ONE ONE EIGHT DECIMAL ZERO</i>	<i>118.005</i>	<i>ONE ONE EIGHT DECIMAL ZERO ZERO FIVE</i>	<i>118.010</i>	<i>ONE ONE EIGHT DECIMAL ZERO ONE ZERO</i>	<i>118.025</i>	<i>ONE ONE EIGHT DECIMAL ZERO TWO FIVE</i>	<i>118.050</i>	<i>ONE ONE EIGHT DECIMAL ZERO FIVE ZERO</i>	<i>118.100</i>	<i>ONE ONE EIGHT DECIMAL ONE</i>	AC91-9, 4.3.2.	No Difference		
<i>Channel</i>	<i>Transmitted as</i>																				
<i>118.000</i>	<i>ONE ONE EIGHT DECIMAL ZERO</i>																				
<i>118.005</i>	<i>ONE ONE EIGHT DECIMAL ZERO ZERO FIVE</i>																				
<i>118.010</i>	<i>ONE ONE EIGHT DECIMAL ZERO ONE ZERO</i>																				
<i>118.025</i>	<i>ONE ONE EIGHT DECIMAL ZERO TWO FIVE</i>																				
<i>118.050</i>	<i>ONE ONE EIGHT DECIMAL ZERO FIVE ZERO</i>																				
<i>118.100</i>	<i>ONE ONE EIGHT DECIMAL ONE</i>																				



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																																							
Chapter 5  Reference 5.2.1.7.3.4.4  PANS	<p><b>PANS.</b>— <i>In airspace where all VHF voice communications channels are separated by 25 kHz or more and the use of six digits as in 5.2.1.7.3.4.3 is not substantiated by the operational requirement determined by the appropriate authorities, the first five digits of the numerical designator should be used, except in the case of both the fifth and sixth digits being zeros, in which case only the first four digits should be used.</i></p> <p><i>N1.The following examples illustrate the application of the procedure in 5.2.1.7.3.4.4 and the associated settings of the aircraft radio management panel for communication equipment with channel separation capabilities of 25 kHz and 8.33/25 kHz:</i></p> <p style="text-align: center;"><i>Radio management panel setting for</i></p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: left;"><i>Channel</i></td> <td style="text-align: center;"><i>Transmitted as</i></td> <td style="text-align: right;"><i>communication</i></td> </tr> <tr> <td><i>equipment with</i></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>25 kHz (5 digits)</i></td> <td style="text-align: right;"><i>8.33/25 kHz (6 digits)</i></td> </tr> </table> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: left;"><i>118.000</i></td> <td style="text-align: center;"><i>ONE ONE EIGHT DECIMAL ZERO</i></td> <td style="text-align: right;"><i>118.00</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>118.000</i></td> <td></td> </tr> <tr> <td style="text-align: left;"><i>118.025</i></td> <td style="text-align: center;"><i>ONE ONE EIGHT DECIMAL ZERO TWO</i></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>118.02 118.025</i></td> <td></td> </tr> <tr> <td style="text-align: left;"><i>118.050</i></td> <td style="text-align: center;"><i>ONE ONE EIGHT DECIMAL ZERO FIVE</i></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>118.05 118.050</i></td> <td></td> </tr> <tr> <td style="text-align: left;"><i>118.075</i></td> <td style="text-align: center;"><i>ONE ONE EIGHT DECIMAL ZERO SEVEN</i></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>118.07 118.075</i></td> <td></td> </tr> <tr> <td style="text-align: left;"><i>118.100</i></td> <td style="text-align: center;"><i>ONE ONE EIGHT DECIMAL ONE</i></td> <td style="text-align: right;"><i>118.10</i></td> </tr> <tr> <td></td> <td style="text-align: center;"><i>118.100</i></td> <td></td> </tr> </table> <p><i>N2.Caution must be exercised with respect to the indication of transmitting channels in VHF radiotelephony communications when five digits of the numerical designator are used in airspace where aircraft are also operated with channel separation capabilities of 8.33/25 kHz. On aircraft installations with a channel separation capability of 8.33 ,Hz and more, it is possible to select six digits on the radio management panel. It should therefore be ensured that the</i></p>	<i>Channel</i>	<i>Transmitted as</i>	<i>communication</i>	<i>equipment with</i>				<i>25 kHz (5 digits)</i>	<i>8.33/25 kHz (6 digits)</i>	<i>118.000</i>	<i>ONE ONE EIGHT DECIMAL ZERO</i>	<i>118.00</i>		<i>118.000</i>		<i>118.025</i>	<i>ONE ONE EIGHT DECIMAL ZERO TWO</i>			<i>118.02 118.025</i>		<i>118.050</i>	<i>ONE ONE EIGHT DECIMAL ZERO FIVE</i>			<i>118.05 118.050</i>		<i>118.075</i>	<i>ONE ONE EIGHT DECIMAL ZERO SEVEN</i>			<i>118.07 118.075</i>		<i>118.100</i>	<i>ONE ONE EIGHT DECIMAL ONE</i>	<i>118.10</i>		<i>118.100</i>		AC91-9, 4.3.2.	No Difference		
<i>Channel</i>	<i>Transmitted as</i>	<i>communication</i>																																										
<i>equipment with</i>																																												
	<i>25 kHz (5 digits)</i>	<i>8.33/25 kHz (6 digits)</i>																																										
<i>118.000</i>	<i>ONE ONE EIGHT DECIMAL ZERO</i>	<i>118.00</i>																																										
	<i>118.000</i>																																											
<i>118.025</i>	<i>ONE ONE EIGHT DECIMAL ZERO TWO</i>																																											
	<i>118.02 118.025</i>																																											
<i>118.050</i>	<i>ONE ONE EIGHT DECIMAL ZERO FIVE</i>																																											
	<i>118.05 118.050</i>																																											
<i>118.075</i>	<i>ONE ONE EIGHT DECIMAL ZERO SEVEN</i>																																											
	<i>118.07 118.075</i>																																											
<i>118.100</i>	<i>ONE ONE EIGHT DECIMAL ONE</i>	<i>118.10</i>																																										
	<i>118.100</i>																																											



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p><i>fifth and sixth digits are set to 25 kHz channels *see Note 1).</i>  <i>N3. The numerical designator corresponds to the channel identification in Annex 10, Volume V, Table 401 (bis).</i></p>				
<p>Chapter 5 Reference 5.2.1.8.1  PANS</p>	<p><b>5.2.1.8 Test procedures</b>   <b>PANS.</b>— <i>The form of test transmissions should be as follows:</i>  <i>a) the identification of the station being called;</i>  <i>b) the aircraft identification;</i>  <i>c) the words "RADIO CHECK";</i>  <i>d) the frequency being used.</i></p>	<p>AC91-9, 4.15.1.</p>	<p>No Difference</p>		
<p>Chapter 5 Reference 5.2.1.8.2  PANS</p>	<p><b>PANS.</b>— <i>The reply to a test transmission should be as follows:</i>  <i>a) the identification of the aircraft;</i>  <i>b) the identification of the aeronautical station replying;</i>  <i>c) information regarding the readability of the aircraft transmission.</i></p>	<p>AC91-9, 4.15.2.</p>	<p>No Difference</p>		
<p>Chapter 5 Reference 5.2.1.8.3  PANS</p>	<p><b>PANS.</b>— <i>The test transmission and reply thereto should be recorded at the aeronautical station.</i></p>	<p>CAR 171.75.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.8.4  PANS	<p><b>PANS.</b>— <i>When the tests are made, the following readability scale should be used:</i></p> <p style="text-align: center;"><i>Readability Scale</i></p> <ol style="list-style-type: none"> <li>1 <i>Unreadable</i></li> <li>2 <i>Readable now and then</i></li> <li>3 <i>Readable but with difficulty</i></li> <li>4 <i>Readable</i></li> <li>5 <i>Perfectly readable</i></li> </ol>	AC91-9, 4.15.3.	No Difference		
Chapter 5 Reference 5.2.1.9.1  Standard	<p><b>5.2.1.9 Exchange of communications</b></p> <p>Communications shall be concise and unambiguous, using standard phraseology whenever available.</p>	AC91-9 Introduction.	No Difference		
Chapter 5 Reference 5.2.1.9.1.1  Recommendation	<p><b>Recommendation.</b>— <i>Abbreviated procedures should only be used after initial contact has been established and where no confusion is likely to arise.</i></p>	AC91-9, 4.7.2.	No Difference		
Chapter 5 Reference 5.2.1.9.2  Standard	<p><i>Acknowledgement of receipt.</i> The receiving operator shall make certain that the message has been received correctly before acknowledging receipt.</p> <p><i>Note.</i>— <i>Acknowledgement of receipt is not to be confused with acknowledgement of intercept in radiotelephony network operations.</i></p>	AC91-9, 4.7.5.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.9.2.1  Standard	When transmitted by an aircraft station, the acknowledgement of receipt of a message shall comprise the call sign of that aircraft.	AC91-9, 4.7.1.	No Difference		
Chapter 5 Reference 5.2.1.9.2.2  PANS	<p><b>PANS.</b>— <i>An aircraft station should acknowledge receipt of important air traffic control messages or parts thereof by reading them back and terminating the readback by its radio call sign.</i></p> <p><i>N1. Air traffic control clearances, instructions and information requiring readback are specified in PANS-ATM (Doc 4444).</i></p> <p><i>N2. The following example illustrates the application of this procedure:</i></p> <p><i>(ATC clearance by network station to an aircraft)</i></p> <p><i>Station:</i> TWA NINE SIX THREE MADRID</p> <p><i>Aircraft:</i> MADRID TWA NINE SIX THREE</p> <p><i>Station:</i> TWA NINE SIX THREE MADRID — ATC CLEARS TWA NINE SIX THREE TO DESCEND TO NINE THOUSAND FEET</p> <p><i>Aircraft (acknowledging):</i> CLEARED TO DESCEND TO NINE THOUSAND FEET — TWA NINE SIX THREE</p> <p><i>Station (denoting accuracy of readback):</i> MADRID</p>	AC91-9, 4.12.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.9.2.3  Standard	When acknowledgement of receipt is transmitted by an aeronautical station: 1) <i>to an aircraft station:</i> it shall comprise the call sign of the aircraft, followed if considered necessary by the call sign of the aeronautical station; 2) <i>to another aeronautical station:</i> it shall comprise the call sign of the aeronautical station that is acknowledging receipt.	AC91-9.	No Difference		
Chapter 5 Reference 5.2.1.9.2.3.1  PANS	<b>PANS.</b> — <i>An aeronautical station should acknowledge position reports and other flight progress reports by reading back the report and terminating the readback by its call sign, except that the readback procedure may be suspended temporarily whenever it will alleviate congestion on the communication channel.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.1.9.2.4  PANS	<b>PANS.</b> — <i>It is permissible for verification for the receiving station to read back the message as an additional acknowledgement of receipt. In such instances, the station to which the information is read back should acknowledge the correctness of readback by transmitting its call sign.</i>	CAR 171.75; AC 91-9.	No Difference		
Chapter 5 Reference 5.2.1.9.2.5  PANS	<b>PANS.</b> — <i>If both position report and other information — such as weather reports — are received in the same message, the information should be acknowledged with the words such as “WEATHER RECEIVED” after the position report has been read back, except when intercept of the information is required by other network stations. Other messages should be acknowledged, the aeronautical station transmitting its call sign only.</i>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.9.3  Standard	<i>End of conversation.</i> A radiotelephone conversation shall be terminated by the receiving station using its own call sign.	AC91-9.	No Difference		
Chapter 5 Reference 5.2.1.9.4.1  Standard	<i>5.2.1.9.4 Corrections and repetitions</i>  When an error has been made in transmission, the word "CORRECTION" shall be spoken, the last correct group or phrase repeated, and then the correct version transmitted.	AC91-9, 4.7.6.	No Difference		
Chapter 5 Reference 5.2.1.9.4.2  Standard	If a correction can best be made by repeating the entire message, the operator shall use the phrase "CORRECTION, I SAY AGAIN" before transmitting the message a second time.	AC 91-9, 4.7.6.	No Difference		
Chapter 5 Reference 5.2.1.9.4.3  Recommendation	<b>Recommendation.</b> — <i>When an operator transmitting a message considers that reception is likely to be difficult, he should transmit the important elements of the message twice.</i>	AC91-9, 4.7.8.	No Difference		
Chapter 5 Reference 5.2.1.9.4.4  Standard	If the receiving operator is in doubt as to the correctness of the message received, he shall request repetition either in full or in part.	AC91-9, 4.7.5.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.1.9.4.5  Standard	If repetition of an entire message is required, the words "SAY AGAIN" shall be spoken. If repetition of a portion of a message is required, the operator shall state: "SAY AGAIN ALL BEFORE...(first word satisfactorily received)"; or "SAY AGAIN...(word before missing portion) TO...(word after missing portion)"; or "SAY AGAIN ALL AFTER...(last word satisfactorily received)".	AC91-9, 4.7.5.	No Difference		
Chapter 5 Reference 5.2.1.9.4.6  Recommendation	<b>Recommendation.</b> — <i>Specific items should be requested, as appropriate, such as "SAY AGAIN ALTIMETER", "SAY AGAIN WIND".</i>	AC91-9, 4.7.5.	No Difference		
Chapter 5 Reference 5.2.1.9.4.7  Standard	If, in checking the correctness of a readback, an operator notices incorrect items, he shall transmit the words "NEGATIVE I SAY AGAIN" at the conclusion of the readback followed by the correct version of the items concerned.	AC91-9, 4.9.2.	No Difference		
Chapter 5 Reference 5.2.1.9.5  PANS	<i>"Operations normal" reports</i> <b>PANS.</b> — <i>When "operations normal" reports are transmitted by aircraft, they should consist of the prescribed call followed by the words "OPERATIONS NORMAL".</i>	AC91-9.	Less protective or partially implemented or not implemented	Not specified.	Note: standard practice.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.1.1  Standard	5.2.2 Establishment and assurance of communications  5.2.2.1 <i>Communications watch/Hours of service</i>  During flight, aircraft stations shall maintain watch as required by the appropriate Authority and shall not cease watch, except for reasons of safety, without informing the aeronautical station(s) concerned.	CAR 91.245, 91.427; AIPNZ ENR 1.1, 3.1.	No Difference		
Chapter 5 Reference 5.2.2.1.1.1  Standard	Aircraft on long over-water flights, or on flights over designated areas over which the carriage of an emergency locator transmitter (ELT) is required, shall continuously guard the VHF emergency frequency 121.5 MHz, except for those periods when aircraft are carrying out communications on other VHF channels or when airborne equipment limitations or cockpit duties do not permit simultaneous guarding of two channels.	AIPNZ ENR 1.1, 3.1.	No Difference		
Chapter 5 Reference 5.2.2.1.1.2  Standard	Aircraft shall continuously guard the VHF emergency frequency 121.5 MHz in areas or over routes where the possibility of interception of aircraft or other hazardous situations exist, and a requirement has been established by the appropriate authority.	AIPNZ ENR 1.1, 3.1.	No Difference		
Chapter 5 Reference 5.2.2.1.1.3  Recommendation	<b>Recommendation.</b> — <i>Aircraft on flights other than those specified in 5.2.2.1.1.1 and 5.2.2.1.1.2 should guard the emergency frequency 121.5 MHz to the extent possible.</i>	AIPNZ ENR 1.1, 3.1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.1.1.4  Standard	The user of the air-to-air VHF communications channel shall ensure that adequate watch is maintained on designated ATS frequencies, the frequency of the aeronautical emergency channel, and any other mandatory watch frequencies.	AIPNZ ENR 1.1, 3.1.	No Difference		
Chapter 5 Reference 5.2.2.1.2  Standard	Aeronautical stations shall maintain watch as required by the appropriate Authority.	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.1.3  Standard	Aeronautical stations shall maintain a continuous listening watch on VHF emergency channel 121.5 MHz during the hours of service of the units at which it is installed.  <i>Note.— See Annex 10, Volume V, 4.1.3.1.1 for provisions related to the utilization of 121.5 MHz at aeronautical stations.</i>	MATS RAC 7.	No Difference		Facility provided at Auckland, Wellington, Ohakea and Christchurch towers.
Chapter 5 Reference 5.2.2.1.4  Standard	When it is necessary for an aircraft station or aeronautical station to suspend operation for any reason, it shall, if possible, so inform other stations concerned, giving the time at which it is expected that operation will be resumed. When operation is resumed, other stations concerned shall be so informed.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.2.2.1.4.1  Standard	When it is necessary to suspend operation beyond the time specified in the original notice, a revised time of resumption of operation shall, if possible, be transmitted at or near the time first specified.	CARs.	No Difference	Not specified.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.1.5  Recommendation	<b>Recommendation.</b> — <i>When two or more ATS frequencies are being used by a controller, consideration should be given to providing facilities to allow ATS and aircraft transmissions on any of the frequencies to be simultaneously retransmitted on the other frequencies in use thus permitting aircraft stations within range to hear all transmissions to and from the controller.</i>	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.2.2.2.1  PANS	5.2.2.2 Principles of network operation (HF communications)  <b>PANS.</b> — <i>The aeronautical stations of a radiotelephony network should assist each other in accordance with the following network principles, in order to provide the air-ground communication service required of the network by aircraft flying on the air routes for which the network is responsible.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.2.2  PANS	<p><b>PANS.</b>— <i>When the network comprises a large number of stations, network communications for flights on any individual route segment should be provided by selected stations, termed “regular stations” for that segment.</i></p> <p><i>N1.The selection of stations to as regular stations for a particular route segment will, where necessary, be undertaken by regional or local agreement, after consultation, if necessary, between the States responsible for the network.</i></p> <p><i>N2.In principle, the regular stations will be those serving the locations immediately concerned with flights on that route segment, i.e. points of take-off and landing, appropriate flight information centres or area control centres and, in some cases, additional suitably located stations required to complete the communication coverage or for intercept purposes.</i></p> <p><i>N3.In selecting the regular stations, account will be taken of the propagation characteristics of the frequencies used.</i></p>		Not Applicable		
Chapter 5 Reference 5.2.2.2.3  PANS	<p><b>PANS.</b>— <i>In areas or on routes where radio conditions, length of flights or distance between aeronautical stations require additional measures to ensure continuity of the air-ground communication throughout the route segment, the regular stations should share between them a responsibility of primary guard whereby each station will provide the primary guard for that portion of the flight during which the messages from the aircraft can be handled most effectively by that station.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.2.4  PANS	<p><b>PANS.</b>— <i>During its tenure of primary guard, each regular station should, among other things:</i></p> <ul style="list-style-type: none"> <li>a) <i>be responsible for designating suitable primary and secondary frequencies for its communications with the aircraft;</i></li> <li>b) <i>receive all position reports and handle other messages from and to the aircraft essential to the safe conduct of the flight;</i></li> <li>c) <i>be responsible for the action required in case of failure of communications (see 5.2.2.7.2).</i></li> </ul>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.2.5  PANS	<p><b>PANS.</b>— <i>The transfer of primary guard from one station to the next will normally take place at the time of the traversing of flight information region or control area boundaries, this guard being provided at any time, as far as possible, by the station serving the flight information centre or area control centre in whose area the aircraft is flying. However, where communication conditions so demand, a station may be required to retain primary guard beyond such geographical boundaries or release its guard before the aircraft reaches the boundary, if appreciable improvement in air-ground communication can be effected thereby.</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.3.1  Standard	<p><b>5.2.2.3</b> <i>Frequencies to be used</i></p> <p>Aircraft stations shall operate on the appropriate radio frequencies.</p>	CAR 91.225, 91.427.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.3.1.1  Standard	The air-ground control radio station shall designate the frequency(ies) to be used under normal conditions by aircraft stations operating under its control.	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.3.1.2  PANS	<b>PANS.</b> — <i>In network operation, the initial designation of primary and secondary frequencies should be made by the network station with which the aircraft makes pre-flight check or its initial contact after take-off. This station should also ensure that other network stations are advised, as required, of the frequency(ies) designated.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.3.2  Recommendation	<b>Recommendation.</b> — <i>An aeronautical station, when designating frequencies in accordance with 5.2.2.3.1.1 or 5.2.2.3.1.2, should take into account the appropriate propagation data and distance over which communications are required.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.3.3  Recommendation	<b>Recommendation.</b> — <i>If a frequency designated by an aeronautical station proves to be unsuitable, the aircraft station should suggest an alternative frequency.</i>	CARs.	Less protective or partially implemented or not implemented	Not specified.	





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.3.4  PANS	<b>PANS.</b> — <i>When, notwithstanding the provisions of 5.1.1, air-ground frequencies are used for the exchange between network stations of messages essential for coordination and cooperation between the stations, such communication should, so far as possible, be effected over network frequencies not being used at that time for the bulk of the air-ground traffic. In all cases, the communication with aircraft stations should take priority over the inter-ground station communications.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.4.1  Standard	<b>5.2.2.4 Establishment of communications</b>  Aircraft stations shall, if possible, communicate directly with the air-ground control radio station appropriate to the area in which the aircraft are flying. If unable to do so, aircraft stations shall use any relay means available and appropriate to transmit messages to the air-ground control radio station.	CAR 91.223; AC91-9.	Less protective or partially implemented or not implemented	Relay provision not specified.	
Chapter 5 Reference 5.2.2.4.2  PANS	<b>PANS.</b> — <i>When, in network operation, communication between an aircraft station and a regular station has not been established after calls on the primary and secondary frequencies, aid should be rendered by one of the other regular stations for that flight, either by calling the attention of the station first called or, in the case of a call made by an aircraft station, by answering the call and taking the traffic.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.4.2  Standard	When normal communications from an aeronautical station to an aircraft station cannot be established, the aeronautical station shall use any relay means available and appropriate to transmit messages to the aircraft station. If these efforts fail, the originator shall be advised in accordance with procedures prescribed by the appropriate Authority.	AIPNZ ENR 1.15, 4.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.4.3.1  PANS	<b>PANS.</b> — <i>Other stations of the network should render assistance by taking similar action only if attempts to establish communications by the regular stations have proved unsuccessful.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.4.4  PANS	<b>PANS.</b> — <i>The provisions of 5.2.2.4.3 and 5.2.2.4.3.1 should also be applied:</i> a) <i>on request of the air traffic services unit concerned;</i> b) <i>when an expected communication from an aircraft has not been received within a time period such that the occurrence of a communication failure is suspected.</i> <i>Note.— A specific time period may be prescribed by the appropriate ATS Authority.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.5.1  PANS	<b>5.2.2.5 Transfer of HF communications</b>  <b>PANS.</b> — <i>An aircraft station should be advised by the appropriate aeronautical station to transfer from one radio frequency or network to another. In the absence of such advice, the aircraft station should notify the appropriate aeronautical station before such transfer takes place.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.5.2  PANS	<b>PANS.</b> — <i>In the case of transfer from one network to another, the transfer should preferably take place while the aircraft is in communication with a station operating in both networks to ensure continuity of communications. If, however, the change network must take place concurrently with the transfer of communication to another network station, the transfer should be coordinated by the two network stations prior to advising or authorizing the frequency change. The aircraft should also be advised of the primary and secondary frequencies to be used after the transfer.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.2.5.3  Standard	An aircraft station which has transferred communications watch from one radio frequency to another shall, when so required by the appropriate ATS Authority, inform the aeronautical station concerned that communications watch has been established on the new frequency.	AC91-9, 4.8.	No Difference		
Chapter 5 Reference 5.2.2.5.4  PANS	<b>PANS.</b> — <i>When entering a network after take-off, an aircraft station should transmit its take-off time or time over the last check-point, to the appropriate regular station.</i>	AC91-9.	Less protective or partially implemented or not implemented	Not specified.	But - see AIPNZ ENR 1.1, 2.1.2.
Chapter 5 Reference 5.2.2.5.5  PANS	<b>PANS.</b> — <i>When entering a new network, an aircraft station should transmit the time over the last checkpoint, or of its last reported position, to the appropriate regular station.</i>	AC91-9.	Less protective or partially implemented or not implemented	Not specified.	But - see AIPNZ ENR 1.1, 2.1.2.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.5.6  PANS	<b>PANS.</b> — <i>Before leaving the network, an aircraft station should in all cases advise the appropriate regular station of its intention to do so by transmitting one of the following phrases, as appropriate:</i> <i>a) when transferring to a pilot-to-controller channel: Aircraft: CHANGING TO ... (air traffic services unit concerned)</i> <i>b) after landing: Aircraft: LANDED ... (location) ... (time)</i>	AC91-9.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.2.2.6.1  Standard	<b>5.2.2.6 Transfer of VHF communications</b>  An aircraft shall be advised by the appropriate aeronautical station to transfer from one radio frequency to another in accordance with agreed procedures. In the absence of such advice, the aircraft station shall notify the appropriate aeronautical station before such a transfer takes place.	AC91-9, 4.8.	No Difference		
Chapter 5 Reference 5.2.2.6.2  Standard	When establishing initial contact on, or when leaving, a VHF frequency, an aircraft station shall transmit such information as may be prescribed by the appropriate Authority.	AC91-9, 4.8.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.7.1.1  Standard	<p>5.2.2.7 Voice communications failure</p> <p>5.2.2.7.1 Air-ground</p> <p>When an aircraft station fails to establish contact with the appropriate aeronautical station on the designated channel, it shall attempt to establish contact on the previous channel used and, if not successful, on another channel appropriate to the route. If these attempts fail, the aircraft station shall attempt to establish communication with the appropriate aeronautical station, other aeronautical stations or other aircraft using all available means and advise the aeronautical station that contact on the assigned channel could not be established. In addition, an aircraft operating within a network shall monitor the appropriate VHF channel for calls from nearby aircraft.</p>	AIPNZ ENR 1.15, 4.	No Difference		
Chapter 5 Reference 5.2.2.7.1.2  Standard	If the attempts specified under 5.2.2.7.1.1 fail, the aircraft station shall transmit its message twice on the designated channel(s), preceded by the phrase "TRANSMITTING BLIND" and, if necessary, include the addressee(s) for which the message is intended.	AIPNZ ENR 1.15, 4.	No Difference		
Chapter 5 Reference 5.2.2.7.1.2.1  PANS	<b>PANS.</b> — <i>In network operation, a message which is transmitted blind should be transmitted twice on both primary and secondary channels. Before changing channel, the aircraft station should announce the channel to which it is changing.</i>	AC91-9.	No Difference	Not specified.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.7.1.3.1  Standard	<p><b>5.2.2.7.1.3 Receiver failure</b></p> <p>When an aircraft station is unable to establish communication due to receiver failure, it shall transmit reports at the scheduled times, or positions, on the channel in use, preceded by the phrase "TRANSMITTING BLIND DUE TO RECEIVER FAILURE". The aircraft station shall transmit the intended message, following this by a complete repetition. During this procedure, the aircraft shall also advise the time of its next intended transmission.</p>	AIPNZ ENR 1.15, 4.	No Difference		
Chapter 5 Reference 5.2.2.7.1.3.2  Standard	An aircraft which is provided with air traffic control or advisory service shall, in addition to complying with 5.2.2.7.1.3.1, transmit information regarding the intention of the pilot-in-command with respect to the continuation of the flight of the aircraft.	AIPNZ ENR 1.15, 4.	No Difference		
Chapter 5 Reference 5.2.2.7.1.3.3  Standard	<p>When an aircraft is unable to establish communication due to airborne equipment failure it shall, when so equipped, select the appropriate SSR code to indicate radio failure.</p> <p><i>Note.— General rules which are applicable in the event of communications failure are contained in Annex 2 to the Convention.</i></p>	AIPNZ ENR 1.15, 4.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.7.2.1  Standard	5.2.2.7.2 <i>Ground-to-air</i>  When an aeronautical station has been unable to establish contact with an aircraft station after calls on the frequencies on which the aircraft is believed to be listening, it shall: a) request other aeronautical stations to render assistance by calling the aircraft and relaying traffic, if necessary; b) request aircraft on the route to attempt to establish communication with the aircraft and relay traffic, if necessary.	MATS RAC 7 In-flight Emergency Response Checklists (IFERC).	No Difference		
Chapter 5 Reference 5.2.2.7.2.2  Standard	The provisions of 5.2.2.7.2.1 shall also be applied: a) on request of the air traffic services unit concerned; b) when an expected communication from an aircraft has not been received within a time period such that the occurrence of a communication failure is suspected.  <i>Note.— A specific time period may be prescribed by the appropriate ATS Authority.</i>	MATS RAC 7 IFERC.	No Difference		
Chapter 5 Reference 5.2.2.7.2.3  Recommendation	<b>Recommendation.</b> — <i>If the attempts specified in 5.2.2.7.2.1 fail, the aeronautical station should transmit messages addressed to the aircraft, other than messages containing air traffic control clearances, by blind transmission on the frequency(ies) on which the aircraft is believed to be listening.</i>	MATS RAC 7 IFERC.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.2.2.7.2.4  Standard	Blind transmission of air traffic control clearances shall not be made to aircraft, except at the specific request of the originator.	MATS RAC 7 IFERC.	Less protective or partially implemented or not implemented	Not specified.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.2.7.3  Standard	<i>Notification of communications failure.</i> The air-ground control radio station shall notify the appropriate air traffic services unit and the aircraft operating agency, as soon as possible, of any failure in air-ground communication.	CAR 171.75; MATS RAC 7 IFERC.	No Difference		
Chapter 5 Reference 5.2.3.1.1  PANS	<p style="text-align: center;">5.2.3 HF message handling</p> <p>5.2.3.1 General</p> <p><b>PANS.</b>— <i>When operating within a network, an aircraft station should, in principle, whenever communications conditions so permit, transmit its messages to the stations of the network from which they can be most readily delivered to their ultimate destinations. In particular, aircraft reports required by air traffic services should be transmitted to the network station serving the flight information centre or area control centre in whose area the aircraft is flying. Conversely, messages to aircraft in flight should, whenever possible, be transmitted directly to the aircraft by the network station serving the location of the originator.</i></p> <p><i>Note.</i>— <i>Exceptionally, an aircraft may need to communicate with an aeronautical station outside the network appropriate to its particular route segment. This is permissible, provided it can be done without interrupting the continuous watch with the communication network appropriate to the route segment, when such watch is required by the appropriate ATS Authority; and provided it does not cause undue interference with the operation of other aeronautical stations.</i></p>	AC91.9.	Less protective or partially implemented or not implemented	Not specified.	





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.1.2  PANS	<p><b>PANS.</b>— <i>Messages passed from an aircraft to a network station should, whenever possible, be intercepted and acknowledged by other stations of the network, which serve locations where the information is also required.</i></p> <p>N1.<i>Determination of the arrangements for dissemination of air-ground messages without address will be a matter for multilateral or local agreement.</i></p> <p>N2.<i>In principle, the number of stations required to intercept are to be kept to a minimum consistent with the operational requirement.</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.2.1  PANS	<p><b>PANS.</b>— <i>Acknowledgement of intercept should be made immediately after the acknowledgement of receipt by the station to which the message was passed.</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.2.2  PANS	<p><b>PANS.</b>— <i>Acknowledgement of an intercept message should be made by transmitting the radio call sign of the station having intercepted the message, followed by the word ROGER, if desired, and the call sign of the station having transmitted the message.</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.2.3  PANS	<p><b>PANS.</b>— <i>In the absence of acknowledgement of intercept within one minute, the station accepting the message from the aircraft should forward it, normally over the aeronautical fixed service, to the station(s) which have failed to acknowledge intercept.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.1.2.3.1  PANS	<b>PANS.</b> — <i>If, in abnormal circumstances, forwarding is necessary using the air-ground channels, the provisions of 5.2.2.3.4 should be observed.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.2.4  PANS	<b>PANS.</b> — <i>When such forwarding is done over the aeronautical fixed telecommunication network, the messages should be addressed to the network station(s) concerned.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.2.5  PANS	<b>PANS.</b> — <i>The station(s) to which the messages have been forwarded should carry out local distribution of them in the same way as if they had been received directly from the aircraft over the air-ground channel.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.2.6  Standard	The aeronautical station receiving an air-report or a message containing meteorological information transmitted by an aircraft in flight shall forward the message without delay: 1)to the air traffic services unit and meteorological offices associated with the station; 2)to the aircraft operating agency concerned or its representative when that agency has made a specific request to receive such messages.	CAR 171.75.	No Difference		The rule incorporates the Standards by reference.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.1.3  PANS	<b>PANS.</b> — <i>The provisions of 5.2.3.1.2 should also be applied, if practicable, in non-network operation.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.4  Recommendation	<b>Recommendation.</b> — <i>When a message addressed to an aircraft in flight is received by the aeronautical station included in the address, and when that station is not able to establish communication with the aircraft to which the message is addressed, the message should be forwarded to those aeronautical stations on the route which may be able to establish communication with the aircraft.</i>  <i>Note.</i> — <i>This does not preclude the transmission by the forwarding aeronautical station, of the original message to the aircraft addressed, if the forwarding station is later able to communicate with that aircraft.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.4.1  Recommendation	<b>Recommendation.</b> — <i>If the aeronautical station to which the message is addressed is unable to dispose of the message in accordance with 5.2.3.1.4, the station of origin should be advised.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.1.4.2  Standard	The aeronautical station forwarding the message shall amend the address thereof, by substituting for its own location indicator the location indicator of the aeronautical station to which the message is being forwarded.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.3.2.1  PANS	<b>PANS.</b> — <i>If it is not possible to deliver an ATS message to the aircraft within the time specified by ATS, the aeronautical station should notify the originator. Thereafter, it should take no further action with respect to this message unless specifically instructed by ATS.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.2.2  PANS	<b>PANS.</b> — <i>If delivery of an ATS message is uncertain because of inability to secure an acknowledgement, the aeronautical station should assume that the message has not been received by the aircraft and should advise the originator immediately that, although the message has been transmitted, it has not been acknowledged.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.2.2  PANS	<b>PANS.</b> — <i>If delivery of an ATS message is uncertain because of inability to secure an acknowledgement, the aeronautical station should assume that the message has not been received by the aircraft and should advise the originator immediately that, although the message has been transmitted, it has not been acknowledged.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.3.2.3  PANS	<b>PANS.</b> — <i>The aeronautical station, having received the message from ATS, should not delegate to another station the responsibility for delivery of the message to the aircraft. However, in case of communication difficulties, other stations should assist, when requested, in relaying the message to the aircraft. In this case, the station having received the message from ATS should obtain without delay definite assurance that the aircraft has correctly acknowledged the message.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5  Reference 5.2.3.3.1  PANS	<p><b>5.2.3.3 Recording of air-ground communications on teletypewriter</b></p> <p><b>PANS.</b>— <i>When recording on teletypewriter, the following procedure should be used:</i></p> <ul style="list-style-type: none"> <li>a) <i>each line should begin at the left margin;</i></li> <li>b) <i>a new line should be used for each transmission;</i></li> <li>c) <i>each communication should contain some or all of the following items in the order shown;</i> <ul style="list-style-type: none"> <li>1) <i>call sign of the calling station;</i></li> <li>2) <i>text of the message;</i></li> <li>3) <i>call sign of the station called or the receiving station, followed by the appropriate abbreviation to indicate "Received", "Readback", or "No reply heard";</i></li> <li>4) <i>call sign of station(s) acknowledging intercept followed by appropriate abbreviation to indicate "Received";</i></li> <li>5) <i>designation of frequency used;</i></li> <li>6) <i>time in UTC of the communication;</i></li> </ul> </li> <li>d) <i>missing parts of the message text should be indicated by typing the three periods (space . space. space. space) or three letters M (space M space M space M space);</i></li> <li>e) <i>correction of typing errors should be made by keyboard manipulation (space E space E space E space), followed by the correct information. Errors detected after the completion of the entry should be corrected after the last entry, using the abbreviation COR, followed by the correct information.</i></li> </ul>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.1.1  PANS	<p style="text-align: center;"><b>5.2.4</b> SELCAL procedures</p> <p><i>Note.— The procedures contained in 5.2.4 are applicable when SELCAL is used and replace certain of the procedures related to calling contained in 5.2.1.</i></p> <p><i>5.2.4.1 General</i></p> <p><b>PANS.—</b> With the selective calling system known as SELCAL, the voice calling is replaced by the transmission of coded tones to the aircraft over the radiotelephony channels. A single selective call consists of a combination of four pre-selected audio tones whose transmission requires approximately 2 seconds. The tones are generated in the aeronautical station coder and are received by a decoder connected to the audio output of the airborne receiver. Receipt of the assigned tone code (SELCAL code) activates a cockpit call system in the form of light and/or chime signals.</p> <p><i>Note.— Due to the limited number of SELCAL codes, similar code assignments to multiple aircraft may be expected. Therefore, the use of correct radiotelephony (RTF) procedures contained in this chapter is emphasized when establishing communications via SELCAL.</i></p>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.1.2  PANS	<p><b>PANS.—</b> SELCAL should be utilized by suitably equipped stations for ground-to-air selective calling on the en-route HF and VHF radio channels.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.1.3  PANS	<b>PANS.</b> — <i>On aircraft equipped with SELCAL, the pilot is still able to keep a conventional listening watch if required.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.2.1  PANS	<b>5.2.4.2 Notification to aeronautical stations of aircraft SELCAL codes</b>  <b>PANS.</b> — <i>It is the responsibility of the aircraft operating agency and the aircraft to ensure that all aeronautical stations, with which the aircraft would normally communicate during a particular flight, know the SELCAL code associated with its radiotelephony call sign.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.2.2  PANS	<b>PANS.</b> — <i>When practicable, the aircraft operating agency should disseminate to all aeronautical stations concerned, at regular intervals, a list of SELCAL codes assigned to its aircraft or flights.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.2.3  PANS	<b>PANS.</b> — <i>The aircraft should:</i> a) <i>include the SELCAL code in the flight plan submitted to appropriate air traffic services unit; and</i> b) <i>ensure that the HF aeronautical station has the correct SELCAL code information by establishing communications temporarily with the HF aeronautical station while still within VHF coverage.</i>  <i>Note.— Provisions regarding completion of the flight plan are set forth in the PANS-ATM (Doc 4444).</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.3.1.  PANS	5.2.4.3 Pre-flight check  PANS.— The aircraft station should contact the appropriate aeronautical station and request a pre-flight SELCAL check and, if necessary, give its SELCAL code.	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.3.2  PANS	PANS.— When primary and secondary frequencies are assigned, a SELCAL check should normally be made first on the secondary frequency and then on the primary frequency. The aircraft station would then be ready for continued communication on the primary frequency.	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.3.3  PANS	PANS.— Should the pre-flight check reveal that either the ground or airborne SELCAL installation is inoperative, the aircraft should maintain a continuous listening watch on its subsequent flight until SELCAL again becomes available.	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.4.1  PANS	5.2.4.4 Establishment of communications  PANS.— When an aeronautical station initiates a call by SELCAL, the aircraft replies with its radio call sign, followed by the phrase "GO AHEAD".	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.5.1  PANS	5.2.4.5 En-route procedures  PANS.— Aircraft stations should ensure that the appropriate aeronautical station(s) are aware that SELCAL watch is being established or maintained.	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.5.2  PANS	<b>PANS.</b> — <i>When so prescribed on the basis of regional air navigation agreements, calls for scheduled reports from aircraft may be initiated by an aeronautical station by means of SELCAL.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.5.3  PANS	<b>PANS.</b> — <i>Once SELCAL watch has been established by a particular aircraft station, aeronautical stations should employ SELCAL whenever they require to call aircraft.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.5.4  PANS	<b>PANS.</b> — <i>In the event the SELCAL signal remains unanswered after two calls on the primary frequency and two calls on the secondary frequency, the aeronautical station should revert to voice calling.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.5.5  PANS	<b>PANS.</b> — <i>Stations in a network should keep each other immediately advised when malfunctioning occurs in a SELCAL installation on the ground or in the air. Likewise, the aircraft should ensure that the aeronautical stations concerned with its flight are immediately made aware of any malfunctioning of its SELCAL installation, and that voice calling is necessary.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.2.4.5.6  PANS	<b>PANS.</b> — <i>All stations should be advised when the SELCAL installation is again functioning normally.</i>	CAR 171.75.	No Difference		
Chapter 5 Reference 5.2.4.6.1  PANS	<p><b>5.2.4.6 SELCAL code assignment to aircraft</b></p> <p><b>PANS.</b>— <i>In principle, the SELCAL code in the aircraft should be associated with the radiotelephony call sign, i.e. where the flight number (service number) is employed in the radio call sign, the SELCAL code in the aircraft should be listed against the flight number. In all other cases, the SELCAL code in the aircraft should be listed against the aircraft registration.</i></p> <p><i>Note.— The use of aircraft radio call signs, consisting of the airline abbreviation followed by the flight service number, is increasing among aircraft operators throughout the world. The SELCAL equipment in aircraft should, therefore, be of a type which permits a particular code being associated with a particular flight number, i.e. equipment which is capable of adjustment in code combinations. At this stage, however, many aircraft still carry SELCAL equipment of the single code type, and it will not be possible for aircraft with such equipment to satisfy the principle set out above. This should not militate against use of the flight number type of radio call sign by an aircraft so equipped if it wishes to apply this type of call sign, but it is essential when a single code airborne equipment is used in conjunction with a flight number type radio call sign that the ground stations be advised in connection with each flight of the SELCAL code available in the aircraft.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.1.1  Standard	<p><b>5.3 Distress and urgency radiotelephony communication procedures</b></p> <p>5.3.1 General</p> <p><i>Note.— The distress and urgency procedures contained in 5.3 relate to the use of radiotelephony. The provisions of Article S30 and Appendix S13 of the ITU Radio Regulations are generally applicable, except that S30.9 permits other procedures to be employed where special arrangements between governments exist, and are also applicable to radiotelephony communications between aircraft stations and stations in the maritime mobile service.</i></p> <p>Distress and urgency traffic shall comprise all radiotelephony messages relative to the distress and urgency conditions respectively. Distress and urgency conditions are defined as:</p> <ul style="list-style-type: none"> <li>a) <i>Distress</i>: a condition of being threatened by serious and/or imminent danger and of requiring immediate assistance.</li> <li>b) <i>Urgency</i>: a condition concerning the safety of an aircraft or other vehicle, or of some person on board or within sight, but which does not require immediate assistance.</li> </ul>	AIPNZ ENR 1.15.	No Difference		
Chapter 5 Reference 5.3.1.2  Standard	<p>The radiotelephony distress signal MAYDAY and the radiotelephony urgency signal PAN PAN shall be used at the commencement of the first distress and urgency communication respectively.</p>	AIPNZ ENR 1.15.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.1.2.1  Standard	At the commencement of any subsequent communication in distress and urgency traffic, it shall be permissible to use the radiotelephony distress and urgency signals.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.1.3  Standard	The originator of messages addressed to an aircraft in distress or urgency condition shall restrict to the minimum the number and volume and content of such messages as required by the condition.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.1.4  Standard	If no acknowledgement of the distress or urgency message is made by the station addressed by the aircraft, other stations shall render assistance, as prescribed in 5.3.2.2 and 5.3.3.2 respectively. <i>Note.— "Other stations" is intended to refer to any other station which has received the distress or urgency message and has become aware that it has not been acknowledged by the station addressed.</i>	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.1.5  Standard	Distress and urgency traffic shall normally be maintained on the frequency on which such traffic was initiated until it is considered that better assistance can be provided by transferring that traffic to another frequency. <i>Note.— 121.5 MHz or alternative available VHF or HF frequencies may be used as appropriate.</i>	AIPNZ ENR 1.15.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.1.6  Standard	In cases of distress and urgency communications, in general, the transmissions by radiotelephony shall be made slowly and distinctly, each word being clearly pronounced to facilitate transcription.	AIPNZ ENR 1.15, 1.3.1, 2.3.1; AC91-9.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.2.1.1  Standard	5.3.2 Radiotelephony distress communications  <i>5.3.2.1 Action by the aircraft in distress</i>  In addition to being preceded by the radiotelephony distress signal MAYDAY ( <i>see</i> 5.3.1.2), preferably spoken three times, the distress message to be sent by an aircraft in distress shall: <ul style="list-style-type: none"> <li>a) be on the air-ground frequency in use at the time;</li> <li>b) consist of as many as possible of the following elements spoken distinctly and, if possible, in the following order:                             <ul style="list-style-type: none"> <li>1) name of the station addressed (time and circumstances permitting);</li> <li>2) the identification of the aircraft;</li> <li>3) the nature of the distress condition;</li> <li>4) intention of the person in command;</li> <li>5) present position, level (i.e. flight level, altitude, etc., as appropriate) and heading.</li> </ul> </li> </ul> <i>N1. The foregoing provisions may be supplemented by the following measures:</i> <ul style="list-style-type: none"> <li>c) the distress message of an aircraft in distress being made on the emergency frequency 121.5 MHz or another aeronautical mobile frequency, if considered necessary or desirable. Not all aeronautical stations maintain a continuous guard on the emergency frequency;</li> <li>d) the distress message of an aircraft in distress being broadcast, if time and circumstances make this course preferable;</li> <li>e) the aircraft transmitting on the maritime mobile service radiotelephony calling frequencies;</li> <li>f) the aircraft using any means at its disposal to attract attention and make known its conditions (including the activation of the appropriate SSR mode and code);</li> <li>g) any station taking any means at its disposal to assist</li> </ul>	AIPNZ ENR 1.15, 1.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	<p>an aircraft in distress;</p> <p>h) any variation on the elements listed under 5.3.2.1.1 b), when the transmitting station is not itself in distress, provided that such circumstance is clearly stated in the distress message.</p> <p><i>N2. The station addressed will normally be that station communicating with the aircraft or in whose area of responsibility the aircraft is operating.</i></p>				
<p>Chapter 5 Reference 5.3.2.2.1  Standard</p>	<p><i>5.3.2.2 Action by the station addressed or first station acknowledging the distress message</i></p> <p>The station addressed by aircraft in distress, or first station acknowledging the distress message, shall:</p> <p>a) immediately acknowledge the distress message;</p> <p>b) take control of the communications or specifically and clearly transfer that responsibility, advising the aircraft if a transfer is made;</p> <p>c) take immediate action to ensure that all necessary information is made available, as soon as possible, to:</p> <p>1) the ATS unit concerned;</p> <p>2) the aircraft operating agency concerned, or its representative, in accordance with pre-established arrangements;</p> <p><i>Note.— The requirement to inform the aircraft operating agency concerned does not have priority over any other action which involves the safety of the flight in distress, or of any other flight in the area, or which might affect the progress of expected flights in the area.</i></p> <p>d) warn other stations, as appropriate, in order to prevent the transfer of traffic to the frequency of the distress communication.</p>	<p>MATS RAC 7.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.2.3.1  Standard	<p><i>5.3.2.3 Imposition of silence</i></p> <p>The station in distress, or the station in control of distress traffic, shall be permitted to impose silence, either on all stations of the mobile service in the area or on any station which interferes with the distress traffic. It shall address these instructions “to all stations”, or to one station only, according to circumstances. In either case, it shall use: STOP TRANSMITTING; the radiotelephony distress signal MAYDAY.</p>	MATS RAC 7 In-flight Emergency Response Checklists (IFERC).	No Difference		
Chapter 5 Reference 5.3.2.3.2  Standard	The use of the signals specified in 5.3.2.3.1 shall be reserved for the aircraft station in distress and for the station controlling the distress traffic.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.2.4.1  Standard	<p><i>5.3.2.4 Action by all other stations</i></p> <p>The distress communications have absolute priority over all other communications, and a station aware of them shall not transmit on the frequency concerned, unless:</p> <ul style="list-style-type: none"> <li>a) the distress is cancelled or the distress traffic is terminated;</li> <li>b) all distress traffic has been transferred to other frequencies;</li> <li>c) the station controlling communications gives permission;</li> <li>d) it has itself to render assistance.</li> </ul>	CARs.	Less protective or partially implemented or not implemented	Not specified.	





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.2.4.2  Standard	Any station which has knowledge of distress traffic, and which cannot itself assist the station in distress, shall nevertheless continue listening to such traffic until it is evident that assistance is being provided.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.2.5.1  Standard	<i>5.3.2.5 Termination of distress communications and of silence</i>  When an aircraft is no longer in distress, it shall transmit a message cancelling the distress condition.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.2.5.2  Standard	When the station which has controlled the distress communication traffic becomes aware that the distress condition is ended, it shall take immediate action to ensure that this information is made available, as soon as possible, to:  1)the ATS unit concerned; 2)the aircraft operating agency concerned, or its representative, in accordance with pre-established arrangements.	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.2.5.3  Standard	The distress communication and silence conditions shall be terminated by transmitting a message, including the words "DISTRESS TRAFFIC ENDED", on the frequency or frequencies being used for the distress traffic. This message shall be originated only by the station controlling the communications when, after the reception of the message prescribed in 5.3.2.5.1, it is authorized to do so by the appropriate authority.	CARs.	Less protective or partially implemented or not implemented	Not specified.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 5 Reference 5.3.3.1.1  Standard</p>	<p>5.3.3 Radiotelephony urgency communications</p> <p><i>5.3.3.1 Action by the aircraft reporting an urgency condition except as indicated in 5.3.3.4</i></p> <p>In addition to being preceded by the radiotelephony urgency signal PAN PAN (<i>see</i> 5.3.1.2), preferably spoken three times and each word of the group pronounced as the French word “panne”, the urgency message to be sent by an aircraft reporting an urgency condition shall:</p> <ol style="list-style-type: none"> <li>a) be on the air-ground frequency in use at the time;</li> <li>b) consist of as many as required of the following elements spoken distinctly and, if possible, in the following order: <ol style="list-style-type: none"> <li>1) the name of the station addressed;</li> <li>2) the identification of the aircraft;</li> <li>3) the nature of the urgency condition;</li> <li>4) the intention of the person in command;</li> <li>5) present position, level (i.e. flight level, altitude, etc., as appropriate) and heading;</li> <li>6) any other useful information.</li> </ol> </li> </ol> <p><i>N1.The foregoing provisions of 5.3.3.1.1 are not intended to prevent an aircraft broadcasting an urgency message, if time and circumstances make this course preferable.</i></p> <p><i>N2.The station addressed will normally be that station communicating with the aircraft or in whose area of responsibility the aircraft is operating.</i></p>	<p>AIPNZ ENR 1.15, 2.</p>	<p>No Difference</p>		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.3.2.1  Standard	<p><i>5.3.3.2 Action by the station addressed or first station acknowledging the urgency message</i></p> <p>The station addressed by an aircraft reporting an urgency condition, or first station acknowledging the urgency message, shall:</p> <ul style="list-style-type: none"> <li>a) acknowledge the urgency message;</li> <li>b) take immediate action to ensure that all necessary information is made available, as soon as possible, to: <ul style="list-style-type: none"> <li>1) the ATS unit concerned;</li> <li>2) the aircraft operating agency concerned, or its representative, in accordance with pre-established arrangements;</li> </ul> </li> </ul> <p><i>Note.— The requirement to inform the aircraft operating agency concerned does not have priority over any other action which involves the safety of the flight in distress, or of any other flight in the area, or which might affect the progress of expected flights in the area.</i></p> <ul style="list-style-type: none"> <li>c) if necessary, exercise control of communications.</li> </ul>	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.3.3.1  Standard	<p><i>5.3.3.3 Action by all other stations</i></p> <p>The urgency communications have priority over all other communications, except distress, and all stations shall take care not to interfere with the transmission of urgency traffic.</p>	CARs.	Less protective or partially implemented or not implemented	Not specified.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.3.3.4.1  Standard	<p>5.3.3.4 <i>Action by an aircraft used for medical transports</i></p> <p>The use of the signal described in 5.3.3.4.2 shall indicate that the message which follows concerns a protected medical transport pursuant to the 1949 Geneva Conventions and Additional Protocols.</p>	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.3.4.2  Standard	<p>For the purpose of announcing and identifying aircraft used for medical transports, a transmission of the radiotelephony urgency signal PAN PAN, preferably spoken three times, and each word of the group pronounced as the French word “panne”, shall be followed by the radiotelephony signal for medical transports MAY-DEE-CAL, pronounced as in the French “médical”. The use of the signals described above indicates that the message which follows concerns a protected medical transport. The message shall convey the following data:</p> <ul style="list-style-type: none"> <li>a) the call sign or other recognized means of identification of the medical transports;</li> <li>b) position of the medical transports;</li> <li>c) number and type of medical transports;</li> <li>d) intended route;</li> <li>e) estimated time en route and of departure and arrival, as appropriate; and</li> <li>f) any other information such as flight altitude, radio frequencies guarded, languages used, and secondary surveillance radar modes and codes.</li> </ul>	CARs.	Less protective or partially implemented or not implemented	Not specified.	
Chapter 5 Reference 5.3.3.5.1  Standard	<p>5.3.3.5 <i>Action by the station addressed or by other stations receiving a medical transports message</i></p> <p>The provisions of 5.3.3.2 and 5.3.3.3 shall apply as appropriate to stations receiving a medical transports message.</p>	CARs.	Less protective or partially implemented or not implemented	Not specified.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 5 Reference 5.4  Standard	<p><b>Communications related to acts of unlawful interference</b></p> <p>The station addressed by an aircraft being subjected to an act of unlawful interference, or first station acknowledging a call from such aircraft, shall render all possible assistance, including notification of appropriate ATS units as well as any other station, agency or person in a position to facilitate the flight.</p>	AIPNZ ENR 1.6, 3.4.15.	No Difference		
Chapter 6 Reference 6.1.1  Standard	<p><b>CHAPTER 6. AERONAUTICAL RADIO NAVIGATION SERVICE</b></p> <p><b>6.1 General</b></p> <p>The aeronautical radio navigation service shall comprise all types and systems of radio navigation aids in the international aeronautical service.</p>	AIPNZ GEN 3.7.	No Difference		
Chapter 6 Reference 6.1.2  Standard	<p>An aeronautical radio navigation aid which is not in continuous operation shall, if practicable, be put into operation on receipt of a request from an aircraft, any controlling authority on the ground, or an authorized representative of an aircraft operating agency.</p>	AIPNZ GEN 3.7.	No Difference		Generally this applies only to ILS installations, which operate as required during published hours of service. The exception is the Chatham Islands NDB, which requires 24 hours prior notice for activation.
Chapter 6 Reference 6.1.2.1  Recommendation	<p><b>Recommendation.</b>— <i>Requests from aircraft should be made to the aeronautical station concerned on the air-ground frequency normally in use.</i></p>	AIPNZ GEN 3.7.	No Difference		Although not specifically stated, this would be normal procedure.



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.1.3  Standard	Arrangements shall be made for the local aeronautical information service unit to receive without delay essential information about changes in the operational status of non-visual aids as required for pre-flight briefing and dissemination in accordance with the provisions of Annex 15.	CAR 171.19, 171.65.	No Difference		
Chapter 6 Reference 6.2.1  Recommendation	<p style="text-align: center;"><b>6.2 Direction finding</b> <i>Introductory Notes</i></p> <p>1) <i>Direction-finding stations work either singly or in groups of two or more stations under the direction of a main direction-finding station.</i></p> <p>2) <i>A direction-finding station working alone can only determine the direction of an aircraft in relation to itself.</i></p> <p><b>Recommendation.</b>— <i>A direction-finding station working alone should give the following, as requested:</i></p> <p>3) <i>true bearing of the aircraft, using the appropriate phrase;</i></p> <p>4) <i>true heading to be steered by the aircraft, with no wind, to head for the direction-finding station using the appropriate phrase;</i></p> <p>5) <i>magnetic bearing of the aircraft, using the appropriate phrase;</i></p> <p>6) <i>magnetic heading to be steered by the aircraft with no wind to make for the station, using the appropriate phrase.</i></p>	AIPNZ GEN 3.4: MATS RAC 4.	Different in character or other means of compliance	VHF Direction-Finding (VDF) is available at selected control towers. Controllers may use VDF to assist in sighting aircraft, or in an emergency on request to provide navigational assistance.	



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.2  Recommendation	<b>Recommendation.</b> — <i>When direction-finding stations work as a network to determine the position of an aircraft, the bearings taken by each station should be sent immediately to the station controlling the direction-finding network to enable the position of the aircraft to be determined.</i>		Not Applicable		
Chapter 6 Reference 6.2.2.1  Recommendation	<b>Recommendation.</b> — <i>The station controlling the network should, on request, give the aircraft its position in one of the following ways:</i> 1) <i>position in relation to a point of reference or in latitude and longitude, using the appropriate phrase;</i> 2) <i>true bearing of the aircraft in relation to the direction-finding station or other specified point, using the appropriate phrase, and its distance from the direction-finding station or point, using the appropriate phrase;</i> 3) <i>magnetic heading to steer with no wind, to make for the direction-finding station or other specified point using the appropriate phrase, and its distance from the direction-finding station or point, using the appropriate phrase.</i>		Not Applicable		
Chapter 6 Reference 6.2.3  Standard	Aircraft stations shall normally make requests for bearings, courses or positions, to the aeronautical station responsible, or to the station controlling the direction-finding network.		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.4  Standard	To request a bearing, heading or position, the aircraft station shall call the aeronautical station or the direction-finding control station on the listening frequency. The aircraft shall then specify the type of service that is desired by the use of the appropriate phrase.		Not Applicable		
Chapter 6 Reference 6.2.5  Standard	As soon as the direction-finding station or group of stations is ready, the station originally called by the aircraft station shall where necessary request transmission for direction-finding service and, if necessary, indicate the frequency to be used by the aircraft station, the number of times the transmission should be repeated, the duration of the transmission required or any special transmission requirement.		Not Applicable		
Chapter 6 Reference 6.2.5.1  Standard	In radiotelephony, an aircraft station which requests a bearing shall end the transmission by repeating its call sign. If the transmission has been too short for the direction-finding station to obtain a bearing, the aircraft shall give a longer transmission for two periods of approximately ten seconds, or alternatively provide such other signals as may be requested by the direction-finding station.  <i>Note.— Certain types of VHF/DF stations require the provision of a modulated signal (voice transmission) in order to take a bearing.</i>		Not Applicable		
Chapter 6 Reference 6.2.6  Standard	When a direction-finding station is not satisfied with its observation, it shall request the aircraft station to repeat the transmission.		Not Applicable		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.7  Standard	When a heading or bearing has been requested, the direction-finding station shall advise the aircraft station in the following form: 1)the appropriate phrase; 2)bearing or heading in degrees in relation to the direction-finding station, sent as three figures; 3)class of bearing; 4)time of observation, if necessary.		Not Applicable		
Chapter 6 Reference 6.2.8  Standard	When a position has been requested, the direction-finding control station, after plotting all simultaneous observations, shall determine the observed position of the aircraft and shall advise the aircraft station in the following form: 1)the appropriate phrase; 2)the position; 3)class of position; 4)time of observation.		Not Applicable		
Chapter 6 Reference 6.2.9  Standard	As soon as the aircraft station has received the bearing, heading or position, it shall repeat back the message for confirmation or correction.		Not Applicable		
Chapter 6 Reference 6.2.10  Standard	When positions are given by bearing or heading and distance from a known point other than the station making the report, the reference point shall be an aerodrome, prominent town or geographic feature. An aerodrome shall be given in preference to other places. When a large city or town is used as a reference place, the bearing or heading, and the distance given shall be measured from its centre.		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 6 Reference 6.2.11  Standard	When the position is expressed in latitude and longitude, groups of figures for degrees and minutes shall be used followed by the letter N or S for latitude and the letter E or W for longitude, respectively. In radiotelephony the words NORTH, SOUTH, EAST or WEST shall be used.		Not Applicable		
Chapter 6 Reference 6.2.12  Standard	According to the estimate by the direction-finding station of the accuracy of the observations, bearings and positions shall be classified as follows: <i>Bearings:</i> Class A — accurate within plus or minus 2 degrees; Class B — accurate within plus or minus 5 degrees; Class C — accurate within plus or minus 10 degrees; Class D — accuracy less than Class C. <i>Positions:</i> Class A — accurate within 9.3 km (5 NM); Class B — accurate within 37 km (20 NM); Class C — accurate within 92 km (50 NM); Class D — accuracy less than Class C.		Not Applicable		
Chapter 6 Reference 6.2.13  Standard	Direction-finding stations shall have authority to refuse to give bearings, heading or positions when conditions are unsatisfactory or when bearings do not fall within the calibrated limits of the station, stating the reason at the time of refusal.		Not Applicable		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.1.1  Standard	<p align="center"><b>CHAPTER 7. AERONAUTICAL BROADCASTING SERVICE</b></p> <p align="center"><b>7.1 General</b></p> <p align="center">Broadcast material</p> <p>The text of broadcast material shall be prepared by the originator in the form desired for transmission.</p>	CAR 171.75.	No Difference		The rule incorporates the Standards by reference. See AIPNZ GEN 3.4, Broadcasting Services.
Chapter 7 Reference 7.1.2.1  Standard	<p align="center"><b>7.1.2</b> Frequencies and schedules</p> <p>Broadcasts shall be made on specified frequencies and at specified times.</p>	CAR 171.75.	No Difference		
Chapter 7 Reference 7.1.2.2  Standard	<p>Schedules and frequencies of all broadcasts shall be publicized in appropriate documents. Any change in frequencies or times shall be publicized by NOTAM at least two weeks in advance of the change.* Additionally, any such change shall, if practicable, be announced on all regular broadcasts for 48 hours preceding the change and shall be transmitted once at the beginning and once at the end of each broadcast.</p> <p><i>*Note.— This does not prevent an emergency change of frequency when required in circumstances which do not permit the promulgation of a NOTAM at least two weeks in advance of the change.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.1.2.3  Standard	Scheduled broadcasts (other than sequential collective type broadcasts), shall be started at the scheduled time by the general call. If a broadcast must be delayed, a short notice shall be transmitted at the scheduled time advising recipients to "stand by" and stating the approximate number of minutes of delay.	CAR 171.75.	No Difference		
Chapter 7 Reference 7.1.2.3.1  Standard	After definite advice has been given to stand by for a certain period, the broadcast shall not be started until the end of the standby period.	CAR 171.75.	No Difference		
Chapter 7 Reference 7.1.2.4  Standard	Where broadcasts are conducted on a time-allotment basis, transmission shall be terminated by each station promptly at the end of the allotted time period whether or not transmission of all material has been completed.	CAR 171.75.	No Difference		
Chapter 7 Reference 7.1.2.4.1  Standard	In sequential collective type broadcasts each station shall be ready to commence its broadcasts at the designated time. If for any reason a station does not commence its broadcast at the designated time, the station immediately following in sequence shall wait and then commence its broadcast at its own designated time.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 7 Reference 7.1.3  Standard	<p style="text-align: center;">Interruption of service</p> <p>In the event of interruption of service at the station responsible for a broadcast, the broadcast shall, if possible, be made by another station until normal service is resumed. If this is not possible, and the broadcast is of the type intended for interception by fixed stations, the stations which are required to copy the broadcasts shall continue to listen on the specified frequencies until normal service is resumed.</p>	CAR 171.75.	No Difference		
Chapter 7 Reference 7.2.1.1  Standard	<p style="text-align: center;"><b>7.2 Radiotelephone broadcast procedures</b></p> <p style="text-align: center;">7.2.1 Broadcast technique</p> <p>Transmissions by radiotelephone shall be as natural, short and concise as practicable consistent with clarity.</p>	CAR 171.75.	No Difference		
Chapter 7 Reference 7.2.1.2  Standard	Rate of speech on radiotelephone broadcasts shall not exceed 100 words per minute.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 7 Reference 7.2.2  Standard	<p>Preamble of the general call</p> <p>The preamble of each radiotelephone broadcast shall consist of the general call, station name, and optionally the time of broadcast (UTC).</p> <p><i>Note.— The following example illustrates the application of this procedure:</i></p> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;"><i>(general call)</i></td> <td><i>ALL STATIONS</i></td> </tr> <tr> <td><i>(the words THIS IS)</i></td> <td><i>THIS IS</i></td> </tr> <tr> <td><i>(station name)</i></td> <td><i>NEW YORK RADIO</i></td> </tr> <tr> <td><i>(time of broadcast)</i></td> <td><i>TIME, ZERO ZERO</i></td> </tr> <tr> <td></td> <td><i>FOUR FIVE</i></td> </tr> </table>	<i>(general call)</i>	<i>ALL STATIONS</i>	<i>(the words THIS IS)</i>	<i>THIS IS</i>	<i>(station name)</i>	<i>NEW YORK RADIO</i>	<i>(time of broadcast)</i>	<i>TIME, ZERO ZERO</i>		<i>FOUR FIVE</i>	CAR 171.75.	No Difference		
<i>(general call)</i>	<i>ALL STATIONS</i>														
<i>(the words THIS IS)</i>	<i>THIS IS</i>														
<i>(station name)</i>	<i>NEW YORK RADIO</i>														
<i>(time of broadcast)</i>	<i>TIME, ZERO ZERO</i>														
	<i>FOUR FIVE</i>														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
<p>Chapter 8 Reference 8.1.1.1</p> <p>Standard</p>	<p style="text-align: center;"><b>CHAPTER 8. AERONAUTICAL MOBILE SERVICE — DATA LINK COMMUNICATIONS</b></p> <p style="text-align: center;"><b>8.1 General</b></p> <p><i>N1. While the provisions of Chapter 8 are based primarily on the use of controller-pilot data link communications (CPDLC), the provisions of 8.1 would apply to other data link applications, where applicable, including Data link—flight information services (e.g. D-ATIS, D-VOLMET, etc.).</i></p> <p><i>N2. For the purposes of these provisions the communication procedures applicable to the aeronautical mobile service, as appropriate, also apply to the aeronautical mobile satellite service.</i></p> <p style="text-align: center;">8.1.1 Composition of data link messages</p> <p>The text of messages shall be composed in standard message format (e.g. CPDLC message set), in plain language or in abbreviations and codes, as prescribed in 3.7. Plain language shall be avoided when the length of the text can be reduced by using appropriate abbreviations and codes. Non-essential words and phrases, such as expressions of politeness, shall not be used.</p>	<p>CAR 171.75.</p>	<p>No Difference</p>		<p>The rule incorporates the Standards by reference.</p>



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.1.1.2  Standard	<p>The following characters are allowed in the composition of messages:</p> <p><i>Letters:</i>                    ABCDEFGHIJKLMNOPQRSTUVWXYZ WXYZ (upper case only)</p> <p><i>Figures:</i>                1 2 3 4 5 6 7 8 9 0</p> <p><i>Other signs:</i>        - (hyphen)                           ? (question mark)                           : (colon)                           ( (open bracket)                           ) (close bracket)                           . (full stop, period, or decimal                           point)                           , (comma)                           ' (apostrophe)                           = (double hyphen or equal sign)</p> <p>                          / (oblique)                           + (plus sign)</p> <p>                          and the space character.                           Characters other than those listed above shall not be                           used in messages.</p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.1.1.3  Standard	<p>Roman numerals shall not be employed. If the originator of a message wishes the addressee to be informed that Roman figures are intended, the Arabic figure or figures shall be written and preceded by the word ROMAN.</p>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.1.2.1  Standard	8.1.2 Display of data link messages  Ground and airborne systems shall allow for messages to be appropriately displayed, printed when required, and stored in a manner that permits timely and convenient retrieval should such action be necessary.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.1.2.2  Standard	Whenever textual presentation is required, the English language shall be displayed as a minimum.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.1  Standard	<b>8.2 CPDLC procedures</b> <i>Note.— The CPDLC message set referred to in this section can be found in the PANS-ATM, Appendix 5.</i>  In all communications the highest standard of discipline shall be observed at all times.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.1.1  Recommendation	<b>Recommendation.—</b> <i>Consequences of human performance, which could affect the accurate reception and comprehension of messages, should be taken into consideration when composing a message.</i> <i>Note.— Guidance material on human performance can be found in the Human Factors Training Manual (Doc 9683) and Human Factors Guidelines for Air Traffic Management (ATM) Systems (Doc 9758).</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.2  Standard	Ground and airborne systems shall provide controllers and pilots with the capability to review and validate any operational messages they send.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.3  Standard	Ground and airborne systems shall provide controllers and pilots with the capability to review, validate and when applicable, acknowledge any operational messages they receive.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.4  Standard	The controller shall be provided with the capability to respond to messages, including emergencies, to issue clearances, instructions and advisories, and to request and provide information, as appropriate.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.5  Standard	The pilot shall be provided with the capability to respond to messages, to request clearances and information, to report information, and to declare or cancel an emergency.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.6  Standard	The pilot and the controller shall be provided with the capability to exchange messages which do not conform to defined formats (i.e. free text messages).	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.7  Standard	Unless specified by the appropriate ATS authority, voice read-back of CPDLC messages shall not be required.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.8.1  Standard	8.2.8 Establishment of CPDLC  The controller and the pilot shall be informed when CPDLC has been successfully established.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.8.2  PANS	<b>PANS.</b> — <i>CPDLC shall be established in sufficient time to ensure that the aircraft is communicating with the appropriate ATC unit.</i>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.8.3  Standard	The controller and pilot shall be informed when CPDLC is available for operational use, at initial establishment, as well as on resumption of CPDLC after a failure.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.8.4  Standard	The pilot shall be able to identify the air traffic control unit providing the air traffic control service at any time while the service is being provided.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.8.5  Standard	When the airborne system detects that CPDLC is available for operational use, it shall send the CPDLC downlink message element CURRENT DATA AUTHORITY.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.8.6.1  PANS	8.2.8.6 Airborne-initiated CPDLC  PANS.— When an ATC unit receives an unexpected request for CPDLC from an aircraft, the circumstances leading to request shall be obtained from the aircraft to determine further action.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.8.6.2  PANS	PANS.— When the ATC unit rejects a request for CPDLC, it shall provide the pilot with the reason for the rejection using an appropriate CPDLC message.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.8.7.1  Standard	8.2.8.7 ATC unit-initiated CPDLC  An ATC unit shall only establish CPDLC with an aircraft if the aircraft has no CPDLC link established, or when authorized by the ATC unit currently having CPDLC established with the aircraft.	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.8.7.2  Standard	When a request for CPDLC is rejected by an aircraft, the reason for the rejection shall be provided using CPDLC downlink message element NOT CURRENT DATA AUTHORITY or message element NOT AUTHORIZED NEXT DATA AUTHORITY, as appropriate. Local procedures shall dictate whether the reason for rejection is presented to the controller. No other reasons for airborne rejection of ATC unit-initiation of CPDLC shall be permitted.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.1  Standard	8.2.9 Exchange of operational CPDLC messages  Controllers and pilots shall construct CPDLC messages using the defined message set, a free text message or a combination of both.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.1.1  PANS	<b>PANS.</b> — <i>When CPDLC is being used, and the intent of the message is included in the CPDLC message set contained in the PANS-ATM, Appendix 5, the associated message shall be used.</i>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.1.2  PANS	<b>PANS.</b> — <i>Except as provided by 8.2.1.2.1, when a controller or pilot communicates via CPDLC, the response should be via CPDLC. When a controller or pilot communicates via voice, the response should be via voice.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9.1.3  PANS	<p><b>PANS.</b>— <i>Whenever a correction to a message sent via CPDLC is deemed necessary or the contents of a message needs to be clarified, the controller or pilot shall use the most appropriate means available for issuing the correct details or for providing clarification.</i></p> <p><i>Note.</i>— <i>The following procedures may be applied by the controller, in terms of correcting clearances, instructions or information, or by a pilot, in terms of correcting a reply to an uplink message or correcting previously advised requests or information.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.1.3.1  PANS	<p><b>PANS.</b>— <i>When voice communications are used to correct a CPDLC message for which no operational response has yet been received, the controller's or pilot's transmission shall be prefaced by the phrase: "DISREGARD CPDLC (message type) MESSAGE, BREAK" — followed by the correct clearance, instruction, information or request.</i></p> <p><i>Note.</i>— <i>It is possible that, at the time the voice communicated clarification is transmitted, the CPDLC message being referred to has not yet reached the recipient , or has reached the recipient but has not been acted upon, or has reached the recipient and has been acted upon.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.1.3.2  PANS	<p><b>PANS.</b>— <i>When referring to and identifying the CPDLC message to be disregarded, caution should be exercised in its phrasing so as to avoid any ambiguity with the issuance of the accompanying corrected clearance, instruction, information or request.</i></p> <p><i>Note.</i>— <i>For example, if SAS445, maintaining FL290, had been instructed via CPDLC to climb to FL350, and the controller needs to correct the clearance utilizing voice communications, the following phrase might be used:</i> SAS445 DISREGARD CPDLC CLIMB CLEARANCE MESSAGE, BREAK, CLIMB TO FL310.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9.1.3.3  PANS	<b>PANS.</b> — <i>If a CPDLC message that requires an operational response is subsequently negotiated via voice, an appropriate CPDLC message closure response shall be sent to ensure proper synchronization of the CPDLC dialogue. This could be achieved either by explicitly instructing the recipient of the message via voice to close the dialogue or by allowing the system to automatically close the dialogue.</i>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.2  Standard	The composition of a CPDLC message shall not exceed five message elements, only two of which may contain the route clearance variable.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.2.1  PANS	<b>PANS.</b> — <i>The use of long messages or messages with multiple clearance elements, multiple clearance request elements or messages with a combination of clearances and information should be avoided where possible.</i>  <i>Note.</i> — <i>Guidance material on the development of local operating procedures and CPDLC good operating technique can be found in the Human Factors Guidelines for Air Traffic Management (ATM) Systems (Doc 9758).</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference												
Chapter 8 Reference 8.2.9.3  Standard	<p>CPDLC ground systems and airborne systems shall be capable of using the CPDLC message urgency and alert attributes to alter presentations in order to draw attention to higher priority messages.</p> <p><i>Note.— Message attributes dictate certain message handling requirements for the CPDLC user receiving a message. Each CPDLC message has three attributes: urgency, alert and response attributes. When a message contains multiple message elements, the highest precedence message element attribute type becomes the attribute type for the entire message.</i></p>	CAR 171.75.	No Difference														
Chapter 8 Reference 8.2.9.3.1  Standard	<p>The urgency attribute shall delineate the queuing requirements for received messages that are displayed to the end-user. Urgency types are presented in Table 8-1.</p> <p><b>Table 8-1. Urgency Attribute (Uplink and Downlink)</b></p> <table border="0" data-bbox="373 857 821 1047"> <thead> <tr> <th style="text-align: left;"><i>Type</i></th> <th style="text-align: left;"><i>Description</i></th> </tr> <tr> <th></th> <th style="text-align: left;"><i>Precedence</i></th> </tr> </thead> <tbody> <tr> <td>D</td> <td>Distress 1</td> </tr> <tr> <td>U</td> <td>Urgent 2</td> </tr> <tr> <td>N</td> <td>Normal 3</td> </tr> <tr> <td>L</td> <td>Low 4</td> </tr> </tbody> </table>	<i>Type</i>	<i>Description</i>		<i>Precedence</i>	D	Distress 1	U	Urgent 2	N	Normal 3	L	Low 4	CAR 171.75.	No Difference		
<i>Type</i>	<i>Description</i>																
	<i>Precedence</i>																
D	Distress 1																
U	Urgent 2																
N	Normal 3																
L	Low 4																





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference										
Chapter 8 Reference 8.2.9.3.2  Standard	The alert attribute shall delineate the type of alerting required upon message receipt. Alert types are presented in Table 8-2. <b>Table 8-2. Alert Attribute (Uplink and Downlink)</b> <table border="0" style="width: 100%;"> <tr> <td style="text-align: center;"><i>Type</i></td> <td style="text-align: center;"><i>Description Precedence</i></td> </tr> <tr> <td style="text-align: center;">H</td> <td style="text-align: center;">High 1</td> </tr> <tr> <td style="text-align: center;">M</td> <td style="text-align: center;">Medium 2</td> </tr> <tr> <td style="text-align: center;">L</td> <td style="text-align: center;">Low 3</td> </tr> <tr> <td style="text-align: center;">N</td> <td style="text-align: center;">No alerting required 4</td> </tr> </table>	<i>Type</i>	<i>Description Precedence</i>	H	High 1	M	Medium 2	L	Low 3	N	No alerting required 4	CAR 171.75.	No Difference		
<i>Type</i>	<i>Description Precedence</i>														
H	High 1														
M	Medium 2														
L	Low 3														
N	No alerting required 4														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference																											
Chapter 8 Reference 8.2.9.3.3  Standard	<p>The response attribute shall delineate valid responses for a given message element. Response types are presented in Table 8-3 for uplink messages and Table 8-4 for downlink messages.</p> <p style="text-align: center;"><b>Table 8-3. Response Attribute (Uplink)</b></p> <table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;"><i>Type</i></th> <th style="text-align: left;"><i>Response required</i></th> <th style="text-align: left;"><i>Valid responses</i></th> </tr> </thead> <tbody> <tr> <td>W/U</td> <td>Yes</td> <td>WILCO, UNABLE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR</td> </tr> <tr> <td>A/N</td> <td>Yes</td> <td>1 AFFIRM, NEGATIVE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR</td> </tr> <tr> <td>R</td> <td>Yes</td> <td>2 ROGER, UNABLE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR</td> </tr> <tr> <td>Y</td> <td>Yes</td> <td>3 Any CPDLC downlink message, LOGICAL ACKNOWLEDGEMENT (only if required)</td> </tr> <tr> <td>N</td> <td>No, unless logical acknowledgement required</td> <td>4 LOGICAL ACKNOWLEDGEMENT (only if required), NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, ERROR</td> </tr> <tr> <td></td> <td></td> <td>5</td> </tr> </tbody> </table> <p style="text-align: center;"><b>Table 8-4. Response Attribute (Downlink)</b></p> <table border="0" style="width: 100%;"> <thead> <tr> <th style="text-align: left;"><i>Type</i></th> <th style="text-align: left;"><i>Response required</i></th> <th style="text-align: left;"><i>Valid responses</i></th> </tr> </thead> <tbody> <tr> <td>Y</td> <td>Yes</td> <td>Any CPDLC</td> </tr> </tbody> </table>	<i>Type</i>	<i>Response required</i>	<i>Valid responses</i>	W/U	Yes	WILCO, UNABLE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR	A/N	Yes	1 AFFIRM, NEGATIVE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR	R	Yes	2 ROGER, UNABLE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR	Y	Yes	3 Any CPDLC downlink message, LOGICAL ACKNOWLEDGEMENT (only if required)	N	No, unless logical acknowledgement required	4 LOGICAL ACKNOWLEDGEMENT (only if required), NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, ERROR			5	<i>Type</i>	<i>Response required</i>	<i>Valid responses</i>	Y	Yes	Any CPDLC	CAR 171.75.	No Difference		
<i>Type</i>	<i>Response required</i>	<i>Valid responses</i>																														
W/U	Yes	WILCO, UNABLE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR																														
A/N	Yes	1 AFFIRM, NEGATIVE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR																														
R	Yes	2 ROGER, UNABLE, STANDBY, NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, LOGICAL ACKNOWLEDGEMENT (only if required), ERROR																														
Y	Yes	3 Any CPDLC downlink message, LOGICAL ACKNOWLEDGEMENT (only if required)																														
N	No, unless logical acknowledgement required	4 LOGICAL ACKNOWLEDGEMENT (only if required), NOT CURRENT DATA AUTHORITY, NOT AUTHORIZED NEXT DATA AUTHORITY, ERROR																														
		5																														
<i>Type</i>	<i>Response required</i>	<i>Valid responses</i>																														
Y	Yes	Any CPDLC																														



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
	uplink message, LOGICAL ACKNOWLEDGEMENT (only if required) 1 N No, unless logical acknowledgement required LOGICAL ACKNOWLEDGEMENT (only if required), SERVICE UNAVAILABLE, FLIGHT PLAN NOT HELD, ERROR 2				
Chapter 8 Reference 8.2.9.3.3.1  PANS	<p><b>PANS.</b>— <i>When a multi-element message requires a response, and the response is in the form of a single message element, the response shall apply to all message elements.</i></p> <p><i>Note.</i>— <i>For example, a multi-element message containing CLIMB TO FL310 MAINTAIN MACH.84, a WILCO response applies to, and indicates compliance with both elements of the message.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.3.3.2  PANS	<p><b>PANS.</b>— <i>When a single message element clearance or any part of a multi-element clearance message cannot be complied with, the pilot shall send an UNABLE response for the whole message.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.3.3.3  PANS	<p><b>PANS.</b>— <i>The controller shall respond with an UNABLE message that applies to all elements of the request when no element(s) of a single or multi-element clearance request can be approved. The current clearance(s) shall not be restated.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9.3.3.4  PANS	<p><b>PANS.</b>— <i>When a multi-element clearance request can only be partially accommodated, the controller shall respond with an UNABLE message applying to all the message elements of the request and, if appropriate, include a reason and/or information on when a clearance may be expected.</i></p> <p><i>Note.</i>— <i>A separate CPDLC message (or messages) may subsequently be transmitted to respond to those elements that can be accommodated.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.3.3.5  PANS	<p><b>PANS.</b>— <i>When all elements of a single or multi-element clearance request can be accommodated, the controller shall respond with clearances corresponding to each element of the request. This response should be a single uplink message.</i></p> <p><i>Note.</i>— <i>For example, while messages containing multi-element clearance requests are to be avoided, a multi-element downlink message containing the indicated message elements:</i></p> <p>REQUEST CLEARANCE YQM YYG YYT YQX TRACK X EINN EDDF REQUEST CLIMB TO FL350 REQUEST MACH 0.84</p> <p><i>could be responded to with</i></p> <p>CLEARED YQM YYG YYT YQX TRACK X EINN EDDF CLIMB TO FL350 REPORT MAINTAINING CROSS YYG AT OR AFTER 1150 NO SPEED RESTRICTION.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9.3.3.6  PANS	<p><b>PANS.</b>— <i>When a CPDLC message contains more than one message element and the response attribute for the message is Y, when utilized, the single response message shall contain the corresponding number of replies in the same order.</i></p> <p><i>Note.</i>— <i>For example, a multi-element uplink message containing</i></p> <p>CONFIRM SQUAWK WHEN CAN YOU ACCEPT FL410</p> <p>could be responded to with SQUAWKING 5525 WE CAN ACCEPT FL410 AT 1636Z</p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.4  Standard	When a ground or airborne system generates the CPDLC message ERROR, the reason for the error shall be included in the message.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.5  Standard	<p>The appropriate ATS authority shall select those message elements contained in PANS-ATM, Appendix 5 that support operations in their airspace. Should an ATS authority choose to select a subset of the message elements, and a received message does not belong to this subset, the ATC unit shall respond by uplinking the message element SERVICE UNAVAILABLE.</p> <p><i>Note.</i>— <i>Further processing of the received message is not required.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9.5.1  Recommendation	<b>Recommendation.</b> — <i>Only the uplink messages appropriate to a particular control sector's operations should be provided to the controller.</i>  <i>Note.</i> — <i>The CPDLC message set contained in PANS-ATM, Appendix 5 was developed to encompass different air traffic management environments.</i>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.5.2  Standard	When considered necessary by the appropriate ATS authority, additional standardized free text message elements shall be made available and used by controllers and pilots for those occasions where the CPDLC message set contained in the PANS-ATM does not provide for specific requirements. In such cases, a list of standardized free text message elements shall be established by the appropriate ATS authority, in consultation with operators and other ATS authorities that may be concerned.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.5.3  Standard	Information concerning CPDLC message elements subset utilized and, if applicable, any additional standardized free text message elements, shall be published in aeronautical information publications.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.5.4  PANS	<b>PANS.</b> — <i>Standardized free text message elements should be pre-formatted to facilitate their use.</i>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9.6.1  PANS	<p><b>8.2.9.6 Transfer of CPDLC</b> <i>Note.— Details on CPDLC transfer can be found in the Manual of Air Traffic Services Data Link Applications (Doc 9694).</i></p> <p><b>PANS.—</b> <i>When CPDLC is transferred, the transfer of voice communications and CPDLC shall commence concurrently.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.6.2  PANS	<p><b>PANS.—</b> <i>When an aircraft is transferred from an ATC unit where CPDLC is available to an ATC unit where CPDLC is not available, CPDLC termination shall commence concurrent with the transfer of voice communications.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.6.3  Standard	<p>When a transfer of CPDLC results in a change of data authority, and there are still messages for which the closure response has not been received (i.e. messages outstanding), the controller transferring the CPDLC shall be informed.</p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.6.3.1  Standard	<p>If the controller needs to transfer the aircraft without replying to any downlink message(s) outstanding, the system shall have the capability to automatically send the appropriate closure response message(s). In such cases, the contents of any automatically sent closure response message(s) shall be promulgated in local instructions.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.9.6.3.2  Standard	When the controller decides to transfer the aircraft without receiving pilot responses to any uplink message(s) outstanding, the ground system shall have the capability to automatically end the dialogue for each message prior to the transfer.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.6.3.2.1  PANS	<b>PANS.</b> — <i>The controller should revert to voice communications to clarify any ambiguity associated with the message(s) outstanding.</i>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.9.6.4  Standard	When a transfer of CPDLC does not result in a change of data authority, and there are still messages outstanding, these messages shall either be forwarded to the appropriate controller or shall be closed in accordance with local instructions and, if necessary, letters of agreement.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.10  Recommendation	Display of CPDLC messages <b>Recommendation.</b> — <i>ATC units utilizing a CPDLC message contained in the PANS-ATM should display the associated text pertaining to that message as presented in the PANS-ATM, Appendix 5.</i>	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.11  PANS	<p style="text-align: center;"><b>Free text messages</b></p> <p><b>PANS.</b>— <i>The use of free text message elements by controllers or pilots, other than standardized free text messages referred to in paragraph 8.2.9.5.2, should be avoided.</i></p> <p><i>Note.</i>— <i>Whilst it is recognized that non-routine and emergency situations may necessitate the use of free text, particularly when voice communications has failed, the avoidance of utilizing free text messages is intended to reduce the possibility of misinterpretation and ambiguity.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.1  PANS	<p style="text-align: center;"><b>8.2.12 Emergencies, hazards and equipment failure procedures</b></p> <p><b>PANS.</b>— <i>When a CPDLC emergency message is received, the controller shall acknowledge receipt of the message by the most efficient means available.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.2  PANS	<p><b>PANS.</b>— <i>When responding via CPDLC to a report indicating unlawful interference, uplink message ROGER 7500 shall be used.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.3  PANS	<p><b>PANS.</b>— <i>When responding via CPDLC to all other emergency or urgency messages, uplink message ROGER shall be used.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.12.4  Standard	When a CPDLC message requires a logical acknowledgement and/or an operational response, and such a response is not received, the pilot or controller, as appropriate, shall be alerted.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.5.1  Recommendation	<p style="text-align: center;">8.2.12.5 FAILURE OF CPDLC</p> <p><i>N1.Action to be taken in the event of a CPDLC initiation failure is covered in 8.2.12.6.</i></p> <p><i>N2.Action to be taken in the event of the failure of a single CPDLC message is covered in 8.2.12.8.</i></p> <p><b>Recommendation.</b>— <i>A CPDLC failure should be detected in a timely manner.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.5.2  Standard	The controller and pilot shall be alerted to a failure of CPDLC as soon as a failure has been detected.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.5.3  PANS	<p><b>PANS.</b>— <i>When a controller or pilot is alerted that CPDLC has failed, and the controller or pilot needs to communicate prior to CPDLC being restored, the controller or pilot should revert to voice, if possible, and preface the information with the phrase:</i></p> <p style="text-align: center;">CPDLC FAILURE.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.12.5.4  PANS	<p><b>PANS.</b>— <i>Controllers having a requirement to transmit information concerning a complete CPDLC ground system failure to all stations likely to intercept should preface such a transmission by the general call ALL STATIONS CPDLC FAILURE, followed by the identification of the calling station.</i></p> <p><i>Note.</i>— <i>No reply is expected to such general calls unless individual stations are subsequently called to acknowledge receipt.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.5.5  PANS	<p><b>PANS.</b>— <i>When CPDLC fails and communications revert to voice, all CPDLC messages outstanding should be considered not delivered and the entire dialogue involving the messages outstanding should be recommenced by voice.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.5.6  PANS	<p><b>PANS.</b>— <i>When CPDLC fails but is restored prior to a need to revert to voice communications, all messages outstanding should be considered not delivered and the entire dialogue involving the messages outstanding should be recommenced via CPDLC.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.6.1  PANS	<p style="text-align: center;"><b>8.2.12.6 INITIATION FAILURE OF CPDLC</b></p> <p><b>PANS.</b>— <i>In the case of an initiation failure, the data link system shall provide an indication of the failure to the ATS unit and the flight crew.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.12.6.2  PANS	<p><b>PANS.</b>— <i>The ATS unit shall establish procedures to resolve, as soon as practicable, initiation failure. Procedures should include, as a minimum, the following:</i></p> <ul style="list-style-type: none"> <li><i>a) when a flight plan is available, verify that the aircraft identification, aircraft registration, and other details contained in the data link initiation request correspond with details in the flight plan, and where differences are detected make the necessary changes; or</i></li> <li><i>b) when a flight plan is not available, create a flight plan with sufficient information in the flight data processing system, to achieve a successful data link initiation; then</i></li> <li><i>c) arrange for the re-initiation of the data link process.</i></li> </ul>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.6.3  PANS	<p><b>PANS.</b>— <i>The aircraft operator shall establish procedures to resolve, as soon as practicable initiation failures. Procedures should include, as a minimum, that the pilot:</i></p> <ul style="list-style-type: none"> <li><i>a) verify the correctness and consistency of the flight plan information available in the FMS or equipment from which the CPDLC communication is initiated, and where differences are detected make the necessary changes; then</i></li> <li><i>b) re-initiate data link.</i></li> </ul>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.7.1  Standard	<p><b>8.2.12.7 INTENTIONAL FAILURE OF CPDLC</b></p> <p>When a system shutdown of the communications network or the CPDLC ground system is planned, a NOTAM shall be published to inform all affected parties of the shutdown period and if necessary, the details of the voice communication frequencies to be used.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.12.7.2  Standard	Aircraft currently in communication with the ATC unit shall be informed by voice or CPDLC of any imminent loss of CPDLC service.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.7.3  Standard	The controller and pilot shall be provided with the capability to abort CPDLC.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.8  PANS	<p>FAILURE OF A SINGLE CPDLC MESSAGE</p> <p><b>PANS.</b>— <i>When a controller or pilot is alerted that a single CPDLC message has failed, the controller or pilot shall take one of the following actions, as appropriate:</i></p> <p>a) <i>via voice, confirm the actions that will be undertaken with respect to the related dialogue, prefacing the information with the phrase:</i> CPDLC MESSAGE FAILURE;</p> <p>b) <i>via CPDLC, reissue the CPDLC message that failed.</i></p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.12.9.1  PANS	<p>8.2.12.9 DISCONTINUATION OF THE USE OF CPDLC PILOT REQUESTS</p> <p><b>PANS.</b>— <i>When a controller requires all stations or a specific flight to avoid sending CPDLC requests for a limited period of time, the following phrase shall be used:</i> <i>((call sign) or ALL STATIONS) STOP SENDING CPDLC REQUESTS [UNTIL ADVISED] [(reason)]</i></p> <p><i>Note.</i>— <i>Under these circumstances, CPDLC remains available for the pilot to, if necessary, respond to messages, report information, and declare and cancel an emergency.</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.12.9.2  PANS	<p><b>PANS.</b>— <i>The resumption of the normal use of CPDLC shall be advised by using the following phrase:</i> <i>((call sign) or ALL STATIONS) RESUME NORMAL CPDLC OPERATIONS</i></p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.13  Standard	Where the testing of CPDLC with an aircraft could affect the air traffic services being provided to the aircraft, coordination shall be effected prior to such testing.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.1  Standard	<p><b>8.2.14 Downstream clearance delivery service</b></p> <p>The appropriate ATS authority shall determine whether an ATC unit supports downstream clearance delivery service.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.14.2.1  Standard	<p align="center"><b>8.2.14.2 ESTABLISHMENT OF DOWNSTREAM CLEARANCE DELIVERY SERVICE</b></p> <p>Downstream clearance delivery service shall only be initiated by the airborne system. The initiation shall indicate that this communication is only to receive a downstream clearance.</p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.2.2  Standard	<p>When an ATC unit rejects a request for downstream clearance delivery service, it shall provide the pilot with the reason for the rejection using the CPDLC message SERVICE UNAVAILABLE.</p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.3.1  Standard	<p align="center"><b>8.2.14.3 OPERATION OF DOWNSTREAM CLEARANCE DELIVERY SERVICE</b></p> <p>The controller and pilot shall be informed when downstream clearance delivery service is available for operational communication.</p>	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.3.2  Standard	<p>The controller and pilot shall be informed of the failure of downstream clearance delivery service.</p>	CAR 171.75.	No Difference		



Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
Chapter 8 Reference 8.2.14.3.3  Standard	The CPDLC message elements that are permitted for downstream clearance delivery service shall be established by regional air navigation agreement.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.3.4  Standard	A clearance request issued as a downstream clearance request shall be clearly identifiable as such to the controller.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.3.5  Standard	A clearance issued as a downstream clearance shall be clearly identifiable as such to the pilot.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.4.1  Standard	8.2.14.4 TERMINATION OF DOWNSTREAM CLEARANCE DELIVERY SERVICE  Termination of downstream clearance delivery service shall only be initiated by the airborne system.	CAR 171.75.	No Difference		
Chapter 8 Reference 8.2.14.4.2  Standard	Downstream clearance delivery service with an ATC unit shall be terminated whenever the downstream data authority becomes the current data authority.	CAR 171.75.	No Difference		





Report on entire Annex

Annex Reference	AERONAUTICAL TELECOMMUNICATIONS  Standard or Recommended Practice	State Legislation, Regulation or Document Reference	Level of implementation of SARP's	Text of the difference to be notified to ICAO	Comments including the reason for the difference
-----------------	---	---	---	--	---

- END -